

 免费电子书

学习

celery

Free unaffiliated eBook created from
Stack Overflow contributors.

#celery

.....	1
1:	2
.....	2
Examples.....	2
.....	2
+ Redis.....	2
.....	2
.....	2
.....	2
.....	3
.....	3
.....	3
2:	4
Examples.....	4
Flower.....	4
.....	5

You can share this PDF with anyone you feel could benefit from it, downloaded the latest version from: [celery](#)

It is an unofficial and free celery ebook created for educational purposes. All the content is extracted from [Stack Overflow Documentation](#), which is written by many hardworking individuals at Stack Overflow. It is neither affiliated with Stack Overflow nor official celery.

The content is released under Creative Commons BY-SA, and the list of contributors to each chapter are provided in the credits section at the end of this book. Images may be copyright of their respective owners unless otherwise specified. All trademarks and registered trademarks are the property of their respective company owners.

Use the content presented in this book at your own risk; it is not guaranteed to be correct nor accurate, please send your feedback and corrections to info@zzzprojects.com

1:

“Celery/。 ” - <http://www.celeryproject.org/>

Celery。 DjangoFlask。

Examples

PythonPyPICelery。

pip

```
$ pip install celery
```

easy_install

```
$ easy_install celery
```

<http://pypi.python.org/pypi/celery/Celery>

```
$ tar xvfz celery-0.0.0.tar.gz
$ cd celery-0.0.0
$ python setup.py build
# python setup.py install # as root
```

+ Redis

Redis。 celery[redis]Celery

```
$ pip install -U celery[redis]
```

Redis

```
BROKER_URL = 'redis://localhost:6379/0'
```

URL

```
redis://:password@hostname:port/db_number
```

tasks.py

```
from celery import Celery
```

```
BROKER_URL = 'redis://localhost:6379/0'
app = Celery('tasks', broker=BROKER_URL)
```

```
@app.task
def add(x, y):
    return x + y
```

Celery ◦ ◦ broker **URL** ◦

workerworker

```
$ celery -A tasks worker --loglevel=info
```

delay() ◦

```
>>> from tasks import add
>>> add.delay(4, 4)
```

AsyncResult ◦

Celery ◦ Redis

```
BROKER_URL = 'redis://localhost:6379/0'
BACKEND_URL = 'redis://localhost:6379/1'
app = Celery('tasks', broker=BROKER_URL, backend=BACKEND_URL)
```

◦

◦ **AsyncResult**

```
>>> result = add.delay(4, 4)
```

ready()

```
>>> result.ready()
False
```

```
>>> result.get(timeout=1)
8
```

<https://riptutorial.com/zh-CN/celery/topic/6987/>

2:

Examples

Flower

FlowerWebCelery。

Flower_{pip}

```
pip install flower
```

proj

```
celery -A proj flower
```

```
http://localhost:5555
```

<https://riptutorial.com/zh-CN/celery/topic/7477/>

S. No		Contributors
1		4444 , Community , jamjar , jegesh , Majid
2		ettanany