



免費電子書

學習

Kotlin

Free unaffiliated eBook created from
Stack Overflow contributors.

#kotlin

	1
1: Kotlin	2
	2
Kotlin	2
	2
Examples	2
	3
Hello World	3
Hello WorldCompanion	3
varargs	4
Kotlin	4
	4
2: DSL	6
	6
Examples	6
DSLInfix	6
DSL	6
lambda	6
lambdas	6
3: Java 8 Stream	8
	8
	8
	8
	8
	8
	9
Examples	9
	9
	9
	9
	9

10	10
.....	10
.....	10
.....	10
.....	10
.....	10
2 -	11
3 -	11
4 -	11
5 - Int.....	11
6 - Ints.....	12
7 - IntString.....	12
.....	12
-	12
1 -	13
5 -	13
6 -	14
7a -	15
7b - SummarizingInt.....	15
4: JUnit	17
Examples.....	17
.....	17
5: Kotlin Android	18
.....	18
Examples.....	18
.....	18
.....	18
.....	19
Kotlin.....	19
6: Kotlin for Java Developers	21
.....	21
Examples.....	21

21	21
.....	21
.....	21
IFTRY.....	22
7: Kotlin.....	23
.....	23
.....	23
Examples.....	23
.....	23
8: Kotlin.....	25
Examples.....	25
toString.....	25
9:.....	26
Examples.....	26
try-catch-finally.....	26
10: Vararg.....	27
.....	27
.....	27
Examples.....	27
vararg.....	27
Spread Operatorvararg.....	27
11:	29
.....	29
.....	29
Examples.....	29
.....	29
Lambda.....	29
.....	30
.....	31
.....	32
.....	32
.....	32
12:	33

.....	33
Examples.....	33
1.....	33
13:	34
.....	34
.....	34
.....	34
Examples.....	34
.....	34
.....	34
Java.....	34
.....	34
.....	35
14:	37
.....	37
.....	37
Examples.....	37
.....	37
15:	38
.....	38
Examples.....	38
java/.....	38
.....	38
16: KotlinRecyclerView	40
.....	40
Examples.....	40
.....	40
17: Lambdas	42
.....	42
.....	42
Examples.....	43
Lambda.....	43

Lambda.....	43
Lambda.....	43
18:	44
.....	44
Examples.....	44
.....	44
.....	44
.....	44
.....	44
.....	44
.....	44
19:	46
Examples.....	46
.....	46
.....	46
.....	46
.....	46
.....	47
20:	48
Examples.....	48
DTOPOJO / POCO.....	48
.....	48
.....	48
KotlinSerializableserialVersionUID.....	48
Kotlin.....	49
let.....	49
apply.....	50
21:	51
.....	51
Examples.....	51
.....	51
.....	51
.....	51
.....	51

52	52
.....	53
22:	54
.....	54
.....	54
.....	54
Examples	54
.....	54
.....	54
.....	54
Java 7+ Path	55
.....	55
Java 8 TemporalISO	55
Companion	56
.....	56
.....	56
.....	56
.....	57
23:	58
Examples	58
.....	58
.....	58
.....	58
.....	59
.....	59
.....	59
.....	59
24:	60
.....	60
Examples	60
.....	60
.....	60

60	60
.....
25:	62
.....	62
Examples	62
if.....	62
if.....	62
whenif-else-if.....	62
when.....	63
.....	63
.....	64
26:	65
Examples	65
.....	65
.....	65
.....	65
.....	65
Kotlin.....	66
RegEx	66
.....	66
.....	66
findCharSequencestartIndexIntMatchResult	66
findAllInputCharSequencestartIndexIntSequence	67
matchEntireCharSequenceMatchResult	67
matchesCharSequenceBoolean	67
containsMatchInInputCharSequenceBoolean	67
splitCharSequenceLimitIntList	67
replaceCharSequenceReplacementStringString	68
27:	69
.....	69
.....	69

.....	69
.....	69
.....	69
Examples	69
-	69
.....	69
28:	71
Examples	71
NullableNon Nullable.....	71
.....	71
null	71
.....	71
Iterable	72
Null Coalescing / Elvis.....	72
.....	72
:).....	72
29:	74
.....	74
Examples	74
.....	74
30: kotlin	75
.....	75
Examples	75
kotlin.logging.....	75
31:	76
.....	76
Examples	76
x.....	76
iterables.....	76
.....	76
.....	77
kotlin	77

.....	77
.....	77
32:	79
.....	79
Examples.....	79
.....	79
downTo.....	79
step.....	79
.....	79
33:	80
Examples.....	80
.....	80
.....	80
34:	81
.....	81
.....	81
.....	81
.....	81
Examples.....	81
.....	81
.....	81
35: Kotlin	82
Examples.....	82
Gradle.....	82
JVM.....	82
Android.....	82
JS.....	82
Android Studio.....	83
.....	83
.....	83
Java.....	83
GroovyGradleKotlin.....	84
36:	86

.....	86
.....	86
Examples	86
.....	86
.....	86
set	86
37:	87
.....	87
.....	87
Kotlin	87
Examples	87
.....	87
38:	89
.....	89
.....	89
.....	89
Examples	89
'open'.....	89
.....	89
.....	89
.....	89
.....	90
.....	90
.....	90
.....	90
Person	90
.....	90
.....	90
.....	90
.....	90
.....	92

You can share this PDF with anyone you feel could benefit from it, download the latest version from: [kotlin](#)

It is an unofficial and free Kotlin ebook created for educational purposes. All the content is extracted from [Stack Overflow Documentation](#), which is written by many hardworking individuals at Stack Overflow. It is neither affiliated with Stack Overflow nor official Kotlin.

The content is released under Creative Commons BY-SA, and the list of contributors to each chapter are provided in the credits section at the end of this book. Images may be copyright of their respective owners unless otherwise specified. All trademarks and registered trademarks are the property of their respective company owners.

Use the content presented in this book at your own risk; it is not guaranteed to be correct nor accurate, please send your feedback and corrections to info@zzzprojects.com

1: Kotlin

Kotlin JetBrains JVM。 Kotlin Java 100。 Kotlin Java。 Kotlin JVM Java JavaScript。

Kotlin

Kotlin Eclipse IntelliJ JDE。 Kotlin Maven Ant Gradle。

```
$ kotlinc Main.kt java MainKt.class Kt。 $ java MainKt$ java MainKt
```

```
Exception in thread "main" java.lang.NoClassDefFoundError: kotlin/jvm/internal/Intrinsics
  at MainKt.main(Main.kt)
Caused by: java.lang.ClassNotFoundException: kotlin.jvm.internal.Intrinsics
  at java.net.URLClassLoader.findClass(URLClassLoader.java:381)
  at java.lang.ClassLoader.loadClass(ClassLoader.java:424)
  at sun.misc.Launcher$AppClassLoader.loadClass(Launcher.java:335)
  at java.lang.ClassLoader.loadClass(ClassLoader.java:357)
... 1 more
```

Java Kotlin run-time jar。

```
java -cp .:/path/to/kotlin/runtime/jar/kotlin-runtime.jar MainKt
```

1.0.0	2016215
1.0.1	2016316
1.0.2	2016513
1.0.3	2016630
1.0.4	2016922
1.0.5	2016118
1.0.6	20161227
1.1.0	201731
1.1.1	2017314
1.1.2	2017425
1.1.3	2017623

Examples

Kotlin_{main}◦ Kotlin“Hello World”

```
package my.program

fun main(args: Array<String>) {
    println("Hello, world!")
}
```

Main.kt

JVM◦ my.program.MainKt◦

package

```
@file:JvmName ("MyApp")
```

my.program.MyApp◦

- @JvmName◦
-

Hello World

Kotlin◦

```
package my.program

object App {
    @JvmStatic fun main(args: Array<String>) {
        println("Hello World")
    }
}
```

my.program.App◦

App◦ App◦

- @JvmStatic

Hello WorldCompanion

CompanionKotlin_{main}◦

```
package my.program

class App {
    companion object {
        @JvmStatic fun main(args: Array<String>) {
            println("Hello World")
        }
    }
}
```

```
my.program.App  
App : Object Declaration
```

“hello”

```
class App {  
    companion object {  
        @JvmStatic fun main(args: Array<String>) {  
            App().run()  
        }  
    }  
  
    fun run() {  
        println("Hello World")  
    }  
}
```

- `@JvmStatic`

varargs

varargs

```
package my.program  
  
fun main(vararg args: String) {  
    println("Hello, world!")  
}
```

Kotlin

javaJava. Kotlin.

javacjava. javajava.

kotlinckotlinkotlinkotlin.

Kotlin. N1 2 3.

Kotlin.

```
fun main(args: Array<String>) {  
  
    println("Enter Two number")  
    var (a, b) = readLine()!!.split(' ') // !! this operator use for  
    NPE(NullPointerException).  
  
    println("Max number is : ${maxNum(a.toInt(), b.toInt())}")  
}
```

```
fun maxNum(a: Int, b: Int): Int {  
  
    var max = if (a > b) {  
        println("The value of a is $a");  
        a  
    } else {  
        println("The value of b is $b")  
        b  
    }  
  
    return max;  
}
```

◦

```
Enter Two number  
71 89 // Enter two number from command line  
  
The value of b is 89  
Max number is: 89
```

!!Null Safety ◦

IntelliJ◦

Kotlin <https://riptutorial.com/zh-TW/kotlin/topic/490/kotlin>

2: DSL

KotlinDSL。

Examples

DSLInfix

```
infix fun <T> T?.shouldBe(expected: T?) = assertEquals(expected, this)
```

DSL

```
@Test
fun test() {
    100.plusOne() shouldBe 101
}
```

DSL

```
class MyExample(val i: Int) {
    operator fun <R> invoke(block: MyExample.() -> R) = block()
    fun Int.bigger() = this > i
}
```

DSL

```
fun main2(args: Array<String>) {
    val ex = MyExample(233)
    ex {
        // bigger is defined in the context of `ex`
        // you can only call this method inside this context
        if (777.bigger()) kotlin.io.println("why")
    }
}
```

lambda

```
val r = Random(233)
infix inline operator fun Int.rem(block: () -> Unit) {
    if (r.nextInt(100) < this) block()
}
```

DSL

```
20 % { println("The possibility you see this message is 20%") }
```

lambda

```
operator fun <R> String.invoke(block: () -> R) = {
    try { block.invoke() }
    catch (e: AssertionError) { System.err.println("$this\n${e.message}") }
}
```

DSL

```
"it should return 2" {
    parse("1 + 1").buildAST().evaluate() shouldBe 2
}
```

shouldBeInfix approach to build DSLInfix approach to build DSL。

DSL <https://riptutorial.com/zh-TW/kotlin/topic/10042/dsl>

3: Java 8 Stream

Kotlin。 Sequence。

```
asSequence() Sequence 。 Sequence 。 toList() toSet() toMap() Sequence 。  
  
// switch to and from lazy  
val someList = items.asSequence().filter { ... }.take(10).map { ... }.toList()  
  
// switch to lazy, but sorted() brings us out again at the end  
val someList = items.asSequence().filter { ... }.take(10).map { ... }.sorted()
```

Kotlin。 Kotlin。 JavaNPE。 Kotlin

```
val someList = people.filter { it.age <= 30 }.map { it.name }
```

```
val someList: List<String> = people.filter { it.age <= 30 }.map { it.name }
```

Kotlin_{people}.people.ageIntIntpeople.nameStringmapList<String> String List。

people? List<People>?

```
val someList = people?.filter { it.age <= 30 }?.map { it.name }
```

List<String>? *Kotlin**Kotlin**Kotlin*

Kotlin。 Sequence“”start。 Java 8Kotlin

```
// Java:  
Stream<String> stream =  
Stream.of("d2", "a2", "b1", "b3", "c").filter(s -> s.startsWith("b"));  
  
stream.anyMatch(s -> true); // ok  
stream.noneMatch(s -> true); // exception
```

```
// Kotlin:  
val stream = listOf("d2", "a2", "b1", "b3", "c").asSequence().filter { it.startsWith('b') }  
  
stream.forEach(::println) // b1, b2  
  
println("Any B ${stream.any { it.startsWith('b') }}") // Any B true  
println("Any C ${stream.any { it.startsWith('c') }}") // Any C false  
  
stream.forEach(::println) // b1, b2
```

Java

```
// Java:  
Supplier<Stream<String>> streamSupplier =
```

```

() -> Stream.of("d2", "a2", "b1", "b3", "c")
    .filter(s -> s.startsWith("a"));

streamSupplier.get().anyMatch(s -> true); // ok
streamSupplier.get().noneMatch(s -> true); // ok

```

Kotlin SequenceSequenceconstrainOnce()

```

val stream = listOf("d2", "a2", "b1", "b3", "c").asSequence().filter { it.startsWith('b') }
    .constrainOnce()

stream.forEach(::println) // b1, b2
stream.forEach(::println) // Error:java.lang.IllegalStateException: This sequence can be
consumed only once.

```

- [Iterable API](#)
- [Array API](#)
- [List API](#)
- [Map API](#)

Examples

```
// Java:
List<String> list = people.stream().map(Person::getName).collect(Collectors.toList());
```

```
// Kotlin:
val list = people.map { it.name } // toList() not needed
```

```
// Java:
String joined = things.stream()
    .map(Object::toString)
    .collect(Collectors.joining(", "));
```

```
// Kotlin:
val joined = things.joinToString() // ", " is used as separator, by default
```

```
// Java:
int total = employees.stream()
    .collect(Collectors.summingInt(Employee::getSalary));
```

```
// Kotlin:
val total = employees.sumBy { it.salary }
```

```
// Java:
Map<Department, List<Employee>> byDept
= employees.stream()
    .collect(Collectors.groupingBy(Employee::getDepartment));
```

```
// Kotlin:
```

```
val byDept = employees.groupBy { it.department }
```

```
// Java:  
Map<Department, Integer> totalByDept  
    = employees.stream()  
        .collect(Collectors.groupingBy(Employee::getDepartment,  
            Collectors.summingInt(Employee::getSalary)));
```

```
// Kotlin:  
val totalByDept = employees.groupBy { it.dept }.mapValues { it.value.sumBy { it.salary } }
```

```
// Java:  
Map<Boolean, List<Student>> passingFailing =  
    students.stream()  
        .collect(Collectors.partitioningBy(s -> s.getGrade() >= PASS_THRESHOLD));
```

```
// Kotlin:  
val passingFailing = students.partition { it.grade >= PASS_THRESHOLD }
```

```
// Java:  
List<String> namesOfMaleMembersCollect = roster  
    .stream()  
    .filter(p -> p.getGender() == Person.Sex.MALE)  
    .map(p -> p.getName())  
    .collect(Collectors.toList());
```

```
// Kotlin:  
val namesOfMaleMembers = roster.filter { it.gender == Person.Sex.MALE }.map { it.name }
```

```
// Java:  
Map<Person.Sex, List<String>> namesByGender =  
    roster.stream().collect(  
        Collectors.groupingBy(  
            Person::getGender,  
            Collectors.mapping(  
                Person::getName,  
                Collectors.toList()));
```

```
// Kotlin:  
val namesByGender = roster.groupBy { it.gender }.mapValues { it.value.map { it.name } }
```

```
// Java:  
List<String> filtered = items.stream()  
    .filter( item -> item.startsWith("o") )  
    .collect(Collectors.toList());
```

```
// Kotlin:  
val filtered = items.filter { item.startsWith('o') }
```

```
// Java:  
String shortest = items.stream()
```

```
.min(Comparator.comparing(item -> item.length()))
.get();
```

```
// Kotlin:
val shortest = items.minBy { it.length }
```

2 -

```
// Java:
Stream.of("a1", "a2", "a3")
    .findFirst()
    .ifPresent(System.out::println);
```

```
// Kotlin:
sequenceOf("a1", "a2", "a3").firstOrNull()?.apply(::println)
```

3 -

```
// Java:
IntStream.range(1, 4).forEach(System.out::println);
```

```
// Kotlin: (inclusive range)
(1..3).forEach(::println)
```

4 -

```
// Java:
Arrays.stream(new int[] {1, 2, 3})
    .map(n -> 2 * n + 1)
    .average()
    .ifPresent(System.out::println); // 5.0
```

```
// Kotlin:
arrayOf(1,2,3).map { 2 * it + 1 }.average().apply(::println)
```

5 - Int

```
// Java:
Stream.of("a1", "a2", "a3")
    .map(s -> s.substring(1))
    .mapToInt(Integer::parseInt)
    .max()
    .ifPresent(System.out::println); // 3
```

```
// Kotlin:
sequenceOf("a1", "a2", "a3")
    .map { it.substring(1) }
    .map(String::toInt)
    .max().apply(::println)
```

6 - Ints

```
// Java:  
IntStream.range(1, 4)  
    .mapToObj(i -> "a" + i)  
    .forEach(System.out::println);  
  
// a1  
// a2  
// a3
```

```
// Kotlin: (inclusive range)  
(1..3).map { "a$it" }.forEach(::println)
```

7 - IntString

```
// Java:  
Stream.of(1.0, 2.0, 3.0)  
    .mapToInt(Double::intValue)  
    .mapToObj(i -> "a" + i)  
    .forEach(System.out::println);  
  
// a1  
// a2  
// a3
```

```
// Kotlin:  
sequenceOf(1.0, 2.0, 3.0).map(Double::toInt).map { "a$it" }.forEach(::println)
```

```
// Java:  
long count = items.stream().filter( item -> item.startsWith("t")).count();
```

```
// Kotlin:  
val count = items.filter { it.startsWith('t') }.size  
// but better to not filter, but count with a predicate  
val count = items.count { it.startsWith('t') }
```

```
■  
  
// Java:  
List<String> myList = Arrays.asList("a1", "a2", "b1", "c2", "c1");  
  
myList.stream()  
    .filter(s -> s.startsWith("c"))  
    .map(String::toUpperCase)  
    .sorted()  
    .forEach(System.out::println);  
  
// C1  
// C2
```

```
// Kotlin:
```

```
val list = listOf("a1", "a2", "b1", "c2", "c1")
list.filter { it.startsWith('c') }.map (String::toUpperCase).sorted()
    .forEach (::println)
```

1 -

```
// Java:
Arrays.asList("a1", "a2", "a3")
    .stream()
    .findFirst()
    .ifPresent(System.out::println);

// Kotlin:
listOf("a1", "a2", "a3").firstOrNull()?.apply(::println)
```

StringifPresent

```
// Kotlin:
inline fun String?.ifPresent	thenDo: (String)->Unit) = this?.apply { thenDo(this) }

// now use the new extension function:
listOf("a1", "a2", "a3").firstOrNull().ifPresent(::println)
```

apply()

?.. <http://stackoverflow.com/questions/34498562/in-kotlin-what-is-the-idiomatic-way-to-deal-with-nullables-values-referencing-o/34498563> 34498563

5 -

```
// Java:
String phrase = persons
    .stream()
    .filter(p -> p.age >= 18)
    .map(p -> p.name)
    .collect(Collectors.joining(" and ", "In Germany ", " are of legal age."));

System.out.println(phrase);
// In Germany Max and Peter and Pamela are of legal age.
```

```
// Kotlin:
val phrase = persons
    .filter { it.age >= 18 }
    .map { it.name }
    .joinToString(" and ", "In Germany ", " are of legal age.")

println(phrase)
// In Germany Max and Peter and Pamela are of legal age.
```

Kotlin

```
// Kotlin:
// data class has equals, hashCode, toString, and copy methods automagically
```

```

data class Person(val name: String, val age: Int)

val persons = listOf(Person("Tod", 5), Person("Max", 33),
                    Person("Frank", 13), Person("Peter", 80),
                    Person("Pamela", 18))

```

6 -

```

// Java:
Map<Integer, String> map = persons
    .stream()
    .collect(Collectors.toMap(
        p -> p.age,
        p -> p.name,
        (name1, name2) -> name1 + ";" + name2));

System.out.println(map);
// {18=Max, 23=Peter;Pamela, 12=David}

```

Kotlin ◦ /Map

```

// Kotlin:
val map1 = persons.map { it.age to it.name }.toMap()
println(map1)
// output: {18=Max, 23=Pamela, 12=David}
// Result: duplicates overridden, no exception similar to Java 8

val map2 = persons.toMap({ it.age }, { it.name })
println(map2)
// output: {18=Max, 23=Pamela, 12=David}
// Result: same as above, more verbose, duplicates overridden

val map3 = persons.toMapBy { it.age }
println(map3)
// output: {18=Person(name=Max, age=18), 23=Person(name=Pamela, age=23), 12=Person(name=David, age=12)}
// Result: duplicates overridden again

val map4 = persons.groupBy { it.age }
println(map4)
// output: {18=[Person(name=Max, age=18)], 23=[Person(name=Peter, age=23), Person(name=Pamela, age=23)], 12=[Person(name=David, age=12)]}
// Result: closer, but now have a Map<Int, List<Person>> instead of Map<Int, String>

val map5 = persons.groupBy { it.age }.mapValues { it.value.map { it.name } }
println(map5)
// output: {18=[Max], 23=[Peter, Pamela], 12=[David]}
// Result: closer, but now have a Map<Int, List<String>> instead of Map<Int, String>

```

```

// Kotlin:
val map6 = persons.groupBy { it.age }.mapValues { it.value.joinToString(",") { it.name } }

println(map6)
// output: {18=Max, 23=Peter;Pamela, 12=David}
// Result: YAY! !

```

joinToStringPersonPerson.name

◦

7a -

```
// Java (verbose):
Collector<Person, StringJoiner, String> personNameCollector =
Collector.of(
    () -> new StringJoiner(" | "),           // supplier
    (j, p) -> j.add(p.name.toUpperCase()),   // accumulator
    (j1, j2) -> j1.merge(j2),                // combiner
    StringJoiner::toString);                  // finisher

String names = persons
    .stream()
    .collect(personNameCollector);

System.out.println(names); // MAX | PETER | PAMELA | DAVID

// Java (concise)
String names = persons.stream().map(p -> p.name.toUpperCase()).collect(Collectors.joining(" | "));

// Kotlin:
val names = persons.map { it.name.toUpperCase() }.joinToString(" | ")
```

7b - SummarizingInt

```
// Java:
IntSummaryStatistics ageSummary =
    persons.stream()
        .collect(Collectors.summarizingInt(p -> p.age));

System.out.println(ageSummary);
// IntSummaryStatistics{count=4, sum=76, min=12, average=19.000000, max=23}

// Kotlin:

// something to hold the stats...
data class SummaryStatisticsInt(var count: Int = 0,
                                var sum: Int = 0,
                                var min: Int = Int.MAX_VALUE,
                                var max: Int = Int.MIN_VALUE,
                                var avg: Double = 0.0) {
    fun accumulate(newInt: Int): SummaryStatisticsInt {
        count++
        sum += newInt
        min = min.coerceAtMost(newInt)
        max = max.coerceAtLeast(newInt)
        avg = sum.toDouble() / count
        return this
    }
}

// Now manually doing a fold, since Stream.collect is really just a fold
val stats = persons.fold(SummaryStatisticsInt()) { stats, person ->
    stats.accumulate(person.age) }
```

```
println(stats)
// output: SummaryStatisticsInt(count=4, sum=76, min=12, max=23, avg=19.0)
```

2Kotlin stdlib

```
// Kotlin:
inline fun Collection<Int>.summarizingInt(): SummaryStatisticsInt
    = this.fold(SummaryStatisticsInt()) { stats, num -> stats.accumulate(num) }

inline fun <T: Any> Collection<T>.summarizingInt(transform: (T)->Int): SummaryStatisticsInt =
    this.fold(SummaryStatisticsInt()) { stats, item -> stats.accumulate(transform(item)) }

summarizingInt

val stats2 = persons.map { it.age }.summarizingInt()

// or

val stats3 = persons.summarizingInt { it.age }
```

- Sequence◦

Java 8 Stream <https://riptutorial.com/zh-TW/kotlin/topic/707/java-8-stream>

4: JUnit

Examples

JUnit

```
@Rule @JvmField val myRule = TemporaryFolder()
```

```
@JvmField myRule @JUnit
```

JUnit <https://riptutorial.com/zh-TW/kotlin/topic/6973/junit>

5: Kotlin Android

KotlinAndroidButterKnife。。

Examples

gradle。

Kotlin build.gradle。

```
buildscript {
    ...
}

apply plugin: "com.android.application"
...
apply plugin: "kotlin-android"
apply plugin: "kotlin-android-extensions"
...
```

activity_main.xml activity_main.xml

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent"
    android:layout_height="match_parent">

    <Button
        android:id="@+id/my_button"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="My button"/>
</LinearLayout>
```

Kotlin

```
import kotlinx.android.synthetic.main.activity_main.my_button

class MainActivity: Activity() {
    override fun onCreate(savedInstanceState: Bundle?) {
        super.onCreate(savedInstanceState)
        setContentView(R.layout.activity_main)
        // my_button is already casted to a proper type of "Button"
        // instead of being a "View"
        my_button.setText("Kotlin rocks!")
    }
}
```

*ID

```
// my_button can be used the same way as before
import kotlinx.android.synthetic.main.activity_main.*
```

//

```
import kotlinx.android.synthetic.main.activity_main.my_button

class NotAView {
    init {
        // This sample won't compile!
        my_button.setText("Kotlin rocks!")
    }
}
```

AndroidAndroid ◦ build.gradle

```
android {
    productFlavors {
        paid {
            ...
        }
        free {
            ...
        }
    }
}
```

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent"
    android:layout_height="match_parent">

    <Button
        android:id="@+id/buy_button"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Buy full version"/>
</LinearLayout>
```

```
import kotlinx.android.synthetic.free.main_activity.buy_button
```

Kotlin

```
mView.afterMeasured {
    // inside this block the view is completely drawn
    // you can get view's height/width, it.height / it.width
}
```

```
inline fun View.afterMeasured(crossinline f: View.() -> Unit) {
    viewTreeObserver.addOnGlobalLayoutListener(object : ViewTreeObserver.OnGlobalLayoutListener {
        override fun onGlobalLayout() {
            if (measuredHeight > 0 && measuredWidth > 0) {
                viewTreeObserver.removeOnGlobalLayoutListener(this)
                f()
            }
        }
    })
}
```

}

Kotlin Android <https://riptutorial.com/zh-TW/kotlin/topic/9474/kotlin-android>

6: Kotlin for Java Developers

KotlinJava。

JavaKotlinKotlinJava。

Examples

KotlinJava

```
val i : Int = 42
```

- valvarfinal “**val ue**”**var iable**。
- ::
- Kotlin

Java	
int i = 42;	var i = 42 var i : Int = 42
final int i = 42;	val i = 42

- ;
- Kotlin
- **Kotlin100Java**
- Kotlin JVM
- Kotlin
- Kotlin`equals / hashCode`
- Kotlin
- Kotlin `new` . .
- Kotlin . . `val a = someMap["key"]`
- **KotlinJVMJava Script Kotlin**
- **Kotlin Java 6** Android
- **KotlinAndroid**
- **Kotlin** .
- **KotlinCoroutines**

Kotlin`==equals` ===.

Java	
a.equals(b);	a == b
a == b;	a === b

```
a != b;      a !== b
```

<https://kotlinlang.org/docs/reference/equality.html>

IFTRY

Kotlin if tryvoid.

KotlinJavaElvis

```
val i = if (someBoolean) 33 else 42
```

try

```
val i = try {
    Integer.parseInt(someString)
}
catch (ex : Exception)
{
    42
}
```

Kotlin for Java Developers <https://riptutorial.com/zh-TW/kotlin/topic/10099/kotlin-for-java-developers>

7: Kotlin

Kotlin。

1. Kotlin.kt。
2. KotlinAnyJavaObject。
3. val - var -
4. .
5. Unit.lt。 6.==。 aba === btrue。

Examples

1.。

```
fun printHello(name: String?): Unit {  
    if (name != null)  
        println("Hello ${name}")  
}  
  
fun printHello(name: String?) {  
    ...  
}
```

2.Single-Expression=

```
fun double(x: Int): Int = x * 2
```

```
fun double(x: Int) = x * 2
```

3.String。

```
In java:  
    int num=10  
    String s = "i =" + i;  
  
In Kotlin  
    val num = 10  
    val s = "i = $num"
```

4.Kotlinnullnullnull。 Stringnull

```
var a: String = "abc"  
a = null // compilation error
```

String

```
var b: String? = "abc"
```

```
b = null // ok
```

5.Kotlin==。 == b

```
a?.equals(b) ?: (b === null)
```

Kotlin <https://riptutorial.com/zh-TW/kotlin/topic/10648/kotlin>

8: Kotlin

Examples

toString

Kotlin `toString` null String? String? .

Android `EditText` .

```
// Incorrect:  
val text = view.textField?.text.toString() ?: ""
```

"null" .

```
// Correct:  
val text = view.textField?.text?.toString() ?: ""
```

Kotlin <https://riptutorial.com/zh-TW/kotlin/topic/6608/kotlin>

Examples

try-catch-finally

KotlinJava

```
try {
    doSomething()
}
catch(e: MyException) {
    handle(e)
}
finally {
    cleanup()
}
```

```
try {
    doSomething()
}
catch(e: FileSystemException) {
    handle(e)
}
catch(e: NetworkException) {
    handle(e)
}
catch(e: MemoryException) {
    handle(e)
}
finally {
    cleanup()
}
```

try

```
val s: String? = try { getString() } catch (e: Exception) { null }
```

Kotlin°

```
fun fileToString(file: File) : String {
    //readAllBytes throws IOException, but we can omit catching it
    fileContent = Files.readAllBytes(file)
    return String(fileContent)
}
```

<https://riptutorial.com/zh-TW/kotlin/topic/7246/>

10: Vararg

- **Vararg** vararg^o
- **Spread Operator** *””^o

Examples

vararg

vararg^o

```
fun printNumbers(vararg numbers: Int) {  
    for (number in numbers) {  
        println(number)  
    }  
}  
  
o  
  
printNumbers(0, 1)           // Prints "0" "1"  
printNumbers(10, 20, 30, 500) // Prints "10" "20" "30" "500"
```

Vararg^o

Spread Operator vararg

Spread Operator *vararg^o

.....

```
fun printNumbers(vararg numbers: Int) {  
    for (number in numbers) {  
        println(number)  
    }  
}
```

...

```
val numbers = intArrayOf(1, 2, 3)  
printNumbers(*numbers)  
  
// This is the same as passing in (1, 2, 3)
```

...

```
val numbers = intArrayOf(1, 2, 3)  
printNumbers(10, 20, *numbers, 30, 40)
```

```
// This is the same as passing in (10, 20, 1, 2, 3, 30, 40)
```

Vararg <https://riptutorial.com/zh-TW/kotlin/topic/5835/vararg>

11:

- **Params** = ...
- **Params** {...}
- **PARAMS** {...}
- < > **PARAMS** {...}
- {...}
- { **ArgName** **ArgType** - > ...}
- { **ArgName** - > ...}
- { **ArgNames** - > ...}
- { **ArgName** **ArgType** - > ...}

PARAMS	Name : Type
ArgName	
ArgType	ArgName
ArgNames	ArgName

Examples

“Lambda”。 “”

```
# Takes no parameters and returns anything
() -> Any?

# Takes a string and an integer and returns ReturnType
(arg1: String, arg2: Int) -> ReturnType
```

() -> Any? **lambda**

```
fun twice(x: () -> Any?) {
    x(); x();
}

fun main() {
    twice {
        println("Foo")
    } # -> Foo
    # -> Foo
}
```

Lambda

Lambda◦ {braces} - ->◦

```
{ name: String ->
    "Your name is $name" //This is returned
}
```

lambda◦

lambda◦

```
{ argumentOne:String, argumentTwo:String ->
    "$argumentOne - $argumentTwo"
}
```

lambdait◦

```
{ "Your name is $it" }
```

lambda◦

```
# These are identical
listOf(1, 2, 3, 4).map { it + 2 }
listOf(1, 2, 3, 4).map({ it + 2 })
```

: :◦ ◦

```
fun addTwo(x: Int) = x + 2
listOf(1, 2, 3, 4).map(::addTwo) # => [3, 4, 5, 6]
```

(ParamTypeA, ParamTypeB, ...) -> ReturnType ParamTypeA ParamTypeB ...`ReturnType1◦

```
fun foo(p0: Foo0, p1: Foo1, p2: Foo2): Bar {
    //...
}
println(::foo::class.java.genericInterfaces[0])
// kotlin.jvm.functions.Function3<Foo0, Foo1, Foo2, Bar>
// Human readable type: (Foo0, Foo1, Foo2) -> Bar
```

◦

```
class Foo
fun Foo.foo(p0: Foo0, p1: Foo1, p2: Foo2): Bar {
    //...
}
val ref = Foo::foo
println(ref::class.java.genericInterfaces[0])
// kotlin.jvm.functions.Function4<Foo, Foo0, Foo1, Foo2, Bar>
// Human readable type: (Foo, Foo0, Foo1, Foo2) -> Bar
// takes 4 parameters, with receiver as first and actual parameters following, in their order

// this function can't be called like an extension function, though
```

```
val ref = Foo::foo
Foo().ref(Foo0(), Foo1(), Foo2()) // compile error

class Bar {
    fun bar()
}
print(Bar::bar) // works on member functions, too.
```

◦

```
object Foo
fun Foo.foo(p0: Foo0, p1: Foo1, p2: Foo2): Bar {
    //...
}
val ref = Foo::foo
println(ref::class.java.genericInterfaces[0])
// kotlin.jvm.functions.Function3<Foo0, Foo1, Foo2, Bar>
// Human readable type: (Foo0, Foo1, Foo2) -> Bar
// takes 3 parameters, receiver not needed

object Bar {
    fun bar()
}
print(Bar::bar) // works on member functions, too.
```

kotlin 1.1 .

1.1.0

```
fun makeList(last: String?): List<String> {
    val list = mutableListOf("a", "b", "c")
    last?.let(list::add)
    return list
}
```

◦ ◦

◦ ◦

```
class Foo
class Bar {
    fun Foo.foo() {}
    val ref = Foo::foo // compile error
}
```

fun Unit {} Unit return

```
fun sayMyName(name: String): String {
    return "Your name is $name"
}
```

```
fun sayMyName(name: String): String = "Your name is $name"
```

```
fun sayMyName(name: String) = "Your name is $name"
```

◦ ◦

```
fun sayMyName(name: String): String = "Your name is $name"
```

inlineinlineC - ◦ lambdas◦

```
inline fun sayMyName(name: String) = "Your name is $name"
```

C

```
inline fun sayMyName() = "Your name is $name"

fun main() {
    val name = "Foo"
    sayMyName() # => Unresolved reference: name
}
```

Kotlin+* ◦ ◦ operator

```
data class IntListWrapper (val wrapped: List<Int>) {
    operator fun get(position: Int): Int = wrapped[position]
}

val a = IntListWrapper(listOf(1, 2, 3))
a[1] // == 2
```

<https://riptutorial.com/zh-TW/kotlin/topic/1280/>

12:

Kotlin

Examples

1

```
fun main(args: Array<String>) {
    launch(CommonPool) { // create new coroutine in common thread pool
        delay(1000L) // non-blocking delay for 1 second (default time unit is ms)
        println("World!") // print after delay
    }
    println("Hello,") // main function continues while coroutine is delayed
    Thread.sleep(2000L) // block main thread for 2 seconds to keep JVM alive
}
```

```
Hello,
World!
```

<https://riptutorial.com/zh-TW/kotlin/topic/10936/>

13:

◦

◦

JVMJAR kotlin-reflect.jar ◦ JS◦

Examples

KClass

```
val c1 = String::class
val c2 = MyClass::class
```

Kotlin◦

```
fun isPositive(x: Int) = x > 0

val numbers = listOf(-2, -1, 0, 1, 2)
println(numbers.filter(::isPositive)) // [1, 2]
```

Java

KotlinKClassJavaClass KClass.java

```
val stringKClass: KClass<String> = String::class
val c1: Class<String> = stringKClass.java

val c2: Class<MyClass> = MyClass::class.java
```

KClass◦

BaseExampleExample

```
open class BaseExample(val baseField: String)

class Example(val field1: String, val field2: Int, baseField: String):
    BaseExample(baseField) {

    val field3: String
        get() = "Property without backing field"

    val field4 by lazy { "Delegated value" }

    private val privateField: String = "Private value"
}
```

```
val example = Example(field1 = "abc", field2 = 1, baseField = "someText")
```

```
example::class.memberProperties.forEach { member ->
    println("${member.name} -> ${member.get(example)}")
}
```

◦ ◦ `private val privateField`**private**member.get(example)◦ ◦ **Java getter**◦ `private val getter`

```
fun isFieldAccessible(property: KProperty1<*, *>): Boolean {
    return property.javaGetter?.modifiers?.let { !Modifier.isPrivate(it) } ?: false
}

val example = Example(field1 = "abc", field2 = 1, baseField = "someText")

example::class.memberProperties.filter { isFieldAccessible(it) }.forEach { member ->
    println("${member.name} -> ${member.get(example)}")
}
```

```
example::class.memberProperties.forEach { member ->
    member.isAccessible = true
    println("${member.name} -> ${member.get(example)}")
}
```

```
class TestClass {
    val readOnlyProperty: String
        get() = "Read only!"

    var readWriteString = "asd"
    var readWriteInt = 23

    var readWriteBackedStringProperty: String = ""
        get() = field + '5'
        set(value) { field = value + '5' }

    var readWriteBackedIntProperty: Int = 0
        get() = field + 1
        set(value) { field = value - 1 }

    var delegatedProperty: Int by TestDelegate()

    private var privateProperty = "This should be private"

    private class TestDelegate {
        private var backingField = 3

        operator fun getValue(thisRef: Any?, prop: KProperty<*>): Int {
            return backingField
        }

        operator fun setValue(thisRef: Any?, prop: KProperty<*>, value: Int) {
            backingField += value
        }
    }
}
```

◦ ◦

```
val instance = TestClass()
TestClass::class.memberProperties
    .filter{ prop.visibility == KVisibility.PUBLIC }
    .filterIsInstance<KMutableProperty<*>>()
    .forEach { prop ->
        System.out.println("${prop.name} -> ${prop.get(instance)}")
    }
```

String"Our Value"。 KotlinJava VM Type Erasure List<String> Properties List<Any>。。

```
val instance = TestClass()
TestClass::class.memberProperties
    .filter{ prop.visibility == KVisibility.PUBLIC }
    // We only want strings
    .filter{ it.returnType.isSubtypeOf(String::class.starProjectedType) }
    .filterIsInstance<KMutableProperty<*>>()
    .forEach { prop ->
        // Instead of printing the property we set it to some value
        prop.setter.call(instance, "Our Value")
    }
```

<https://riptutorial.com/zh-TW/kotlin/topic/2402/>

14:

Kotlin4。

-
-
-
-
- <visibility modifier> val/var <variable name> = <value>

Examples

```
public val name = "Avijit"  
  
private val name = "Avijit"  
  
protected val name = "Avijit"  
  
internal val name = "Avijit"
```

<https://riptutorial.com/zh-TW/kotlin/topic/10019/>

15:

object javaSingletons.java.Javakotlin.

Examples

java/

```
object CommonUtils {  
  
    var anyname: String ="Hello"  
  
    fun dispMsg(message: String) {  
        println(message)  
    }  
}
```

```
CommonUtils.anyname  
CommonUtils.dispMsg("like static call")
```

Kotlin SomeSingleton.INSTANCE.

java

```
public enum SharedRegistry {  
    INSTANCE;  
    public void register(String key, Object thing) {}  
}  
  
public static void main(String[] args) {  
    SharedRegistry.INSTANCE.register("a", "apple");  
    SharedRegistry.INSTANCE.register("b", "boy");  
    SharedRegistry.INSTANCE.register("c", "cat");  
    SharedRegistry.INSTANCE.register("d", "dog");  
}
```

kotlin

```
object SharedRegistry {  
    fun register(key: String, thing: Object) {}  
}  
  
fun main(Array<String> args) {  
    SharedRegistry.register("a", "apple")  
    SharedRegistry.register("b", "boy")  
    SharedRegistry.register("c", "cat")  
    SharedRegistry.register("d", "dog")  
}
```

◦

<https://riptutorial.com/zh-TW/kotlin/topic/10152/>

16: KotlinRecyclerView

KotlinRecyclerView。

Examples

Kotlinactivity_main.xmlRecyclerView。

```
class MainActivity : AppCompatActivity() {

    lateinit var mRecyclerView : RecyclerView
    val mAdapter : RecyclerViewAdapter = RecyclerViewAdapter()

    override fun onCreate(savedInstanceState: Bundle?) {
        super.onCreate(savedInstanceState)
        setContentView(R.layout.activity_main)
        val toolbar = findViewById(R.id.toolbar) as Toolbar
        setSupportActionBar(toolbar)

        mRecyclerView = findViewById(R.id.recycler_view) as RecyclerView

        mRecyclerView.setHasFixedSize(true)
        mRecyclerView.layoutManager = LinearLayoutManager(this)
        mAdapter.RecyclerView(getList(), this)
        mRecyclerView.adapter = mAdapter
    }

    private fun getList(): ArrayList<String> {
        var list : ArrayList<String> = ArrayList()
        for (i in 1..10) { // equivalent of 1 <= i && i <= 10
            println(i)
            list.add("$i")
        }
        return list
    }
}
```

Recyclermain_item.xml

```
class RecyclerViewAdapter : RecyclerView.Adapter<RecyclerViewAdapter.ViewHolder>() {

    var mItems: ArrayList<String> = ArrayList()
    lateinit var mClick : OnClick

    fun RecyclerViewAdapter(item : ArrayList<String>, mClick : OnClick){
        this.mItems = item
        this.mClick = mClick;
    }

    override fun onBindViewHolder(holder: ViewHolder, position: Int) {
        val item = mItems[position]
        holder.bind(item, mClick, position)
    }

    override fun onCreateViewHolder(parent: ViewGroup, viewType: Int): ViewHolder {
```

```
    val layoutInflater = LayoutInflater.from(parent.context)
    return ViewHolder(layoutInflater.inflate(R.layout.main_item, parent, false))
}

override fun getItemCount(): Int {
    return mItems.size
}

class ViewHolder(view: View) : RecyclerView.ViewHolder(view) {
    val card = view.findViewById(R.id.card) as TextView
    fun bind(str: String, mClick: OnClick, position: Int){
        card.text = str
        card.setOnClickListener { view ->
            mClick.onClickListner(position)
        }
    }
}
}
```

KotlinRecyclerView <https://riptutorial.com/zh-TW/kotlin/topic/10143/kotlinrecyclerview>

17: Lambdas

- {parameterName: ParameterType otherParameterName: OtherParameterType -> anExpression}
-
- val addition: Int -> Int = {a, b -> a + b}
- it
- val square: Int -> Int = {it * it}
-
- -> ResultType
- InputType -> ResultType
- InputType1 InputType2 -> ResultType

```
data class User(val fistName: String, val lastName: String) {  
    fun username(userNameGenerator: (String, String) -> String) =  
        userNameGenerator(fistName, secondName)  
}
```

lambda lambda

```
val user = User("foo", "bar")  
println(user.username { firstName, secondName ->  
    "${firstName.toUpperCase()}"_"${secondName.toUpperCase()}"  
}) // prints FOO_BAR
```

lambda

```
// valid:  
val addition: (Int, Int) = { a, b -> a + b }  
// valid:  
val addition = { a: Int, b: Int -> a + b }  
// error (type inference failure):  
val addition = { a, b -> a + b }
```

lambda it.

```
listOf(1, 2, 3).map { it * 2 } // [2, 4, 6]
```

Examples

Lambda

```
val allowedUsers = users.filter { it.age > MINIMUM_AGE }
```

Lambda

```
val isOfAllowedAge = { user: User -> user.age > MINIMUM_AGE }
val allowedUsers = users.filter(isOfAllowedAge)
```

Lambda

```
object Benchmark {
    fun realtime(body: () -> Unit): Duration {
        val start = Instant.now()
        try {
            body()
        } finally {
            val end = Instant.now()
            return Duration.between(start, end)
        }
    }
}
```

```
val time = Benchmark.realtime({
    // some long-running code goes here ...
})
println("Executed the code in $time")
```

Lambdas <https://riptutorial.com/zh-TW/kotlin/topic/5878/lambda>

18:

Kotlin

Examples

```
val foo : Int by lazy { 1 + 1 }
println(foo)
```

2

```
var foo : Int by Delegates.observable("1") { property, oldValue, newValue ->
    println("${property.name} was changed from $oldValue to $newValue")
}
foo = 2
```

foo was changed from 1 to 2
foo was changed from 1 to 2

```
val map = mapOf("foo" to 1)
val foo : String by map
println(foo)
```

1

```
class MyDelegate {
    operator fun getValue(owner: Any?, property: KProperty<*>): String {
        return "Delegated value"
    }
}

val foo : String by MyDelegate()
println(foo)
```

Delegated value

KotlinNull Type WeakReference<T>

WeakReference

```
class MyMemoryExpensiveClass {
    companion object {
        var reference: WeakReference<MyMemoryExpensiveClass>? = null

        fun doWithReference(block: (MyMemoryExpensiveClass) -> Unit) {
            reference?.let {
                it.get()?.let(block)
            }
        }
    }

    init {
```

```
        reference = WeakReference(this)
    }
}
```

WeakReference

```
class WeakReferenceDelegate<T>(initialValue: T? = null) : ReadWriteProperty<Any, T?> {
    var reference = WeakReference(initialValue)
    private set

    override fun getValue(thisRef: Any, property: KProperty<*>): T? = reference.get()

    override fun setValue(thisRef: Any, property: KProperty<*>, value: T?) {
        reference = WeakReference(value)
    }
}
```

WeakReference

```
class MyMemoryExpensiveClass {
    companion object {
        var reference: MyMemoryExpensiveClass? by
            WeakReferenceDelegate<MyMemoryExpensiveClass>()

        fun doWithReference(block: (MyMemoryExpensiveClass) -> Unit) {
            reference?.let(block)
        }
    }

    init {
        reference = this
    }
}
```

<https://riptutorial.com/zh-TW/kotlin/topic/10571/>

Examples

String `string[index] string[index]`。

```
val str = "Hello, World!"
println(str[1]) // Prints e
```

for。

```
for (c in str) {
    println(c)
}
```

Kotlin

-
-
- ◦ ◦ \t \b \n \r \' \" \\\\$ ◦ **Unicode** \uFF00 ◦

```
val s = "Hello, world!\n"
```

"""

```
val text = """
    for (c in "foo")
        print(c)
"""

```

trimMargin◦

```
val text = """
    |Tell me and I forget.
    |Teach me and I remember.
    |Involve me and I learn.
    |(Benjamin Franklin)
"""
.trimMargin()
```

| **trimMargin**; `trimMargin(">")` ◦

◦ ◦ \$

```
val i = 10
val s = "i = $i" // evaluates to "i = 10"
```

```
val s = "abc"
```

```
val str = "$s.length is ${s.length}" // evaluates to "abc.length is 3"
```

```
val str = "\$foo" // evaluates to "$foo"
```

◦ ◦

```
val price = """
${'$'}9.99
"""
```

Kotlin==

```
val str1 = "Hello, World!"
val str2 = "Hello," + " World!"
println(str1 == str2) // Prints true
```

====◦

```
val str1 = """
|Hello, World!
""".trimMargin()

val str2 = """
#Hello, World!
""".trimMargin("#")

val str3 = str1

println(str1 == str2) // Prints true
println(str1 === str2) // Prints false
println(str1 === str3) // Prints true
```

<https://riptutorial.com/zh-TW/kotlin/topic/8285/>

20:

Examples

DTOPOJO / POCO

kotlin ◦ data

```
data class User(var firstname: String, var lastname: String, var age: Int)
```

User

- val **s**
- equals()
- hashCode()
- toString()
- copy()
- componentN() N

```
data class User(var firstname: String = "Joe", var lastname: String = "Bloggs", var age: Int = 20)
```

◦

```
val list = listOf(1,2,3,4,5,6)

//filter out even numbers

val even = list.filter { it % 2 == 0 }

println(even) //returns [2,4]
```

◦ ◦ ◦

```
class MyTable private constructor(table: Table<Int, Int, Int>) : Table<Int, Int, Int> by table {

    constructor() : this(TreeBasedTable.create()) // or a different type of table if desired

}
```

MyTable MyTable() ◦ MyTableTable<Int, Int, Int> ◦ ◦

so.

KotlinSerializableserialVersionUID

KotlinserialVersionUID ◦

```
private const val MySpecialCase

class MySpecialCase : Serializable {
    companion object {
        private const val serialVersionUID: Long = 123
    }
}
```

getter / setter...

```
class MySpecialCase : Serializable {
    companion object {
        private val serialVersionUID: Long = 123
    }
}
```

getSerialVersionUID**getter**getSerialVersionUID °

```
class MySpecialCase : Serializable {
    companion object {
        @JvmStatic private val serialVersionUID: Long = 123
    }
}
```

MySpecialCase**getter**getSerialVersionUID °

serialVersionUIDSerializable°

Kotlin

KotlinJava

```
fun doSomething() {
    someOtherAction()
    return this
}
```

```
fun <T: Any> T.fluently(func: ()->Unit): T {
    func()
    return this
}
```

```
fun doSomething() {
    return fluently { someOtherAction() }
}
```

let

let **Kotlin**°

```
val str = "foo"
str.let {
    println(it) // it
}
```

"foo"Unit。

let also *let*◦ *also* **reutrn** *Unit*◦

null null letalso

```
val str: String? = someFun()
str?.let {
    println(it)
}
```

strnulllet◦ null ?◦

apply

apply

thisthis◦

kdocapply◦ apply thisapply◦ ◦

```
File(dir).apply { mkdirs() }
```

```
fun makeDir(String path): File {
    val result = new File(path)
    result.mkdirs()
    return result
}
```

<https://riptutorial.com/zh-TW/kotlin/topic/2273/>

Kotlin

Examples

Kotlin.

```
interface MyInterface {
    fun bar()
}
```

```
class Child : MyInterface {
    override fun bar() {
        print("bar() was called")
    }
}
```

Kotlin

```
interface MyInterface {
    fun withImplementation() {
        print("withImplementation() was called")
    }
}
```

```
class MyClass: MyInterface {
    // No need to reimplement here
}
val instance = MyClass()
instance.withImplementation()
```

gettersetter

```
interface MyInterface2 {
    val helloWorld
        get() = "Hello World!"
}
```

```
interface MyInterface3 {
    // this property won't compile!
    var helloWorld: Int
        get() = field
        set(value) { field = value }
}
```

```
interface A {
    fun notImplemented()
    fun implementedOnlyInA() { print("only A") }
```

```

        fun implementedInBoth() { print("both, A") }
        fun implementedInOne() { print("implemented in A") }
    }

interface B {
    fun implementedInBoth() { print("both, B") }
    fun implementedInOne() // only defined
}

class MyClass: A, B {
    override fun notImplemented() { print("Normal implementation") }

    // implementedOnlyInA() can be normally used in instances

    // class needs to define how to use interface functions
    override fun implementedInBoth() {
        super<B>.implementedInBoth()
        super<A>.implementedInBoth()
    }

    // even if there's only one implementation, there multiple definitions
    override fun implementedInOne() {
        super<A>.implementedInOne()
        print("implementedInOne class implementation")
    }
}

```

◦ ◦

```

interface MyInterface {
    val property: Int // abstract

    val propertyWithImplementation: String
        get() = "foo"

    fun foo() {
        print(property)
    }
}

class Child : MyInterface {
    override val property: Int = 29
}

```

◦ ◦ ◦

```

interface FirstTrait {
    fun foo() { print("first") }
    fun bar()
}

interface SecondTrait {
    fun foo() { print("second") }
    fun bar() { print("bar") }
}

class ClassWithConflict : FirstTrait, SecondTrait {
    override fun foo() {

```

```
super<FirstTrait>.foo() // delegate to the default implementation of FirstTrait
super<SecondTrait>.foo() // delegate to the default implementation of SecondTrait
}

// function bar() only has a default implementation in one interface and therefore is ok.
}
```

```
interface MyInterface {
    fun funcOne() {
        //optional body
        print("Function with default implementation")
    }
}
```

super。

```
super.funcOne()
```

<https://riptutorial.com/zh-TW/kotlin/topic/900/>

22:

- fun TypeName.extensionNameparams...{/ * body * /} //
 - fun <TAny> TypeNameWithGenerics <T>.extensionNameparams...{/ * body * /} //
 - myObj.extensionNameargs...//
- reference-type;◦ ◦

Examples

◦

```
fun IntArray.addTo(dest: IntArray) {  
    for (i in 0 .. size - 1) {  
        dest[i] += this[i]  
    }  
}
```

IntArrayIntArray ◦ this ◦

```
val myArray = intArrayOf(1, 2, 3)  
intArrayOf(4, 5, 6).addTo(myArray)
```

◦ ◦

```
open class Super  
  
class Sub : Super()  
  
fun Super.myExtension() = "Defined for Super"  
  
fun Sub.myExtension() = "Defined for Sub"  
  
fun callMyExtension(myVar: Super) {  
    println(myVar.myExtension())  
}  
  
callMyExtension(Sub())
```

"Defined for Super" myVarSuper ◦

IntLong

```
fun Long.humanReadable(): String {  
    if (this <= 0) return "0"  
    val units = arrayOf("B", "KB", "MB", "GB", "TB", "EB")  
    val digitGroups = (Math.log10(this.toDouble()) / Math.log10(1024.0)).toInt();  
    return DecimalFormat("#,##0.#").format(this/Math.pow(1024.0, digitGroups.toDouble())) + "  
" + units[digitGroups];  
}
```

```
fun Int.humanReadable(): String {
    return this.toLong().humanReadable()
}
```

```
println(1999549L.humanReadable())
println(someInt.humanReadable())
```

Java 7+ Path

API `exist` `notExists` `deleteRecursively` **Java 7+** `Path`

```
fun Path.exists(): Boolean = Files.exists(this)
fun Path.notExists(): Boolean = !this.exists()
fun Path.deleteRecursively(): Boolean = this.toFile().deleteRecursively()
```

```
val dir = Paths.get(dirName)
if (dir.exists()) dir.deleteRecursively()
```

Kotlin

```
val x: Path = Paths.get("dirName").apply {
    if (Files.notExists(this)) throw IllegalStateException("The important file does not exist")
}
```

apply. .

```
infix inline fun <T> T.verifiedBy(verifyWith: (T) -> Unit): T {
    verifyWith(this)
    return this
}

infix inline fun <T: Any> T.verifiedWith(verifyWith: T.() -> Unit): T {
    this.verifyWith()
    return this
}
```

```
val x: Path = Paths.get("dirName") verifiedWith {
    if (Files.notExists(this)) throw IllegalStateException("The important file does not
exist")
}
```

lambda.

TverifiedByT: Any?◦ verifiedWith◦

Java 8 TemporalISO

```
fun Temporal.toISOString(): String = DateTimeFormatter.ISO_INSTANT.format(this)
```

```
val dateAsString = someInstant.toIsoString()
```

Companion

- SomethingfromString

```
class Something {  
    companion object {}  
}  
  
class SomethingElse {  
}  
  
fun Something.Companion.fromString(s: String): Something = ...  
  
fun SomethingElse.fromString(s: String): SomethingElse = ...  
  
fun main(args: Array<String>) {  
    Something.fromString("") //valid as extension function declared upon the  
                           //companion object  
  
    SomethingElse().fromString("") //valid, function invoked on instance not  
                           //statically  
  
    SomethingElse.fromString("") //invalid  
}
```

◦ this **KotlinKT-9686KT-13053** ◦ ◦

color ◦ colorCache thislazy

```
class KColor(val value: Int)  
  
private val colorCache = mutableMapOf<KColor, Color>()  
  
val KColor.color: Color  
    get() = colorCache.getOrPut(this) { Color(value, true) }
```

View◦

Anko

```
inline fun <reified T : View> View.find(id: Int): T = findViewById(id) as T  
inline fun <reified T : View> Activity.find(id: Int): T = findViewById(id) as T  
inline fun <reified T : View> Fragment.find(id: Int): T = view?.findViewById(id) as T  
inline fun <reified T : View> RecyclerView.ViewHolder.find(id: Int): T =  
itemView?.findViewById(id) as T  
  
inline fun <reified T : View> View.findOptional(id: Int): T? = findViewById(id) as? T  
inline fun <reified T : View> Activity.findOptional(id: Int): T? = findViewById(id) as? T  
inline fun <reified T : View> Fragment.findOptional(id: Int): T? = view?.findViewById(id) as?  
T  
inline fun <reified T : View> RecyclerView.ViewHolder.findOptional(id: Int): T? =  
itemView?.findViewById(id) as? T
```

```
val yourButton by lazy { find<Button>(R.id.yourButtonId) }
val yourText by lazy { find<TextView>(R.id.yourTextId) }
val yourEdittextOptional by lazy { findOptional<EditText>(R.id.yourOptionEdittextId) }
```

<https://riptutorial.com/zh-TW/kotlin/topic/613/>

23:

Examples

Kotlin `Array<T>`。

```
emptyArray<T>()
```

```
val empty = emptyArray<String>()

var strings = Array<String>(size = 5, init = { index -> "Item #$index" })
print(Arrays.toString(a)) // prints "[Item #0, Item #1, Item #2, Item #3, Item #4]"
print(a.size) // prints 5
```

```
get(index: Int): T set(index: Int, value: T)
```

```
strings.set(2, "ChangedItem")
print(strings.get(2)) // prints "ChangedItem"

// You can use subscription as well:
strings[2] = "ChangedItem"
print(strings[2]) // prints "ChangedItem"
```

Array<T>。

Kotlin		JVM
BooleanArray	<code>booleanArrayOf(true, false)</code>	<code>boolean[]</code>
ByteArray	<code>byteArrayOf(1, 2, 3)</code>	<code>byte[]</code>
CharArray	<code>charArrayOf('a', 'b', 'c')</code>	<code>char[]</code>
DoubleArray	<code>doubleArrayOf(1.2, 5.0)</code>	<code>double[]</code>
FloatArray	<code>floatArrayOf(1.2, 5.0)</code>	<code>float[]</code>
IntArray	<code>intArrayOf(1, 2, 3)</code>	<code>int[]</code>
LongArray	<code>longArrayOf(1, 2, 3)</code>	<code>long[]</code>
ShortArray	<code>shortArrayOf(1, 2, 3)</code>	<code>short[]</code>

```
average() Byte Int Long Short Double FloatDouble
```

```
val doubles = doubleArrayOf(1.5, 3.0)
print(doubles.average()) // prints 2.25

val ints = intArrayOf(1, 4)
println(ints.average()) // prints 2.5
```

```
component1() component2() ... component5()

indexgetOrNull(index: Int)null

first() last()

toHashSet () HashSet<T>

sortedArray() sortedArrayDescending()current

sort() sortDescending

min() max()
```

Java: in ◦

```
val asc = Array(5, { i -> (i * i).toString() })
for(s : String in asc){
    println(s);
}
```

for◦

```
val asc = Array(5, { i -> (i * i).toString() })
for(s in asc){
    println(s);
}
```

```
val a = arrayOf(1, 2, 3) // creates an Array<Int> of size 3 containing [1, 2, 3].
```

```
val a = Array(3) { i -> i * 2 } // creates an Array<Int> of size 3 containing [0, 2, 4]
```

```
val a = arrayOfNulls<Int>(3) // creates an Array<Int?> of [null, null, null]
```

◦ ◦

<https://riptutorial.com/zh-TW/kotlin/topic/5722/>

24:

JavaKotlin。EnumClass

```
EnumClass.valueOf(value: String): EnumClass  
EnumClass.values(): Array<EnumClass>
```

```
valueOf()IllegalArgumentException。
```

```
val name: String  
val ordinal: Int
```

Comparable。

Examples

```
enum class Color(val rgb: Int) {  
    RED(0xFF0000),  
    GREEN(0x00FF00),  
    BLUE(0x0000FF)  
}
```

◦ ; ◦

abstract ◦

```
enum class Color {  
    RED {  
        override val rgb: Int = 0xFF0000  
    },  
    GREEN {  
        override val rgb: Int = 0x00FF00  
    },  
    BLUE {  
        override val rgb: Int = 0x0000FF  
    }  
;  
abstract val rgb: Int  
  
fun colorString() = "#%06X".format(0xFFFFFFF and rgb)  
}
```

```
enum class Color {  
    RED, GREEN, BLUE  
}
```

◦ ◦

```
enum class Planet(var population: Int = 0) {
    EARTH(7 * 100000000),
    MARS();

    override fun toString() = "$name [population=$population]"
}

println(Planet.MARS) // MARS [population=0]
Planet.MARS.population = 3
println(Planet.MARS) // MARS [population=3]
```

<https://riptutorial.com/zh-TW/kotlin/topic/2286/>

25:

Java switch when。 break。 behaviors

```
when (x) {  
    "foo", "bar" -> println("either foo or bar")  
    else -> println("didn't match anything")  
}
```

Examples

if

```
val str = "Hello!"  
if (str.length == 0) {  
    print("The string is empty!")  
} else if (str.length > 5) {  
    print("The string is short!")  
} else {  
    print("The string is long!")  
}
```

else-branches if。

if

if

```
val str = if (condition) "Condition met!" else "Condition not met!"
```

elseif。

else if。

```
val str = if (condition1){  
    "Condition1 met!"  
} else if (condition2) {  
    "Condition2 met!"  
} else {  
    "Conditions not met!"  
}
```

Kotlin val str: String =

when if-else-if

when else-if-branches if

```

when {
    str.length == 0 -> print("The string is empty!")
    str.length > 5  -> print("The string is short!")
    else             -> print("The string is long!")
}

```

if-else-if

```

if (str.length == 0) {
    print("The string is empty!")
} else if (str.length > 5) {
    print("The string is short!")
} else {
    print("The string is long!")
}

```

ifelse-branch。

```

when {
    condition -> {
        doSomething()
        doSomeMore()
    }
    else -> doSomethingElse()
}

```

when

when -statement `==equals` `o`

```

when (x) {
    "English" -> print("How are you?")
    "German" -> print("Wie geht es dir?")
    else -> print("I don't know that language yet :(")
}

```

when

```

val names = listOf("John", "Sarah", "Tim", "Maggie")
when (x) {
    in names -> print("I know that name!")
    !in 1..10 -> print("Argument was not in the range from 1 to 10")
    is String -> print(x.length) // Due to smart casting, you can use String-functions here
}

```

```

val greeting = when (x) {
    "English" -> "How are you?"
    "German" -> "Wie geht es dir?"
    else -> "I don't know that language yet :("
}
print(greeting)

```

whenelse `o`

when enum

```
enum class Day {
    Sunday,
    Monday,
    Tuesday,
    Wednesday,
    Thursday,
    Friday,
    Saturday
}

fun doOnDay(day: Day) {
    when(day) {
        Day.Sunday ->      // Do something
        Day.Monday, Day.Tuesday ->      // Do other thing
        Day.Wednesday ->    // ...
        Day.Thursday ->    // ...
        Day.Friday ->     // ...
        Day.Saturday ->   // ...
    }
}
```

Tuesday MondayTuesday enum◦

◦ else

```
fun doOnDay(day: Day) {
    when(day) {
        Day.Monday ->      // Work
        Day.Tuesday ->     // Work hard
        Day.Wednesday ->   // ...
        Day.Thursday ->    //
        Day.Friday ->     //
        else ->           // Party on weekend
    }
}
```

if-then-else when enum◦

kotlin enum

<https://riptutorial.com/zh-TW/kotlin/topic/2685/>

26:

Examples

“”。 when“” - 。

```
import kotlin.text.regex

var string = /* some string */

val regex1 = Regex( /* pattern */ )
val regex2 = Regex( /* pattern */ )
/* etc */

when {
    regex1.matches(string) -> /* do stuff */
    regex2.matches(string) -> /* do stuff */
    /* etc */
}
```

“”。 whenwhen。

```
import kotlin.text.regex

var string = /* some string */

when {
    Regex( /* pattern */ ).matches(string) -> /* do stuff */
    Regex( /* pattern */ ).matches(string) -> /* do stuff */
    /* etc */
}
```

whenwhen“argument-ful”。 whenwhenEntrywhen。 “immutable locals”“anonymous temporaries”。

```
import kotlin.text.regex

var string = /* some string */

when (RegexWhenArgument(string)) {
    Regex( /* pattern */ ) -> /* do stuff */
    Regex( /* pattern */ ) -> /* do stuff */
    /* etc */
}
```

when

```
class RegexWhenArgument (val whenArgument: CharSequence) {
    operator fun equals(whenEntry: Regex) = whenEntry.matches(whenArgument)
    override operator fun equals(whenEntry: Any?) = (whenArgument == whenEntry)
}
```

Kotlin

Regex Regex null.

RegEx

Kotlin Regex(pattern: String) regex find(..) replace(..).

Regex in input cd true

```
val regex = Regex(pattern = "c|d")
val matched = regex.containsMatchIn(input = "abc")      // matched: true
```

Regex pattern in input . containsMatchIn(..).

find(..) matchEntire(..) MatchResult? . ? MatchResult Kotlin null.

find(..) null Kotlin Regex null

```
val matchResult =
    Regex("c|d").find("efg")           // matchResult: null
val a = matchResult?.value           // a: null
val b = matchResult?.value.orEmpty() // b: ""
a?.toUpperCase()                   // Still needs question mark. => null
b.toUpperCase()                    // Accesses the function directly. => ""
```

orEmpty() b null ? b .

Kotlin Java !!

```
a!! .toUpperCase()                  // => KotlinNullPointerException
```

Kotlin Java Java .

```
"""\d{3}-\d{3}-\d{4}"" " raw Kotlin string
"\\" \d{3}-\\" \d{3}-\\ \d{4}" // standard Java string
```

findCharSequence startInt MatchResult

input Regex pattern . MatchResult? startInt in input null . MatchResult? MatchResult? value . startInt 0 .

```
val phoneNumber :String? = Regex(pattern = """\d{3}-\d{3}-\d{4}""")
```

```
.find(input = "phone: 123-456-7890, e..")?.value // phoneNumber: 123-456-7890
```

```
input.phoneNumbernull。
```

findAllInInputCharSequencesstartIndexInt Sequence

```
patterninput。
```

```
val matchedResults = Regex(pattern = """\d+""").findAll(input = "ab12cd34ef")
val result = StringBuilder()
for (matchedText in matchedResults) {
    result.append(matchedText.value + " ")
}
println(result) // => 12 34
```

```
matchedResultsMatchResult。inputfindAll(..)。
```

matchEntireCharSequenceMatchResult

```
inputpatterninput。null。
```

```
val a = Regex("""\d+""").matchEntire("100")?.value // a: 100
val b = Regex("""\d+""").matchEntire("100 dollars")?.value // b: null
```

matchesCharSequenceBoolean

```
true。。
```

```
val regex = Regex(pattern = """\d+""")
regex.matches(input = "50") // => true
regex.matches(input = "50 dollars") // => false
```

containsMatchInInputCharSequenceBoolean

```
true。。
```

```
Regex("""\d+""").containsMatchIn("50 dollars") // => true
Regex("""\d+""").containsMatchIn("Fifty dollars") // => false
```

splitCharSequenceLimitIntList

◦

```
val a = Regex("""\d+""").split("ab12cd34ef")      // a: [ab, cd, ef]
val b = Regex("""\d+""").split("This is a test") // b: [This is a test]
```

◦ input ◦

replaceCharSequenceReplacementString String

inputpattern◦

x

```
val result = Regex("""\d+""").replace("ab12cd34ef", "x") // result: abxcdxef
```

<https://riptutorial.com/zh-TW/kotlin/topic/8364/>

27:

◦ List◦

◦

- class *ClassName* < **TypeName** >
- class *ClassName* <*>
- *ClassName* <in **UpperBound** >
- *ClassName* <out **LowerBound** >
- class *Name* < **TypeName** **UpperBound** >



Kotlin Generics_{TAny?} ◦

```
class Consumer<T>
```

TT: Any? ◦ T: Any ◦

```
class Consumer<T: Any>
```

Examples

-

- ◦

```
class Consumer<in T> { fun consume(t: T) { ... } }

fun charSequencesConsumer() : Consumer<CharSequence>() = ...

val stringConsumer : Consumer<String> = charSequenceConsumer() // OK since in-projection
val anyConsumer : Consumer<Any> = charSequenceConsumer() // Error, Any cannot be passed

val outConsumer : Consumer<out CharSequence> = ... // Error, T is `in`-parameter
```

- List<out T> TComparator<in T> T◦

Java

```
val takeList : MutableList<out SomeType> = ... // Java: List<? extends SomeType>
val takenValue : SomeType = takeList[0] // OK, since upper bound is SomeType
takeList.add(takenValue) // Error, lower bound for generic is not specified
```

```
val putList : MutableList<in SomeType> = ... // Java: List<? super SomeType>
val valueToPut : SomeType = ...
putList.add(valueToPut) // OK, since lower bound is SomeType
putList[0] // This expression has type Any, since no upper bound is specified
```

```
val starList : MutableList<*> = ... // Java: List<?>
starList[0] // This expression has type Any, since no upper bound is specified
starList.add(someValue) // Error, lower bound for generic is not specified
```

- JavaKotlinVariant Generics.

<https://riptutorial.com/zh-TW/kotlin/topic/1147/>

Examples

NullableNon Nullable

`String` 。 ? `String?`

```
var string      : String = "Hello World!"
var nullableString: String? = null

string = nullableString    // Compiler error: Can't assign nullable to non-nullable type.
nullableString = string    // This will work however!
```

◦

? . `nullnull`;

```
val string: String? = "Hello World!"
print(string.length)    // Compile error: Can't directly access property of nullable type.
print(string?.length)   // Will print the string's length, or "null" if the string is null.
```

null

nullKotlin`apply`

```
obj?.apply {
    foo()
    bar()
}
```

`obj` `foobar` `this` `apply` `this` `obj` `null`。

`let` `apply`

```
nullable?.let { notnull ->
    notnull.foo()
    notnull.bar()
}
```

`notnull` `lambda` `it`。

null

```
var string: String? = "Hello!"
print(string.length)    // Compile error
if(string != null) {
    // The compiler now knows that string can't be null
```

```
    print(string.length) // It works now!
}
```

null.

◦

Iterable

Collection<T?>Collections<T> ◦ filterNotNull◦

```
val a: List<Int?> = listOf(1, 2, 3, null)
val b: List<Int> = a.filterNotNull()
```

Null Coalescing / Elvis

if-else◦ elvis?: Kotlin◦

```
val value: String = data?.first() ?: "Nothing here."
```

data?.first()datanull"Nothing here"data?.first()data?.first()◦

◦

```
val value: String = data?.second()
?: throw IllegalArgumentException("Value can't be null!")
```

NullPointerExceptionsdata!! .second()!!

!!nullabilitynull◦ nullKotlinNullPointerException◦

```
val message: String? = null
println(message!!) //KotlinNullPointerException thrown, app crashes
```

:)

Kotlinnull reference◦ a “anullx”

```
var a: String? = "Nullable String Value"
```

anull◦ a◦ if...else◦

```
val b: Int = if (a != null) a.length else -1
```

Elvis ?:if...elseElvis

```
val b = a?.length ?: -1
```

```
?: a?.length nullelvis -1 ◦ ◦
```

<https://riptutorial.com/zh-TW/kotlin/topic/2080/>

Kotlin

Examples

```
interface Foo {  
    fun example()  
}  
  
class Bar {  
    fun example() {  
        println("Hello, world!")  
    }  
}  
  
class Baz(b : Bar) : Foo by b  
  
Baz(Bar()).example()
```

Hello, world!

<https://riptutorial.com/zh-TW/kotlin/topic/10575/>

30: kotlin

Kotlin

Examples

kotlin.logging

```
class FooWithLogging {
    companion object: KLogging()

    fun bar() {
        logger.info { "hello $name" }
    }

    fun logException(e: Exception) {
        logger.error(e) { "Error occurred" }
    }
}
```

kotlin.logging

kotlin <https://riptutorial.com/zh-TW/kotlin/topic/3258/kotlin>

31:

Kotlin plain int

Examples

X

```
repeat(10) { i ->
    println("This line will be printed 10 times")
    println("We are on the ${i + 1}. loop iteration")
}
```

iterables

for iterable

```
val list = listOf("Hello", "World", "!")
for(str in list) {
    print(str)
}
```

Kotlin

```
for(i in 0..9) {
    print(i)
}
```

```
for((index, element) in iterable.withIndex()) {
    print("$element at index $index")
}
```

forEach

```
iterable.forEach {
    print(it.toString())
}
```

it Lambda

while do-while

```
while(condition) {
    doSomething()
}

do {
    doSomething()
```

```
} while (condition)
```

do-while◦

◦

```
while(true) {  
    if(condition1) {  
        continue // Will immediately start the next iteration, without executing the rest of  
        the loop body  
    }  
    if(condition2) {  
        break // Will exit the loop completely  
    }  
}
```

breakcontinue

```
outer@ for(i in 0..10) {  
    inner@ for(j in 0..10) {  
        break      // Will break the inner loop  
        break@inner // Will break the inner loop  
        break@outer // Will break the outer loop  
    }  
}
```

forEach◦

kotlin

```
//iterates over a map, getting the key and value at once  
  
var map = hashMapOf(1 to "foo", 2 to "bar", 3 to "baz")  
  
for ((key, value) in map) {  
    println("Map[$key] = $value")  
}
```

Kotlin◦

```
fun factorial(n: Long): Long = if (n == 0) 1 else n * factorial(n - 1)  
  
println(factorial(10)) // 3628800
```

factorial◦

Kotlin◦

map◦

```
val numbers = listOf(1, 2, 3, 4, 5, 6, 7, 8, 9, 0)
```

```
val numberStrings = numbers.map { "Number $it" }
```

◦ ◦ **filter**◦

```
val numbers = listOf(1, 2, 3, 4, 5, 6, 7, 8, 9, 0)
val numberStrings = numbers.filter { it % 2 == 0 }.map { "Number $it" }
```

<https://riptutorial.com/zh-TW/kotlin/topic/2727/>

32:

rangeTo..in..

Examples

IntRangeLongRangeCharRange。 Java for-loop

```
for (i in 1..4) print(i) // prints "1234"  
for (i in 4..1) print(i) // prints nothing
```

downTo

◦ downTo

```
for (i in 4 downTo 1) print(i) // prints "4321"
```

step

1step

```
for (i in 1..4 step 2) print(i) // prints "13"  
for (i in 4 downTo 1 step 2) print(i) // prints "42"
```

enduntil

```
for (i in 1 until 10) { // i in [1, 10), 10 is excluded  
    println(i)  
}
```

<https://riptutorial.com/zh-TW/kotlin/topic/10121/>

33:

Examples

◦

```
annotation class Strippable
```

```
@Target(AnnotationTarget.CLASS, AnnotationTarget.FUNCTION,  
AnnotationTarget.VALUE_PARAMETER, AnnotationTarget.EXPRESSION)  
annotation class Strippable
```

```
annotation class Strippable(val importanceValue: Int)
```

- JavaIntLong;
-
- Foo :: class
-
-
-
- @Target
- @Retention
- @Repeatable
- @MustBeDocumented API API

```
@Target(AnnotationTarget.CLASS, AnnotationTarget.FUNCTION,  
        AnnotationTarget.VALUE_PARAMETER, AnnotationTarget.EXPRESSION)  
@Retention(AnnotationRetention.SOURCE)  
@MustBeDocumented  
annotation class Fancy
```

<https://riptutorial.com/zh-TW/kotlin/topic/4074/>

34:

- (String) -> BooleanPair<Person, Person> ◦

- ◦

- **typealias alias-name = existing-type**

- JVM◦ ◦

Examples

```
typealias StringValidator = (String) -> Boolean
typealias Reductor<T, U, V> = (T, U) -> V
```

```
typealias Parents = Pair<Person, Person>
typealias Accounts = List<Account>
```

<https://riptutorial.com/zh-TW/kotlin/topic/9453/>

35: Kotlin

Examples

Gradle

```
kotlin-gradle-plugin GradleKotlin. Kotlin. Kotlin 1.0.3 kotlin-gradle-plugin 1.0.3°
```

```
gradle.propertiesExtraPropertiesExtension
```

```
buildscript {  
    ext.kotlin_version = '1.0.3'  
  
    repositories {  
        mavenCentral()  
    }  
  
    dependencies {  
        classpath "org.jetbrains.kotlin:kotlin-gradle-plugin:$kotlin_version"  
    }  
}
```

◦

JVM

```
apply plugin: 'kotlin'
```

Android

```
apply plugin: 'kotlin-android'
```

JS

```
apply plugin: 'kotlin2js'
```

- **kotlin** src/main/kotlin
- **java** src/main/java
- **kotlin** src/test/kotlin
- **java** src/test/java
- src/main/resources
- src/test/resources

```
SourceSets °
```

Kotlin

```
dependencies {
    compile "org.jetbrains.kotlin:kotlin-stdlib:$kotlin_version"
}
```


Kotlin Reflection
compile "org.jetbrains.kotlin:kotlin-reflect:\$kotlin_version"

Android Studio

Android StudioAndroidKotlin。

Kotlin>>>JetBrains...> Kotlin>Android Studio。

Android StudioCtrl + Shift + A.“Kotlin”Enter。



Android StudioGradle。

Java

JavaKotlinCtrl + Shift + A“JavaKotlin”。.kt Kotlin。

```
package com.orangeflash81.myapplication;

public class Foo {
    private String name = "Joe Bloggs";

    String getName() { return name; }

    void setName(String value) { name = value; }
}
```

GroovyGradleKotlin

- [gradle-script-kotlin](#)
- /
 - build.gradle.kts
 - gradlew
 - gradlew.bat
 - settings.gradle
- build.gradle.kts
- [IntelliJGradle](#)◦
- [IntelliJbuild.gradle.kts](#)◦ /IntelliJ
- [Gradle](#)

Windows Gradle 3.3◦ ◦

OSXUbuntu.

Maven Jitpack Groovy. .

Kotlin <https://riptutorial.com/zh-TW/kotlin/topic/2501/kotlin>

36:

Kotlin API

- listOf
- arrayListOf
- mutableListOfKotlin MutableList
- first

Examples

```
// Create a new read-only List<String>
val list = listOf("Item 1", "Item 2", "Item 3")
println(list) // prints "[Item 1, Item 2, Item 3]"
```

```
// Create a new read-only Map<Integer, String>
val map = mapOf(Pair(1, "Item 1"), Pair(2, "Item 2"), Pair(3, "Item 3"))
println(map) // prints "{1=Item 1, 2=Item 2, 3=Item 3}"
```

set

```
// Create a new read-only Set<String>
val set = setOf(1, 3, 5)
println(set) // prints "[1, 3, 5]"
```

<https://riptutorial.com/zh-TW/kotlin/topic/8846/>

37:

◦

3

1. ◦
2. lambda◦
3. ◦

Kotlin

Kotlin

-
-
- Ktor
-

Examples

lambda◦ JFrame

```
import javax.swing.*

fun JFrame.menuBar(init: JMenuBar.() -> Unit) {
    val menuBar = JMenuBar()
    menuBar.init()
    setJMenuBar(menuBar)
}

fun JMenuBar.menu(caption: String, init: JMenu.() -> Unit) {
    val menu = JMenu(caption)
    menu.init()
    add(menu)
}

fun JMenu.menuItem(caption: String, init: JMenuItem.() -> Unit) {
    val menuItem = JMenuItem(caption)
    menuItem.init()
    add(menuItem)
}
```

```
class MyFrame : JFrame() {
    init {
        menuBar {
            menu("Menu1") {
                menuItem("Item1") {
                    // Initialize MenuItem with some Action
                }
                menuItem("Item2") {}
            }
        }
    }
}
```

```
        }
        menu("Menu2") {
            menuItem("Item3") {}
            menuItem("Item4") {}
        }
    }
}
```

<https://riptutorial.com/zh-TW/kotlin/topic/6010/>

38:


◦

Apples OrangesPears ◦ ◦

Fruit getFruit()

Fruit ◦

- {}
- class {Derived Class}{Base Class}{Init Arguments}
- {}
- {DC-Object}{Base Class} == true



Examples

'open'

Kotlin **final**◦

open◦

```
open class Thing {  
    // I can now be extended!  
}
```

open◦

```
open class BaseClass {  
    val x = 10  
}
```

```
class DerivedClass: BaseClass() {  
    fun foo() {  
        println("x is equal to " + x)  
    }  
}
```

```
}
```

```
fun main(args: Array<String>) {
    val derivedClass = DerivedClass()
    derivedClass.foo() // prints: 'x is equal to 10'
}
```

```
open class Person {
    fun jump() {
        println("Jumping...")
    }
}
```

```
class Ninja: Person() {
    fun sneak() {
        println("Sneaking around...")
    }
}
```

Person

```
fun main(args: Array<String>) {
    val ninja = Ninja()
    ninja.jump() // prints: 'Jumping...'
    ninja.sneak() // prints: 'Sneaking around...'
}
```

```
abstract class Car {
    abstract val name: String;
    open var speed: Int = 0;
}

class BrokenCar(override val name: String) : Car() {
    override var speed: Int
        get() = 0
        set(value) {
            throw UnsupportedOperationException("The car is broken")
        }
}

fun main(args: Array<String>) {
    val car: Car = BrokenCar("Lada")
    car.speed = 10
}
```

```
interface Ship {
    fun sail()
    fun sink()
}

object Titanic : Ship {

    var canSail = true
}
```

```
override fun sail() {  
    sink()  
}  
  
override fun sink() {  
    canSail = false  
}  
}
```

<https://riptutorial.com/zh-TW/kotlin/topic/5622/>

S. No		Contributors
1	Kotlin	babedev , Community , cyberscientist , ganesshkumar , Ihor Kucherenko , Jayson Minard , mnoronha , neworld , Parker Hoyes , Ruckus T-Boom , Sach , Sean Reilly , Sheigutn , Simón Oroño , UnKnown , Urko Pineda
2	DSL	Dmitriy L , ice1000
3	Java 8 Stream	Brad , Gerson , Jayson Minard , Piero Divasto , Sam
4	JUnit	jenglert
5	Kotlin Android	Jemo Mgebrishvili , Ritave
6	Kotlin for Java Developers	Thorsten Schleinzer
7	Kotlin	Shinoo Goyal
8	Kotlin	Grigory Konushev , Spidfire
9		Brad Larson , jerekSEL , Sapan Zaveri
10	Vararg	byxor , piotrek1543 , Sam
11		Aaron Christiansen , baha , Caelum , glee8e , Jayson Minard , KeksArmee , madhead , Spidfire
12		Jemo Mgebrishvili
13		atok , Kirill Rakhman , madhead , Ritave , Sup
14		Avijit Karmakar
15		Divya , glee8e
16	KotlinRecyclerView	Mohit Suthar
17	Lambdas	memoizr , Rich Kuzsma
18		Sam , Seaskyways
19		Januson , Sam
20		Aaron Christiansen , Adam Arold , Brad Larson , Héctor , Jayson Minard , Konrad Jamrozik , madhead , mayojava , razzledazzle , Sapan Zaveri , Serge Nikitin , yole

21		Divya , Jan Vladimir Mostert , Jayson Minard , Ritave , Robin
22		Dávid Tímár , Jayson Minard , Kevin Robatel , Konrad Jamrozik , olivierlemasle , Parker Hoyes , razzledazzle
23		egor.zhdan , Sam , UnKnown
24		David Soroko , Kirill Rakhman , SerCe
25		Abdullah , Alex Facciorusso , jpmcosta , Kirill Rakhman , Robin , Spidfire
26		Espen , Travis
27		hotkey , Jayson Minard , KeksArmee
28		KeksArmee , Kirill Rakhman , piotrek1543 , razzledazzle , Robin , SerCe , Spidfire , technerd , Thorsten Schleinzer
29		Sam
30	kotlin	Konrad Jamrozik , olivierlemasle , oshai
31		Ben Leggiero , JaseAnderson , mayojava , razzledazzle , Robin
32		Nihal Saxena
33		Brad Larson , Caelum , Héctor , Mood , piotrek1543 , Sapan Zaveri
34		Kevin Robatel
35	Kotlin	Aaron Christiansen , elect , madhead
36		Ascension
37		Slav
38		byxor , KeksArmee , piotrek1543 , Slav