LEARNING Objective-C Language

Free unaffiliated eBook created from **Stack Overflow contributors.**

#objective-c

Table of Contents

About
Chapter 1: Getting started with Objective-C Language 2
Versions2
Examples
Hello World
Compiling the program
Chapter 2: Basic Data Types
Syntax
Examples4
BOOL
id4
SEL5
IMP (implementation pointer)6
NSInteger and NSUInteger7
Chapter 3: Blocks
Syntax
Remarks
Examples9
Blocks as Method Parameters9
Defining and Assigning10
Blocks as Properties
Block Typedefs
Blocks as local variables
Chapter 4: BOOL / bool / Boolean / NSCFBoolean
Examples12
BOOL/Boolean/bool/NSCFBoolean12
BOOL VS Boolean
Chapter 5: Categories
Syntax14
Remarks14

Examples	
Simple Category	14
Declaring a class method	
Adding a property with a category	
Conforming to protocol	
Create a Category on XCode	16
Chapter 6: Classes and Objects	
Syntax	19
Examples	
Creating classes with initialization values	19
Singleton Class	19
The "instancetype" return type	21
Specifying Generics	21
Difference between allocation and initialization	22
Chapter 7: Continue and Break!	
Examples	
Continue and Break Statement	
Chapter 8: Declare class method and instance method	
Introduction	
Syntax	25
Examples	
How to declare class method and instance method	
Chapter 9: Enums	27
Syntax	27
Examples	
typedef enum declaration in Objective-C	
Converting C++ std::vector to an Objective-C Array	28
Chapter 10: Error Handling	30
Syntax	
⊢xampies	
Asserting	

Error & Exception handling with try catch block	30
Chapter 11: Fast Enumeration	32
Examples	
Fast enumeration of an NSArray	32
Fast enumeration of an NSArray with index	32
Chapter 12: Format-Specifiers	33
Introduction	33
Syntax	33
Remarks	
Examples	34
Integer Example - %i	34
Chapter 13: Grand Central Dispatch	35
Introduction	35
Examples	35
What is Grand central dispatch	35
Chapter 14: Inheritance	36
Syntax	36
Examples	
Car is inherited from Vehicle	36
Chapter 15: Key Value Coding / Key Value Observing	38
Examples	38
Most Common Real Life Key Value Coding Example	38
Key Value Observing	38
Querying KVC Data	40
Collection Operators	40
Chapter 16: Logging	44
Syntax	44
Remarks	44
Examples	44
Logging	44
NSLog vs printf	44

NSLog Output Format
Logging Variable Values45
Empty message is not printed45
Removing Log Statements from Release Builds46
UsingFUNCTION46
NSLog and BOOL type46
Logging NSLog meta data47
Logging by Appending to a File
Chapter 17: Low-level Runtime Environment
Remarks
Examples
Attach object to another existing object (association)49
Augmenting methods using Method Swizzling49
Calling methods directly
Chapter 18: Memory Management
Examples
Automatic Reference Counting
Strong and weak references
Manual Memory Management
Memory management rules when using manual reference counting
Chapter 19: Methods
Syntax
Examples
Method parameters
Create a basic method
Return values
Class methods
Calling methods
Instance methods
Pass by value parameter passing
Pass by reference parameter passing60

Literals	Examples	
NSNumber 62 NSArray 62 NSDictionary 62 Container subscripting 63 Chapter 21: Multi-Threading 64 Examples 64 Creating a simple thread. 64 Creating a simple thread. 64 Create more complex thread. 64 Thread-local storage 65 Chapter 22: NSArray 66 Syntax 66 Examples 66 Creating Arrays 66 Finding out the Number of Elements in an Array 66 Accessing elements 66 First and Last Item 67 Filtering Arrays With Predicates 67 Converting NSArray to NSMutableArray to allow modification 67 SystDescriptor 68 Blocks 68 Performance 68 Converting between Sets and Arrays 68 Reverse an Array 68 Doing through 69 Using Generics 69 Comparing arrays. 68	Literals	62
NSArray. 62 NSDictionary. 62 Container subscripting. 63 Chapter 21: Multi-Threading. 64 Examples. 64 Creating a simple thread. 64 Create more complex thread. 64 Create more complex thread. 66 Chapter 22: NSArray. 66 Syntax. 66 Creating a simple thread. 66 Creating Arrays. 66 Creating Arrays. 66 Finding out the Number of Elements in an Array. 66 Accessing elements. 66 First and Last Item 67 Fittering Arrays With Predicates. 67 Converting NSArray to NSMutableArray to allow modification. 67 Syntax 68 Performance 68 Converting between Sets and Arrays. 68 Converting between Sets and Arrays. 68 Reverse an Array. 68 Looping through. 69 Using Generics. 69 Comparing arrays. 60	NSNumber	62
NSDictionary .62 Container subscripting .63 Chapter 21: Multi-Threading .64 Examples .64 Creating a simple thread .64 Create more complex thread .64 Thread-local storage .65 Chapter 22: NSArray .66 Syntax .66 Creating a single thread .66 Creating Arrays .66 Creating a single item .66 Creating a single item .66 Finding out the Number of Elements in an Array .66 First and Last Item .67 Filtering Arrays With Predicates .67 Converting NSArray to NSMutableArray to allow modification. .67 Sorting array with custom objects .67 Converting NSArray to NSMutableArray to allow modification. .67 NSSortDescriptor .68 Blocks .68 Performance .68 Converting between Sets and Arrays .68 Reverse an Array. .68 Looping through .69 Using Generics .69 Com	NSArray	62
Container subscripting 63 Chapter 21: Multi-Threading 64 Examples 64 Creating a simple thread 64 Create more complex thread 64 Thread-local storage 65 Chapter 22: NSArray 66 Syntax 66 Examples. 66 Creating Arrays 66 Creating Arrays 66 Finding out the Number of Elements in an Array 86 Accessing elements 66 First and Last Item 67 Filtering Arrays With Predicates 67 Converting NSArray to NSMutableArray to allow modification 67 Sorting array with custom objects 67 Converting NSArray to NSMutableArray to allow modification 67 NSSortDescriptor 68 Blocks 68 Performance 68 Converting between Sets and Arrays 68 Looping through 69 Using Generics 69 Enumerating using blocks 69 Comparing arrays 69	NSDictionary	62
Chapter 21: Multi-Threading 64 Examples. 64 Creating a simple thread. 64 Create more complex thread. 64 Thread-local storage. 65 Chapter 22: NSArray. 66 Syntax. 66 Examples. 66 Creating Arrays. 66 Finding out the Number of Elements in an Array. 66 Accessing elements. 66 Getting a single item 66 First and Last Item 67 Filtering Nravys With Predicates. 67 Converting NSArray to NSMutableArray to allow modification. 67 Sorting array with custom objects. 67 Compare method. 67 NSSortDescriptor 68 Blocks. 68 Converting between Sets and Arrays. 68 Reverse an Array. 68 Looping through. 69 Using Generics. 69 Enumerating using blocks. 69 Comparing arrays. 70	Container subscripting	63
Examples.	Chapter 21: Multi-Threading	64
Creating a simple thread. .64 Create more complex thread. .64 Thread-local storage. .65 Chapter 22: NSArray. .66 Syntax. .66 Examples. .66 Creating Arrays. .66 Finding out the Number of Elements in an Array. .66 Accessing elements. .66 Getting a single item. .66 First and Last Item. .67 Filtering Arrays With Predicates. .67 Converting NSArray to NSMutableArray to allow modification. .67 Sorting array with custom objects. .67 Compare method. .67 NSSortDescriptor. .68 Blocks. .68 Performance. .68 Converting between Sets and Arrays. .68 Reverse an Array. .68 Looping through. .69 Using Generics. .69 Enumerating using blocks. .69 Comparing arrays. .60	Examples	64
Create more complex thread. 64 Thread-local storage. 65 Chapter 22: NSArray. 66 Syntax. 66 Examples. 66 Creating Arrays. 66 Finding out the Number of Elements in an Array. 66 Accessing elements. 66 Getting a single item. 66 First and Last Item. 67 Filtering Arrays With Predicates. 67 Converting NSArray to NSMutableArray to allow modification. 67 Sorting array with custom objects. 67 NSSortDescriptor. 68 Blocks. 68 Performance. 68 Looping through. 69 Using Generics. 69 Enumerating using blocks. 69 Comparing arrays. 70	Creating a simple thread	64
Thread-local storage .65 Chapter 22: NSArray .66 Syntax .66 Examples .66 Creating Arrays .66 Finding out the Number of Elements in an Array .66 Accessing elements .66 Getting a single item .66 First and Last Item .67 Filtering Arrays With Predicates .67 Converting NSArray to NSMutableArray to allow modification .67 Sorting array with custom objects .67 Compare method. .67 NSSortDescriptor .68 Blocks .68 Performance .68 Converting between Sets and Arrays .68 Looping through .69 Using Generics .69 Enumerating using blocks .69 Comparing arrays .69	Create more complex thread	64
Chapter 22: NSArray. 66 Syntax. 66 Examples. 66 Creating Arrays. 66 Finding out the Number of Elements in an Array. 66 Accessing elements. 66 Getting a single item. 66 First and Last Item. 67 Filtering Arrays With Predicates. 67 Converting NSArray to NSMutableArray to allow modification. 67 Sorting array with custom objects. 67 NSSortDescriptor. 68 Blocks. 68 Performance 68 Looping through. 69 Using Generics. 69 Comparing arrays. 69 Comparing arrays. 69	Thread-local storage	65
Syntax	Chapter 22: NSArray	66
Examples. 66 Creating Arrays. 66 Finding out the Number of Elements in an Array. 66 Accessing elements. 66 Getting a single item. 66 First and Last Item. 67 Filtering Arrays With Predicates. 67 Converting NSArray to NSMutableArray to allow modification. 67 Sorting array with custom objects. 67 Compare method. 67 NSSortDescriptor. 68 Blocks. 68 Performance. 68 Converting between Sets and Arrays. 68 Reverse an Array. 68 Looping through. 69 Using Generics. 69 Comparing arrays. 70	Syntax	66
Creating Arrays 66 Finding out the Number of Elements in an Array 66 Accessing elements 66 Getting a single item 66 First and Last Item 67 Filtering Arrays With Predicates 67 Converting NSArray to NSMutableArray to allow modification 67 Sorting array with custom objects 67 Compare method 67 NSSortDescriptor 68 Blocks 68 Converting between Sets and Arrays 68 Reverse an Array 68 Looping through 69 Using Generics 69 Comparing arrays 70	Examples	66
Finding out the Number of Elements in an Array. 66 Accessing elements. 66 Getting a single item. 66 First and Last Item. 67 Filtering Arrays With Predicates. 67 Converting NSArray to NSMutableArray to allow modification. 67 Sorting array with custom objects. 67 Compare method. 67 NSSortDescriptor. 68 Blocks. 68 Converting between Sets and Arrays. 68 Reverse an Array. 68 Looping through. 69 Using Generics. 69 Comparing arrays. 69	Creating Arrays	66
Accessing elements 66 Getting a single item. 66 First and Last Item. 67 Filtering Arrays With Predicates 67 Converting NSArray to NSMutableArray to allow modification. 67 Sorting array with custom objects 67 Compare method. 67 NSSortDescriptor. 68 Blocks. 68 Performance. 68 Converting between Sets and Arrays. 68 Looping through. 69 Using Generics. 69 Comparing arrays. 69 Comparing arrays. 70	Finding out the Number of Elements in an Array	66
Getting a single item. 66 First and Last Item. 67 Filtering Arrays With Predicates. 67 Converting NSArray to NSMutableArray to allow modification. 67 Sorting array with custom objects. 67 Compare method. 67 NSSortDescriptor. 68 Blocks. 68 Performance 68 Converting between Sets and Arrays. 68 Looping through. 69 Using Generics. 69 Enumerating using blocks. 69 Comparing arrays. 70	Accessing elements	
First and Last Item 67 Filtering Arrays With Predicates 67 Converting NSArray to NSMutableArray to allow modification 67 Sorting array with custom objects 67 Compare method 67 NSSortDescriptor 68 Blocks 68 Performance 68 Converting between Sets and Arrays 68 Looping through 69 Using Generics 69 Enumerating using blocks 69 Comparing arrays 70	Getting a single item	66
Filtering Arrays With Predicates. 67 Converting NSArray to NSMutableArray to allow modification. 67 Sorting array with custom objects. 67 Compare method. 67 NSSortDescriptor. 68 Blocks. 68 Performance. 68 Converting between Sets and Arrays. 68 Looping through. 69 Using Generics. 69 Comparing arrays. 70	First and Last Item	67
Converting NSArray to NSMutableArray to allow modification 67 Sorting array with custom objects 67 Compare method 67 NSSortDescriptor 68 Blocks 68 Performance 68 Converting between Sets and Arrays 68 Reverse an Array 68 Looping through 69 Using Generics 69 Comparing arrays 70	Filtering Arrays With Predicates	67
Sorting array with custom objects67Compare method67NSSortDescriptor68Blocks68Performance68Converting between Sets and Arrays68Reverse an Array68Looping through69Using Generics69Enumerating using blocks69Comparing arrays70	Converting NSArray to NSMutableArray to allow modification	
Compare method .67 NSSortDescriptor .68 Blocks .68 Performance .68 Converting between Sets and Arrays .68 Reverse an Array .68 Looping through .69 Using Generics .69 Enumerating using blocks .69 Comparing arrays .70	Sorting array with custom objects	67
NSSortDescriptor 68 Blocks 68 Performance 68 Converting between Sets and Arrays 68 Reverse an Array 68 Looping through 69 Using Generics 69 Enumerating using blocks 69 Comparing arrays 70	Compare method	67
Blocks. 68 Performance 68 Converting between Sets and Arrays. 68 Reverse an Array. 68 Looping through. 69 Using Generics. 69 Enumerating using blocks. 69 Comparing arrays. 70	NSSortDescriptor	
Performance 68 Converting between Sets and Arrays 68 Reverse an Array 68 Looping through 69 Using Generics 69 Enumerating using blocks 69 Comparing arrays 70	Blocks	
Converting between Sets and Arrays.68Reverse an Array.68Looping through.69Using Generics.69Enumerating using blocks.69Comparing arrays.70	Performance	
Reverse an Array.68Looping through.69Using Generics.69Enumerating using blocks.69Comparing arrays.70	Converting between Sets and Arrays	68
Looping through	Reverse an Array	
Using Generics	Looping through	69
Enumerating using blocks	Using Generics	69
Comparing arrays	Enumerating using blocks	69
	Comparing arrays	70

Add objects to NSArray
Chapter 23: NSArray
Examples
Creating NSArray instances
Sorting Arrays
Filter NSArray and NSMutableArray71
Chapter 24: NSAttributedString
Examples
Creating a string that has custom kerning (letter spacing) editshare
Create a string with text struck through73
Using Enumerating over Attributes in a String and underline part of string
How you create a tri-color attributed string74
Chapter 25: NSCache
Examples
NSCache
Chapter 26: NSCalendar
Examples76
System Locale Information76
Initializing a Calendar
Calendrical Calculations
Chapter 27: NSData
Examples
Create
Get NSData lengh
Encoding and decoding a string using NSData Base6478
NSData and Hexadecimal String79
Chapter 28: NSDate
Remarks
Examples
Creating an NSDate
Date Comparison
Convert NSDate that is composed from hour and minute (only) to a full NSDate

Chapter 29: NSDictionary.84Examples.84Create.84NSDictionary to NSArray.84NSDictionary to NSData.84NSDictionary to JSON.85Block Based Enumeration.85Fast Enumeration.85Chapter 30: NSDictionary.86Syntax.86Remarks.86
Examples.84Create.84NSDictionary to NSArray.84NSDictionary to NSData.84NSDictionary to JSON.85Block Based Enumeration.85Fast Enumeration.85Chapter 30: NSDictionary.86Syntax.86Remarks.86
Create
NSDictionary to NSArray.84NSDictionary to NSData.84NSDictionary to JSON.85Block Based Enumeration.85Fast Enumeration.85Chapter 30: NSDictionary86Syntax.86Remarks.86
NSDictionary to NSData.84NSDictionary to JSON.85Block Based Enumeration.85Fast Enumeration.85Chapter 30: NSDictionary.86Syntax.86Remarks.86
NSDictionary to JSON
Block Based Enumeration .85 Fast Enumeration .85 Chapter 30: NSDictionary .86 Syntax .86 Remarks .86
Fast Enumeration .85 Chapter 30: NSDictionary .86 Syntax .86 Remarks .86
Chapter 30: NSDictionary 86 Syntax 86 Remarks 86
Syntax
Remarks
Examples
Creating using literals
Creating using dictionaryWithObjectsAndKeys:86
Creating using plists
Setting a Value in NSDictionary
Standard
Shorthand
Getting a Value from NSDictionary
Standard
Shorthand
Check if NSDictionary already has a key or not
Chapter 31: NSJSONSerialization
Syntax
Parameters
Remarks
Examples
JSON Parsing using NSJSONSerialization Objective c
Chapter 32: NSMutableArray
Examples
Adding elements

	T
Deleting Elements	1
Sorting Arrays9	2
Move object to another index9	2
Filtering Array content with Predicate9	2
Creating an NSMutableArray9	2
Chapter 33: NSMutableDictionary	4
Parameters	4
Examples	4
NSMutableDictionary Example9	4
Removing Entries From a Mutable Dictionary9	5
Chapter 34: NSObject	7
Introduction9	7
Syntax9	7
Examples	7
NSObject	7
Chapter 35: NSPredicate	9
Syntax	9
·	
Remarks	9
Remarks	9 9
Remarks .9 Examples .9 Filter By Name .9	9 9 9
Remarks .9 Examples .9 Filter By Name .9 Find movies except given ids .10	9 9 9
Remarks .9 Examples .9 Filter By Name .9 Find movies except given ids .10 Find all the objects which is of type movie .10	9 9 9 0
Remarks .9 Examples .9 Filter By Name .9 Find movies except given ids .0 Find all the objects which is of type movie .10 Find Distinct object ids of array .0	9 9 0 1
Remarks .9 Examples .9 Filter By Name .9 Find movies except given ids .10 Find all the objects which is of type movie .10 Find Distinct object ids of array .10 Find movies with specific ids .10	9 9 0 1 1
Remarks .9 Examples .9 Filter By Name .9 Find movies except given ids .10 Find all the objects which is of type movie .10 Find Distinct object ids of array .10 Find movies with specific ids .10 Case Insensitive comparison with exact title match .10	9 9 0 1 1 1
Remarks. 9 Examples. 9 Filter By Name. 9 Find movies except given ids. 10 Find all the objects which is of type movie. 10 Find Distinct object ids of array. 10 Find movies with specific ids. 10 Case Insensitive comparison with exact title match. 10 Case sensitive with exact title match. 10	9 9 0 1 1 1
Remarks 9 Examples 9 Filter By Name 9 Find movies except given ids 10 Find all the objects which is of type movie 10 Find all the object ids of array 10 Find movies with specific ids 10 Find movies with specific ids 10 Case Insensitive comparison with exact title match 10 Case Insensitive comparison with matching subset 10	9 9 0 1 1 1 1
Remarks. 9 Examples. 9 Filter By Name. 9 Find movies except given ids. 10 Find all the objects which is of type movie. 10 Find Distinct object ids of array. 10 Find movies with specific ids. 10 Case Insensitive comparison with exact title match. 10 Case Insensitive comparison with matching subset. 10 Chapter 36: NSRegularExpression. 10	9 9 0 1 1 1 1 1 2
Remarks 9 Examples 9 Filter By Name 9 Find movies except given ids 10 Find all the objects which is of type movie 10 Find Distinct object ids of array 10 Find movies with specific ids 10 Case Insensitive comparison with exact title match 10 Case Insensitive comparison with matching subset 10 Chapter 36: NSRegularExpression 10 Syntax 10	9 9 0 1 1 1 1 1 2 2
Remarks	9 9 0 1 1 1 1 1 1 1 2 2 2 2

Check whether a string matches a pattern	102
Chapter 37: NSSortDescriptor	104
Examples	104
Sorted by combinations of NSSortDescriptor	104
Chapter 38: NSString	
Introduction	
Remarks	105
Examples	105
Creation	
String Length	
Changing Case	106
Comparing Strings	
Joining an Array of Strings	
Encoding and Decoding	107
Splitting	
Searching for a Substring	
Working with C Strings	
Removing Leading and Trailing Whitespace	110
Formatting	110
Reversing a NSString Objective-C	110
Chapter 39: NSTextAttachment	112
Syntax	112
Remarks	
Examples	
NSTextAttachment Example	
Chapter 40: NSTimer	113
Examples	112
Chapter 41: NSURL	

Examples	115
Create	
Compare NSURL	
Modifying and Converting a File URL with removing and appending path	115
Chapter 42: NSUrl send a post request	
Examples	117
Simple POST request	
Simple Post Request With Timeout	
Chapter 43: NSUserDefaults	
Examples	
Simple example	
Clear NSUserDefaults	
Chapter 44: Predefined Macros	
Introduction	
Syntax	
Examples	
Predefined Macros	
Chapter 45: Properties	120
Suntax	120
Deremetere	
Examples	
What are properties?	
Custom getters and setters	
Properties that cause updates	
Chapter 46: Protocols	
Examples	
Basic Protocol Definition	
Optional and required methods	
Conforming to Protocols	
Forward Declarations	
Checking existance of optional method implementations	
Check conforms Protocol	

Chapter 47: Protocols and Delegates	
Remarks	129
Examples	129
Implementation of Protocols and Delegation mechanism	
Chapter 48: Random Integer	
Examples	131
Basic Random Integer	
Random Integer within a Range	
Chapter 49: Singletons	132
Introduction	132
Examples	132
Using Grand Central Dispatch (GCD)	
Creating Singleton class and also preventing it from having multiple instances using alloc	132
Creating Singleton and also preventing it from having multiple instance using alloc/init,	133
Chapter 50: Structs	
Syntax	135
Remarks	135
Examples	135
CGPoint	
Defining a Structure and Accessing Structure Members	136
Chapter 51: Subscripting	
Examples	138
Subscripts with NSArray	
Subscripts with NSDictionary	
Custom Subscripting	
Chapter 52: Unit testing using Xcode	140
Remarks	140
Examples	140
Testing a block of code or some method:	141
Feed the dummy data to the method under test if required & then compare the expe	cted & act 141
Testing asynchronous block of code:	141

Measuring Performance of a block of code:	141
Running Test Suits:	142
Note:	142
Chapter 53: XML parsing	144
Examples	144
XML Parsing	.144
Credits	146



You can share this PDF with anyone you feel could benefit from it, downloaded the latest version from: objective-c-language

It is an unofficial and free Objective-C Language ebook created for educational purposes. All the content is extracted from Stack Overflow Documentation, which is written by many hardworking individuals at Stack Overflow. It is neither affiliated with Stack Overflow nor official Objective-C Language.

The content is released under Creative Commons BY-SA, and the list of contributors to each chapter are provided in the credits section at the end of this book. Images may be copyright of their respective owners unless otherwise specified. All trademarks and registered trademarks are the property of their respective company owners.

Use the content presented in this book at your own risk; it is not guaranteed to be correct nor accurate, please send your feedback and corrections to info@zzzprojects.com

Chapter 1: Getting started with Objective-C Language

Versions

Version	Release Date
1.0	1983-01-01
2.0	2007-10-27
Modern	2014-03-10

Examples

Hello World

This program will output "Hello World!"

```
#import <Foundation/Foundation.h>
int main(int argc, char * argv[]) {
    NSLog(@"Hello World!");
}
```

#import is a pre-processor directive, which indicates we want to import or include the information from that file into the program. In this case, the compiler will copy the contents of Foundation.h in the Foundation framework to the top of the file. The main difference between #import and #include is that #import is "smart" enough to not reprocess files that have already been included in other #includes.

The C Language documentation explains the main function.

The NSLOG() function will print the string provided to the console, along with some debugging information. In this case, we use an Objective-C string literal: <code>@"Hello World!"</code>. In C, you would write this as "Hello World!", however, Apple's Foundation Framework adds the NSString class which provides a lot of useful functionality, and is used by NSLog. The simplest way to create an instance of NSString is like this: <code>@"string content here"</code>.

Technically, NSLog() is part of Apple's Foundation Framework and is not actually part of the Objective-C language. However, the Foundation Framework is ubiquitous throughout Objective-C programming. Since the Foundation Framework is not open-source and cannot be used outside of Apple development, there are open-source alternatives to the framework which are associated with OPENStep and GNUStep.

Compiling the program

Assuming we want to compile our Hello World program, which consist of a single hello.m file, the command to compile the executable is:

clang -framework Foundation hello.m -o hello

Then you can run it:

./hello

This will output:

Hello World!

The options are:

- -framework: Specifies a framework to use to compile the program. Since this program uses Foundation, we include the Foundation framework.
- -o: This option indicate to which file we'd like to output our program. In our case hello. If not specified, the default value is a.out.

Read Getting started with Objective-C Language online: https://riptutorial.com/objective-c/topic/199/getting-started-with-objective-c-language

Chapter 2: Basic Data Types

Syntax

- BOOL havePlutonium = YES; // Direct assignment
- BOOL fastEnough = (car.speedInMPH >= 88); // Comparison expression
- BOOL fluxCapacitorActive = (havePlutonium && fastEnough); // Boolean expression
- •
- id somethingWicked = [witchesCupboard lastObject]; // Retrieve untyped object
- id powder = prepareWickedIngredient(somethingWicked); // Pass and return
- if ([ingredient isKindOfClass:[Toad class]]) { // Test runtime type

Examples

BOOL

The BOOL type is used for boolean values in Objective-C. It has two values, YES, and NO, in contrast to the more common "true" and "false".

Its behavior is straightforward and identical to the C language's.

```
BOOL areEqual = (1 == 1); // areEqual is YES
BOOL areNotEqual = !areEqual // areNotEqual is NO
NSCAssert(areEqual, "Mathematics is a lie"); // Assertion passes
BOOL shouldFlatterReader = YES;
if (shouldFlatterReader) {
    NSLog(@"Only the very smartest programmers read this kind of material.");
}
```

A BOOL is a primitive, and so it cannot be stored directly in a Foundation collection. It must be wrapped in an NSNumber. Clang provides special syntax for this:

NSNumber * yes = @YES; // Equivalent to [NSNumber numberWithBool:YES] NSNumber * no = @NO; // Equivalent to [NSNumber numberWithBool:NO]

The BOOL implementation is directly based on C's, in that it is a typedef of the C99 standard type bool. The YES and NO values are defined to __objc_yes and __objc_no, respectively. These special values are compiler builtins introduced by Clang, which are translated to (BOOL)1 and (BOOL)0. If they are not available, YES and NO are defined directly as the cast-integer form. The definitions are found in the Objective-C runtime header objc.h

id

id is the generic object pointer, an Objective-C type representing "any object". An instance of any Objective-C class can be stored in an id variable. An id and any other class type can be assigned

back and forth without casting:

```
id anonymousSurname = @"Doe";
NSString * surname = anonymousSurname;
id anonymousFullName = [NSString stringWithFormat:@"%@, John", surname];
```

This becomes relevant when retrieving objects from a collection. The return types of methods like <code>objectAtIndex:</code> are id for exactly this reason.

```
DataRecord * record = [records objectAtIndex:anIndex];
```

It also means that a method or function parameter typed as id can accept any object.

When an object is typed as *id*, any known message can be passed to it: method dispatch does not depend on the compile-time type.

```
NSString * extinctBirdMaybe =
        [anonymousSurname stringByAppendingString:anonymousSurname];
```

A message that the object does not actually respond to will still cause an exception at runtime, of course.

```
NSDate * nope = [anonymousSurname addTimeInterval:10];
// Raises "Does not respond to selector" exception
```

Guarding against exception.

```
NSDate * nope;
if([anonymousSurname isKindOfClass:[NSDate class]]){
    nope = [anonymousSurname addTimeInterval:10];
}
```

The id type is defined in objc.h

```
typedef struct objc_object {
    Class isa;
} *id;
```

SEL

Selectors are used as method identifiers in Objective-C.

In the example below, there are two selectors. new and setName:

```
Person* customer = [Person new];
[customer setName:@"John Doe"];
```

Each pair of brackets corresponds to a message send. On the first line we send a message

containing the new selector to the Person class and on the second line we send a message containing the setName: selector and a string. The receiver of these messages uses the selector to look up the correct action to perform.

Most of the time, message passing using the bracket syntax is sufficient, but occasionally you need to work with the selector itself. In these cases, the $_{SEL}$ type can be used to hold a reference to the selector.

If the selector is available at compile time, you can use @selector() to get a reference to it.

```
SEL s = @selector(setName:);
```

And if you need to find the selector at runtime, use NSSelectorFromString.

```
SEL s NSSelectorFromString(@"setName:");
```

When using NSSelectorFromString, make sure to wrap the selector name in a NSString.

It is commonly used to check if a delegate implements an optional method.

```
if ([self.myDelegate respondsToSelector:@selector(doSomething)]) {
    [self.myDelegate doSomething];
}
```

IMP (implementation pointer)

IMP is a C type referring to the implementation of a method, also known as an implementation pointer. It is a pointer to the start of a method implementation.

Syntax:

```
id (*IMP)(id, SEL, ...)
```

IMP is defined by:

```
typedef id (*IMP)(id self,SEL _cmd,...);
```

To access this IMP, the message "methodForSelector" can be used.

Example 1:

IMP ImpDoSomething = [myObject methodForSelector:@selector(doSomething)];

The method adressed by the IMP can be called by dereferencing the IMP.

ImpDoSomething(myObject, @selector(doSomething));

So these calls are equal:

https://riptutorial.com/

```
myImpDoSomething(myObject, @selector(doSomething));
[myObject doSomething]
[myObject performSelector:mySelector]
[myObject performSelector:@selector(doSomething)]
[myObject performSelector:NSSelectorFromString(@"doSomething")];
```

Example :2:

Here, we call [NSObject methodForSelector which returns us a pointer to the C function that actually implements the method, which we can the subsequently call directly.

NSInteger and NSUInteger

The NSInteger is just a typedef for either an int or a long depending on the architecture. The same goes for a NSUInteger which is a typedef for the unsigned variants. If you check the NSInteger you will see the following:

```
#if __LP64__ || (TARGET_OS_EMBEDDED && !TARGET_OS_IPHONE) || TARGET_OS_WIN32 ||
NS_BUILD_32_LIKE_64
typedef long NSInteger;
typedef unsigned long NSUInteger;
#else
typedef int NSInteger;
typedef unsigned int NSUInteger;
#endif
```

The difference between an signed and an unsigned int or long is that a signed int or long can contain negative values. The range of the int is -2 147 483 648 to 2 147 483 647 while the unsigned int has a range of 0 to 4 294 967 295. The value is doubled because the first bit isn't used anymore to say the value is negative or not. For a long and NSInteger on 64-bit architectures, the range is much wider.

Most methods Apple provides are returning an NS(U)Integer over the normal int. You'll get a warning if you try to cast it to a normal int because you will lose precision if you are running on a 64-bit architecture. Not that it would matter in most cases, but it is easier to use NS(U)Integer. For example, the count method on a array will return an NSUInteger.

```
NSNumber *iAmNumber = @0;
NSInteger iAmSigned = [iAmNumber integerValue];
```

NSUInteger iAmUnsigned = [iAmNumber unsignedIntegerValue]; NSLog(@"%ld", iAmSigned); // The way to print a NSInteger.

NSLog(@"%lu", iAmUnsigned); // The way to print a NSUInteger.

Just like a BOOL, the NS(U)Integer is a primitive datatype, so you sometimes need to wrap it in a NSNumber you can use the @ before the integer to cast it like above and retrieve it using the methods below. But to cast it to NSNumber, you could also use the following methods:

```
[NSNumber numberWithInteger:0];
[NSNumber numberWithUnsignedInteger:0];
```

Read Basic Data Types online: https://riptutorial.com/objective-c/topic/4564/basic-data-types

Chapter 3: Blocks

Syntax

• // Declare as a local variable:

returnType (^blockName)(parameterType1, parameterType2, ...) = ^returnType(argument1, argument2, ...) {...};

• // Declare as a property:

@property (nonatomic, copy, nullability) returnType (^blockName)(parameterTypes);

• // Declare as a method parameter:

 (void)someMethodThatTakesABlock:(returnType (^nullability)(parameterTypes))blockName;

• // Declare as an argument to a method call:

[someObject someMethodThatTakesABlock:^returnType (parameters) {...}];

• // Declare as a typedef:

typedef returnType (^TypeName)(parameterTypes);

TypeName blockName = ^returnType(parameters) {...};

• // Declare a C function return a block object:

BLOCK_RETURN_TYPE (^function_name(function parameters))(BLOCK_PARAMETER_TYPE);

Remarks

Blocks are specified by the Language Specification for Blocks for C, Objective-C, C++ and Objective-C++.

Additionally, the Blocks ABI is defined by the Block Implementation Specification.

Examples

Blocks as Method Parameters

```
- (void)methodWithBlock:(returnType (^)(paramType1, paramType2, ...))name;
```

Defining and Assigning

A block that performs addition of two double precision numbers, assigned to variable addition:

```
double (^addition) (double, double) = ^double(double first, double second) {
    return first + second;
};
```

The block can be subsequently called like so:

```
double result = addition(1.0, 2.0); // result == 3.0
```

Blocks as Properties

```
@interface MyObject : MySuperclass
@property (copy) void (^blockProperty)(NSString *string);
@end
```

When assigning, since self retains blockProperty, block should not contain a strong reference to self. Those mutual strong references are called a "retain cycle" and will prevent the release of either object.

```
__weak __typeof(self) weakSelf = self;
self.blockProperty = ^(NSString *string) {
    // refer only to weakSelf here. self will cause a retain cycle
};
```

It is highly unlikely, but self might be deallocated inside the block, somewhere during the execution. In this case weakSelf becomes nil and all messages to it have no desired effect. This might leave the app in an unknown state. This can be avoided by retaining weakSelf with a __strong ivar during block execution and clean up afterward.

```
__weak __typeof(self) weakSelf = self;
self.blockProperty = ^(NSString *string) {
    __strong __typeof(weakSelf) strongSelf = weakSelf;
    // refer only to strongSelf here.
    // ...
    // At the end of execution, clean up the reference
    strongSelf = nil;
};
```

Block Typedefs

typedef double (^Operation) (double first, double second);

If you declare a block type as a typedef, you can then use the new type name instead of the full description of the arguments and return values. This defines <code>operation</code> as a block that takes two

doubles and returns a double.

The type can be used for the parameter of a method:

or as a variable type:

Without the typedef, this is much messier:

Blocks as local variables

```
returnType (^blockName)(parameterType1, parameterType2, ...) = ^returnType(argument1,
argument2, ...) {...};
float (^square)(float) = ^(float x) {return x*x;};
square(5); // resolves to 25
square(-7); // resolves to 49
```

Here's an example with no return and no parameters:

```
NSMutableDictionary *localStatus;
void (^logStatus)() = ^(void){ [MYUniversalLogger logCurrentStatus:localStatus]};
// Insert some code to add useful status information
// to localStatus dictionary
logStatus(); // this will call the block with the current localStatus
```

Read Blocks online: https://riptutorial.com/objective-c/topic/540/blocks

Chapter 4: BOOL / bool / Boolean / NSCFBoolean

Examples

BOOL/Boolean/bool/NSCFBoolean

- 1. bool is a datatype defined in C99.
- 2. Boolean values are used in conditionals, such as if or while statements, to conditionally perform logic or repeat execution. When evaluating a conditional statement, the value 0 is considered "false", while any other value is considered "true". Because NULL and nil are defined as 0, conditional statements on these nonexistent values are also evaluated as "false".
- 3. BOOL is an Objective-C type defined as signed char with the macros YES and NO to represent true and false

From the definition in objc.h:

```
#if (TARGET_OS_IPHONE && __LP64__) || TARGET_OS_WATCH
typedef bool BOOL;
#else
typedef signed char BOOL;
// BOOL is explicitly signed so @encode(BOOL) == "c" rather than "C"
// even if -funsigned-char is used.
#endif
#define YES ((BOOL)1)
#define NO ((BOOL)0)
```

4. NSCFBoolean is a private class in the NSNumber class cluster. It is a bridge to the CFBooleanRef type, which is used to wrap boolean values for Core Foundation property lists and collections. CFBoolean defines the constants kCFBooleanTrue and kCFBooleanFalse. Because CFNumberRef and CFBooleanRef are different types in Core Foundation, it makes sense that they are represented by different bridging classes in NSNumber.

BOOL VS Boolean

BOOL

- Apple's Objective-C frameworks and most Objective-C/Cocoa code uses BOOL.
- · Use BOOL in objective-C, when dealing with any CoreFoundation APIs

Boolean

· Boolean is an old Carbon keyword , defined as an unsigned char

Read BOOL / bool / Boolean / NSCFBoolean online: https://riptutorial.com/objectivec/topic/7267/bool---boolean---nscfboolean

Chapter 5: Categories

Syntax

- @interface ClassName (categoryName) // ClassName is the class to be extended
- // Method and property declarations
- @end

Remarks

To avoid method name clashes, it is recommended to use prefixes (like xyz_i in the example). If methods with the same name exist, it is undefined which one will be used in the runtime.

Examples

Simple Category

Interface and implementation of a simple category on NSArray, named Filter, with a single method that filters numbers.

It is good practice to add a prefix (PF) to the method to ensure we don't overwrite any future NSArray methods.

```
@interface NSArray (PFFilter)
- (NSArray *)pf_filterSmaller:(double)number;
0end
@implementation NSArray (PFFilter)
- (NSArray *)pf_filterSmaller:(double)number
{
   NSMutableArray *result = [NSMutableArray array];
    for (id val in self)
    {
        if ([val isKindOfClass:[NSNumber class] && [val doubleValue] >= number)
        {
           [result addObject:val];
        }
    }
    return [result copy];
}
Gend
```

Declaring a class method

Header file UIColor+XYZPalette.h:

@interface UIColor (XYZPalette)
+(UIColor *)xyz_indigoColor;

@end

and implementation UIColor+XYZPalette.m:

```
@implementation UIColor (XYZPalette)
+(UIColor *)xyz_indigoColor
{
    return [UIColor colorWithRed:75/255.0f green:0/255.0f blue:130/255.0f alpha:1.0f];
}
@end
```

Adding a property with a category

Properties can be added with categories using associated objects, a feature of the Objective-C runtime.

Note that the property declaration of retain, nonatomic matches the last argument to objc_setAssociatedObject. See Attach object to another existing object for explanations.

```
#import <objc/runtime.h>
@interface UIViewController (ScreenName)
@property (retain, nonatomic) NSString *screenName;
@end
@implementation UIViewController (ScreenName)
@dynamic screenName;
- (NSString *)screenName {
    return objc_getAssociatedObject(self, @selector(screenName));
}
- (void)setScreenName:(NSString *)screenName {
    objc_setAssociatedObject(self, @selector(screenName), screenName, OBJC_ASSOCIATION_RETAIN_NONATOMIC);
}
@end
```

Conforming to protocol

You can add protocols to standard classes to extends their functionality:

```
@protocol EncodableToString <NSObject>
- (NSString *)toString;
@end
@interface NSDictionary (XYZExtended) <EncodableToString>
@end
@implementation NSDictionary (XYZExtended)
- (NSString *)toString {
    return self.description;
}
@end
```

where xyz your project's prefix

Create a Category on XCode

Categories provide the ability to add some extra functionality to an object without subclassing or changing the actual object.

For example we want to set some custom fonts. Let's create a category that add functionality to UIFont class. Open your XCode project, click on File -> New -> File and choose Objective-C file, click Next enter your category name say "CustomFont" choose file type as Category and Class as UIFont then Click "Next" followed by "Create."



Choose	options f	for your	new file:
--------	-----------	----------	-----------

Choose options for your new file	2:		
File:	CustomFont		
File Type:	Category		
Classe	LIIEopt		
01035.	oront		
Cancel		Previous	Next

Declare the Category Method :-

Click "UIFont+CustomFonts.h" to view the new category's header file. Add the following code to the interface to declare the method.

@interface UIFont (CustomFonts)	
+(UIFont *)productSansRegularFontWithSize:(CGFloat)siz	ze;
lend	

Now Implement the Category Method:-

Click "UIFont+CustomFonts.m" to view the category's implementation file. Add the following code to create a method that will set ProductSansRegular Font.



Import your category

Now set the Label font

[self.label setFont:[UIFont productSansRegularFontWithSize:16.0]];

Read Categories online: https://riptutorial.com/objective-c/topic/550/categories

Chapter 6: Classes and Objects

Syntax

- Cat *cat = [[Cat alloc] init]; // Create cat object of type Cat
- Dog *dog = [[Dog alloc] init]; // Create dog object of type Dog
- NSObject *someObject = [NSObject alloc]; [someObject init]; // don't do this
- XYZObject *object = [XYZObject new]; // Use new to create objects if NO arguments are needed for initialization
- NSString *someString = @"Hello, World!"; // Creating an NSString with literal syntax
- NSNumber *myFloat = @3.14f; // Another example to create a NSNumber using literal syntax
- NSNumber *myInt = @(84 / 2); // Create an object using a boxed expression

Examples

Creating classes with initialization values

```
#import <Foundation/Foundation.h>
@interface Car:NSObject {
   NSString *CarMotorCode;
   NSString *CarChassisCode;
}
- (instancetype)initWithMotorValue:(NSString *) motorCode
andChassisValue: (NSInteger) chassisCode;
- (void) startCar;
- (void) stopCar;
Gend
@implementation Car
- (instancetype)initWithMotorValue:(NSString *) motorCode
andChassisValue: (NSInteger) chassisCode {
   CarMotorCode = motorCode;
   CarChassisCode = chassisCode;
    return self;
}
- (void) startCar {...}
- (void) stopCar {...}
0end
```

The method initWithMotorValue: type andChassisValue: type will be used to initialize the Car objects.

Singleton Class

What is a Singleton Class?

A singleton class returns the same instance no matter how many times an application requests it. Unlike a regular class, A singleton object provides a global point of access to the resources of its class.

When to Use Singleton Classes?

Singletons are used in situations where this single point of control is desirable, such as with classes that offer some general service or resource.

How to Create Singleton Classes

First, create a New file and subclass it from NSObject. Name it anything, we will use CommonClass here. Xcode will now generate CommonClass.h and CommonClass.m files for you.

In your CommonClass.h file:

```
#import <Foundation/Foundation.h>
@interface CommonClass : NSObject {
}
+ (CommonClass *)sharedObject;
@property NSString *commonString;
@end
```

In your CommonClass.m File:

```
#import "CommonClass.h"
@implementation CommonClass
+ (CommonClass *) sharedObject {
    static CommonClass *sharedClass = nil;
   static dispatch_once_t onceToken;
   dispatch_once(&onceToken, ^{
      sharedClass = [[self alloc] init];
   });
   return sharedClass;
}
- (id) init {
   if (self = [super init]) {
       self.commonString = @"this is string";
   }
   return self;
}
0end
```

How to Use Singleton Classes

The Singleton Class that we created earlier will be accessible from anywhere in the project as long as you have imported <code>CommonClass.h</code> file in the relevant module. To modify and access the shared

data in Singleton Class, you will have to access the shared Object of that class which can be accessed by using *sharedObject* method like following:

[CommonClass sharedObject]

To read or modify the elements in Shared Class, do the following:

```
NSString *commonString = [[CommonClass sharedObject].commonString; //Read the string in
singleton class
NSString *newString = @"New String";
[CommonClass sharedObject].commonString = newString;//Modified the string in singleton class
```

The "instancetype" return type

Objective-C supports a special type called `instancetype that can only be used as type returned by a method. It evaluates to the class of the receiving object.

Consider the following class hierarchy:

```
@interface Foo : NSObject
- (instancetype)initWithString:(NSString *)string;
@end
@interface Bar : Foo
@end
```

When [[Foo alloc] initWithString:@"abc"] is called, the compiler can infer that the return type is Foo *. The Bar class derived from Foo but did not override the declaration of the initializer. Yet, thanks to instancetype, the compiler can infer that [[Bar alloc] initWithString:@"xyz"] returns a value of type Bar *.

Consider the return type of -[Foo initWithString:] being Foo * instead: if you would call [[Bar alloc] initWithString:], the compiler would infer that a Foo * is returned, not a Bar * as is the intention of the developer. The instancetype solved this issue.

Before the introduction of instancetype, initializers, static methods like singleton accessors and other methods that want to return an instance of the receiving class needed to return an id. The problem is that id means "an object of any type". The compiler is thus not able to detect that NSString *wrong = [[Foo alloc] initWithString:@"abc"]; is assigning to a variable with an incorrect type.

Due to this issue, **initializers should always use instancetype instead of** id as the return value.

Specifying Generics

You can enhance your own classes with generics just like NSArray or NSDictionary.

```
@interface MyClass<__covariant T>
@property (nonnull, nonatomic, strong, readonly) NSArray<T>* allObjects;
- (void) addObject:(nonnull T)obj;
@end
```

Difference between allocation and initialization

In most object oriented languages, allocating memory for an object and initializing it is an atomic operation:

```
// Both allocates memory and calls the constructor
MyClass object = new MyClass();
```

The object then is already "valid" but we always want to call a method to actually set up the object, which we call an *initializer*. These serve the same purpose as *constructors* in other languages. By convention, these methods start with init. From a language point of view, they are just normal methods.

```
// Allocate memory and set all properties and variables to 0/NO/nil.
MyClass *object = [MyClass alloc];
// Initialize the object.
object = [object init];
// Shorthand:
object = [[MyClass alloc] init];
```

Read Classes and Objects online: https://riptutorial.com/objective-c/topic/758/classes--and-objects

Chapter 7: Continue and Break!

Examples

Continue and Break Statement

The continue statement in Objective-C programming language works somewhat like the break statement. Instead of forcing termination, however, continue forces the next iteration of the loop to take place, skipping any code in between.

For the for loop, continue statement causes the conditional test and increment portions of the loop to execute. For the while and do...while loops, continue statement causes the program control pass to the conditional tests.

```
#import <Foundation/Foundation.h>
int main ()
{
   /* local variable definition */
   int a = 10;
   /* do loop execution */
   do
   {
      if( a == 15)
      {
         /* skip the iteration */
         a = a + 1;
         continue;
      }
      NSLog(@"value of a: %d\n", a);
      a++;
   }while( a < 20 );</pre>
   return 0;
}
```

Output:

2013-09-07 22:20:35.647 demo[29998] value of a: 10 2013-09-07 22:20:35.647 demo[29998] value of a: 11 2013-09-07 22:20:35.647 demo[29998] value of a: 12 2013-09-07 22:20:35.647 demo[29998] value of a: 13 2013-09-07 22:20:35.647 demo[29998] value of a: 14 2013-09-07 22:20:35.647 demo[29998] value of a: 16 2013-09-07 22:20:35.647 demo[29998] value of a: 17 2013-09-07 22:20:35.647 demo[29998] value of a: 17 2013-09-07 22:20:35.647 demo[29998] value of a: 18 2013-09-07 22:20:35.647 demo[29998] value of a: 18

Refer to this link for more information.
Read Continue and Break! online: https://riptutorial.com/objective-c/topic/8709/continue-and-break-

Chapter 8: Declare class method and instance method

Introduction

Instance method are methods that are specific to particular classes. Instance methods are declared and defined followed by - (minus) symbol.

Class methods can be called by class name itself .Class methods are declared and defined by using + (plus)sign .

Syntax

- 1. -(void)testInstanceMethod; //Class methods declare with "+" sign
- 2. (void)classMethod;//instance methods declare with "-" sign

Examples

How to declare class method and instance method.

instance methods use an instance of a class.

```
@interface MyTestClass : NSObject
- (void)testInstanceMethod;
@end
```

They could then be used like so:

```
MyTestClass *object = [[MyTestClass alloc] init];
[object testInstanceMethod];
```

Class method can be used with just the class name.

```
@interface MyClass : NSObject
+ (void)aClassMethod;
@end
```

They could then be used like so:

```
[MyClass aClassMethod];
```

class methods are the convenience methods on many Foundation classes like [NSString's +stringWithFormat:] or NSArray's +arrayWithArray

Read Declare class method and instance method online: https://riptutorial.com/objective-c/topic/8214/declare-class-method-and-instance-method

Chapter 9: Enums

Syntax

typedef NS_ENUM(type, name) {...} -- type is the type of enumeration and name is the name
of the enum. values are in "...". This creates a basic enum and a type to go with it; programs
like Xcode will assume a variable with the enum type has one of the enum values

Examples

Defining an enum

Enums are defined by the following the syntax above.

```
typedef NS_ENUM(NSUInteger, MyEnum) {
    MyEnumValueA,
    MyEnumValueB,
    MyEnumValueC,
};
```

You also can set your own raw-values to the enumeration types.

```
typedef NS_ENUM(NSUInteger, MyEnum) {
    MyEnumValueA = 0,
    MyEnumValueB = 5,
    MyEnumValueC = 10,
};
```

You can also specify on the first value and all the following will use it with increment:

```
typedef NS_ENUM(NSUInteger, MyEnum) {
    MyEnumValueA = 0,
    MyEnumValueB,
    MyEnumValueC,
};
```

Variables of this enum can be created by MyEnum enumVar = MyEnumValueA.

typedef enum declaration in Objective-C

A enum declares a set of ordered values - the typedef just adds a handy name to this. The 1st element is 0 etc.

```
typedef enum {
Monday=1,
Tuesday,
Wednesday
```

```
} WORKDAYS;
WORKDAYS today = Monday;//value 1
```

Converting C++ std::vector to an Objective-C Array

Many C++ libraries use enums and return/receive data using vectors that contain enums. As C enums are not Objective-C objects, Objective-C collections cannot be used directly with C enums. The example below deals with this by using a combination of an NSArray and generics and a wrapper object for the array. This way, the collection can be explicit about the data type and there is no worry about possible memory leaks with C arrays Objective-C objects are used.

Here is the C enum & Objective-C equivalent object:

```
typedef enum
{
 Error0 = 0,
 Error1 = 1,
 Error2 = 2
} MyError;
@interface ErrorEnumObj : NSObject
@property (nonatomic) int intValue;
+ (instancetype) objWithEnum: (MyError) myError;
- (MyError) getEnumValue;
@end
@implementation ErrorEnumObj
+ (instancetype) objWithEnum: (MyError) error
{
   ErrorEnumObj * obj = [ErrorEnumObj new];
   obj.intValue = (int)error;
   return obj;
}
- (MyError) getEnumValue
{
   return (MyError)self.intValue;
}
0end
```

And here is a possible use of it in Objective-C++ (the resulting NSArray can be used in Objective-C only files as no C++ is used).

```
class ListenerImpl : public Listener
{
    public:
        ListenerImpl(Listener* listener) : _listener(listener) {}
        void onError(std::vector<MyError> errors) override
        {
            NSMutableArray<ErrorEnumObj *> * array = [NSMutableArray<ErrorEnumObj *> new];
        }
}
```

```
for (auto&& myError : errors)
{
     [array addObject:[ErrorEnumObj objWithEnum:myError]];
}
[_listener onError:array];
}
private:
__weak Listener* _listener;
}
```

If this kind of solution is to be used on multiple enums, the creation of the EnumObj (declaration & implementation) can be done using a macro (to create a template like solution).

Read Enums online: https://riptutorial.com/objective-c/topic/1461/enums

Chapter 10: Error Handling

Syntax

• NSAssert(condition, fmtMessage, *arg1, arg2, ...*) (args in italics are optional) -- Asserts that *condition* evaluates to a true value. If it doesn't than the assertion will raise an exception (NSAssertionException), with the *fmtMessage* formatted with the args provided

Examples

Asserting

```
@implemenetation Triangle
...
-(void)setAngles:(NSArray *)_angles {
    self.angles = _angles;
    NSAssert((self.angles.count == 3), @"Triangles must have 3 angles. Array '%@' has %i",
    self.angles, (int)self.angles.count);
    CGFloat angleA = [self.angles[0] floatValue];
    CGFloat angleB = [self.angles[1] floatValue];
    CGFloat angleC = [self.angles[2] floatValue];
    CGFloat sum = (angleA + angleB + angleC);
    NSAssert((sum == M_PI), @"Triangles' angles must add up to pi radians (180°). This
    triangle's angles add up to %f radians (%f°)", (float)sum, (float)(sum * (180.0f / M_PI)));
}
```

These assertions make sure that you don't give a triangle incorrect angles, by throwing an exception if you do. If they didn't throw an exception than the triangle, not being a true triangle at all, might cause some bugs in later code.

Error & Exception handling with try catch block

Exceptions represent programmer-level bugs like trying to access an array element that doesn't exist.

Errors are user-level issues like trying load a file that doesn't exist. Because errors are expected during the normal execution of a program.

Example:

```
NSLog(@"The selected Name is: %@", name);
} @catch(NSException *theException) {
    NSLog(@"An exception occurred: %@", theException.name);
    NSLog(@"Here are some details: %@", theException.reason);
} @finally {
    NSLog(@"Executing finally block");
}
```

OUTPUT:

An exception occurred: NSRangeException

Here are some details: *** -[__NSArrayl objectAtIndex:]: index 3 beyond bounds [0 .. 2]

Executing finally block

Read Error Handling online: https://riptutorial.com/objective-c/topic/1459/error-handling

Chapter 11: Fast Enumeration

Examples

Fast enumeration of an NSArray

This example shows how to use fast enumeration in order to traverse through an NSArray.

When you have an array, such as

```
NSArray *collection = @[@"fast", @"enumeration", @"in objc"];
```

You can use the for ... in syntax to go through each item of the array, automatically starting with the first at index 0 and stopping with the last item:

```
for (NSString *item in collection) {
    NSLog(@"item: %@", item);
}
```

In this example, the output generated would look like

// item: fast
// item: enumeration
// item: in objc

Fast enumeration of an NSArray with index.

This example shows how to use fast enumeration in order to traverse through an NSArray. With this way you can also track current object's index while traversing.

Suppose you have an array,

```
NSArray *weekDays = @[@"Monday", @"Tuesday", @"Wednesday", @"Thursday", @"Friday",
@"Saturday", @"Sunday"];
```

Now you can traverse through the array like below,

```
[weekDays enumerateObjectsUsingBlock:^(id obj, NSUInteger idx, BOOL *stop) {
    //... Do your usual stuff here
    obj // This is the current object
    idx // This is the index of the current object
    stop // Set this to true if you want to stop
}];
```

Read Fast Enumeration online: https://riptutorial.com/objective-c/topic/5583/fast-enumeration

Chapter 12: Format-Specifiers

Introduction

Format-Specifiers are used in Objective-c to implant object-values into a string.

Syntax

- %@ //String
- %d //Signed 32-bit integer
- %D //Signed 32-bit integer
- %u //Unsigned 32-bit integer
- %U //Unsigned 32-bit integer
- %x //Unsigned 32-bit integer in lowercase hexadecimal format
- %X //Unsigned 32-bit integer in UPPERCASE hexadecimal format
- %o //Unsigned 32-bit integer in octal format
- %O //Unsigned 32-bit integer in octal format
- %f //64-bit floating-point number
- %F //64-bit floating-point number printed in decimal notation
- %e //64-bit floating-point number in lowercase scientific notation format
- %E //64-bit floating-point number in UPPERCASE scientific notation format
- %g //special case %e which uses %f when less than 4 sig-figs are available, else %e
- %G //special case %E which uses %f when less than 4 sig-figs are available, else %E
- %c //8-bit unsigned character
- %C //16-bit UTF-16 code unit
- %s //UTF8 String
- %S //16-bit variant of %s
- %p //Void Pointer in lowercase hexidecmial format with leading '0x'
- %zx //special case %p which removes leading '0x' (For use with no-type cast)
- %a //64-bit floating-point number in scientific notation with leading '0x' and one hexadecimal digit before the decimal point using a 'p' to notate the exponent.
- %A //64-bit floating-point number in scientific notation with leading '0x' and one hexadecimal digit before the decimal point using an 'P' to notate the exponent.

Remarks

Due to the nature of format-specifiers, if you wish to include the percentage symbol (%) in your string, you must escape it using a second percentage symbol.

Example:

```
int progress = 45;//percent
NSString *progressString = [NSString stringWithFormat:@"Progress: %i%%", (int)progress];
```

```
NSLog(progressString);//logs "Progress: 45%"
```

No Format Specifier for BOOL-type exists.

Common-use solutions include:

```
BOOL myBool = YES;
NSString *boolState = [NSString stringWithFormat:@"BOOL state: %@", myBool?@"true":@"false"];
NSLog(boolState);//logs "true"
```

Which utilizes a ternary operator for casting a string-equivalent.

```
BOOL myBool = YES;
NSString *boolState = [NSString stringWithFormat:@"BOOL state: %i", myBool];
NSLog(boolState);//logs "1" (binary)
```

Which utilizes an (int) cast for implanting a binary-equivalent.

Examples

Integer Example - %i

```
int highScore = 57;
NSString *scoreBoard = [NSString stringWithFormat:@"HighScore: %i", (int)highScore];
NSLog(scoreBoard);//logs "HighScore: 57"
```

Read Format-Specifiers online: https://riptutorial.com/objective-c/topic/9048/format-specifiers

Chapter 13: Grand Central Dispatch

Introduction

Grand Central Dispatch (GCD) In iOS, Apple provides two ways to do multitasking: The Grand Central Dispatch (GCD) and NSOperationQueue frameworks.We will discuss here about GCD. GCD is a lightweight way to represent units of work that are going to be executed concurrently You don't schedule these units of work; the system takes care of scheduling for you. Adding dependency among blocks can be a headache. Canceling or suspending a block creates extra work for you as a developer!

Examples

What is Grand central dispatch.

What is Concurrency?

- Doing multiple things at the same time.
- Taking advantage of number of cores available in multicore CPUs.
- Running multiple programs in parallel.

Objectives of Concurrency

- Running program in background without hogging CPU.
- Define Tasks, Define Rules and let the system take the responsibility of performing them.
- Improve responsiveness by ensuring that the main thread is free to respond to user events.

DISPATCH QUEUES

Grand central dispatch – dispatch queues allows us to execute arbitrary blocks of code either asynchronously or synchronously All Dispatch Queues are first in – first out All the tasks added to dispatch queue are started in the order they were added to the dispatch queue.

Read Grand Central Dispatch online: https://riptutorial.com/objective-c/topic/8280/grand-centraldispatch

Chapter 14: Inheritance

Syntax

1. @interface derived-class-Name: base-class-Name

Examples

Car is inherited from Vehicle

Consider a base class Vehicle and its derived class Car as follows:

```
#import <Foundation/Foundation.h>
@interface Vehicle : NSObject
{
    NSString *vehicleName;
   NSInteger vehicleModelNo;
}
- (id) initWithName: (NSString *) name andModel: (NSInteger) modelno;
- (void)print;
0end
@implementation Vehicle
- (id) initWithName: (NSString *) name andModel: (NSInteger) modelno{
    vehicleName = name;
    vehicleModelNo = modelno;
    return self;
}
- (void)print{
    NSLog(@"Name: %@", vehicleName);
    NSLog(@"Model: %ld", vehicleModelNo);
}
0end
@interface Car : Vehicle
{
   NSString *carCompanyName;
}
- (id)initWithName: (NSString *)name andModel: (NSInteger)modelno
  andCompanyName:(NSString *)companyname;
- (void)print;
0end
@implementation Car
```

```
- (id)initWithName:(NSString *)name andModel:(NSInteger) modelno
 andCompanyName: (NSString *) companyname
  {
   vehicleName = name;
   vehicleModelNo = modelno;
   carCompanyName = companyname;
   return self;
}
 (void)print
_
{
   NSLog(@"Name: %@", vehicleName);
   NSLog(@"Model: %ld", vehicleModelNo);
   NSLog(@"Company: %@", carCompanyName);
}
Gend
int main(int argc, const char * argv[])
{
   NSAutoreleasePool * pool = [[NSAutoreleasePool alloc] init];
   NSLog(@"Base class Vehicle Object");
   Vehicle *vehicle = [[Vehicle alloc]initWithName:@"4Wheeler" andModel:1234];
   [vehicle print];
   NSLog(@"Inherited Class Car Object");
   Car *car = [[Car alloc]initWithName:@"S-Class"
   andModel:7777 andCompanyName:@"Benz"];
    [car print];
    [pool drain];
   return 0;
}
```

When the above code is compiled and executed, it produces the following result:

2016-09-29 18:21:03.561 Inheritance[349:303] Base class Vehicle Object

2016-09-29 18:21:03.563 Inheritance[349:303] Name: 4Wheeler

2016-09-29 18:21:03.563 Inheritance[349:303] Model: 1234

2016-09-29 18:21:03.564 Inheritance[349:303] Inherited Class Car Object

2016-09-29 18:21:03.564 Inheritance[349:303] Name: S-Class

2016-09-29 18:21:03.565 Inheritance[349:303] Model: 7777

2016-09-29 18:21:03.565 Inheritance[349:303] Company: Benz

Read Inheritance online: https://riptutorial.com/objective-c/topic/7117/inheritance

Chapter 15: Key Value Coding / Key Value Observing

Examples

Most Common Real Life Key Value Coding Example

Key Value Coding is integrated into NSObject using NSKeyValueCoding protocol.

What this means?

It means that any id object is capable of calling valueForKey method and its various variants like valueForKeyPath etc. '

It also means that any id object can invoke setValue method and its various variants too.

Example:

```
id obj = [[MyClass alloc] init];
id value = [obj valueForKey:@"myNumber"];
int myNumberAsInt = [value intValue];
myNumberAsInt = 53;
[obj setValue:@(myNumberAsInt) forKey:@"myNumber"];
```

Exceptions:

Above example assumes that MyClass has an NSNumber Property called myNumber. If myNumber does not appear in MyClass interface definition, an NSUndefinedKeyException can be raised at possibly both lines 2 and 5 - popularly known as:

this class is not key value coding-compliant for the key myNumber.

Why this is SO powerful:

You can write code that can access properties of a class dynamically, without needing interface for that class. This means that a table view can display values from any properties of an NSObject derived object, provided its property names are supplied dynamically at runtime.

In the example above, the code can as well work without MyClass being available and id type obj being available to calling code.

Key Value Observing

Setting up key value observing.

In this case, we want to observe the ${\tt contentOffset}$ on an object that our observer owns

```
11
// Class to observe
11
@interface XYZScrollView: NSObject
@property (nonatomic, assign) CGPoint contentOffset;
@end
@implementation XYZScrollView
Gend
11
// Class that will observe changes
11
@interface XYZObserver: NSObject
@property (nonatomic, strong) XYZScrollView *scrollView;
0end
@implementation XYZObserver
// simple way to create a KVO context
static void *XYZObserverContext = &XYZObserverContext;
// Helper method to add self as an observer to
// the scrollView's contentOffset property
- (void)addObserver {
    // NSKeyValueObservingOptions
    11
    // - NSKeyValueObservingOptionNew
    // - NSKeyValueObservingOptionOld
    // - NSKeyValueObservingOptionInitial
    // - NSKeyValueObservingOptionPrior
    11
    // can be combined:
    // (NSKeyValueObservingOptionNew | NSKeyValueObservingOptionOld)
   NSString *keyPath = NSStringFromSelector(@selector(contentOffset));
   NSKeyValueObservingOptions options = NSKeyValueObservingOptionNew;
    [self.scrollView addObserver: self
                      forKeyPath: keyPath
                         options: options
                         context: XYZObserverContext];
}
- (void) observeValueForKeyPath: (NSString *) keyPath ofObject: (id) object
change:(NSDictionary<NSString *,id> *)change context:(void *)context {
    if (context == XYZObserverContext) { // check the context
        // check the keyPath to see if it's any of the desired keyPath's.
        // You can observe multiple keyPath's
        if ([keyPath isEqualToString: NSStringFromSelector(@selector(contentOffset))]) {
            // change dictionary keys:
            // - NSKeyValueChangeKindKey
            // - NSKeyValueChangeNewKey
            // - NSKeyValueChangeOldKey
            // - NSKeyValueChangeIndexesKey
```

```
// - NSKeyValueChangeNotificationIsPriorKey
            // the change dictionary here for a CGPoint observation will
            // return an NSPoint, so we can take the CGPointValue of it.
            CGPoint point = [change[NSKeyValueChangeNewKey] CGPointValue];
            // handle point
        1
    } else {
        // if the context doesn't match our current object's context
        // we want to pass the observation parameters to super
        [super observeValueForKeyPath: keyPath
                            ofObject: object
                              change: change
                              context: context];
   }
}
// The program can crash if an object is not removed as observer
// before it is dealloc'd
//
// Helper method to remove self as an observer of the scrollView's
// contentOffset property
- (void) removeObserver {
   NSString *keyPath = NSStringFromSelector(@selector(contentOffset));
    [self.scrollView removeObserver: self forKeyPath: keyPath];
}
Gend
```

Querying KVC Data

```
if ([[dataObject objectForKey:@"yourVariable"] isEqualToString:"Hello World"]) {
   return YES;
} else {
   return NO;
}
```

You can query values stored using KVC quickly and easily, without needing to retrieve or cast these as local variables.

Collection Operators

Collection Operators can be used in a KVC key path to perform an operation on a "collection-type" property (i.e. NSArray, NSSet and similar). For example, a common operation to perform is to count the objects in a collection. To achieve this, you use the @count collection operator.

```
self.array = @[@5, @4, @3, @2, @1];
NSNumber *count = [self.array valueForKeyPath:@"@count"];
NSNumber *countAlt = [self valueForKeyPath:@"array.@count"];
// count == countAlt == 5
```

While this is completely redundant here (we could have just accessed the count property), it can

be useful on occasion, though it is rarely necessary. There are, however, some collection operators that are much more useful, namely <code>@max, @min, @sum, @avg</code> and the <code>@unionOf</code> family. It is important to note that these operators *also* require a separate key path *following* the operator to function correctly. Here's a list of them and the type of data they work with:

Operator	Data Type
@count	(none)
@max	NSNumber, NSDate, int (and related), etc.
@min	NSNumber, NSDate, int (and related), etc.
@sum	NSNumber, int (and related), double (and related), etc.
@avg	NSNumber, int (and related), double (and related), etc.
@unionOfObjects	NSArray, NSSet, etc .
@distinctUnionOfObjects	NSArray, NSSet, etc .
@unionOfArrays	NSArray <nsarray*></nsarray*>
@distinctUnionOfArrays	NSArray <nsarray*></nsarray*>
@distinctUnionOfSets	NSSet <nsset*></nsset*>

<code>@max</code> and <code>@min</code> will return the highest or lowest value, respectively, of a property of objects in the collection. For example, look at the following code:

```
// "Point" class used in our collection
@interface Point : NSObject
@property NSInteger x, y;
+ (instancetype)pointWithX: (NSInteger)x y: (NSInteger)y;
@end
. . .
self.points = @[[Point pointWithX:0 y:0],
               [Point pointWithX:1 y:-1],
                [Point pointWithX:5 y:-6],
                [Point pointWithX:3 y:0],
                [Point pointWithX:8 y:-4],
];
NSNumber *maxX = [self valueForKeyPath:@"points.@max.x"];
NSNumber *minX = [self valueForKeyPath:@"points.@min.x"];
NSNumber *maxY = [self valueForKeyPath:@"points.@max.y"];
NSNumber *minY = [self valueForKeyPath:@"points.@min.y"];
NSArray<NSNumber*> *boundsOfAllPoints = @[maxX, minX, maxY, minY];
```

• • •

In just a 4 lines of code and pure Foundation, with the power of Key-Value Coding collection operators we were able to extract a rectangle that encapsulates all of the points in our array.

It is important to note that these comparisons are made by invoking the *compare*: method on the objects, so if you ever want to make your own class compatible with these operators, you must implement this method.

esum will, as you can probably guess, add up all the values of a property.

```
@interface Expense : NSObject
@property NSNumber *price;
+ (instancetype)expenseWithPrice:(NSNumber *)price;
@end
....
self.expenses = @[[Expense expenseWithPrice:@1.50],
                    [Expense expenseWithPrice:@9.99],
                    [Expense expenseWithPrice:@2.78],
                    [Expense expenseWithPrice:@9.99],
                    [Expense expenseWithPrice:@9.99],
                    [Expense expenseWithPrice:@1.50]];
NSNumber *totalExpenses = [self valueForKeyPath:@"expenses.@sum.price"];
```

Here, we used <code>@sum</code> to find the total price of all the expenses in the array. If we instead wanted to find the average price we're paying for each expense, we can use <code>@avg</code>:

```
NSNumber *averagePrice = [self valueForKeyPath:@"expenses.@avg.price"];
```

Finally, there's the <code>@unionOf</code> family. There are five different operators in this family, but they all work mostly the same, with only small differences between each. First, there's <code>@unionOfObjects</code> which will return an array of the properties of objects in an array:

```
// See "expenses" array above
NSArray<NSNumber*> *allPrices = [self valueForKeyPath:
    @"expenses.@unionOfObjects.price"];
// Equal to @[ @1.50, @9.99, @2.78, @9.99, @24.95 ]
```

@distinctUnionOfObjects functions the same as @unionOfObjects, but it removes duplicates:

```
NSArray<NSNumber*> *differentPrices = [self valueForKeyPath:
    @"expenses.@distinctUnionOfObjects.price"];
// Equal to @[ @1.50, @9.99, @2.78, @24.95 ]
```

And finally, the last 3 operators in the <code>@unionOf</code> family will go one step deeper and return an array of values found for a property contained inside dually-nested arrays:

```
NSArray<NSArray<Expense*,Expense*>*> *arrayOfArrays =
    @ [
        @[ [Expense expenseWithPrice:@19.99],
           [Expense expenseWithPrice:@14.95],
           [Expense expenseWithPrice:@4.50],
          [Expense expenseWithPrice:@19.99]
        ],
        @[ [Expense expenseWithPrice:@3.75],
          [Expense expenseWithPrice:@14.95]
         ]
     ];
// @unionOfArrays
NSArray<NSNumber*> allPrices = [arrayOfArrays valueForKeyPath:
    @"@unionOfArrays.price"];
// Equal to @[ @19.99, @14.95, @4.50, @19.99, @3.75, @14.95 ];
// @distinctUnionOfArrays
NSArray<NSNumber*> allPrices = [arrayOfArrays valueForKeyPath:
   @"@distinctUnionOfArrays.price"];
// Equal to @[ @19.99, @14.95, @4.50, @3.75 ];
```

The one missing from this example is <code>@distinctUnionOfSets</code>, however this functions exactly the same as <code>@distinctUnionOfArrays</code>, but works with and returns <code>NSSetS</code> instead (there is no non-distinct version because in a set, every object must be distinct anyway).

And that's it! Collection operators can be really powerful if used correctly, and can help to avoid having to loop through stuff unnecessarily.

One last note: you can also use the standard collection operators on arrays of NSNumbers (without additional property access). To do this, you access the self pseudo-property that just returns the object:

```
NSArray<NSNumber*> *numbers = @[@0, @1, @5, @27, @1337, @2048];
NSNumber *largest = [numbers valueForKeyPath:@"@max.self"];
NSNumber *smallest = [numbers valueForKeyPath:@"@min.self"];
NSNumber *total = [numbers valueForKeyPath:@"@sum.self"];
NSNumber *average = [numbers valueForKeyPath:@"@avg.self"];
```

Read Key Value Coding / Key Value Observing online: https://riptutorial.com/objectivec/topic/556/key-value-coding---key-value-observing

Chapter 16: Logging

Syntax

- NSLog(@"text to log"); // Basic text log
- NSLog(@"data: %f %.2f", myFloat, anotherFloat); // Logging text including float numbers.
- NSLog(@"data: %i", myInteger); // Logging text including integer number.
- NSLog(@"data: %@", myStringOrObject); // Logging text referencing another String or any NSObject derived object.

Remarks

For logging various types of objects and data-types refer to: Objective-C, Format Specifiers

Examples

Logging

```
NSLog(@"Log Message!");
NSLog(@"NSString value: %@", stringValue);
NSLog(@"Integer value: %d", intValue);
```

The first argument of NSLOG is an NSString containing the log message format. The rest of the parameters are used as values to substitute in place of the format specifiers.

The formatting works exactly the same as printf, except for the additional format specifier se for an arbitrary Objective-C object. This:

```
NSLog(@"%@", object);
```

is equivalent to:

NSLog(@"%s", [object description].UTF8String);

NSLog vs printf

```
NSLog(@"NSLog message");
printf("printf message\n");
```

Output:

```
2016-07-16 08:58:04.681 test[46259:1244773] NSLog message printf message
```

NSLog

outputs the date, time, process name, process ID, and thread ID in addition to the log message. printf just outputs the message.

NSLOG requires an NSString and automatically adds a newline at the end. printf requires a C string and does not automatically add a newline.

NSLog sends output to stderr, printf sends output to stdout.

Some format-specifiers in printf vs NSLog are different. For example when including a nested string, the following differences incur:

```
NSLog(@"My string: %@", (NSString *)myString);
printf("My string: %s", [(NSString *)myString UTF8String]);
```

NSLog Output Format

NSLog(@"NSLog message");

The message that gets printed by calling MSLog has the following format when viewed in Console.app:

Date	Time	Program name	Process ID		Thread ID	Message
2016-07-16	08:58:04.681	test	[46259	:	1244773]	NSLog message

Logging Variable Values

You shouldn't call NSLOG without a literal format string like this:

```
NSLog(variable); // Dangerous code!
```

If the variable is not an NSString, the program will crash, because NSLOG expects an NSString.

If the variable is an NSString, it will work unless your string contains a %. NSLog will parse the % sequence as a format specifier and then read a garbage value off the stack, causing a crash or even executing arbitrary code.

Instead, always make the first argument a format specifier, like this:

```
NSLog(@"%@", anObjectVariable);
NSLog(@"%d", anIntegerVariable);
```

Empty message is not printed

When NSLOG is asked to print empty string, it omits the log completely.

NSString *name = @""; NSLog(@"%@", name); // Resolves to @""

The above code will print nothing.

It is a good practice to prefix logs with labels:

NSString *name = @""; NSLog(@"Name: %@", name); // Resolves to @"Name: "

The above code will print:

```
2016-07-21 14:20:28.623 App[87711:6153103] Name:
```

Removing Log Statements from Release Builds

Messages printed from NSLOG are displayed on Console.app even in the release build of your app, which doesn't make sense for printouts that are only useful for debugging. To fix this, you can use this macro for debug logging instead of NSLOG.

```
#ifdef DEBUG
#define DLog(...) NSLog(__VA_ARGS__)
#else
#define DLog(...)
#endif
```

To use:

```
NSString *value = @"value 1";
DLog(@"value = %@", value);
// little known fact: programmers look for job postings in Console.app
NSLog(@"We're hiring!");
```

In debug builds, DLog will call NSLog. In release builds, DLog will do nothing.

Using __FUNCTION __

```
NSLog(@"%s %@", __FUNCTION__, @"etc etc");
```

Inserts the class and method name into the output:

```
2016-07-22 12:51:30.099 loggingExample[18132:2971471] -[ViewController viewDidLoad] etc etc
```

NSLog and BOOL type

There is no format specifier to print boolean type using NSLog. One way to print boolean value is to convert it to a string.

BOOL boolValue = YES; NSLog(@"Bool value %@", boolValue ? @"YES" : @"NO");

Output:

2016-07-30 22:53:18.269 Test[4445:64129] Bool value YES

Another way to print boolean value is to cast it to integer, achieving a binary output (1=yes, 0=no).

```
BOOL boolValue = YES;
NSLog(@"Bool value %i", boolValue);
```

Output:

```
2016-07-30 22:53:18.269 Test[4445:64129] Bool value 1
```

Logging NSLog meta data

NSLog(@"%s %d %s, yourVariable: %@", __FILE__, __LINE__, __PRETTY_FUNCTION__, yourVariable);

Will log the file, line number and function data along with any variables you want to log. This can make the log lines much longer, particularly with verbose file and method names, however it can help to speed up error diagnostics.

You can also wrap this in a Macro (store this in a Singleton or where you'll need it most);

```
#define ALog(fmt, ...) NSLog((@"%s [Line %d] " fmt), __PRETTY_FUNCTION_, __LINE__,
##__VA_ARGS__);
```

Then when you want to log, simply call

ALog(@"name: %@", firstName);

Which will give you something like;

-[AppDelegate application:didFinishLaunchingWithOptions:] [Line 27] name: John

Logging by Appending to a File

NSLog is good, but you can also log by appending to a file instead, using code like:

```
NSFileHandle* fh = [NSFileHandle fileHandleForWritingAtPath:path];
if ( !fh ) {
   [[NSFileManager defaultManager] createFileAtPath:path contents:nil attributes:nil];
   fh = [NSFileHandle fileHandleForWritingAtPath:path];
}
if ( fh ) {
```

```
@try {
    [fh seekToEndOfFile];
    [fh writeData:[self dataUsingEncoding:enc]];
    }
    @catch (...) {
    }
    [fh closeFile];
}
```

Read Logging online: https://riptutorial.com/objective-c/topic/724/logging

Chapter 17: Low-level Runtime Environment

Remarks

In order to use the Objective-C runtime, you need to import it.

#import <objc/objc.h>

Examples

Attach object to another existing object (association)

It's possible to attach an object to an existing object as if there was a new property. This is called *association* and allows one to extend existing objects. It can be used to provide storage when adding a property via a class extension or otherwise add additional information to an existing object.

The associated object is automatically released by the runtime once the target object is deallocated.

```
#import <objc/runtime.h>
// "Key" for association. Its value is never used and doesn't
// matter. The only purpose of this global static variable is to
// provide a guaranteed unique value at runtime: no two distinct
// global variables can share the same address.
static char key;
id target = ...;
id payload = ...;
objc_setAssociateObject(target, &key, payload, OBJC_ASSOCIATION_RETAIN);
// Other useful values are OBJC_ASSOCIATION_COPY
// and OBJ_ASSOCIATION_ASSIGN
id queryPayload = objc_getAssociatedObject(target, &key);
```

Augmenting methods using Method Swizzling

The Objective-C runtime allows you to change the implementation of a method at runtime. This is called *method swizzling* and is often used to exchange the implementations of two methods. For example, if the methods foo and bar are exchanged, sending the message foo will now execute the implementation of bar and vice versa.

This technique can be used to augment or "patch" existing methods which you cannot edit directly, such as methods of system-provided classes.

In the following example, the -[NSUserDefaults synchronize] method is augmented to print the execution time of the original implementation.

IMPORTANT: Many people try to do swizzling using method_exchangeImplementations. However, this
approach is dangerous if you need to call the method you're replacing, because you'll be calling it
using a different selector than it is expecting to receive. As a result, your code can break in
strange and unexpected ways—particularly if multiple parties swizzle an object in this way.
Instead, you should always do swizzling using setImplementation in conjunction with a C function,
allowing you to call the method with the original selector.

```
#import "NSUserDefaults+Timing.h"
#import <objc/runtime.h> // Needed for method swizzling
static IMP old_synchronize = NULL;
static void new_synchronize(id self, SEL _cmd);
@implementation NSUserDefaults(Timing)
+ (void)load
{
   Method originalMethod = class_getInstanceMethod([self class], @selector(synchronize:));
   IMP swizzleImp = (IMP)new_synchronize;
   old_synchronize = method_setImplementation(originalMethod, swizzleImp);
}
Gend
static void new_synchronize(id self, SEL _cmd);
{
   NSDate *started;
   BOOL returnValue;
    started = [NSDate date];
   // Call the original implementation, passing the same parameters
   // that this function was called with, including the selector.
   returnValue = old_synchronize(self, _cmd);
   NSLog(@"Writing user defaults took %f seconds.", [[NSDate date]
timeIntervalSinceDate:started]);
   return returnValue;
}
Gend
```

If you need to swizzle a method that takes parameters, you just add them as additional parameters to the function. For example:

```
static IMP old_viewWillAppear_animated = NULL;
static void new_viewWillAppear_animated(id self, SEL _cmd, BOOL animated);
...
Method originalMethod = class_getClassMethod([UIViewController class],
@selector(viewWillAppear:));
IMP swizzleImp = (IMP)new_viewWillAppear_animated;
old_viewWillAppear_animated = method_setImplementation(originalMethod, swizzleImp);
```

```
...
static void new_viewWillAppear_animated(id self, SEL _cmd, BOOL animated)
{
    ...
    old_viewWillAppear_animated(self, _cmd, animated);
    ...
}
```

Calling methods directly

If you need to call an Objective-C method from C code, you have two ways: using objc_msgSend, or obtaining the IMP (method implementation function pointer) and calling that.

```
#import <objc/objc.h>
@implementation Example
- (double) negate: (double) value {
    return -value;
}
 (double) invert: (double) value {
   return 1 / value;
}
lend
// Calls the selector on the object. Expects the method to have one double argument and return
a double.
double performSelectorWithMsqSend(id object, SEL selector, double value) {
   // We declare pointer to function and cast `objc_msgSend` to expected signature.
   // WARNING: This step is important! Otherwise you may get unexpected results!
   double (*msgSend)(id, SEL, double) = (typeof(msgSend)) & objc_msgSend;
    // The implicit arguments of self and _cmd need to be passed in addition to any explicit
arguments.
    return msgSend(object, selector, value);
}
// Does the same as the above function, but by obtaining the method's IMP.
double performSelectorWithIMP(id object, SEL selector, double value) {
   // Get the method's implementation.
   IMP imp = class_getMethodImplementation([self class], selector);
   // Cast it so the types are known and ARC can work correctly.
   double (*callableImp)(id, SEL, double) = (typeof(callableImp)) imp;
   // Again, you need the explicit arguments.
   return callableImp(object, selector, value);
}
int main() {
   Example *e = [Example new];
    // Invoke negation, result is -4
    double x = performSelectorWithMsgSend(e, @selector(negate:), 4);
```

```
// Invoke inversion, result is 0.25
double y = performSelectorWithIMP(e, @selector(invert:), 4);
}
```

objc_msgSend works by obtaining the IMP for the method and calling that. The IMPs for the last several methods called are cached, so if you're sending an Objective-C message in a very tight loop you can get acceptable performance. In some cases, manually caching the IMP can give slightly better performance, although this is a last resort optimization.

Read Low-level Runtime Environment online: https://riptutorial.com/objective-c/topic/1180/low-level-runtime-environment

Chapter 18: Memory Management

Examples

Automatic Reference Counting

With automatic reference counting (ARC), the compiler inserts retain, release, and autorelease statements where they are needed, so you don't have to write them yourself. It also writes dealloc methods for you.

The sample program from Manual Memory Management looks like this with ARC:

```
@interface MyObject : NSObject {
   NSString *_property;
}
0end
@implementation MyObject
@synthesize property = _property;
- (id) initWithProperty: (NSString *) property {
   if (self = [super init]) {
       _property = property;
   }
   return self;
}
- (NSString *)property {
    return property;
}
- (void) setProperty: (NSString *) property {
    _property = property;
}
0end
int main() {
   MyObject *obj = [[MyObject alloc] init];
   NSString *value = [[NSString alloc] initWithString:@"value"];
    [obj setProperty:value];
    [obj setProperty:@"value"];
}
```

You are still able to override the dealloc method to clean up resources not handled by ARC. Unlike when using manual memory management you do not call [super dealloc].

```
-(void)dealloc {
//clean up
}
```

Strong and weak references

Modern

A weak reference looks like one of these:

```
@property (weak) NSString *property;
NSString *__weak variable;
```

If you have a weak reference to an object, then under the hood:

- You're not retaining it.
- When it gets deallocated, every reference to it will automatically be set to nil

Object references are always strong by default. But you can explicitly specify that they're strong:

```
@property (strong) NSString *property;
NSString *__strong variable;
```

A strong reference means that while that reference exists, you are retaining the object.

Manual Memory Management

This is an example of a program written with manual memory management. You really shouldn't write your code like this, unless for some reason you can't use ARC (like if you need to support 32-bit). The example avoids <code>@property</code> notation to illustrate how you used to have to write getters and setters.

```
@interface MyObject : NSObject {
   NSString *_property;
}
0end
@implementation MyObject
@synthesize property = _property;
- (id) initWithProperty: (NSString *) property {
    if (self = [super init]) {
        // Grab a reference to property to make sure it doesn't go away.
        // The reference is released in dealloc.
       _property = [property retain];
    }
    return self;
}
- (NSString *)property {
    return [[property retain] autorelease];
}
- (void) setProperty: (NSString *) property {
    // Retain, then release. So setting it to the same value won't lose the reference.
    [property retain];
    [_property release];
    _property = property;
```

```
}
- (void)dealloc {
   [_property release];
    [super dealloc]; // Don't forget!
}
@end
int main() {
   // create object
   // obj is a reference that we need to release
   MyObject *obj = [[MyObject alloc] init];
   // We have to release value because we created it.
   NSString *value = [[NSString alloc] initWithString:@"value"];
    [obj setProperty:value];
    [value release];
    // However, string constants never need to be released.
   [obj setProperty:@"value"];
    [obj release];
}
```

Memory management rules when using manual reference counting.

These rules apply only if you use manual reference counting!

1. You own any object you create

By calling a method whose name begins with alloc, new, copy or mutableCopy. For example:

```
NSObject *object1 = [[NSObject alloc] init];
NSObject *object2 = [NSObject new];
NSObject *object3 = [object2 copy];
```

That means that you are responsible for releasing these objects when you are done with them.

2. You can take ownership of an object using retain

To take ownership for an object you call the retain method.

For example:

```
NSObject *object = [NSObject new]; // object already has a retain count of 1
[object retain]; // retain count is now 2
```

This makes only sense in some rare situations.

For example when you implement an accessor or an init method to take ownership:

```
- (void) setStringValue: (NSString *) stringValue {
```

```
[_privateStringValue release]; // Release the old value, you no longer need it
  [stringValue retain]; // You make sure that this object does not get deallocated
outside of your scope.
  _privateStringValue = stringValue;
}
```

3. When you no longer need it, you must relinquish ownership of an object you own

```
NSObject* object = [NSObject new]; // The retain count is now 1
[object performAction1]; // Now we are done with the object
[object release]; // Release the object
```

4. You must not relinquish ownership of an object you do not own

That means when you didn't take ownership of an object you don't release it.

5. Autoreleasepool

The autoreleasepool is a block of code that releases every object in the block that received an autorelease message.

Example:

```
@autoreleasepool {
    NSString* string = [NSString stringWithString:@"We don't own this object"];
}
```

We have created a string without taking ownership. The *NSString* method *stringWithString*: has to make sure that the string is correctly deallocated after it is no longer needed. Before the method returns the newly created string calls the autorelease method so it does not have to take ownership of the string.

This is how the stringWithString: is implemented:

```
+ (NSString *)stringWithString:(NSString *)string {
    NSString *createdString = [[NSString alloc] initWithString:string];
    [createdString autorelease];
    return createdString;
}
```

It is necessary to use autoreleasepool blocks because you sometimes have objects that you don't own (the fourth rules does not always apply).

Automatic reference counting takes automatically care of the rules so you don't have to.

Read Memory Management online: https://riptutorial.com/objective-c/topic/2751/memorymanagement

Chapter 19: Methods

Syntax

- - or +: The type of method. Instance or class?
- (): Where the return type goes. Use void if you don't want to return anything!
- Next is the name of the method. Use camelCase and make the name easy to remember an understand.
- If your method needs parameters, now is the time! The first parameter come right after the name of the function like this : (type) parameterName. All the other parameters are done this Way parameterLabel: (type) parameterName
- What does your method do? Put it all here, in the curly braces {}!

Examples

Method parameters

If you want to pass in values to a method when it is called, you use parameters:

```
- (int)addInt:(int)intOne toInt:(int)intTwo {
  return intOne + intTwo;
}
```

The colon (:) separates the parameter from the method name.

The parameter type goes in the parentheses (int).

The parameter name goes after the parameter type.

Create a basic method

This is how to create a basic method that logs 'Hello World" to the console:

```
- (void)hello {
   NSLog(@"Hello World");
}
```

The - at the beginning denotes this method as an instance method.

The (void) denotes the return type. This method doesn't return anything, so you enter void.

The 'hello' is the name of the method.

Everything in the ${}_{\{\cdot\}}$ is the code run when the method is called.

Return values

When you want to return a value from a method, you put the type you want to return in the first set of parentheses.

```
- (NSString)returnHello {
  return @"Hello World";
}
```

The value you want to return goes after the return keyword;

Class methods

A class method is called on the class the method belongs to, not an instance of it. This is possible because Objective-C classes are also objects. To denote a method as a class method, change the – to a +:

```
+ (void)hello {
    NSLog(@"Hello World");
}
```

Calling methods

Calling an instance method:

```
[classInstance hello];
@interface Sample
-(void)hello; // exposing the class Instance method
@end
@implementation Sample
-(void)hello{
            NSLog(@"hello");
        }
@end
```

Calling an instance method on the current instance:

```
[self hello];
@implementation Sample
  -(void)otherMethod{
    [self hello];
  }
  -(void)hello{
    NSLog(@"hello");
  }
```

@end

Calling a method that takes arguments:

```
[classInstance addInt:1 toInt:2];
@implementation Sample
    -(void)add:(NSInteger)add to:(NSInteger)to
    NSLog(@"sum = %d",(add+to));
    }
@end
```

Calling a class method:

```
[Class hello];
@interface Sample
+(void)hello; // exposing the class method
@end
@implementation Sample
+(void)hello{
            NSLog(@"hello");
        }
@end
```

Instance methods

An instance method is a method that's available on a particular instance of a class, after the instance has been instantiated:

```
MyClass *instance = [MyClass new];
[instance someInstanceMethod];
```

Here's how you define one:

```
@interface MyClass : NSObject
- (void)someInstanceMethod; // "-" denotes an instance method
@end
@implementation MyClass
- (void)someInstanceMethod {
    NSLog(@"Whose idea was it to have a method called \"someInstanceMethod\"?");
}
@end
```

Pass by value parameter passing

In pass by value of parameter passing to a method, actual parameter value is copied to formal
parameter value. So actual parameter value will not change after returning from called function.

```
@interface SwapClass : NSObject
-(void) swap:(NSInteger)num1 andNum2:(NSInteger)num2;
@end
@implementation SwapClass
-(void) num:(NSInteger)num1 andNum2:(NSInteger)num2{
    int temp;
    temp = num1;
    num1 = num2;
    num2 = temp;
}
@end
```

Calling the methods:

```
NSInteger a = 10, b =20;
SwapClass *swap = [[SwapClass alloc]init];
NSLog(@"Before calling swap: a=%d,b=%d",a,b);
[swap num:a andNum2:b];
NSLog(@"After calling swap: a=%d,b=%d",a,b);
```

Output:

```
2016-07-30 23:55:41.870 Test[5214:81162] Before calling swap: a=10,b=20 2016-07-30 23:55:41.871 Test[5214:81162] After calling swap: a=10,b=20
```

Pass by reference parameter passing

In pass by reference of parameter passing to a method, address of actual parameter is passed to formal parameter. So actual parameter value will be changed after returning from called function.

```
@interface SwapClass : NSObject
-(void) swap:(int)num1 andNum2:(int)num2;
@end
@implementation SwapClass
-(void) num:(int*)num1 andNum2:(int*)num2{
    int temp;
    temp = *num1;
    *num1 = *num2;
    *num2 = temp;
}
@end
```

Calling the methods:

```
int a = 10, b =20;
SwapClass *swap = [[SwapClass alloc]init];
NSLog(@"Before calling swap: a=%d,b=%d",a,b);
[swap num:&a andNum2:&b];
NSLog(@"After calling swap: a=%d,b=%d",a,b);
```

Output:

```
2016-07-31 00:01:47.067 Test[5260:83491] Before calling swap: a=10,b=20
2016-07-31 00:01:47.070 Test[5260:83491] After calling swap: a=20,b=10
```

Read Methods online: https://riptutorial.com/objective-c/topic/1457/methods

Chapter 20: Modern Objective-C

Examples

Literals

Modern Objective C provides ways to reduce amount of code you need to initialize some common types. This new way is very similar to how NSString objects are initialized with constant strings.

NSNumber

Old way:

```
NSNumber *number = [NSNumber numberWithInt:25];
```

Modern way:

```
NSNumber *number = @25;
```

Note: you can also store BOOL values in NSNumber objects using @YES, @NO or @(someBoolValue);

NSArray

Old way:

```
NSArray *array = [[NSArray alloc] initWithObjects:@"One", @"Two", [NSNumber numberWithInt:3],
@"Four", nil];
```

Modern way:

```
NSArray *array = @[@"One", @"Two", @3, @"Four"];
```

NSDictionary

Old way:

```
NSDictionary *dictionary = [NSDictionary dictionaryWithObjectsAndKeys: array, @"Object",
[NSNumber numberWithFloat:1.5], @"Value", @"ObjectiveC", @"Language", nil];
```

Modern way:

NSDictionary *dictionary = @{@"Object": array, @"Value": @1.5, @"Language": @"ObjectiveC"};

Container subscripting

In modern Objective C syntax you can get values from NSArray and NSDictionary containers using container subscripting.

Old way:

```
NSObject *object1 = [array objectAtIndex:1];
NSObject *object2 = [dictionary objectForKey:@"Value"];
```

Modern way:

```
NSObject *object1 = array[1];
NSObject *object2 = dictionary[@"Value"];
```

You can also insert objects into arrays and set objects for keys in dictionaries in a cleaner way:

Old way:

```
// replacing at specific index
[mutableArray replaceObjectAtIndex:1 withObject:@"NewValue"];
// adding a new value to the end
[mutableArray addObject:@"NewValue"];
[mutableDictionary setObject:@"NewValue" forKey:@"NewKey"];
```

Modern way:

```
mutableArray[1] = @"NewValue";
mutableArray[[mutableArray count]] = @"NewValue";
mutableDictionary[@"NewKey"] = @"NewValue";
```

Read Modern Objective-C online: https://riptutorial.com/objective-c/topic/9486/modern-objective-c

Chapter 21: Multi-Threading

Examples

Creating a simple thread

The most simple way to create a thread is by calling a selector "in the background". This means a new thread is created to execute the selector. The receiving object can be any object, not just self, but it needs to respond to the given selector.

Create more complex thread

Using a subclass of NSThread allows implementation of more complex threads (for example, to allow passing more arguments or to encapsulate all related helper methods in one class). Additionally, the NSThread instance can be saved in a property or variable and can be queried about its current state (whether it's still running).

The NSThread class supports a method called cancel that can be called from any thread, which then sets the cancelled property to YES in a thread-safe way. The thread implementation can query (and/or observe) the cancelled property and exit its main method. This can be used to gracefully shut down a worker thread.

```
// Create a new NSThread subclass
@interface MyThread : NSThread
// Add properties for values that need to be passed from the caller to the new
// thread. Caller must not modify these once the thread is started to avoid
// threading issues (or the properties must be made thread-safe using locks).
@property NSInteger someProperty;
@end
@implementation MyThread
- (void)main
{
    @autoreleasepool {
        // The main thread method goes here
```

```
NSLog(@"New thread. Some property: %ld", (long)self.someProperty);
}
@end
MyThread *thread = [[MyThread alloc] init];
thread.someProperty = 42;
[thread start];
```

Thread-local storage

Every thread has access to a mutable dictionary that is local to the current thread. This allows to cache informations in an easy way without the need for locking, as each thread has its own dedicated mutable dictionary:

```
NSMutableDictionary *localStorage = [NSThread currentThread].threadDictionary;
localStorage[someKey] = someValue;
```

The dictionary is automatically released when the thread terminates.

Read Multi-Threading online: https://riptutorial.com/objective-c/topic/3350/multi-threading

Chapter 22: NSArray

Syntax

- NSArray *words; // Declaring immutable array
- NSMutableArray *words; // Declaring mutable array
- NSArray *words = [NSArray arrayWithObjects: @"one", @"two", nil]; // Array initialization syntax
- NSArray *words = @[@"list", @"of", @"words", @123, @3.14]; // Declaring array literals
- NSArray *stringArray = [NSArray arrayWithObjects: [NSMutableArray array], [NSMutableArray array], [NSMutableArray array], nil]; // Creating multidimentional arrays

Examples

Creating Arrays

Creating immutable arrays:

```
NSArray *myColors = [NSArray arrayWithObjects: @"Red", @"Green", @"Blue", @"Yellow", nil];
// Using the array literal syntax:
NSArray *myColors = @[@"Red", @"Green", @"Blue", @"Yellow"];
```

For mutable arrays, see NSMutableArray.

Finding out the Number of Elements in an Array

```
NSArray *myColors = [NSArray arrayWithObjects: @"Red", @"Green", @"Blue", @"Yellow", nil];
NSLog (@"Number of elements in array = %lu", [myColors count]);
```

Accessing elements

NSArray *myColors = @[@"Red", @"Green", @"Blue", @"Yellow"];
// Preceding is the preferred equivalent to [NSArray arrayWithObjects:...]

Getting a single item

The <code>objectAtIndex:</code> method provides a single object. The first object in an <code>NSArray</code> is index 0. Since an <code>NSArray</code> can be homogenous (holding different types of objects), the return type is <code>id</code> ("any object"). (An <code>id</code> can be assigned to a variable of any other object type.) Importantly, <code>NSArray</code>s can only contain objects. They cannot contain values like <code>int</code>.

```
NSUInteger idx = 2;
NSString *color = [myColors objectAtIndex:idx];
// color now points to the string @"Green"
```

Clang provides a better subscript syntax as part of its array literals functionality:

```
NSString *color = myColors[idx];
```

Both of these throw an exception if the passed index is less than 0 or greater than count - 1.

First and Last Item

```
NSString *firstColor = myColors.firstObject;
NSString *lastColor = myColors.lastObject;
```

The firstObject and lastObject are computed properties and return nil rather than crashing for empty arrays. For single element arrays they return the same object. Although, the firstObject method was not introduced to NSArray until iOS 4.0.

Filtering Arrays With Predicates

More about

NSPredicate:

Apple doc : NSPredicate

Converting NSArray to NSMutableArray to allow modification

```
NSArray *myColors = [NSArray arrayWithObjects: @"Red", @"Green", @"Blue", @"Yellow", nil];
// Convert myColors to mutable
NSMutableArray *myColorsMutable = [myColors mutableCopy];
```

Sorting array with custom objects

Compare method

Either you implement a compare-method for your object:

```
- (NSComparisonResult)compare:(Person *)otherObject {
    return [self.birthDate compare:otherObject.birthDate];
}
NSArray *sortedArray = [drinkDetails sortedArrayUsingSelector:@selector(compare:)];
```

NSSortDescriptor

You can easily sort by multiple keys by adding more than one to the array. Using custom comparator-methods is possible as well. Have a look at the documentation.

Blocks

```
NSArray *sortedArray;
sortedArray = [drinkDetails sortedArrayUsingComparator:^NSComparisonResult(id a, id b) {
    NSDate *first = [(Person*)a birthDate];
    NSDate *second = [(Person*)b birthDate];
    return [first compare:second];
}];
```

Performance

The -compare: and block-based methods will be quite a bit faster, in general, than using NSSortDescriptor as the latter relies on KVC. The primary advantage of the NSSortDescriptor method is that it provides a way to define your sort order using data, rather than code, which makes it easy to e.g. set things up so users can sort an NSTableView by clicking on the header row.

Converting between Sets and Arrays

```
NSSet *set = [NSSet set];
NSArray *array = [NSArray array];
NSArray *fromSet = [set allObjects];
NSSet *fromArray = [NSSet setWithArray:array];
```

Reverse an Array

NSArray *reversedArray = [myArray.reverseObjectEnumerator allObjects];

Looping through

```
NSArray *myColors = @[@"Red", @"Green", @"Blue", @"Yellow"];
// Fast enumeration
// myColors cannot be modified inside the loop
for (NSString *color in myColors) {
    NSLog(@"Element %@", color);
}
// Using indices
for (NSUInteger i = 0; i < myColors.count; i++) {</pre>
   NSLog(@"Element %d = %@", i, myColors[i]);
}
// Using block enumeration
[myColors enumerateObjectsUsingBlock:^(id obj, NSUInteger idx, BOOL * stop) {
    NSLog(@"Element %d = %@", idx, obj);
    // To abort use:
    *stop = YES
}];
// Using block enumeration with options
[myColors enumerateObjectsWithOptions:NSEnumerationReverse usingBlock:^(id obj, NSUInteger
idx, BOOL * stop) {
   NSLog(@"Element %d = %@", idx, obj);
}];
```

Using Generics

For added safety we can define the type of object that the array contains:

```
NSArray<NSString *> *colors = @[@"Red", @"Green", @"Blue", @"Yellow"];
NSMutableArray<NSString *> *myColors = [NSMutableArray arrayWithArray:colors];
[myColors addObject:@"Orange"]; // OK
[myColors addObject:[UIColor purpleColor]]; // "Incompatible pointer type" warning
```

It should be noted that this is checked during compilation time only.

Enumerating using blocks

```
NSArray *myColors = @[@"Red", @"Green", @"Blue", @"Yellow"];
[myColors enumerateObjectsUsingBlock:^(id obj, NSUInteger idx, BOOL *stop) {
    NSLog(@"enumerating object %@ at index %lu", obj, idx);
}];
```

By setting the stop parameter to YES you can indicate that further enumeration is not needed. to do this simply set stop = YES.

NSEnumerationOptions

You can enumerate the array in reverse and / or concurrently :

Enumerating subset of array

Comparing arrays

Arrays can be compared for equality with the aptly named **isEqualToArray:** method, which returns **YES** when both arrays have the same number of elements and every pair pass an **isEqual:** comparison.

The important thing is every pair must pass the isEqual: test. For custom objects this method should be implemented. It exists in the NSObject protocol.

Add objects to NSArray

```
NSArray *a = @[@1];
a = [a arrayByAddingObject:@2];
a = [a arrayByAddingObjectsFromArray:@[@3, @4, @5]];
```

These methods are optimized to recreate the new array very efficiently, usually without having to destroy the original array or even allocate more memory.

```
Read NSArray online: https://riptutorial.com/objective-c/topic/736/nsarray
```

Chapter 23: NSArray

Examples

Creating NSArray instances

```
NSArray *array1 = [NSArray arrayWithObjects:@"one", @"two", @"three", nil];
NSArray *array2 = @[@"one", @"two", @"three"];
```

Sorting Arrays

The most flexible ways to sort an array is with the sortedArrayUsingComparator: method. This accepts an **^NSComparisonResult(id obj1, id obj2) block**.

Return Value	Description
NSOrderedAscending	obj1 comes before obj2
NSOrderedSame	obj1 and obj2 have no order
NSOrderedDescending	obj1 comes after obj2

Example:

Filter NSArray and NSMutableArray

```
NSMutableArray *array =
    [NSMutableArray arrayWithObjects:@"Ken", @"Tim", @"Chris", @"Steve",@"Charlie",@"Melissa",
nil];
NSPredicate *bPredicate =
    [NSPredicate predicateWithFormat:@"SELF beginswith[c] 'c'"];
NSArray *beginWithB =
    [array filteredArrayUsingPredicate:bPredicate];
// beginWith "C" contains { @"Chris", @"Charlie" }.
NSPredicate *sPredicate =
    [NSPredicate predicateWithFormat:@"SELF contains[c] 'a'"];
```

```
[array filterUsingPredicate:sPredicate];
// array now contains { @"Charlie", @"Melissa" }
```

Read NSArray online: https://riptutorial.com/objective-c/topic/1181/nsarray

Chapter 24: NSAttributedString

Examples

Creating a string that has custom kerning (letter spacing) editshare

NSAttributedstring (and its mutable sibling NSMutableAttributedstring) allows you to create strings that are complex in their appearance to the user.

A common application is to use this to display a string and adding custom kerning / letter-spacing.

This would be achieved as follows (where label is a UILabel), giving a different kerning for the word "kerning"

```
NSMutableAttributedString *attributedString;
attributedString = [[NSMutableAttributedString alloc] initWithString:@"Apply kerning"];
[attributedString addAttribute:NSKernAttributeName value:@5 range:NSMakeRange(6, 7)];
[label setAttributedText:attributedString];
```

Create a string with text struck through

Using Enumerating over Attributes in a String and underline part of string

```
NSMutableDictionary *attributesDictionary = [NSMutableDictionary dictionary];
 [attributesDictionary setObject:[UIFont systemFontOfSize:14] forKey:NSFontAttributeName];
 //[attributesDictionary setObject:[UIColor redColor] forKey:NSForegroundColorAttributeName];
NSMutableAttributedString *attributedString = [[NSMutableAttributedString
alloc]initWithString:@"Google www.google.com link" attributes:attributesDictionary];
 [attributedString enumerateAttribute: (NSString *) NSFontAttributeName
                             inRange:NSMakeRange(0, [attributedString length])
options:NSAttributedStringEnumerationLongestEffectiveRangeNotRequired
                          usingBlock:^(id value, NSRange range, BOOL *stop) {
                              NSLog(@"Attribute: %@, %@", value, NSStringFromRange(range));
                             }1;
 NSMutableAttributedString *attributedStr = [[NSMutableAttributedString alloc]
initWithString:@"www.google.com "];
  [attributedString addAttribute:NSUnderlineStyleAttributeName
                         value:[NSNumber numberWithInt:NSUnderlineStyleDouble]
                         range:NSMakeRange(7, attributedStr.length)];
  [attributedString addAttribute:NSForegroundColorAttributeName
```

```
value:[UIColor blueColor]
range:NSMakeRange(6,attributedStr.length)];
_attriLbl.attributedText = attributedString;//_attriLbl (of type UILabel) added in
storyboard
```

Output:

Google www.google.com link

How you create a tri-color attributed string.

```
NSMutableAttributedString * string = [[NSMutableAttributedString alloc]
initWithString:@"firstsecondthird"];
[string addAttribute:NSForegroundColorAttributeName value:[UIColor redColor]
range:NSMakeRange(0,5)];
[string addAttribute:NSForegroundColorAttributeName value:[UIColor greenColor]
range:NSMakeRange(5,6)];
[string addAttribute:NSForegroundColorAttributeName value:[UIColor blueColor]
range:NSMakeRange(11,5)];
```

Range : start to end string

Here we have firstsecondthird string so in first we have set range (0,5) so from starting first character to fifth character it will display in green text color.

Read NSAttributedString online: https://riptutorial.com/objective-c/topic/3725/nsattributedstring

Chapter 25: NSCache

Examples

NSCache

You use it the same way you would use NSMutableDictionary. The difference is that when NSCache detects excessive memory pressure (i.e. it's caching too many values) it will release some of those values to make room.

If you can recreate those values at runtime (by downloading from the Internet, by doing calculations, whatever) then NSCache may suit your needs. If the data cannot be recreated (e.g. it's user input, it is time-sensitive, etc.) then you should not store it in an NSCache because it will be destroyed there.

Read NSCache online: https://riptutorial.com/objective-c/topic/8257/nscache

Chapter 26: NSCalendar

Examples

System Locale Information

+currentCalendar returns the logical calendar for the current user.

```
NSCalendar *calender = [NSCalendar currentCalendar];
NSLog(@"%@",calender);
```

+autoupdatingCurrentCalendar returns the current logical calendar for the current user.

```
NSCalendar *calender = [NSCalendar autoupdatingCurrentCalendar];
NSLog(@"%@",calender);
```

Initializing a Calendar

- initWithCalendarIdentifier: Initializes a newly-allocated NSCalendar object for the calendar specified by a given identifier.

```
NSCalendar *calender = [[NSCalendar alloc]initWithCalendarIdentifier:@"gregorian"];
NSLog(@"%@",calender);
```

- setFirstWeekday: Sets the index of the first weekday for the receiver.

```
NSCalendar *calender = [NSCalendar autoupdatingCurrentCalendar];
[calender setFirstWeekday:1];
NSLog(@"%d",[calender firstWeekday]);
```

- setLocale: Sets the locale for the receiver.

```
NSCalendar *calender = [NSCalendar autoupdatingCurrentCalendar];
[calender setLocale:[NSLocale currentLocale]];
NSLog(@"%@",[calender locale]);
```

- setMinimumDaysInFirstWeek: Sets the minimum number of days in the first week of the receiver.

```
NSCalendar *calender = [NSCalendar autoupdatingCurrentCalendar];
[calender setMinimumDaysInFirstWeek:7];
NSLog(@"%d",[calender minimumDaysInFirstWeek]);
```

- setTimeZone: Sets the time zone for the receiver.

```
NSCalendar *calender = [NSCalendar autoupdatingCurrentCalendar];
[calender setTimeZone:[NSTimeZone timeZoneForSecondsFromGMT:0]];
NSLog(@"%@",[calender timeZone]);
```

Calendrical Calculations

- components:fromDate: Returns a NSDateComponents object containing a given date decomposed into specified components

```
NSCalendar *calender = [NSCalendar autoupdatingCurrentCalendar];
[calender setTimeZone:[NSTimeZone timeZoneForSecondsFromGMT:0]];
NSLog(@"%@",[calender components:NSCalendarUnitDay fromDate:[NSDate date]]);
NSLog(@"%@",[calender components:NSCalendarUnitYear fromDate:[NSDate date]]);
NSLog(@"%@",[calender components:NSCalendarUnitMonth fromDate:[NSDate date]]);
```

- components:fromDate:toDate:options: Returns, as an NSDateComponents object using specified components, the difference between two supplied dates.

```
NSCalendar *calender = [NSCalendar autoupdatingCurrentCalendar];
[calender setTimeZone:[NSTimeZone timeZoneForSecondsFromGMT:0]];
NSLog(@"%@",[calender components:NSCalendarUnitYear fromDate:[NSDate
dateWithTimeIntervalSince1970:0] toDate:[NSDate dateWithTimeIntervalSinceNow:18000]
options:NSCalendarWrapComponents]);
```

- dateByAddingComponents:toDate:options: Returns a new NSDate object representing the absolute time calculated by adding given components to a given date.

```
NSCalendar *calender = [NSCalendar autoupdatingCurrentCalendar];
NSDateComponents *dateComponent = [[NSDateComponents alloc]init];
[dateComponent setYear:10];
NSLog(@"%@",[calender dateByAddingComponents:dateComponent toDate:[NSDate
dateWithTimeIntervalSinceNow:0] options:NSCalendarWrapComponents] );
```

- dateFromComponents: Returns a new NSDate object representing the absolute time calculated from given components.

```
NSCalendar *calender = [NSCalendar autoupdatingCurrentCalendar];
NSDateComponents *dateComponent = [[NSDateComponents alloc]init];
[dateComponent setYear:2020];
NSLog(@"%@",[calender dateFromComponents:dateComponent]);
```

Read NSCalendar online: https://riptutorial.com/objective-c/topic/2903/nscalendar

Chapter 27: NSData

Examples

Create

From NSString:

```
NSString *str = @"Hello world";
NSData *data = [str dataUsingEncoding:NSUTF8StringEncoding];
```

From Int:

```
int i = 1;
NSData *data = [NSData dataWithBytes: &i length: sizeof(i)];
```

You can also use the following methods:

- + dataWithContentsOfURL:
- + dataWithContentsOfURL:options:error:
- + dataWithData:
- initWithBase64EncodedData:options:
- initWithBase64EncodedString:options:
- initWithBase64Encoding:
- initWithBytesNoCopy:length:
- initWithBytesNoCopy:length:deallocator:
- initWithBytesNoCopy:length:freeWhenDone:
- initWithContentsOfFile:
- initWithContentsOfFile:options:error:
- initWithContentsOfMappedFile:
- initWithContentsOfURL:
- initWithContentsOfURL:options:error:
- initWithData:

Get NSData lengh

```
NSString *filePath = [[NSFileManager defaultManager] pathForRessorce: @"data" ofType:@"txt"];
NSData *data = [NSData dataWithContentsOfFile:filePath];
int len = [data length];
```

Encoding and decoding a string using NSData Base64

Encoding

```
//Create a Base64 Encoded NSString Object
NSData *nsdata = [@"iOS Developer Tips encoded in Base64"
dataUsingEncoding:NSUTF8StringEncoding];
```

```
// Get NSString from NSData object in Base64
```

```
NSString *base64Encoded = [nsdata base64EncodedStringWithOptions:0];
// Print the Base64 encoded string
NSLog(@"Encoded: %@", base64Encoded);
```

Decoding:

```
// NSData from the Base64 encoded str
NSData *nsdataFromBase64String = [[NSData alloc]initWithBase64EncodedString:base64Encoded
options:0];
// Decoded NSString from the NSData
NSString *base64Decoded = [[NSString alloc] initWithData:nsdataFromBase64String
encoding:NSUTF8StringEncoding];
NSLog(@"Decoded: %@", base64Decoded);
```

NSData and Hexadecimal String

Get NSData from Hexadecimal String

```
+ (NSData *) dataFromHexString: (NSString *) string
{
    string = [string lowercaseString];
    NSMutableData *data= [NSMutableData new];
    unsigned char whole_byte;
    char byte_chars[3] = \{ ' \setminus 0', ' \setminus 0', ' \setminus 0' \};
    int i = 0;
    int length = (int) string.length;
    while (i < length-1) {</pre>
        char c = [string characterAtIndex:i++];
        if (c < '0' || (c > '9' \&\& c < 'a') || c > 'f')
             continue;
        byte_chars[0] = c;
        byte_chars[1] = [string characterAtIndex:i++];
        whole_byte = strtol(byte_chars, NULL, 16);
        [data appendBytes:&whole_byte length:1];
    }
    return data;
}
```

Get Hexadecimal String from data:

```
+ (NSString *)hexStringForData:(NSData *)data
{
    if (data == nil) {
        return nil;
    }
    NSMutableString *hexString = [NSMutableString string];
    const unsigned char *p = [data bytes];
    for (int i=0; i < [data length]; i++) {
        [hexString appendFormat:@"%02x", *p++];
    }
    return hexString;</pre>
```

Read NSData online: https://riptutorial.com/objective-c/topic/1532/nsdata

Chapter 28: NSDate

Remarks

NSDate is a very simple value type, representing one exact moment in universal time. It does not contain information about time zones, daylight saving time, calendars, or locale.

NSDate is really only an immutable wrapper around an NSTimeInterval which is a double. There is no mutable subclass, as with some other value types in Foundation.

Examples

Creating an NSDate

The NSDate class provides methods for creating NSDate objects corresponding to a given date and time. An NSDate can be initialized using the designated initializer, which:

Returns an NSDate object initialized relative to 00:00:00 UTC on 1 January 2001 by a given number of seconds.

```
NSDate *date = [[NSDate alloc] initWithTimeIntervalSinceReferenceDate:100.0];
```

NSDate also provides an easy way to create an NSDate equal to the current date and time:

```
NSDate *now = [NSDate date];
```

It is also possible to create an NSDate a given amount of seconds from the current date and time:

```
NSDate *tenSecondsFromNow = [NSDate dateWithTimeIntervalSinceNow:10.0];
```

Date Comparison

There are 4 methods for comparing NSDates in Objective-C:

- - (BOOL)isEqualToDate:(NSDate *)anotherDate
- - (NSDate *)earlierDate:(NSDate *)anotherDate
- - (NSDate *)laterDate:(NSDate *)anotherDate
- - (NSComparisonResult)compare:(NSDate *)anotherDate

Consider the following example using 2 dates, NSDate date1 = July 7, 2016 and NSDate date2 = July 2, 2016:

```
NSDateComponents *comps1 = [[NSDateComponents alloc]init];
comps.year = 2016;
comps.month = 7;
comps.day = 7;
```

```
NSDateComponents *comps2 = [[NSDateComponents alloc]init];
    comps.year = 2016;
    comps.month = 7;
    comps.day = 2;
NSDate* date1 = [calendar dateFromComponents:comps1]; //Initialized as July 7, 2016
NSDate* date2 = [calendar dateFromComponents:comps2]; //Initialized as July 2, 2016
```

Now that the NSDates are created, they can be compared:

```
if ([date1 isEqualToDate:date2]) {
    //Here it returns false, as both dates are not equal
}
```

We can also use the earlierDate: and laterDate: methods of the NSDate class:

```
NSDate *earlierDate = [date1 earlierDate:date2];//Returns the earlier of 2 dates. Here
earlierDate will equal date2.
NSDate *laterDate = [date1 laterDate:date2];//Returns the later of 2 dates. Here laterDate
will equal date1.
```

Lastly, we can use NSDate's compare: method:

```
NSComparisonResult result = [date1 compare:date2];
if (result == NSOrderedAscending) {
    //Fails
    //Comes here if date1 is earlier than date2. In our case it will not come here.
}else if (result == NSOrderedSame) {
    //Fails
    //Comes here if date1 is the same as date2. In our case it will not come here.
}else{//NSOrderedDescending
    //Succeeds
    //Comes here if date1 is later than date2. In our case it will come here
}
```

Convert NSDate that is composed from hour and minute (only) to a full NSDate

There are many cases when one has created an NSDate from only an hour and minute format, i.e: 08:12

The downside for this situation is that your NSDate is almost completely "naked" and what you need to do is to create: day, month, year, second and time zone in order to this object to "play along" with other NSDate types.

For the sake of the example let's say that hourAndMinute is the NSDate type that is composed from hour and minute format:

```
NSDateComponents *hourAndMintuteComponents = [calendar components:NSCalendarUnitHour |
NSCalendarUnitMinute
```

fromDate:hourAndMinute];

Now your object is the total opposite of being "naked".

Converting NSDate to NSString

If ww have NSDate object, and we want to convert it into NSString. There are different types of Date strings. How we can do that?, It is very simple. Just 3 steps.

1. Create NSDateFormatter Object

NSDateFormatter *dateFormatter = [[NSDateFormatter alloc] init];

2. Set the date format in which you want your string.

dateFormatter.dateFormat = @"yyyy-MM-dd 'at' HH:mm";

3. Now, get the formatted string

```
NSDate *date = [NSDate date]; // your NSDate object
NSString *dateString = [dateFormatter stringFromDate:date];
```

This will give output something like this: 2001-01-02 at 13:00

Note:

Creating an NSDateFormatter instance is an expensive operation, so it is recommended to create it once and reuse when possible.

Read NSDate online: https://riptutorial.com/objective-c/topic/1981/nsdate

Chapter 29: NSDictionary

Examples

Create

```
NSDictionary *dict = [[NSDictionary alloc] initWithObjectsAndKeys:@"value1", @"key1",
@"value2", @"key2", nil];
```

or

```
NSArray *keys = [NSArray arrayWithObjects:@"key1", @"key2", nil];
NSArray *objects = [NSArray arrayWithObjects:@"value1", @"value2", nil];
NSDictionary *dictionary = [NSDictionary dictionaryWithObjects:objects
forKeys:keys];
```

or using appropriate literal syntax

```
NSDictionary *dict = @{@"key": @"value", @"nextKey": @"nextValue"};
```

NSDictionary to NSArray

```
NSDictionary *myDictionary = [[NSDictionary alloc] initWithObjectsAndKeys:@"value1", @"key1",
@"value2", @"key2", nil];
NSArray *copiedArray = myDictionary.copy;
```

Get keys:

```
NSArray *keys = [myDictionary allKeys];
```

Get values:

```
NSArray *values = [myDictionary allValues];
```

NSDictionary to NSData

```
NSDictionary *myDictionary = [[NSDictionary alloc] initWithObjectsAndKeys:@"value1", @"key1",
@"value2", @"key2", nil];
NSData *myData = [NSKeyedArchiver archivedDataWithRootObject:myDictionary];
```

Reserve path:

```
NSDictionary *myDictionary = (NSDictionary*) [NSKeyedUnarchiver
unarchiveObjectWithData:myData];
```

NSDictionary to JSON

```
NSDictionary *myDictionary = [[NSDictionary alloc] initWithObjectsAndKeys:@"value1", @"key1",
@"value2", @"key2", nil];
NSMutableDictionary *mutableDictionary = [myDictionary mutableCopy];
NSData *data = [NSJSONSerialization dataWithJSONObject:myDictionary
options:NSJSONWritingPrettyPrinted error:nil];
NSString *jsonString = [[NSString alloc] initWithData:data encoding:NSUTF8StringEncoding];
```

Block Based Enumeration

Enumerating dictionaries allows you to run a block of code on each dictionary key-value pair using

the method enumerateKeysAndObjectsUsingBlock: (void (^) (id key, id obj, BOOL *stop))block

Example:

Fast Enumeration

NSDictionary can be enumerated using fast enumeration, just like other collection types:

```
NSDictionary stockSymbolsDictionary = @{
    @"AAPL": @"Apple",
    @"GOOGL": @"Alphabet",
    @"MSFT": @"Microsoft",
    @"AMZN": @"Amazon"
    };
for (id key in stockSymbolsDictionary)
{
    id value = dictionary[key];
    NSLog(@"Key: %@, Value: %@", key, value);
}
```

Because NSDictionary is inherently unordered, the order of keys that in the for loop is not guaranteed.

Read NSDictionary online: https://riptutorial.com/objective-c/topic/847/nsdictionary

Chapter 30: NSDictionary

Syntax

- @{ key: value, ... }
- [NSDictionary dictionaryWithObjectsAndKeys: value, key, ..., nil];
- dict[key] = value;
- id value = dict[key];

Remarks

The NSDictionary class declares the programmatic interface to objects that manage immutable associations of keys and values. Use this class or its subclass NSMutableDictionary when you need a convenient and efficient way to retrieve data associated with an arbitrary key. NSDictionary creates static dictionaries, and NSMutableDictionary creates dynamic dictionaries. (For convenience, the term dictionary refers to any instance of one of these classes without specifying its exact class membership.)

A key-value pair within a dictionary is called an entry. Each entry consists of one object that represents the key and a second object that is that key's value. Within a dictionary, the keys are unique. That is, no two keys in a single dictionary are equal (as determined by isEqual:). In general, a key can be any object (provided that it conforms to the NSCopying protocol—see below), but note that when using key-value coding the key must be a string (see Key-Value Coding Fundamentals). Neither a key nor a value can be nil; if you need to represent a null value in a dictionary, you should use NSNull.

NSDictionary is "toll-free bridged" with its Core Foundation counterpart, CFDictionaryRef. See Toll-Free Bridging for more information on toll-free bridging.

Examples

Creating using literals

```
NSDictionary *inventory = @{
    @"Mercedes-Benz SLK250" : @(13),
    @"BMW M3 Coupe" : @(self.BMWM3CoupeInventory.count),
    @"Last Updated" : @"Jul 21, 2016",
    @"Next Update" : self.nextInventoryUpdateString
};
```

Creating using dictionaryWithObjectsAndKeys:

```
NSDictionary *inventory = [NSDictionary dictionaryWithObjectsAndKeys:
 [NSNumber numberWithInt:13], @"Mercedes-Benz SLK250",
 [NSNumber numberWithInt:22], @"Mercedes-Benz E350",
 [NSNumber numberWithInt:19], @"BMW M3 Coupe",
 [NSNumber numberWithInt:16], @"BMW X6",
 nil];
```

nil must be passed as the last parameter as a sentinel signifying the end.

It's important to remember that when instantiating dictionaries this way the values go first and the keys second. In the example above the strings are the keys and the numbers are the values. The method's name reflects this too: dictionaryWithObjectsAndKeys. While this is not incorrect, the more modern way of instantiating dictionaries (with literals) is prefered.

Creating using plists

```
NSString *pathToPlist = [[NSBundle mainBundle] pathForResource:@"plistName"
    ofType:@"plist"];
NSDictionary *plistDict = [[NSDictionary alloc] initWithContentsOfFile:pathToPlist];
```

Setting a Value in NSDictionary

There are multiple ways to set a key's object in an NSDictionary, corresponding to the ways you get a value. For instance, to add a lamborghini to a list of cars

Standard

[cars setObject:lamborghini forKey:@"Lamborghini"];

Just like any other object, call the method of NSDictionary that sets an object of a key, <code>objectForKey:</code>. Be careful not to confuse this with <code>setValue:forKey:</code>; that's for a completely different thing, Key Value Coding

Shorthand

```
cars[@"Lamborghini"] = lamborghini;
```

This is the syntax that you use for dictionaries in most other languages, such as C#, Java, and Javascript. It's much more convenient than the standard syntax, and arguably more readable (especially if you code in these other languages), but of course, it isn't *standard*. It's also only available in newer versions of Objective C

Getting a Value from NSDictionary

There are multiple ways to get an object from an NSDictionary with a key. For instance, to get a lamborghini from a list of cars

Standard

```
Car * lamborghini = [cars objectForKey:@"Lamborghini"];
```

Just like any other object, call the method of NSDictionary that gives you an object for a key, <code>objectForKey:</code>. Be careful not to confuse this with <code>valueForKey:</code>; that's for a completely different thing, Key Value Coding

Shorthand

```
Car * lamborghini = cars[@"Lamborghini"];
```

This is the syntax that you use for dictionaries in most other languages, such as C#, Java, and Javascript. It's much more convenient than the standard syntax, and arguably more readable (especially if you code in these other languages), but of course, it isn't *standard*. It's also only available in newer versions of Objective C

Check if NSDictionary already has a key or not

Objective c:

```
//this is the dictionary you start with.
NSDictionary *dict = [NSDictionary dictionaryWithObjectsAndKeys:@"name1", @"Sam",@"name2",
@"Sanju",nil];
//check if the dictionary contains the key you are going to modify. In this example, @"Sam"
if (dict[@"name1"] != nil) {
    //there is an entry for Key name1
}
else {
    //There is no entry for name1
}
```

Read NSDictionary online: https://riptutorial.com/objective-c/topic/875/nsdictionary

Chapter 31: NSJSONSerialization

Syntax

 (id)JSONObjectWithData:(NSData *)data options:(NSJSONReadingOptions)opt error:(NSError * _Nullable *)error

Parameters

Operator	Description
data	A data object containing JSON data
opt	Options for reading the JSON data and creating the Foundation objects.
error	If an error occurs, upon return contains an NSError object that describes the problem.

Remarks

NSJSONSerialization is Available in iOS 5.0 and later An object that may be converted to JSON must have the following properties:

- The top level object is an NSArray or NSDictionary.
- All objects are instances of NSString, NSNumber, NSArray, NSDictionary, or NSNull.
- All dictionary keys are instances of NSString.
- Numbers are not NaN or infinity.

Examples

JSON Parsing using NSJSONSerialization Objective c

```
NSError *e = nil;
NSString *jsonString = @"[{\"id\": \"1\", \"name\":\"sam\"}]";
NSData *data = [jsonString dataUsingEncoding:NSUTF8StringEncoding];
NSArray *jsonArray = [NSJSONSerialization JSONObjectWithData: data options:
NSJSONReadingMutableContainers error: &e];
if (!jsonArray) {
    NSLog(@"Error parsing JSON: %@", e);
} else {
    for(NSDictionary *item in jsonArray) {
        NSLog(@"Item: %@", item);
```

}

Output:

```
Item: {
    id = 1;
    name = sam;
}
```

Example 2:Using contents of url:

```
//Parsing:
NSData *data = [NSData dataWithContentsOfURL:@"URL HERE"];
NSError *error;
NSDictionary *json = [NSJSONSerialization JSONObjectWithData:data options:kNilOptions
error:&error];
NSLog(@"json :%@",json);
```

Sample response:

```
json: {
   MESSAGE = "Test Message";
   RESPONSE = (
               {
           email = "test@gmail.com";
           id = 15;
           phone = 1234567890;
           name = Staffy;
       }
    );
   STATUS = SUCCESS;
}
NSMutableDictionary *response = [[[json valueForKey:@"RESPONSE"]
objectAtIndex:0]mutableCopy];
NSString *nameStr = [response valueForKey:@"name"];
NSString *emailIdStr = [response valueForKey:@"email"];
```

Read NSJSONSerialization online: https://riptutorial.com/objective-c/topic/2587/nsjsonserialization

Chapter 32: NSMutableArray

Examples

Adding elements

```
NSMutableArray *myColors;
myColors = [NSMutableArray arrayWithObjects: @"Red", @"Green", @"Blue", @"Yellow", nil];
[myColors addObject: @"Indigo"];
[myColors addObject: @"Violet"];
//Add objects from an NSArray
```

NSArray *myArray = @[@"Purple",@"Orange"]; [myColors addObjectsFromArray:myArray];

Insert Elements

```
NSMutableArray *myColors;
int i;
int count;
myColors = [NSMutableArray arrayWithObjects: @"Red", @"Green", @"Blue", @"Yellow", nil];
[myColors insertObject: @"Indigo" atIndex: 1];
[myColors insertObject: @"Violet" atIndex: 3];
```

Deleting Elements

Remove at specific index:

```
[myColors removeObjectAtIndex: 3];
```

Remove the first instance of a specific object:

[myColors removeObject: @"Red"];

Remove all instances of a specific object:

```
[myColors removeObjectIdenticalTo: @"Red"];
```

Remove all objects:

[myColors removeAllObjects];

Remove last object:

[myColors removeLastObject];

Sorting Arrays

```
NSMutableArray *myColors = [NSMutableArray arrayWithObjects: @"red", @"green", @"blue",
@"yellow", nil];
NSArray *sortedArray;
sortedArray = [myColors sortedArrayUsingSelector:@selector(localizedCaseInsensitiveCompare:)];
```

Move object to another index

Move Blue to the beginning of the array:

```
NSMutableArray *myColors = [NSMutableArray arrayWithObjects: @"Red", @"Green", @"Blue",
@"Yellow", nil];
NSUInteger fromIndex = 2;
NSUInteger toIndex = 0;
id blue = [[[self.array objectAtIndex:fromIndex] retain] autorelease];
[self.array removeObjectAtIndex:fromIndex];
[self.array insertObject:blue atIndex:toIndex];
```

myColors **iS NOW** [@"Blue", @"Red", @"Green", @"Yellow"].

Filtering Array content with Predicate

Using **filterUsingPredicate:** This Evaluates a given predicate against the arrays content and return objects that match.

Example:

```
NSMutableArray *array = [NSMutableArray array];
[array setArray:@[@"iOS",@"macOS",@"tvOS"]];
NSPredicate *predicate = [NSPredicate predicateWithFormat:@"SELF beginswith[c] 'i'"];
NSArray *resultArray = [array filteredArrayUsingPredicate:predicate];
NSLog(@"%@",resultArray);
```

Creating an NSMutableArray

NSMutableArray can be initialized as an empty array like this:

```
NSMutableArray *array = [[NSMutableArray alloc] init];
// or
NSMutableArray *array2 = @[].mutableCopy;
// or
NSMutableArray *array3 = [NSMutableArray array];
```

NSMutableArray can be initialized with another array like this:

```
NSMutableArray *array4 = [[NSMutableArray alloc] initWithArray:anotherArray];
// or
NSMutableArray *array5 = anotherArray.mutableCopy;
```

Read NSMutableArray online: https://riptutorial.com/objective-c/topic/2008/nsmutablearray

Chapter 33: NSMutableDictionary

Parameters

objects	keys
An array containing the values for the new dictionary.	CellAn array containing the keys for the new dictionary. Each key is copied and the copy is added to the dictionary.

Examples

NSMutableDictionary Example

+ dictionaryWithCapacity:

Creates and returns a mutable dictionary, initially giving it enough allocated memory to hold a given number of entries.

```
NSMutableDictionary *dict = [NSMutableDictionary dictionaryWithCapacity:1];
NSLog(@"%@",dict);
```

- init

Initializes a newly allocated mutable dictionary.

```
NSMutableDictionary *dict = [[NSMutableDictionary alloc] init];
NSLog(@"%@",dict);
```

+ dictionaryWithSharedKeySet:

Creates a mutable dictionary which is optimized for dealing with a known set of keys.

```
id sharedKeySet = [NSDictionary sharedKeySetForKeys:@[@"key1", @"key2"]]; // returns
NSSharedKeySet
NSMutableDictionary *dict = [NSMutableDictionary dictionaryWithSharedKeySet:sharedKeySet];
dict[@"key1"] = @"Easy";
dict[@"key2"] = @"Tutorial";
//We can an object thats not in the shared keyset
dict[@"key3"] = @"Website";
NSLog(@"%@",dict);
```

OUTPUT

{

```
key1 = Eezy;
key2 = Tutorials;
key3 = Website;
```

}

Adding Entries to a Mutable Dictionary

- setObject:forKey:

Adds a given key-value pair to the dictionary.

```
NSMutableDictionary *dict = [NSMutableDictionary dictionary];
[dict setObject:@"Easy" forKey:@"Key1"];
NSLog(@"%@",dict);
```

OUTPUT

{
 Key1 = Eezy;
}

- setObject:forKeyedSubscript:

Adds a given key-value pair to the dictionary.

```
NSMutableDictionary *dict = [NSMutableDictionary dictionary];
[dict setObject:@"Easy" forKeyedSubscript:@"Key1"];
NSLog(@"%@",dict);
```

```
OUTPUT { Key1 = Easy; }
```

Removing Entries From a Mutable Dictionary

- removeObjectForKey:

Removes a given key and its associated value from the dictionary.

```
NSMutableDictionary *dict = [NSMutableDictionary
dictionaryWithDictionary:@{@"key1":@"Easy",@"key2": @"Tutorials"}];
[dict removeObjectForKey:@"key1"];
NSLog(@"%@",dict);
```

OUTPUT

```
{
    key2 = Tutorials;
}
```

- removeAllObjects

Empties the dictionary of its entries.
```
NSMutableDictionary *dict = [NSMutableDictionary
dictionaryWithDictionary:@{@"key1":@"Eezy",@"key2": @"Tutorials"}];
[dict removeAllObjects];
NSLog(@"%@",dict);
```

OUTPUT

{ }

- removeObjectsForKeys:

Removes from the dictionary entries specified by elements in a given array.

```
NSMutableDictionary *dict = [NSMutableDictionary
dictionaryWithDictionary:@{@"key1":@"Easy",@"key2": @"Tutorials"}];
[dict removeObjectsForKeys:@[@"key1"]];
NSLog(@"%@",dict);
```

OUTPUT

```
{
    key2 = Tutorials;
}
```

Read NSMutableDictionary online: https://riptutorial.com/objectivec/topic/3103/nsmutabledictionary

Chapter 34: NSObject

Introduction

NSObject is the root class of Cocoa, however the Objective-C language itself does not define any root classes at all its define by Cocoa, Apple's Framework. This root class of most Objective-C class hierarchies, from which subclasses inherit a basic interface to the runtime system and the ability to behave as Objective-C objects.

This class have all basic property of <code>Objective'C</code> class object like:

self.

class (name of the class).

superclass (superclass of current class).

Syntax

- self
- superclass
- init
- alloc
- new
- isEqual
- isKindOfClass
- isMemberOfClass
- description

Examples

NSObject

@interface NSString : NSObject (NSObject is a base class of NSString class).

You can use below methods for allocation of string class:

- (instancetype)init
- + (instancetype)new
- + (instancetype)alloc

For Copy any object :

- (id)copy;

(id)mutableCopy;

For compare objects :

- (BOOL)isEqual:(id)object

To get superclass of current class :

superclass

To check which kind of class is this ?

- (BOOL)isKindOfClass:(Class)aClass

Some property of NON-ARC classes:

- (instancetype)retain OBJC_ARC_UNAVAILABLE;
- (oneway void) release OBJC_ARC_UNAVAILABLE;
- (instancetype)autorelease OBJC_ARC_UNAVAILABLE;
- (NSUInteger)retainCount

Read NSObject online: https://riptutorial.com/objective-c/topic/9355/nsobject

Chapter 35: NSPredicate

Syntax

· CONTAINS operator : It allows to filter objects with matching subset.

```
NSPredicate *filterByName = [NSPredicate predicateWithFormat:@"self.title CONTAINS[cd]
%@",@"Tom"];
```

• LIKE : Its simple comparison filter.

```
NSPredicate *filterByNameCIS = [NSPredicate predicateWithFormat:@"self.title LIKE[cd]
%@",@"Tom and Jerry"];
```

• = operator : It returns all the objects with matching filter value.

```
NSPredicate *filterByNameCS = [NSPredicate predicateWithFormat:@"self.title = %@",@"Tom and
Jerry"];
```

· IN operator : It allows you to filter objects with specific filter set.

```
NSPredicate *filterByIds = [NSPredicate predicateWithFormat:@"self.id IN %@",@[@"7CDF6D22-
8D36-49C2-84FE-E31EECCECB79", @"7CDF6D22-8D36-49C2-84FE-E31EECCECB76"]];
```

• NOT IN operator : It allows you to find Inverse objects with specific set.

```
NSPredicate *filterByNotInIds = [NSPredicate predicateWithFormat:@"NOT (self.id IN
%@)",@[@"7CDF6D22-8D36-49C2-84FE-E31EECCECB79", @"7CDF6D22-8D36-49C2-84FE-E31EECCECB76"]];
```

Remarks

For more details read NSPredicate in Apple documentation

Examples

Filter By Name

```
@"id": @"7CDF6D22-8D36-49C2-84FE-E31EECCECB73",
                        @"title": @"Titanic",
                        @"url": @"http://abc.com/playback.m3u8",
                        @"thumbnailURL": @"http://abc.com/thumbnail.png",
                        @"isMovie" : @1
                    },
                    Q {
                        @"id": @"7CDF6D22-8D36-49C2-84FE-E31EECCECB74",
                        @"title": @"Star Wars",
                        @"url": @"http://abc.com/playback.m3u8",
                        @"thumbnailURL": @"http://abc.com/thumbnail.png",
                        @"isMovie" : @1
                    },
                    @{
                        @"id": @"7CDF6D22-8D36-49C2-84FE-E31EECCECB75",
                        @"title": @"Pokemon",
                        @"url": @"http://abc.com/playback.m3u8",
                        @"thumbnailURL": @"http://abc.com/thumbnail.png",
                        @"isMovie" : @0
                    },
                    Q {
                        @"id": @"7CDF6D22-8D36-49C2-84FE-E31EECCECB76",
                        @"title": @"Avatar",
                        @"url": @"http://abc.com/playback.m3u8",
                        @"thumbnailURL": @"http://abc.com/thumbnail.png",
                        @"isMovie" : @1
                    },
                    Q {
                        @"id": @"7CDF6D22-8D36-49C2-84FE-E31EECCECB77",
                        @"title": @"Popey",
                        @"url": @"http://abc.com/playback.m3u8",
                        @"thumbnailURL": @"http://abc.com/thumbnail.png",
                        @"isMovie" : @1
                    },
                    @{
                        @"id": @"7CDF6D22-8D36-49C2-84FE-E31EECCECB78",
                        @"title": @"Tom and Jerry",
                        @"url": @"http://abc.com/playback.m3u8",
                        @"thumbnailURL": @"http://abc.com/thumbnail.png",
                        @"isMovie" : @1
                    },
                    @{
                        @"id": @"7CDF6D22-8D36-49C2-84FE-E31EECCECB79",
                        @"title": @"The wolf",
                        @"url": @"http://abc.com/playback.m3u8",
                        @"thumbnailURL": @"http://abc.com/thumbnail.png",
                        @"isMovie" : @1
                    }
                    ];
// *** Case Insensitive comparision with excate title match ***
NSPredicate *filterByNameCIS = [NSPredicate predicateWithFormat:@"self.title LIKE[cd]
%@",@"Tom and Jerry"];
NSLog(@"Filter By Name(CIS) : %@",[array filteredArrayUsingPredicate:filterByNameCIS]);
```

Find movies except given ids

```
// *** Find movies except given ids ***
```

Q {

```
NSPredicate *filterByNotInIds = [NSPredicate predicateWithFormat:@"NOT (self.id IN
%@)",@[@"7CDF6D22-8D36-49C2-84FE-E31EECCECB79", @"7CDF6D22-8D36-49C2-84FE-E31EECCECB76"]];
NSLog(@"Filter movies except given Ids : %@",[array
filteredArrayUsingPredicate:filterByNotInIds]);
```

Find all the objects which is of type movie

```
// *** Find all the objects which is of type movie, Both the syntax are valid ***
NSPredicate *filterByMovieType = [NSPredicate predicateWithFormat:@"self.isMovie = %@",@1];
// OR
//NSPredicate *filterByMovieType = [NSPredicate predicateWithFormat:@"self.isMovie =
%@",[NSNumber numberWithBool:YES]];
NSLog(@"Filter By Movie Type : %@",[array filteredArrayUsingPredicate:filterByMovieType]);
```

Find Distinct object ids of array

```
// *** Find Distinct object ids of array ***
NSLog(@"Distinct id : %@",[array valueForKeyPath:@"@distinctUnionOfObjects.id"]);
```

Find movies with specific ids

```
// *** Find movies with specific ids ***
NSPredicate *filterByIds = [NSPredicate predicateWithFormat:@"self.id IN %@",@[@"7CDF6D22-
8D36-49C2-84FE-E31EECCECB79", @"7CDF6D22-8D36-49C2-84FE-E31EECCECB76"]];
NSLog(@"Filter By Ids : %@",[array filteredArrayUsingPredicate:filterByIds]);
```

Case Insensitive comparison with exact title match

```
// *** Case Insensitive comparison with exact title match ***
NSPredicate *filterByNameCIS = [NSPredicate predicateWithFormat:@"self.title LIKE[cd]
%@",@"Tom and Jerry"];
NSLog(@"Filter By Name(CIS) : %@",[array filteredArrayUsingPredicate:filterByNameCIS]);
```

Case sensitive with exact title match

```
// *** Case sensitive with exact title match ***
NSPredicate *filterByNameCS = [NSPredicate predicateWithFormat:@"self.title = %@",@"Tom and
Jerry"];
NSLog(@"Filter By Name(CS) : %@",[array filteredArrayUsingPredicate:filterByNameCS]);
```

Case Insensitive comparison with matching subset

```
// *** Case Insensitive comparison with matching subset ***
NSPredicate *filterByName = [NSPredicate predicateWithFormat:@"self.title CONTAINS[cd]
%@",@"Tom"];
NSLog(@"Filter By Containing Name : %@",[array filteredArrayUsingPredicate:filterByName]);
```

Read NSPredicate online: https://riptutorial.com/objective-c/topic/2004/nspredicate

Chapter 36: NSRegularExpression

Syntax

- NSRegularExpression *regex = [NSRegularExpression regularExpressionWithPattern:PATTERN options:OPTIONS error:ERROR];
- NSArray<NSTextCheckingResult *> *results = [regex matchesInString:STRING options:OPTIONS range:RANGE_IN_STRING];
- NSInteger numberOfMatches = [regex numberOfMatchesInString:STRING options:OPTIONS range:RANGE_IN_STRING];

Examples

Find all the numbers in a string

The output will be match: 42 and match: 8672.

Check whether a string matches a pattern

```
NSString *testString1 = @"(555) 123-5678";
NSString *testString2 = @"not a phone number";
NSError *error = nil;
NSRegularExpression *regex = [NSRegularExpression regularExpressionWithPattern:@"^\\(\\d{3}\\)
\\d{3}\\-\\d{4}$"
options:NSRegularExpressionCaseInsensitive error:&error];
NSInteger result1 = [regex numberOfMatchesInString:testString1 options:0 range:NSMakeRange(0,
testString1.length)];
NSInteger result2 = [regex numberOfMatchesInString:testString2 options:0 range:NSMakeRange(0,
testString2.length)];
NSLog(@"Is string 1 a phone number? %@", result1 > 0 ? @"YES" : @"NO");
NSLog(@"Is string 2 a phone number? %@", result2 > 0 ? @"YES" : @"NO");
```

The output will show that the first string is a phone number and the second one isn't.

Read NSRegularExpression online: https://riptutorial.com/objectivec/topic/2484/nsregularexpression

Chapter 37: NSSortDescriptor

Examples

Sorted by combinations of NSSortDescriptor

```
NSArray *aryFName = @[ @"Alice", @"Bob", @"Charlie", @"Quentin" ];
NSArray *aryLName = @[ @"Smith", @"Jones", @"Smith", @"Alberts" ];
NSArray *aryAge = @[ @24, @27, @33, @31 ];
//Create a Custom class with properties for firstName & lastName of type NSString *,
//and age, which is an NSUInteger.
NSMutableArray *aryPerson = [NSMutableArray array];
[firstNames enumerateObjectsUsingBlock:^(id obj, NSUInteger idx, BOOL *stop) {
   Person *person = [[Person alloc] init];
   person.firstName = [aryFName objectAtIndex:idx];
   person.lastName = [aryLName objectAtIndex:idx];
   person.age = [aryAge objectAtIndex:idx];
    [aryPerson addObject:person];
}];
NSSortDescriptor *firstNameSortDescriptor = [NSSortDescriptor
sortDescriptorWithKey:@"firstName"
                                             ascending:YES
                                             selector:@selector(localizedStandardCompare:)];
NSSortDescriptor *lastNameSortDescriptor = [NSSortDescriptor sortDescriptorWithKey:@"lastName"
                                            ascending:YES
                                            selector:@selector(localizedStandardCompare:)];
NSSortDescriptor *ageSortDescriptor = [NSSortDescriptor sortDescriptorWithKey:@"age"
                                       ascending:NO];
NSLog(@"By age: %@", [aryPerson sortedArrayUsingDescriptors:@[ageSortDescriptor]]);
// "Charlie Smith", "Quentin Alberts", "Bob Jones", "Alice Smith"
NSLog(@"By first name: %@", [aryPerson
sortedArrayUsingDescriptors:@[firstNameSortDescriptor]]);
// "Alice Smith", "Bob Jones", "Charlie Smith", "Quentin Alberts"
NSLog(@"By last name, first name: %@", [aryPerson
sortedArrayUsingDescriptors:@[lastNameSortDescriptor, firstNameSortDescriptor]]);
// "Quentin Alberts", "Bob Jones", "Alice Smith", "Charlie Smith"
```

Read NSSortDescriptor online: https://riptutorial.com/objective-c/topic/5833/nssortdescriptor

Chapter 38: NSString

Introduction

The *NSString* class is a part of Foundation framework to work with strings (series of characters). It also includes methods for comparing, searching and modifying strings.

Remarks

For nesting various types of objects and data-types into NSStrings refer to: Objective-C, Format Specifiers

Examples

Creation

Simple:

```
NSString *newString = @"My String";
```

From multiple strings:

```
NSString *stringOne = @"Hello";
NSString *stringTwo = @"world";
NSString *newString = [NSString stringWithFormat:@"My message: %@ %@",
stringOne, stringTwo];
```

Using Mutable String

```
NSString *stringOne = @"Hello";
NSString *stringTwo = @"World";
NSMutableString *mutableString = [NSMutableString new];
[mutableString appendString:stringOne];
[mutableString appendString:stringTwo];
```

From NSData:

When initializing from NSData, an explicit encoding must be provided as NSString is not able to guess how characters are represented in the raw data stream. The most common encoding nowadays is UTF-8, which is even a requirement for certain data like JSON.

Avoid using +[NSString stringWithUTF8String:] since it expects an explicitly NULL-terminated C-string, which -[NSData bytes] does not provide.

NSString *newString = [[NSString alloc] initWithData:myData encoding:NSUTF8StringEncoding];

From NSArray:

```
NSArray *myArray = [NSArray arrayWithObjects:@"Apple", @"Banana", @"Strawberry", @"Kiwi",
nil];
NSString *newString = [myArray componentsJoinedByString:@" "];
```

String Length

NSString has a length property to get the number of characters.

```
NSString *string = @"example";
NSUInteger length = string.length; // length equals 7
```

As in the Splitting Example, keep in mind that NSString uses UTF-16 to represent characters. The length is actually just the number of UTF-16 code units. This can differ from what the user perceives as characters.

Here are some cases that might be surprising:

```
@"e".length == 1 // LATIN SMALL LETTER E WITH ACUTE (U+00E9)
@"e".length == 2 // LATIN SMALL LETTER E (U+0065) + COMBINING ACUTE ACCENT (U+0301)
@"I".length == 2 // HEAVY BLACK HEART (U+2764) + VARIATION SELECTOR-16 (U+FE0F)
@"II".length == 4 // REGIONAL INDICATOR SYMBOL LETTER I (U+1F1EE) + REGIONAL INDICATOR SYMBOL
LETTER T (U+1F1F9)
```

In order to get the number of user-perceived characters, known technically as "grapheme clusters ", you must iterate over the string with -enumerateSubstringsInRange:options:usingBlock: and keep a count. This is demonstrated in an answer by Nikolai Ruhe on Stack Overflow.

Changing Case

To convert a String to uppercase, use uppercaseString:

```
NSString *myString = @"Emphasize this";
NSLog(@"%@", [myString uppercaseString]; // @"EMPHASIZE THIS"
```

To convert a String to lowercase, use <code>lowercaseString</code>:

```
NSString *myString = @"NORMALIZE this";
NSLog(@"%@", [myString lowercaseString]; // @"normalize this"
```

To capitalize the first letter character of each word in a string, use capitalizedString:

```
NSString *myString = @"firstname lastname";
NSLog(@"%@", [myString capitalizedString]); // @"Firstname Lastname"
```

Comparing Strings

Strings are compared for equality using isEqualToString:

https://riptutorial.com/

The == operator just tests for object identity and does not compare the logical values of objects, so it can't be used:

```
NSString *stringOne = @"example";
NSString *stringTwo = [stringOne mutableCopy];
BOOL objectsAreIdentical = (stringOne == stringTwo); // NO
BOOL stringsAreEqual = [stringOne isEqualToString:stringTwo]; // YES
```

The expression (stringOne == stringTwo) tests to see if the memory addresses of the two strings are the same, which is usually not what we want.

If the string variables can be nil you have to take care about this case as well:

```
BOOL equalValues = stringOne == stringTwo || [stringOne isEqualToString:stringTwo];
```

This condition returns YES when strings have equal values or both are nil.

To order two strings alphabetically, use compare:.

NSComparisonResult result = [firstString compare:secondString];

NSComparisonResult Can be:

- NSOrderedAscending: The first string comes before the second string.
- NSOrderedSame: The strings are equal.
- NSOrderedDescending: The second string comes before the first string.

To compare two strings equality, use isEqualToString:.

BOOL result = [firstString isEqualToString:secondString];

To compare with the empty string (@""), better use length.

BOOL result = string.length == 0;

Joining an Array of Strings

To combine an NSArray of NSString into a new NSString:

```
NSArray *yourWords = @[@"Objective-C", @"is", @"just", @"awesome"];
NSString *sentence = [yourWords componentsJoinedByString:@" "];
```

// Sentence is now: @"Objective-C is just awesome"

Encoding and Decoding

// decode
NSString *string = [[NSString alloc] initWithData:utf8Data

https://riptutorial.com/

```
encoding:NSUTF8StringEncoding];
```

```
// encode
NSData *utf8Data = [string dataUsingEncoding:NSUTF8StringEncoding];
```

Some supported encodings are:

- NSASCIIStringEncoding
- NSUTF8StringEncoding
- NSUTF16StringEncoding (== NSUnicodeStringEncoding)

Note that utf8Data.bytes does not include a terminating null character, which is necessary for C strings. If you need a C string, use UTF8String:

```
const char *cString = [string UTF8String];
printf("%s", cString);
```

Splitting

You can split a string into an array of parts, divided by a separator character.

```
NSString * yourString = @"Stack,Exchange,Network";
NSArray * yourWords = [yourString componentsSeparatedByString:@","];
// Output: @[@"Stack", @"Exchange", @"Network"]
```

If you need to split on a set of several different delimiters, use -[NSString

 $\verb|componentsSeparatedByCharactersInSet:].$

If you need to break a string into its **individual characters**, loop over the length of the string and convert each character into a new string.

As in the Length Example, keep in mind that a "character" here is a UTF-16 code unit, not necessarily what the user sees as a character. If you use this loop with <code>@"DD"</code>, you'll see that it's split into four pieces.

In order to get a list of the user-perceived characters, use -

```
enumerateSubstringsInRange:options:usingBlock:.
```

This preserves grapheme clusters like the Italian flag as a single substring.

Searching for a Substring

To search if a String contains a substring, do the following:

```
NSString *myString = @"This is for checking substrings";
NSString *subString = @"checking";
BOOL doesContainSubstring = [myString containsString:subString]; // YES
```

If targeting iOS 7 or OS X 10.9 (or earlier):

```
BOOL doesContainSubstring = ([myString rangeOfString:subString].location != NSNotFound); //
YES
```

Working with C Strings

To convert NSString to const char USe - [NSString UTF8String]:

```
NSString *myNSString = @"Some string";
const char *cString = [myNSString UTF8String];
```

You could also use -[NSString cStringUsingEncoding:] if your string is encoded with something other than UTF-8.

For the reverse path use -[NSString stringWithUTF8String:]:

```
const *char cString = "Some string";
NSString *myNSString = [NSString stringWithUTF8String:cString];
myNSString = @(cString); // Equivalent to the above.
```

Once you have the const char *, you can work with it similarly to an array of chars:

```
printf("%c\n", cString[5]);
```

If you want to modify the string, make a copy:

```
char *cpy = calloc(strlen(cString)+1, 1);
strncpy(cpy, cString, strlen(cString));
// Do stuff with cpy
free(cpy);
```

Removing Leading and Trailing Whitespace

```
NSString *someString = @" Objective-C Language \n";
NSString *trimmedString = [someString stringByTrimmingCharactersInSet:[NSCharacterSet
whitespaceAndNewlineCharacterSet]];
//Output will be - "Objective-C Language"
```

Method stringByTrimmingCharactersInSet returns a new string made by removing from both ends of the String characters contained in a given character set.

We can also just remove only whitespace or newline

```
// Removing only WhiteSpace
NSString *trimmedWhiteSpace = [someString stringByTrimmingCharactersInSet:[NSCharacterSet
whitespaceCharacterSet]];
//Output will be - "Objective-C Language \n"
// Removing only NewLine
NSString *trimmedNewLine = [someString stringByTrimmingCharactersInSet:[NSCharacterSet
newlineCharacterSet]];
//Output will be - " Objective-C Language "
```

Formatting

The NSString formatting supports all the format strings available on the printf ANSI-C function. The only addition made by the language is the %e symbol used for formatting all the Objective-C objects.

It is possible to format integers

```
int myAge = 21;
NSString *formattedAge = [NSString stringWithFormat:@"I am %d years old", my_age];
```

Or any object subclassed from NSObject

```
NSDate *now = [NSDate date];
NSString *formattedDate = [NSString stringWithFormat:@"The time right now is: %@", now];
```

For a complete list of Format Specifiers, please see: Objective-C, Format Specifiers, Syntax

Reversing a NSString Objective-C

```
// myString is "hi"
NSMutableString *reversedString = [NSMutableString string];
NSInteger charIndex = [myString length];
while (charIndex > 0) {
    charIndex--;
    NSRange subStrRange = NSMakeRange(charIndex, 1);
    [reversedString appendString:[myString substringWithRange:subStrRange]];
}
```

Read NSString online: https://riptutorial.com/objective-c/topic/832/nsstring

Chapter 39: NSTextAttachment

Syntax

1. NSTextAttachment *attachmentName = [[NSTextAttachment alloc] init];

Remarks

NSTextAttachment objects are used by the NSAttributedString class cluster as the values for attachment attributes. The objects you create with this class are referred to as text attachment objects, or when no confusion will result, as text attachments or merely attachments.

Examples

NSTextAttachment Example

```
NSTextAttachment *attachment = [[NSTextAttachment alloc] init];
attachment.image = [UIImage imageNamed:@"imageName"];
attachment.bounds = CGRectMake(0, 0, 35, 35);
NSAttributedString *attachmentString = [NSAttributedString
attributedStringWithAttachment:attachment];
```

Read NSTextAttachment online: https://riptutorial.com/objective-c/topic/7143/nstextattachment

Chapter 40: NSTimer

Examples

Creating a Timer

This will create a timer to call the doSomething method on self in 5.0 seconds.

```
[NSTimer scheduledTimerWithTimeInterval:5.0
target:self
selector:@selector(doSomething)
userInfo:nil
repeats:NO];
```

Setting the repeats parameter to false/NO indicates that we want the timer to fire only once. If we set this to true/YES, it would fire every five seconds until manually invalidated.

Invalidating a timer

```
[timer invalidate];
timer = nil;
```

This will stop the timer from firing. **Must be called from the thread the timer was created in,** see Apple's notes:

You must send this message from the thread on which the timer was installed. If you send this message from another thread, the input source associated with the timer may not be removed from its run loop, which could prevent the thread from exiting properly.

Setting nil will help you next to check whether it's running or not.

```
if(timer) {
    [timer invalidate];
    timer = nil;
}
//Now set a timer again.
```

Manually firing a timer

[timer fire];

Calling the fire method causes an NSTimer to perform the task it would have usually performed on a schedule.

In a **non-repeating timer**, this will automatically invalidate the timer. That is, calling fire before the time interval is up will result in only one invocation.

In a repeating timer, this will simply invoke the action without interrupting the usual schedule.

Storing information in the Timer

When creating a timer, you can set the userInfo parameter to include information that you want to pass to the function you call with the timer.

By taking a timer as a parameter in said function, you can access the userInfo property.

Read NSTimer online: https://riptutorial.com/objective-c/topic/3773/nstimer

Chapter 41: NSURL

Examples

Create

From NSString:

```
NSString *urlString = @"https://www.stackoverflow.com";
NSURL *myUrl = [NSURL URLWithString: urlString];
```

You can also use the following methods:

```
- initWithString:
+ URLWithString:relativeToURL:
```

- initWithString:relativeToURL:
- + fileURLWithPath:isDirectory:
- initFileURLWithPath:isDirectory:
- + fileURLWithPath:
- initFileURLWithPath:

```
Designated Initializer
```

- + fileURLWithPathComponents:
- + URLByResolvingAliasFileAtURL:options:error:
- + URLByResolvingBookmarkData:options:relativeToURL:bookmarkDataIsStale:error:
- initByResolvingBookmarkData:options:relativeToURL:bookmarkDataIsStale:error:
- + fileURLWithFileSystemRepresentation:isDirectory:relativeToURL:
- getFileSystemRepresentation:maxLength:
- initFileURLWithFileSystemRepresentation:isDirectory:relativeToURL:

Compare NSURL

```
NSString *urlString = @"https://www.stackoverflow.com";
NSURL *myUrl = [NSURL URLWithString: urlString];
NSURL *myUrl2 = [NSURL URLWithString: urlString];
if ([myUrl isEqual:myUrl2]) return YES;
```

Modifying and Converting a File URL with removing and appending path

1. URLByDeletingPathExtension:

If the receiver represents the root path, this property contains a copy of the original URL. If the URL has multiple path extensions, only the last one is removed.

2. URLByAppendingPathExtension:

Returns a new URL made by appending a path extension to the original URL.

Example:

Read NSURL online: https://riptutorial.com/objective-c/topic/1187/nsurl

Chapter 42: NSUrl send a post request

Examples

Simple POST request

```
// Create the request.
NSMutableURLRequest *request = [NSMutableURLRequest requestWithURL:[NSURL
URLWithString:@"http://google.com"]];
// Specify that it will be a POST request
request.HTTPMethod = @"POST";
// This is how we set header fields
[request setValue:@"application/xml; charset=utf-8" forHTTPHeaderField:@"Content-Type"];
// Convert your data and set your request's HTTPBody property
NSString *stringData = @"some data";
NSData *requestBodyData = [stringData dataUsingEncoding:NSUTF8StringEncoding];
request.HTTPBody = requestBodyData;
// Create url connection and fire request
NSURLConnection *conn = [[NSURLConnection alloc] initWithRequest:request delegate:self];
```

Simple Post Request With Timeout

```
// Create the request.
NSMutableURLRequest *request = [NSMutableURLRequest requestWithURL:[NSURL
URLWithString:@"http://google.com"]];
// Specify that it will be a POST request
request.HTTPMethod = @"POST";
// Setting a timeout
request.timeoutInterval = 20.0;
// This is how we set header fields
[request setValue:@"application/xml; charset=utf-8" forHTTPHeaderField:@"Content-Type"];
// Convert your data and set your request's HTTPBody property
NSString *stringData = @"some data";
NSData *requestBodyData = [stringData dataUsingEncoding:NSUTF8StringEncoding];
request.HTTPBody = requestBodyData;
// Create url connection and fire request
NSURLConnection *conn = [[NSURLConnection alloc] initWithRequest:request delegate:self];
```

Read NSUrl send a post request online: https://riptutorial.com/objective-c/topic/7243/nsurl-send-a-post-request

Chapter 43: NSUserDefaults

Examples

Simple example

For example:

FOR SAVING:

```
NSUserDefaults *prefs = [NSUserDefaults standardUserDefaults];
// saving an NSString
[prefs setObject:txtUsername.text forKey:@"userName"];
[prefs setObject:txtPassword.text forKey:@"password"];
```

[prefs synchronize];

FOR RETRIEVING

```
NSUserDefaults *prefs = [NSUserDefaults standardUserDefaults];
```

```
// getting an NSString
NSString *savedUsername = [prefs stringForKey:@"userName"];
NSString *savedPassword = [prefs stringForKey:@"password"];
```

Clear NSUserDefaults

NSString *appDomain = [[NSBundle mainBundle] bundleIdentifier];
[[NSUserDefaults standardUserDefaults] removePersistentDomainForName:appDomain];

Read NSUserDefaults online: https://riptutorial.com/objective-c/topic/10713/nsuserdefaults

Chapter 44: Predefined Macros

Introduction

ANSI C defines a number of macros. Although each one is available for your use in programming, the predefined macros should not be directly modified.

Syntax

- 1. DATE The current date as a character literal in "MMM DD YYYY" format
- 2. TIME The current time as a character literal in "HH:MM:SS" format
- 3. FILE This contains the current filename as a string literal.
- 4. LINE This contains the current line number as a decimal constant.
- 5. **STDC** Defined as 1 when the compiler complies with the ANSI standard.

Examples

Predefined Macros

```
#import <Foundation/Foundation.h>
int main()
{
    NSLog(@"File :%s\n", __FILE___);
    NSLog(@"Date :%s\n", __DATE___);
    NSLog(@"Time :%s\n", __TIME___);
    NSLog(@"Line :%d\n", __LINE___);
    NSLog(@"ANSI :%d\n", __STDC___);
    return 0;
}
```

When the above code in a file main.m is compiled and executed, it produces the following result:

```
2013-09-14 04:46:14.859 demo[20683] File :main.m
2013-09-14 04:46:14.859 demo[20683] Date :Sep 14 2013
2013-09-14 04:46:14.859 demo[20683] Time :04:46:14
2013-09-14 04:46:14.859 demo[20683] Line :8
2013-09-14 04:46:14.859 demo[20683] ANSI :1
```

Read Predefined Macros online: https://riptutorial.com/objective-c/topic/8254/predefined-macros

Chapter 45: Properties

Syntax

- @property (optional_attributes, ...) type identifier,
- @synthesize identifier = optional_backing_ivar,
- @dynamic identifier,

Parameters

Attribute	Description
atomic	Implicit. Enables synchronization in synthesized accessor methods.
nonatomic	Disables synchronization in the synthesized accessor methods.
readwrite	Implicit. Synthesizes getter, setter and backing ivar.
readonly	Synthesizes only the getter method and backing ivar, which can be assigned directly.
getter= name	Specifies the name of getter method, implicit is propertyName.
setter= name	Specifies the name of setter method, implicity is ${\tt setPropertyName}$. Colon : must be a part of the name.
strong	Implicit for objects under ARC. The backing ivar is synthesized usingstrong, which prevents deallocation of referenced object.
retain	Synonym for strong.
сору	Same as ${\tt strong}$, but the synthesized setter also calls ${\tt -copy}$ on the new value.
unsafe_unretained	<i>Implicit, except for objects under ARC.</i> The backing ivar is synthesized using <u>unsafe_unretained</u> , which (for obejcts) results in dangling pointer once the referenced object deallocates.
assign	Synonym for unsafe_unretained. Suitable for non-object types.
weak	Backing ivar is synthesized using <u>_weak</u> , so the value will be nullified once the referenced object is deallocated.
class	Property accessors are synthesized as class methods, instead of instance methods. No backing storage is synthesized.
nullable	The property accepts nil values. Mainly used for Swift bridging.

https://riptutorial.com/

Attribute	Description
nonnull	The property doesn't accept nil values. Mainly used for Swift bridging.
null_resettable	The property accepts nil values in setter, but never returns nil values from getter. Your custom implementation of getter or setter must ensure this behavior. Mainly used for Swift bridging.
null_unspecified	<i>Implicit.</i> The property doesn't specify handling of nil values. Mainly used for Swift bridging.

Examples

What are properties?

Here is an example class which has a couple of instance variables, without using properties:

```
@interface TestClass : NSObject {
   NSString *_someString;
   int _someInt;
}
-(NSString *)someString;
- (void) setSomeString: (NSString *) newString;
-(int)someInt;
- (void) setSomeInt: (NSString *) newInt;
@end
@implementation TestClass
-(NSString *)someString {
   return _someString;
}
-(void)setSomeString:(NSString *)newString {
    _someString = newString;
}
-(int)someInt {
   return _someInt;
}
- (void) setSomeInt: (int) newInt {
    _someInt = newInt;
}
0end
```

This is quite a lot of boilerplate code to create a simple instance variable. You have to create the instance variable & create accessor methods which do nothing except set or return the instance variable. So with Objective-C 2.0, Apple introduced properties, which auto-generate some or all of

the boilerplate code.

Here is the above class rewritten with properties:

```
@interface TestClass
@property NSString *someString;
@property int someInt;
@end
@implementation testClass
@end
```

A property is an instance variable paired with auto-generated getters and setters. For a property called <code>someString</code>, the getter and setter are called <code>someString</code> and <code>setSomeString</code>: respectively. The name of the instance variable is, by default, the name of the property prefixed with an underscore (so the instance variable for <code>someString</code> is called <code>_someString</code>, but this can be overridden with an <code>@synthesize</code> directive in the <code>@implementation</code> section:

Properties can be accessed by calling the getters and setters:

```
[testObject setSomeString:@"Foo"];
NSLog(@"someInt is %d", [testObject someInt]);
```

They can also be accessed using dot notation:

```
testObject.someString = @"Foo";
NSLog(@"someInt is %d", testObject.someInt);
```

Custom getters and setters

The default property getters and setters can be overridden:

```
@interface TestClass
@property NSString *someString;
@end
@implementation TestClass
// override the setter to print a message
- (void)setSomeString:(NSString *)newString {
    NSLog(@"Setting someString to %@", newString);
    // Make sure to access the ivar (default is the property name with a _
```

```
// at the beginning) because calling self.someString would call the same
// method again leading to an infinite recursion
_someString = newString;
}
- (void) doSomething {
    // The next line will call the setSomeString: method
    self.someString = @"Test";
}
@end
```

This can be useful to provide, for example, lazy initialization (by overriding the getter to set the initial value if it has not yet been set):

```
- (NSString *)someString {
    if (_someString == nil) {
        _someString = [self getInitialValueForSomeString];
    }
    return _someString;
}
```

You can also make a property that computes its value in the getter:

```
@interface Circle : NSObject
@property CGPoint origin;
@property CGFloat radius;
@property (readonly) CGFloat area;
@end
@implementation Circle
- (CGFloat)area {
    return M_PI * pow(self.radius, 2);
}
@end
```

Properties that cause updates

This object, shape has a property image that depends on numberOfSides and sideWidth. If either one of them is set, than the image has to be recalculated. But recalculation is presumably long, and only needs to be done once if both properties are set, so the shape provides a way to set both properties and only recalculate once. This is done by setting the property ivars directly.

In Shape.h

```
@interface Shape {
    NSUInteger numberOfSides;
    CGFloat sideWidth;
    UIImage * image;
}
```

// Initializer that takes initial values for the properties.
- (instancetype)initWithNumberOfSides: (NSUInteger)numberOfSides withWidth: (CGFloat)width;
// Method that allows to set both properties in once call.
// This is useful if setting these properties has expensive side-effects.
// Using a method to set both values at once allows you to have the side// effect executed only once.
- (void)setNumberOfSides: (NSUInteger)numberOfSides andWidth: (CGFloat)width;
// Properties using default attributes.
@property NSUInteger numberOfSides;
@property CGFloat sideWidth;
// Property using explicit attributes.
@property(strong, readonly) UIImage * image;
@end

In Shape.m

```
@implementation AnObject
// The variable name of a property that is auto-generated by the compiler
// defaults to being the property name prefixed with an underscore, for
// example "_propertyName". You can change this default variable name using
// the following statement:
// @synthesize propertyName = customVariableName;
- (id)initWithNumberOfSides:(NSUInteger)numberOfSides withWidth:(CGFloat)width {
    if ((self = [self init])) {
       [self setNumberOfSides:numberOfSides andWidth:width];
    }
   return self;
}
- (void) setNumberOfSides: (NSUInteger) numberOfSides {
    _numberOfSides = numberOfSides;
    [self updateImage];
}
- (void) setSideWidth: (CGFloat) sideWidth {
    _sideWidth = sideWidth;
    [self updateImage];
}
- (void)setNumberOfSides:(NSUInteger)numberOfSides andWidth:(CGFloat)sideWidth {
    _numberOfSides = numberOfSides;
    _sideWidth = sideWidth;
    [self updateImage];
}
// Method that does some post-processing once either of the properties has
// been updated.
- (void)updateImage {
    . . .
```

}

@end

When properties are assigned to (using <code>object.property = value</code>), the setter method <code>setProperty:</code> is called. This setter, even if provided by <code>@synthesize</code>, can be overridden, as it is in this case for <code>numberOfSides</code> and <code>sideWidth</code>. However, if you set an property's ivar directly (through <code>property</code> if the object is self, or <code>object->property</code>), it doesn't call the getter or setter, allowing you to do things like multiple property sets that only call one update or bypass side-effects caused by the setter.

Read Properties online: https://riptutorial.com/objective-c/topic/1818/properties

Chapter 46: Protocols

Examples

Basic Protocol Definition

Defining a new protocol:

@protocol NewProtocol
- (void)protocolMethod:(id)argument;
- (id)anotherMethod;

0end

Optional and required methods

By default, all the methods declared in a protocol are required. This means that any class that conforms to this protocol must implement those methods.

It is also possible to declare optional methods. These method can be implemented only if needed.

You mark optional methods with the <code>@optional</code> directive.

```
@protocol NewProtocol
- (void)protocolMethod:(id)argument;
@optional
- (id)anotherMethod;
@end
```

In this case, only anotherMethod is marked as optional; the methods without the <code>@optional</code> directive are assumed to be required.

The <code>@optional</code> directive applies to methods that follow, until the end of the protocol definition or, until another directive is found.

```
@protocol NewProtocol
- (void)protocolMethod:(id)argument;
@optional
- (id)anotherMethod;
- (void)andAnotherMethod:(id)argument;
@required
- (void)lastProtocolMethod;
@end
```

This last example defines a protocol with two optional methods and two required methods.

Conforming to Protocols

The following syntax indicate that a class adopts a protocol, using angle brackets.

```
@interface NewClass : NSObject <NewProtocol>
...
@end
```

This means that any instance of NewClass will respond to methods declared in its interface but also it will provide an implementation for all the required methods of NewProtocol.

It is also possible for a class to conform to multiple protocols, by separating them with comma.

```
@interface NewClass : NSObject <NewProtocol, AnotherProtocol, MyProtocol>
...
@end
```

Like when conforming to a single protocol, the class must implement each required method of each protocols, and each optional method you choose to implement.

Forward Declarations

It's possible to declare protocol name without methods:

@protocol Person;

use it your code (class definition, etc):

```
@interface World : NSObject
@property (strong, nonatomic) NSArray<id<some>> *employees;
@end
```

and later define protocol's method somewhere in your code:

```
@protocol Person
- (NSString *)gender;
- (NSString *)name;
@end
```

It's useful when you don't need to know protocols details until you import that file with protocol definition. So, your class header file stays clear and contains details of the class only.

Checking existance of optional method implementations

```
if ([object respondsToSelector:@selector(someOptionalMethodInProtocol:)])
{
    [object someOptionalMethodInProtocol:argument];
}
```

Check conforms Protocol

Returns a Boolean indicating if the class conform the protocol:

[MyClass conformsToProtocol:@protocol(MyProtocol)];

Read Protocols online: https://riptutorial.com/objective-c/topic/448/protocols

Chapter 47: Protocols and Delegates

Remarks

Protocols and Delegates are two related but different concept:

A *Protocol* is a interface a class can conforms to, meaning that class implements the listed methods.

A Delegate is typically an anonymous object that conforms to a protocol.

The application of *Delegate* called *Delegation* is a design pattern.

At one end we have the concept of *Inheritance* which creates a tight coupling between the subclass and its superclass whereas *Delegation* design pattern provides an alternative to avoid this tight coupling using which we can create a much looser relationship based on anonymous *Delegate* objects.

Examples

Implementation of Protocols and Delegation mechanism.

Suppose you have two views \mathtt{ViewA} and \mathtt{ViewB}

Instance of ViewB is created inside ViewA, so ViewA can send message to ViewB's instance, but for the reverse to happen we need to implement delegation (so that using delegate ViewB's instance could send message to ViewA)

Follow these steps to implement the delegation

1. In ViewB create protocol as

```
@protocol ViewBDelegate
-(void) exampleDelegateMethod;
@end
```

2. Declare the delegate in the sender class

```
@interface ViewB : UIView
@property (nonatomic, weak) id< ViewBDelegate > delegate;
@end
```

3. Adopt the protocol in Class ViewA

@interfac ViewA: UIView < ViewBDelegate >

4. Set the delegate

```
-(void) anyFunction
{
    // create Class ViewB's instance and set the delegate
    [viewB setDelegate:self];
}
```

5. Implement the delegate method in class ViewA

```
-(void) exampleDelegateMethod
{
    // will be called by Class ViewB's instance
}
```

6. Use the method in class ${\tt ViewB}$ to call the delegate method as

```
-(void) callDelegateMethod
{
    [delegate exampleDelegateMethod];
    //assuming the delegate is assigned otherwise error
}
```

Read Protocols and Delegates online: https://riptutorial.com/objective-c/topic/7832/protocols-and-delegates

Chapter 48: Random Integer

Examples

Basic Random Integer

The arc4random_uniform() function is the simplest way to get high-quality random integers. As per the manual:

arc4random_uniform(upper_bound) will return a uniformly distributed random number less than upper_bound.

arc4random_uniform() is recommended over constructions like "arc4random() % upper_bound" as it avoids "modulo bias" when the upper bound is not a power of two.

uint32_t randomInteger = arc4random_uniform(5); // A random integer between 0 and 4

Random Integer within a Range

The following code demonstrates usage of arc4random_uniform() to generate a random integer between 3 and 12:

```
uint32_t randomIntegerWithinRange = arc4random_uniform(10) + 3; // A random integer between 3 and 12
```

This works to create a range because $arc4random_uniform(10)$ returns an integer between 0 and 9. Adding 3 to this random integer produces a range between 0 + 3 and 9 + 3.

Read Random Integer online: https://riptutorial.com/objective-c/topic/1573/random-integer
Chapter 49: Singletons

Introduction

Just make sure you read this thread (What is so bad about singletons?) before using it.

Examples

Using Grand Central Dispatch (GCD)

GCD will guarantee that your singleton only gets instantiated once, even if called from multiple threads. Insert this into any class for a singleton instance called shared.

```
+ (instancetype)shared {
    // Variable that will point to the singleton instance. The `static`
    // modifier makes it behave like a global variable: the value assigned
    // to it will "survive" the method call.
    static id _shared;
    static dispatch_once_t _onceToken;
    dispatch_once(&_onceToken, ^{{
        // This block is only executed once, in a thread-safe way.
        // Create the instance and assign it to the static variable.
        _shared = [self new];
    });
    return _shared;
}
```

Creating Singleton class and also preventing it from having multiple instances using alloc/init.

We can create Singleton class in such a way that developers are forced to used the shared instance (singleton object) instead of creating their own instances.

```
@implementation MySingletonClass
+ (instancetype)sharedInstance
{
    static MySingletonClass *_sharedInstance = nil;
    static dispatch_once_t oncePredicate;
    dispatch_once(&oncePredicate, ^{
        __sharedInstance = [[self alloc] initClass];
    });
    return _sharedInstance;
}
-(instancetype)initClass
```

```
{
    self = [super init];
    if(self)
    {
        //Do any additional initialization if required
    }
    return self;
}
- (instancetype) init
{
    @throw [NSException exceptionWithName:@"Not designated initializer"
                                    reason:@"Use [MySingletonClass sharedInstance]"
                                  userInfo:nil];
   return nil;
}
0end
/*Following line will throw an exception
  with the Reason: "Use [MySingletonClass sharedInstance] "
  when tried to alloc/init directly instead of using sharedInstance ^{\star/}
MySingletonClass *mySingletonClass = [[MySingletonClass alloc] init];
```

Creating Singleton and also preventing it from having multiple instance using alloc/init, new.

```
//MySingletonClass.h
@interface MYSingletonClass : NSObject
+ (instancetype)sharedInstance;
-(instancetype)init NS_UNAVAILABLE;
-(instancetype)new NS_UNAVAILABLE;
0end
//MySingletonClass.m
@implementation MySingletonClass
+ (instancetype) sharedInstance
{
    static MySingletonClass *_sharedInstance = nil;
    static dispatch_once_t oncePredicate;
    dispatch_once(&oncePredicate, ^{
        _sharedInstance = [[self alloc]init];
    });
    return _sharedInstance;
}
-(instancetype)init
{
    self = [super init];
    if(self)
    {
        //Do any additional initialization if required
```

```
}
return self;
}
@end
```

Read Singletons online: https://riptutorial.com/objective-c/topic/2834/singletons

Chapter 50: Structs

Syntax

• typedef struct { typeA propertyA; typeB propertyB; ... } StructName

Remarks

In Objective C, you should almost always use an object instead of a struct. However, there are still cases where using a struct is better, such as:

- When you're going to be creating and destroying a lot of values of the (struct) type, so you need good performance and small memory usage
 - Structs are faster to create and use because when calling a method on an object, the method has to be determined at runtime
 - Structs take up less size because objects have an extra property isa, which holds their class
- When the value has only a couple of properties and a small total size (take CGSize; it has 2 floats which are 4 bytes each, so it can take up 8 bytes), and is going to be used a lot (ties in with the first point)
- When you could use unions or bitfields, and importantly, *need the size saved by them* because you need small memory usage (ties in with the first point)
- When you *really* want to store an array inside of the struct, since Objective-C objects can't directly store C-arrays. However, note that you can still "indirectly" get an array in an Objective-C object by making it a reference (i.e. type * in place of the C-array type[])
- When you need to communicate with some other code, such as a library, that's coded in C; structs are fully implemented in C but objects are not

Examples

CGPoint

One really good example of a struct is CGPoint; it's a simple value that represents a 2-dimensional point. It has 2 properties, x and y, and can be written as

```
typedef struct {
    CGFloat x;
    CGFloat y;
} CGPoint;
```

If you used Objective-C for Mac or iOS app development before, you've almost certainly come across cgPoint; cgPoints hold the position of pretty much everything on screen, from views and controls to objects in a game to changes in a gradient. This means that cgPoints are used a lot.

This is even more true with really performance-heavy games; these games tend to have a lot of objects, and all of these objects need positions. These positions are often either cGPoints, or some other type of struct that conveys a point (such as a 3-dimensional point for 3d games).

Points like CGPoint could easily be represented as objects, like

```
@interface CGPoint {
    CGFloat x;
    CGFloat y;
}
... //Point-related methods (e.g. add, isEqualToPoint, etc.)
@property(nonatomic, assign)CGFloat x;
@property(nonatomic, assign)CGFloat y;
@end
@implementation CGPoint
@synthesize x, y;
...
@end
```

However, if *CGPoint* was used in this way it would take a lot longer to create and manipulate points. In smaller, faster programs this wouldn't really cause a difference, and in those cases it would be OK or maybe even better to use object points. But in large programs where points are be used a lot, using objects as points can really hurt performance, making the program slower, and also waste memory, which could force the program to crash.

Defining a Structure and Accessing Structure Members

The format of the struct statement is this:

```
struct [structure tag]
{
    member definition;
    member definition;
    ...
    member definition;
} [one or more structure variables];
```

Example: declare the ThreeFloats structure:

```
typedef struct {
   float x, y, z;
} ThreeFloats;
@interface MyClass
- (void)setThreeFloats:(ThreeFloats)threeFloats;
- (ThreeFloats)threeFloats;
```

Sending an instance of MyClass the message valueForKey: with the parameter @"threeFloats" will invoke the MyClass method threeFloats and return the result wrapped in an NSValue.

Read Structs online: https://riptutorial.com/objective-c/topic/3792/structs

Chapter 51: Subscripting

Examples

Subscripts with NSArray

Subscripts can be used to simplify retrieving and setting elements in an array. Given the following array

NSArray *fruit = @[@"Apples", @"Bananas", @"Cherries"];

This line

[fruit objectAtIndex: 1];

Can be replaced by

fruit[1];

They can also be used to set an element in a mutable array.

```
NSMutableArray *fruit = [@[@"Apples", @"Bananas", @"Cherries"] mutableCopy];
fruit[1] = @"Blueberries";
NSLog(@"%@", fruit[1]); //Blueberries
```

If the index of the subscript equals the count of the array, the element will be appended to the array.

Repeated subscripts may be used to access elements of nested arrays.

```
NSArray *fruit = @[@"Apples", @"Bananas", @"Cherries"];
NSArray *vegetables = @[@"Avocado", @"Beans", @"Carrots"];
NSArray *produce = @[fruit, vegetables];
NSLog(@"%@", produce[0][1]); //Bananas
```

Subscripts with NSDictionary

Subscripts can also be used with NSDictionary and NSMutableDictionary. The following code:

```
NSMutableDictionary *myDictionary = [@{@"Foo": @"Bar"} mutableCopy];
[myDictionary setObject:@"Baz" forKey:@"Foo"];
NSLog(@"%@", [myDictionary objectForKey:@"Foo"]); // Baz
```

Can be shortened to:

```
NSMutableDictionary *myDictionary = [@{@"Foo": @"Bar"} mutableCopy];
myDictionary[@"Foo"] = @"Baz";
NSLog(@"%@", myDictionary[@"Foo"]); // Baz
```

Custom Subscripting

You can add subscripting to your own classes by implementing the required methods.

For indexed subscripting (like arrays):

- (id)objectAtIndexedSubscript:(NSUInteger)idx
- (void)setObject:(id)obj atIndexedSubscript:(NSUInteger)idx

For keyed subscripting (like dictionaries):

- (id)objectForKeyedSubscript:(id)key
- (void)setObject:(id)obj forKeyedSubscript:(id <NSCopying>)key

Read Subscripting online: https://riptutorial.com/objective-c/topic/3825/subscripting

Chapter 52: Unit testing using Xcode

Remarks

Dependencies:

- If application uses third party libraries or cocoa pods, then those libraries or pods are needed to be install for test as well.
- Test class (Test Suit) extends XCTestCase.

Get brushed up before starting:

- All test classes have two methods in common setUp & tearDown.
- setUp runs before every testcase & tearDown after every testcase.
- Test cases runs alphabetically.
- In Test Driven Development, it is good to create dummy test data first.
- Test case methods starts with "test" keyword.
- Test methods accept no parameters & return no value.

Appendix:

There are several other methods for comparing the expected result & actual result out of an operation. Some of those methods are listed below:

- XCTAssertNil(expression, comment) generates a failure if expression != nil.
- XCTAssertNotNil(expression, comment) generates a failure if expression = nil.
- XCTAssert(expression, comment) generates a failure if expression == false.
- XCTAssertTrue(expression, comment) generates a failure if expression == false.
- XCTAssertFalse(expression, comment) generates a failure if expression != false.
- XCTAssertEqualObjects(expression1, expression2, comment) generates a failure if expression1 is not equal to expression2.
- XCTAssertEqualObjects(expression1, expression2, comment) generates a failure if expression1 is equal to expression2.
- XCTAssertNotEqual(expression1, expression2, comment) generates a failure if expression1 == expression2.
- XCTAssertEqual(expression1, expression2, comment) generates a failure if expression1 != expression2.
- XCTAssertGreaterThanOrEqual(expression1, expression2, comment) generates a failure when (expression1 < expression2).

Examples

Testing a block of code or some method:

- Import the class, which contains the method to be tested.
- Perform the operation with dummy data.
- Now compare the result of operation with expected result.

```
- (void)testReverseString{
NSString *originalString = @"hi_my_name_is_siddharth";
NSString *reversedString = [self.someObject reverseString:originalString];
NSString *expectedReversedString = @"htrahddis_si_eman_ym_ih";
XCTAssertEqualObjects(expectedReversedString, reversedString, @"The reversed string did not
match the expected reverse");
}
```

Feed the dummy data to the method under test if required & then compare the expected & actual results.

Testing asynchronous block of code:

```
- (void)testDoSomethingThatTakesSomeTime{
XCTestExpectation *completionExpectation = [self expectationWithDescription:@"Long method"];
[self.someObject doSomethingThatTakesSomeTimesWithCompletionBlock:^(NSString *result) {
    XCTAssertEqualObjects(@"result", result, @"Result was not correct!");
    [completionExpectation fulfill];
}];
[self waitForExpectationsWithTimeout:5.0 handler:nil];
}
```

- Feed the dummy data to the method under test if required.
- The test will pause here, running the run loop, until the timeout is hit or all expectations are fulfilled.
- Timeout is the expected time for the asynchronous block to response.

Measuring Performance of a block of code:

1. For Synchronous methods :

```
- (void)testPerformanceReverseString {
    NSString *originalString = @"hi_my_name_is_siddharth";
    [self measureBlock:^{
        [self.someObject reverseString:originalString];
    }];
}
```

2. For Asynchronous methods :

```
- (void)testPerformanceOfAsynchronousBlock {
    [self measureMetrics:@[XCTPerformanceMetric_WallClockTime] automaticallyStartMeasuring:YES
forBlock:^{
    XCTestExpectation *expectation = [self
expectationWithDescription:@"performanceTestWithResponse"];
    [self.someObject doSomethingThatTakesSomeTimesWithCompletionBlock:^(NSString *result) {
        [expectation fulfill];
    }];
    [self waitForExpectationsWithTimeout:5.0 handler:^(NSError *error) {
     }];
}];
```

- These performance measure block gets executed for 10 times consecutively & then the average is calculated, & on the basis of this average performance result gets created & baseline is accepted for further evaluation.
- The performance result is compared with the previous test results & baseline with a customizable max standard deviation.

Running Test Suits:

Run all tests by choosing Product > Test. Click the Test Navigator icon to view the status and results of the tests. You can add a test target to a project (or add a class to a test) by clicking the Add (plus) button in the bottom-left corner of the test navigator. To view the source code for a particular test, select it from the test list. The file opens in the source code editor.

Note:

Make sure that include unit test case box is checked when creating a new project as shown below:

Choose options for your new project:		
Product Name:		
Organization Name:	DMI	
Organization Identifier:	com.DMI	
Bundle Identifier:	com.DMI.ProductName	
Language:	Objective-C	\$
Devices:	Universal	\$
	Use Core Data	
	🗸 Include Unit Tests	
	🗸 Include UI Tests	
Cancel		Previous

Read Unit testing using Xcode online: https://riptutorial.com/objective-c/topic/5160/unit-testing-using-xcode

Chapter 53: XML parsing

Examples

XML Parsing

```
<?xml version="1.0" encoding="UTF-8"?>
<GeocodeResponse>
 <status>0K</status>
 <result>
  <type>premise</type>
  <formatted_address>4201 Oak Lawn Ave, Dallas, TX 75219, USA
     formatted_address>
  <address_component>
   <long_name>4201</long_name>
   <short_name>4201</short_name>
   <type>street_number</type>
  </address_component>
  <address_component>
   <long_name>Oak Lawn Avenue</long_name>
   <short_name>Oak Lawn Ave</short_name>
   <type>route</type>
  </address_component>
  <address_component>
   <long_name>Oak Lawn</long_name>
   <short_name>Oak Lawn</short_name>
   <type>neighborhood</type>
   <type>political</type>
  </address_component>
  <address_component>
   <long_name>Dallas</long_name>
   <short_name>Dallas</short_name>
   <type>locality</type>
   <type>political</type>
  </address_component>
 </result>
</GeocodeResponse>
```

We will parse the highlighted tag data through NSXMLParser

We have declared few properties as follows

```
@property(nonatomic, strong)NSMutableArray *results;
@property(nonatomic, strong)NSMutableString *parsedString;
@property(nonatomic, strong)NSXMLParser *xmlParser;
//Fetch xml data
NSURLSession *session=[NSURLSession sessionWithConfiguration:[NSURLSessionConfiguration]
```

```
NSURLSessionDataTask *task=[session dataTaskWithRequest:[NSURLRequest requestWithURL:[NSURL
URLWithString:YOUR_XMLURL]] completionHandler:^(NSData * _Nullable data, NSURLResponse *
_Nullable response, NSError * _Nullable error) {
    self.xmlParser=[[NSXMLParser alloc] initWithData:data];
    self.xmlParser.delegate=self;
    if([self.xmlParser parse]) {
        //If parsing completed successfully
        NSLog(@"%@",self.results);
    }
}];
[task resume];
```

Then we define the NSXMLParserDelegate

defaultSessionConfiguration]];

```
(void)parser: (NSXMLParser *)parser didStartElement: (NSString *)elementName
namespaceURI:(nullable NSString *)namespaceURI qualifiedName:(nullable NSString *)qName
attributes:(NSDictionary<NSString *, NSString *> *)attributeDict{
    if([elementName isEqualToString:@"GeocodeResponse"]) {
        self.results=[[NSMutableArray alloc] init];
    }
    if([elementName isEqualToString:@"formatted_address"]) {
        self.parsedString=[[NSMutableString alloc] init];
    }
}
- (void)parser: (NSXMLParser *)parser foundCharacters: (NSString *)string{
    if(self.parsedString) {
        [self.parsedString appendString:[string
stringByTrimmingCharactersInSet:[NSCharacterSet whitespaceAndNewlineCharacterSet]]];
    }
}
- (void)parser: (NSXMLParser *)parser didEndElement: (NSString *)elementName
namespaceURI: (nullable NSString *) namespaceURI qualifiedName: (nullable NSString *) qName {
    if([elementName isEqualToString:@"formatted_address"]){
        [self.results addObject:self.parsedString];
        self.parsedString=nil;
    }
}
```

Read XML parsing online: https://riptutorial.com/objective-c/topic/8048/xml-parsing

Credits

S. No	Chapters	Contributors
1	Getting started with Objective-C Language	Ali Riahipour, Community, connor, insys, J F, Jeff Wolski, Josh Brown, Josh Caswell, Niraj, StrAbZ, tbodt
2	Basic Data Types	connor, Josh Caswell, Muhammad Zohaib Ehsan, ok404, Sietse, sudo, Sujania, user459460
3	Blocks	BB9z, connor, danh, Fantini, insys, J F, Jeff Wolski, Johannes Fahrenkrug, Josh Caswell, Kote, Lito, Oliver Atkinson, Seán Labastille, tbodt, Yevhen Dubinin
4	BOOL / bool / Boolean / NSCFBoolean	Md. Ibrahim Hassan, user459460
5	Categories	atroutt, DarkDust, Ekta Padaliya, Faran Ghani, Håvard, insys, Mykola Denysyuk, Orlando, Paulo Fierro, phi, WMios
6	Classes and Objects	Byron, DarkDust, HCarrasko, Jens Meder, Josh Caswell, NSNoob, ok404, RamenChef, tbodt
7	Continue and Break!	Md. Ibrahim Hassan
8	Declare class method and instance method	Ruby, user459460
9	Enums	Daniel Bocksteger, DavidA, Doc, Doron Yakovlev-Golani, IostInTransit, Mikhail Larionov, user459460
10	Error Handling	Doc, Sujania
11	Fast Enumeration	ff10, shuvo
12	Format-Specifiers	Albert Renshaw
13	Grand Central Dispatch	user459460
14	Inheritance	ВКО
15	Key Value Coding / Key Value Observing	Cory Wilhite, insys, Jason McDermott, Nirav Bhatt, ThatsJustCheesy, WMios

16	Logging	Albert Renshaw, Chris Prince, connor, Daniel Bocksteger, DarkDust, DavidA, HariKrishnan.P, HCarrasko, Iulian Onofrei, Jason McDermott, Josh Caswell, Kornel, Nicolas Miari, NobodyNada, Peter N Lewis, Samet DEDE, Tapan Prakash, tbodt, Thomas Tempelmann, Tricertops, WMios
17	Low-level Runtime Environment	connor, DarkDust, dgatwood, Grady Player, Josh Caswell, orta, tbodt, Tricertops
18	Memory Management	James P, ok404, Tamarous, tbodt, Tricertops
19	Methods	Caleb Kleveter, Jon Schneider, Joshua, jsondwyer, mrtnf, Sujania, Tapan Prakash, tbodt
20	Modern Objective-C	pckill
21	Multi-Threading	DarkDust, jsondwyer
22	NSArray	animuson, AnthoPak, Bharath, DarkDust, Ekta Padaliya, Evan, HCarrasko, Irfan, j.f., James P, Jeff Wolski, Johannes Fahrenkrug, Jon Schneider, Joost, Josh Caswell, Joshua, jsondwyer, Losiowaty, mrtnf, mszaro, Muhammad Zohaib Ehsan, njuri, NSNoob, Paulo Fierro, Ruby, tbodt
23	NSAttributedString	Patrick, Sujania, user459460
24	NSCache	user459460
25	NSCalendar	byJeevan, connor
26	NSData	Patrick, Sujania, WMios
27	NSDate	jsondwyer, Nikolai Ruhe, Patrick, Sujania, WMios
28	NSDictionary	connor, Fantini, insys, Kevin Stewart, Mykola Denysyuk, Patrick, Sujania
29	NSJSONSerialization	connor, Sujania
30	NSMutableArray	aniket.ghode, animuson, DavidA, HCarrasko, J F, Joost, Ruby, Spidy, Sujania, tbodt, william205
31	NSMutableDictionary	Ravi Dhorajiya
32	NSObject	CodeChanger
33	NSPredicate	Dipen Panchasara
34	NSRegularExpression	Johannes Fahrenkrug
35	NSSortDescriptor	4444, Rahul

36	NSString	Albert Renshaw, animuson, AnthoPak, Cœur, DarkDust, Darshan Kunjadiya, David Mangon, il Malvagio Dottor Prosciutto, James P, Jeff Wolski, Johnny Rockex, Jon Schneider, Josh Caswell, Joshua, jsondwyer, Md. Ibrahim Hassan, Nikolai Ruhe, NSNoob, Orlando, Patrick, Paulo Fierro, RamenChef, Ruby, Srinivasan Saivenkat, Sunil Sharma, tbodt, Tricertops, ViratA, WMios
37	NSTextAttachment	ВКО
38	NSTimer	Arc676, DarkDust, Hemang, Jason McDermott, Patrick, Ruby
39	NSURL	Patrick, Sujania
40	NSUrl send a post request	Md. Ibrahim Hassan
41	NSUserDefaults	Adriana Carelli
42	Predefined Macros	user459460
43	Properties	DarkDust, dgatwood, Doc, J F, Nef10, NobodyNada, tbodt, Tricertops
44	Protocols	Håvard, insys, jsondwyer, Mykola Denysyuk, Patrick, RamenChef, StrAbZ, tbodt, Tricertops
45	Protocols and Delegates	RamenChef, Sanjay Mohnani
46	Random Integer	Josh Caswell, jsondwyer
47	Singletons	Amit Kalghatgi, Andrew Hoos, connor, Daniel Bocksteger, DarkDust, Glenn Smith, Itachi, pckill, Peter DeWeese
48	Structs	Doc, Sujania
49	Subscripting	connor, tbodt
50	Unit testing using Xcode	ajmccall, Amon, Siddharth Sunil
51	XML parsing	iphonic, Stephen Leppik