

 免费电子书

学习

Scala Language

Free unaffiliated eBook created from
Stack Overflow contributors.

#scala

.....	1
1: Scala	2
.....	2
.....	2
Examples.....	2
"Hello World".....	2
Hello WorldApp.....	3
.....	3
.....	3
Hello World.....	4
Scala REPL.....	4
Scala Quicksheet.....	5
2: Hive	7
Examples.....	7
Apache SparkHive UDF.....	7
3: Implicits	8
.....	8
.....	8
Examples.....	8
.....	8
.....	8
.....	9
".....	10
REPL.....	10
4: Java	11
Examples.....	11
ScalaJava.....	11
.....	11
ScalaJava.....	11
Scala - scala-java8-compatible.....	12
5: JSON	14

Examples.....	14
JSON with spray-json.....	14
SBT.....	14
.....	14
JSON.....	14
JSON.....	14
DSL.....	14
.....	14
.....	15
JSONCirce.....	15
play-jsonJSON.....	16
JSONjson4s.....	18
6: Quasiquotes.....	21
Examples.....	21
quasiquotes.....	21
7: Scala.js.....	22
.....	22
Examples.....	22
Scala.jsconsole.log.....	22
.....	22
.....	22
.....	22
DOM.....	22
SBT.....	22
.....	22
.....	22
.....	22
JavaScript.....	23
8: Scaladoc.....	24
.....	24
.....	24

Examples.....	24
Scaladoc.....	24
9: scalaz.....	26
.....	26
Examples.....	26
ApplyUsage.....	26
FunctorUsage.....	26
ArrowUsage.....	26
10: Scala.....	28
Examples.....	28
.....	28
.....	28
.....	28
11: VarValDef.....	30
.....	30
Examples.....	30
VarValDef.....	30
VAR.....	30
VAL.....	30
.....	31
.....	31
val.....	32
".....	32
Def.....	33
.....	33
12: XML.....	35
Examples.....	35
XML.....	35
13: Gradle.....	36
Examples.....	36
.....	36

Gradle Scala.....	36
.....	36
.....	39
14: ScalaCheck.....	41
.....	41
Examples.....	41
Scalacheckscalatest.....	41
15: ScalaTest.....	44
Examples.....	44
Hello World Spec Test.....	44
Spec Test Cheatsheet.....	44
ScalaTestSBT.....	45
16:	46
.....	46
.....	46
Examples.....	46
valvar.....	46
valvar.....	46
.....	46
.....	47
“”.....	47
result.....	47
.....	47
.....	48
.....	48
.....	48
17:	49
Examples.....	49
.....	49
18:	50
.....	50
Examples.....	50

.....	50
.....	50
19:	52
.....	52
.....	52
Examples.....	52
.....	52
.....	52
.....	53
.....	53
PartialFunctions.....	53
20:	54
.....	54
.....	54
.....	54
Examples.....	54
.....	54
.....	54
.....	55
21:	56
.....	56
Examples.....	56
.....	56
.....	56
.....	56
22: SAM	58
.....	58
Examples.....	58
Lambda.....	58
23:	59
Examples.....	59

Monad.....	59
24:	61
Examples.....	61
.....	61
25:	62
.....	62
Examples.....	62
.....	62
.....	62
26:	63
.....	63
Examples.....	63
curried.....	63
.....	63
.....	63
.....	63
.....	64
Currying.....	64
Currying.....	65
27:	67
.....	67
.....	67
Examples.....	67
.....	67
.....	67
28:	68
Examples.....	68
.....	68
29:	69
.....	69
Examples.....	69
Hello String Interpolation.....	69

f.....	69
.....	69
.....	70
.....	70
.....	71
30:	72
.....	72
.....	72
.....	72
Examples.....	72
.....	72
.....	72
.....	73
31:	75
.....	75
.....	75
Examples.....	75
.....	75
.....	75
For.....	75
Monadic.....	76
For.....	77
.....	77
32:	78
.....	78
Examples.....	78
.....	78
.....	78
33:	80
.....	80
Examples.....	80
.....	80

.....	80
34:	82
.....	82
.....	82
.....	82
Examples.....	82
.....	82
Do-While.....	82
35:	83
.....	83
Examples.....	83
.....	83
.....	83
.....	84
.....	85
36:	87
.....	87
Examples.....	87
.....	87
.....	87
Unapply -	88
.....	89
.....	89
.....	89
37:	91
.....	91
Examples.....	91
.....	91
.....	91
.....	91
38:	93
Examples.....	93

.....	93
.....	93
.....	93
.....	94
.....	94
-	94
39:	96
.....	96
Examples	96
Scala Enumeration	96
.....	97
traitcaseallValues-macro	98
40:	100
.....	100
Examples	100
.....	100
.....	100
.....	101
.....	102
.....	102
.....	102
.....	103
41:	104
.....	104
.....	104
Examples	104
.....	104
.....	105
Seq	105
.....	106
.....	106
.....	107
.....	107
.....	

@	108
.....	108
tableswitchlookupswitch	109
.....	109
.....	110
42:	112
.....	112
.....	112
.....	112
Examples	112
.....	112
.....	112
.....	113
43:	114
.....	114
Examples	114
.....	114
.....	114
.....	115
44:	116
.....	116
Examples	116
case	116
45:	117
.....	117
Examples	117
.....	117
{ } vs	117
SingletonCompanion	118
.....	118
.....	119

.....	119
.....	119
.....	121
.....	121
.....	121
46:	123
Examples.....	123
.....	123
.....	123
.....	123
Ints.....	123
.....	123
47:	125
Examples.....	125
.....	125
.....	125
.....	125
.....	125
48:	127
Examples.....	127
.....	127
49:	128
.....	128
.....	128
.....	128
Examples.....	128
Continutations.....	128
.....	129
50:	130
.....	130
.....	130
Examples.....	130

.....	130
51:	131
.....	131
.....	131
Examples.....	131
.....	131
.....	131
.....	131
.....	132
.....	132
.....	132
52:	133
.....	133
Examples.....	133
.....	133
53: Scala	134
Examples.....	134
Linuxdpkg.....	134
Ubuntu.....	134
Mac OSXMacports.....	135
54:	136
Examples.....	136
.....	136
.....	136
55:	137
.....	137
Examples.....	137
.....	137
OptionNull.....	137
.....	138
.....	138
.....	138

56:	140
Examples	140
.....	140
.....	140
.....	140
trampolinescala.util.control.TailCalls	141
57:	142
Examples	142
.....	142
`collect`	142
.....	143
.....	143
map	144
58:	145
Examples	145
.....	145
.....	145
.....	145
.....	146
mapgetOrElse	146
.....	146
Java	146
.....	146
try-catch	147
EitherOption	147
59:	148
Examples	148
.....	148
.....	148
.....	148
.....	149
.....	149

60:	151
.....	151
Examples.....	151
.....	151
.....	151
.....	152
61:	154
Examples.....	154
.....	154
nx.....	154
Cheatsheet.....	155
Cheatsheet.....	155
.....	156
.....	156
2.....	156
.....	156
.....	157
.....	157
Scala.....	157
.....	158
.....	158
foreach.....	159
.....	159
62:	161
.....	161
Examples.....	161
.....	161
.....	161
.....	162
.....	163

You can share this PDF with anyone you feel could benefit from it, downloaded the latest version from: [scala-language](#)

It is an unofficial and free Scala Language ebook created for educational purposes. All the content is extracted from [Stack Overflow Documentation](#), which is written by many hardworking individuals at Stack Overflow. It is neither affiliated with Stack Overflow nor official Scala Language.

The content is released under Creative Commons BY-SA, and the list of contributors to each chapter are provided in the credits section at the end of this book. Images may be copyright of their respective owners unless otherwise specified. All trademarks and registered trademarks are the property of their respective company owners.

Use the content presented in this book at your own risk; it is not guaranteed to be correct nor accurate, please send your feedback and corrections to info@zzzprojects.com

1: Scala

Scala。。

Scala。 [Scala “Scala”](#)。 [scalafiddle.net](#)Web。

2.10.1	2013313
2.10.2	201366
2.10.3	2013101
2.10.4	2014324
2.10.5	201535
2.10.6	2015918
2.11.0	2014421
2.11.1	2014521
2.11.2	2014724
2.11.4	2014-10-30
2.11.5	2014114
2.11.6	201535
2.11.7	2015623
2.11.8	201638
2.11.11	2017419
2.12.0	2016113
2.12.1	2016126
2.12.2	2017419

Examples

"Hello World

HelloWorld.scala

```
object Hello {
  def main(args: Array[String]): Unit = {
    println("Hello World!")
  }
}
```

JVM

```
$ scalac HelloWorld.scala
```

```
$ scala Hello
```

ScalamainHello◦ main◦

JavaScala◦ scala HelloHelloscala Hello◦ main◦ .scala◦ main◦

args◦

```
object HelloWorld {
  def main(args: Array[String]): Unit = {
    println("Hello World!")
    for {
      arg <- args
    } println(s"Arg=$arg")
  }
}
```

```
$ scalac HelloWorld.scala
```

```
$ scala HelloWorld 1 2 3
Hello World!
Arg=1
Arg=2
Arg=3
```

Hello WorldApp

```
object HelloWorld extends App {
  println("Hello, world!")
}
```

App main◦ HelloWorld""◦

2.11.0

App◦ main◦

2.11.0

App◦ main◦

DelayedInit App ◦ ◦

Appthis.args

```
object HelloWorld extends App {  
  println("Hello World!")  
  for {  
    arg <- this.args  
  } println(s"Arg=$arg")  
}
```

App mainmain ◦

Hello World

Scala◦ HelloWorld.scala

```
println("Hello")
```

\$

```
$ scala HelloWorld.scala  
Hello
```

.scala scala HelloWorld .class◦

scala◦

bashshell'shell preamble'Scala◦ HelloWorld.sh

```
#!/bin/sh  
exec scala "$0" "$@"  
!#  
println("Hello")
```

#!###'#shell preamble'bash◦ ◦

“”◦ shell

```
$ chmod a+x HelloWorld.sh
```

chmod◦

```
$ ./HelloWorld.sh
```

Scala REPL

scala [REPL](#) Read-Eval-Print Loop

```

nford:~ $ scala
Welcome to Scala 2.11.8 (Java HotSpot(TM) 64-Bit Server VM, Java 1.8.0_66).
Type in expressions for evaluation. Or try :help.

scala>

```

REPL Scala `val poem = "As halcyons we shall be"`

```

scala> val poem = "As halcyons we shall be"
poem: String = As halcyons we shall be

```

`val`

```

scala> print(poem)
As halcyons we shall be

```

`val`

```

scala> poem = "Brooding on the open sea"
<console>:12: error: reassignment to val
    poem = "Brooding on the open sea"

```

REPL `val` Scala

```

scala> val poem = "Brooding on the open sea"
poem: String = Brooding on the open sea

```

REPL `REPL` Scala

Scala Quicksheet

<code>int</code>	<code>val x = 3</code>
<code>int</code>	<code>var x = 3</code>
	<code>val x: Int = 27</code>
	<code>lazy val y = print("Sleeping in.")</code>
	<code>val f = (x: Int) => x * x</code>
	<code>val f: Int => Int = (x: Int) => x * x</code>
	<code>def f(x: Int) = x * x</code>
	<code>def f(x: Int): Int = x * x</code>
	<code>class Hopper(someParam: Int) { ... }</code>
	<code>object Hopper(someParam: Int) { ... }</code>
	<code>trait Grace { ... }</code>

	<code>Seq(1,2,3).head</code>
	<code>val result = if(x > 0) "Positive!"</code>
	<code>Seq(1,2,3).tail</code>
	<code>for { x <- Seq(1,2,3) } print(x)</code>
	<code>for { x <- Seq(1,2,3) y <- Seq(4,5,6) } print(x + ":" + y)</code>
	<code>List(1,2,3).foreach { println }</code>
	<code>print("Ada Lovelace")</code>
	<code>List('b','c','a').sorted</code>

Scala <https://riptutorial.com/zh-CN/scala/topic/216/scala>

2: Hive

Examples

Apache SparkHive UDF

```
import org.apache.spark.sql.functions._

// Create a function that uses the content of the column inside the dataframe
val code = (param: String) => if (param == "myCode") 1 else 0
// With that function, create the udf function
val myUDF = udf(code)
// Apply the udf to a column inside the existing dataframe, creating a dataframe with the
additional new column
val newDataframe = aDataframe.withColumn("new_column_name", myUDF(col(inputColumn)))
```

Hive <https://riptutorial.com/zh-CN/scala/topic/8241/hive>

3: Implicit

- `val xT = ???`

◦

“”◦

1. ◦
2. ◦
3. ◦

Examples

◦ ◦

```
case class Foo(i: Int)

// without the implicit
Foo(40) + 2    // compilation-error (type mismatch)

// defines how to turn a Foo into an Int
implicit def fooToInt(foo: Foo): Int = foo.i

// now the Foo is converted to Int automatically when needed
Foo(40) + 2    // 42
```

42Foo(42) ◦

```
implicit def intToFoo(i: Int): Foo = Foo(i)
```

◦

◦ ◦

◦

Scala `scala.Predef` JavaScala ◦ ◦

◦

```
// import the duration methods
import scala.concurrent.duration._

// a normal method:
def doLongRunningTask(timeout: FiniteDuration): Long = timeout.toMillis

val timeout = 1.second
// timeout: scala.concurrent.duration.FiniteDuration = 1 second
```

```
// to call it
doLongRunningTask(timeout) // 1000
```

◦ ◦

```
// import the duration methods
import scala.concurrent.duration._

// dummy methods that use the implicit parameter
def doLongRunningTaskA()(implicit timeout: FiniteDuration): Long = timeout.toMillis
def doLongRunningTaskB()(implicit timeout: FiniteDuration): Long = timeout.toMillis

// we define the value timeout as implicit
implicit val timeout: FiniteDuration = 1.second

// we can now call the functions without passing the timeout parameter
doLongRunningTaskA() // 1000
doLongRunningTaskB() // 1000
```

scalac ◦ ◦

◦

implicitNotFound

```
@annotation.implicitNotFound(msg = "Select the proper implicit value for type M[${A}]!")
case class M[A](v: A) {}

def usage[O](implicit x: M[O]): O = x.v

//Does not work because no implicit value is present for type `M[Int]`
//usage[Int] //Select the proper implicit value for type M[Int]!
implicit val first: M[Int] = M(1)
usage[Int] //Works when `second` is not in scope
implicit val second: M[Int] = M(2)
//Does not work because more than one implicit values are present for the type `M[Int]`
//usage[Int] //Select the proper implicit value for type M[Int]!
```

Akka ActorSystem◦ FPscalaz ◦

Int Long String◦

◦

StringwithoutVowels◦

```
object StringUtil {
  implicit class StringEnhancer(str: String) {
    def withoutVowels: String = str.replaceAll("[aeiou]", "")
  }
}
```

str String "" withoutVowels ◦


```
import StringUtil.StringEnhancer // Brings StringEnhancer into implicit scope

println("Hello world".withoutVowels) // Hll wrld
```

```
implicit def toStringEnhancer(str: String): StringEnhancer = new StringEnhancer(str)
```

Value

```
implicit class StringEnhancer(val str: String) extends AnyVal {
  /* conversions code here */
}
```

withoutVowelsStringEnhancer

"

```
case class Example(p1:String, p2:String)(implicit ctx1:SomeCtx1, ctx2:SomeCtx2)
```

SomeCtx1 SomeCtx1

implicitly

```
Example("something","somethingElse")(new SomeCtx1(), implicitly[SomeCtx2])
```

REPL

REPL

implicit

```
scala> :implicits
```

Predef.scala

```
scala> :implicits -v
```

```
scala> reflect.runtime.universe.reify(expr) // No quotes. reify is a macro operating directly
on code.
```

```
scala> import reflect.runtime.universe._
scala> reify(Array("Alice", "Bob", "Eve").mkString(", "))
resX: Expr[String] = Expr[String](Predef.refArrayOps(Array.apply("Alice", "Bob",
"Eve") (Predef.implicitly)).mkString(", "))
```

Implicits <https://riptutorial.com/zh-CN/scala/topic/1732/implicits>

4: Java

Examples

ScalaJava

Java

```
import scala.collection.JavaConverters._

val scalaList = List(1, 2, 3)
JavaLibrary.process(scalaList.asJava)
```

JavaJavaScala

```
import scala.collection.JavaConverters._

val javaCollection = JavaLibrary.getList
val scalaCollection = javaCollection.asScala
```

ScalaJava[◦] .asJava.asScala[◦]

JVM[◦] new[◦]

```
val a = Array("element")
```

aArray[String] [◦]

```
val acs: Array[CharSequence] = a
//Error: type mismatch; found   : Array[String]   required: Array[CharSequence]
```

StringCharSequence Array[String]Array[CharSequence] [◦]

TraversableLike ArrayOps Array

```
val b: Array[Int] = a.map(_.length)
```

Scala TraversableOnce toArrayClassTag

```
List(0).toArray
//> res1: Array[Int] = Array(0)
```

ScalaTraversableOnceJava[◦]

ScalaJava

ScalaJavaConverters

◦

	Java
	java.util.Iterator
	java.util.Enumeration
	java.util.Iterable
	java.util.Collection
mutable.Buffer	java.util.List
mutable.Set	java.util.Set
mutable.Map	java.util.Map
mutable.ConcurrentMap	java.util.concurrent.ConcurrentMap

ScalaJavaScala

	Java
SEQ	java.util.List
mutable.Seq	java.util.List
	java.util.Set
	java.util.Map

JavaScala

Scala - scala-java8-compat

ScalaJava 8

scala.FunctionNjava.util.function

```
import java.util.function._
import scala.compat.java8.FunctionConverters._

val foo: Int => Boolean = i => i > 7
def testBig(ip: IntPredicate) = ip.test(9)
println(testBig(foo.asJava)) // Prints true

val bar = new UnaryOperator[String]{ def apply(s: String) = s.reverse }
```

```
List("cod", "herring").map(bar.asScala)    // List("doc", "gnirrih")

def testA[A](p: Predicate[A])(a: A) = p.test(a)
println(testA(asJavaPredicate(foo))(4))    // Prints false
```

scala.Optionjava.utilOptionalDoubleOptionalIntOptionalLong

```
import scala.compat.java8.OptionConverters._

class Test {
  val o = Option(2.7)
  val oj = o.asJava      // Optional[Double]
  val ojd = o.asPrimitive // OptionalDouble
  val ojds = ojd.asScala // Option(2.7) again
}
```

ScalaJava 8 Streams

```
import java.util.stream.IntStream

import scala.compat.java8.StreamConverters._
import scala.compat.java8.collectionImpl.{Accumulator, LongAccumulator}

val m = collection.immutable.HashMap("fish" -> 2, "bird" -> 4)
val parStream: IntStream = m.parValueStream
val s: Int = parStream.sum
// 6, potentially computed in parallel
val t: List[String] = m.seqKeyStream.toScala[List]
// List("fish", "bird")
val a: Accumulator[(String, Int)] = m.accumulate // Accumulator[(String, Int)]

val n = a.stepper.fold(0)(_ + _.length) +
  a.parStream.count // 8 + 2 = 10

val b: LongAccumulator = java.util.Arrays.stream(Array(2L, 3L, 4L)).accumulate
// LongAccumulator
val l: List[Long] = b.toList // List(2L, 3L, 4L)
```

Java <https://riptutorial.com/zh-CN/scala/topic/2441/java>

5: JSON

Examples

JSON with spray-json

spray-jsonJSON。 “”

SBT

SBTspray-json

```
libraryDependencies += "io.spray" %% "spray-json" % "1.3.2"
```

1.3.2。

spray-json[repo.spray.io](https://github.com/spray/spray-json)。

```
import spray.json._
import DefaultJsonProtocol._
```

JSONDefaultJsonProtocol。 JSON。

JSON

```
// generates an intermediate JSON representation (abstract syntax tree)
val res = """"{ "foo": "bar" }""".parseJson // JsValue = {"foo":"bar"}

res.convertTo[Map[String, String]] // Map(foo -> bar)
```

JSON

```
val values = List("a", "b", "c")
values.toJson.prettyPrint // ["a", "b", "c"]
```

DSL

DSL。

JSON

```
case class Address(street: String, city: String)
case class Person(name: String, address: Address)

// create the formats and provide them implicitly
implicit val addressFormat = jsonFormat2(Address)
implicit val personFormat = jsonFormat2(Person)

// serialize a Person
Person("Fred", Address("Awesome Street 9", "SuperCity"))
val fredJsonString = fred.toJson.prettyPrint
```

JSON

```
{
  "name": "Fred",
  "address": {
    "street": "Awesome Street 9",
    "city": "SuperCity"
  }
}
```

JSON

```
val personRead = fredJsonString.parseJson.convertTo[Person]
//Person(Fred,Address(Awesome Street 9,SuperCity))
```

JsonFormat ◦ ScalaJSON ◦ ◦

```
implicit object BetterPersonFormat extends JsonFormat[Person] {
  // deserialization code
  override def read(json: JsValue): Person = {
    val fields = json.asJsObject("Person object expected").fields
    Person(
      name = fields("name").convertTo[String],
      address = fields("home").convertTo[Address]
    )
  }

  // serialization code
  override def write(person: Person): JsValue = JsObject(
    "name" -> person.name.toJson,
    "home" -> person.address.toJson
  )
}
```

JSONCirce

Circe / decode jsoncase

```
import io.circe._
```

```
import io.circe.generic.auto._
import io.circe.parser._
import io.circe.syntax._

case class User(id: Long, name: String)

val user = User(1, "John Doe")

// {"id":1,"name":"John Doe"}
val json = user.asJson.noSpaces

// Right(User(1L, "John Doe"))
val res: Either[Error, User] = decode[User](json)
```

play-jsonJSON

play-jsonjson

SBT libraryDependencies += "com.typesafe.play" %% "play-json" % "2.4.8"

```
import play.api.libs.json._
import play.api.libs.functional.syntax._ // if you need DSL
```

DefaultFormat/° JSON°

json

```
// generates an intermediate JSON representation (abstract syntax tree)
val res = Json.parse("""{ "foo": "bar" }""") // JsValue = {"foo":"bar"}

res.as[Map[String, String]] // Map(foo -> bar)
res.validate[Map[String, String]] // JsSuccess(Map(foo -> bar),)
```

json

```
val values = List("a", "b", "c")
Json.stringify(Json.toJson(values)) // ["a", "b", "c"]
```

DSL

```
val json = parse("""{ "foo": [{"foo": "bar"}]}""")
(json \ "foo").get // Simple path: [{"foo":"bar"}]
(json \\ "foo") // Recursive path: List([{"foo":"bar"}], "bar")
(json \ "foo")(0).get // Index lookup (for JsArrays): {"foo":"bar"}
```

JsSuccess / JsError.get array(i)°

```
case class Address(street: String, city: String)
case class Person(name: String, address: Address)

// create the formats and provide them implicitly
implicit val addressFormat = Json.format[Address]
implicit val personFormat = Json.format[Person]
```

```
// serialize a Person
val fred = Person("Fred", Address("Awesome Street 9", "SuperCity"))
val fredJsonString = Json.stringify(Json.toJson(Json.toJson(fred)))

val personRead = Json.parse(fredJsonString).as[Person] //Person(Fred,Address(Awesome Street 9,SuperCity))
```

JsonFormatscalaJson

```
case class Address(street: String, city: String)

// create the formats and provide them implicitly
implicit object AddressFormatCustom extends Format[Address] {
  def reads(json: JsValue): JsResult[Address] = for {
    street <- (json \ "Street").validate[String]
    city <- (json \ "City").validate[String]
  } yield Address(street, city)

  def writes(x: Address): JsValue = Json.obj(
    "Street" -> x.street,
    "City" -> x.city
  )
}

// serialize an address
val address = Address("Awesome Street 9", "SuperCity")
val addressJsonString = Json.stringify(Json.toJson(Json.toJson(address)))
//{"Street":"Awesome Street 9","City":"SuperCity"}

val addressRead = Json.parse(addressJsonString).as[Address]
//Address(Awesome Street 9,SuperCity)
```

jsoncase isAlive in case class vs is_alive in json

```
case class User(username: String, friends: Int, enemies: Int, isAlive: Boolean)

object User {

  import play.api.libs.functional.syntax._
  import play.api.libs.json._

  implicit val userReads: Reads[User] = (
    (JsPath \ "username").read[String] and
    (JsPath \ "friends").read[Int] and
    (JsPath \ "enemies").read[Int] and
    (JsPath \ "is_alive").read[Boolean]
  ) (User.apply _)
}
```

Json

```
case class User(username: String, friends: Int, enemies: Int, isAlive: Option[Boolean])

object User {

  import play.api.libs.functional.syntax._
  import play.api.libs.json._
```



```
implicit val userReads: Reads[User] = (
  (JsPath \ "username").read[String] and
  (JsPath \ "friends").read[Int] and
  (JsPath \ "enemies").read[Int] and
  (JsPath \ "is_alive").readNullable[Boolean]
) (User.apply _)
}
```

json

UnixJson

```
{
  "field": "example field",
  "date": 1459014762000
}
```

```
case class JsonExampleV1(field: String, date: DateTime)
object JsonExampleV1{
  implicit val r: Reads[JsonExampleV1] = (
    (__ \ "field").read[String] and
    (__ \ "date").read[DateTime] (Reads.DefaultJodaDateReads)
  ) (JsonExampleV1.apply _)
}
```

◦ json

```
{
  "id": 91,
  "data": "Some data"
}
```

```
case class MyIdentifier(id: Long)

case class JsonExampleV2(id: MyIdentifier, data: String)
```

Longidenfier

```
object JsonExampleV2 {
  implicit val r: Reads[JsonExampleV2] = (
    (__ \ "id").read[Long].map(MyIdentifier) and
    (__ \ "data").read[String]
  ) (JsonExampleV2.apply _)
}
```

<https://github.com/pedrorijo91/scala-play-json-examples>

JSONjson4s

json4sjson◦

SBT

```
libraryDependencies += "org.json4s" %% "json4s-native" % "3.4.0"
//or
libraryDependencies += "org.json4s" %% "json4s-jackson" % "3.4.0"
```

```
import org.json4s.JsonDSL._
import org.json4s._
import org.json4s.native.JsonMethods._

implicit val formats = DefaultFormats
```

DefaultFormats/°

json

```
// generates an intermediate JSON representation (abstract syntax tree)
val res = parse("""{ "foo": "bar" }""") // JValue = {"foo":"bar"}
res.extract[Map[String, String]]       // Map(foo -> bar)
```

json

```
val values = List("a", "b", "c")
compact(render(values)) // ["a", "b", "c"]
```

DSL

```
json \ "foo" //Simple path: JArray(List(JObject(List((foo,JString(bar))))))
json \ \ "foo" //Recursive path: ~List([{"foo":"bar"}], "bar")
(json \ "foo")(0) //Index lookup (for JsArrays): JObject(List((foo,JString(bar))))
("foo" -> "bar") ~ ("field" -> "value") // {"foo":"bar","field":"value"}
```

```
import org.json4s.native.Serialization.{read, write}

case class Address(street: String, city: String)
val addressString = write(Address("Awesome stree", "Super city"))
// {"street":"Awesome stree","city":"Super city"}

read[Address](addressString) // Address(Awesome stree,Super city)
//or
parse(addressString).extract[Address]
```

°

```
trait Location
case class Street(name: String) extends Location
case class City(name: String, zipcode: String) extends Location
case class Address(street: Street, city: City) extends Location
case class Locations (locations : List[Location])

implicit val formats = Serialization.formats(ShortTypeHints(List(classOf[Street],
classOf[City], classOf[Address])))

val locationsString = write(Locations(Street("Lavelle Street"):: City("Super city","74658")))
```

```
read[Locations](locationsString)
```

```
class AddressSerializer extends CustomSerializer[Address](format => {
  {
    case JObject(JField("Street", JString(s)) :: JField("City", JString(c)) :: Nil) =>
      new Address(s, c)
  },
  {
    case x: Address => ("Street" -> x.street) ~ ("City" -> x.city)
  }
})

implicit val formats = DefaultFormats + new AddressSerializer
val str = write[Address](Address("Awesome Stree", "Super City"))
// {"Street":"Awesome Stree","City":"Super City"}
read[Address](str)
// Address(Awesome Stree,Super City)
```

JSON <https://riptutorial.com/zh-CN/scala/topic/2348/json>

6: Quasiquotes

Examples

quasiquotes

quasiquotesTree ◦

```
object macro {
  def addCreationDate(): java.util.Date = macro impl.addCreationDate
}

object impl {
  def addCreationDate(c: Context)(): c.Expr[java.util.Date] = {
    import c.universe._

    val date = q"new java.util.Date()" // this is the quasiquote
    c.Expr[java.util.Date](date)
  }
}
```

scala◦

Quasiquotes <https://riptutorial.com/zh-CN/scala/topic/4032/quasiquotes>

7: Scala.js

Scala.js Scala JavaScript JVM JavaScript

Examples

Scala.jsconsole.log

```
println("Hello Scala.js") // In ES6: console.log("Hello Scala.js");
```

```
val lastNames = people.map(p => p.lastName)
// Or shorter:
val lastNames = people.map(_.lastName)
```

```
class Person(val firstName: String, val lastName: String) {
  def fullName(): String =
    s"$firstName $lastName"
}
```

```
val personMap = Map(
  10 -> new Person("Roger", "Moore"),
  20 -> new Person("James", "Bond")
)
val names = for {
  (key, person) <- personMap
  if key > 15
} yield s"$key = ${person.firstName}"
```

DOM

```
import org.scalajs.dom
import dom.document

def appendP(target: dom.Node, text: String) = {
  val pNode = document.createElement("p")
  val textNode = document.createTextNode(text)
  pNode.appendChild(textNode)
  target.appendChild(pNode)
}
```

SBT

```
libraryDependencies += "org.scala-js" %% "scalajs-dom" % "0.9.1" // (Triple %%)
```

```
sbt run
```

```
sbt ~run
```

JavaScript

```
sbt fastOptJS
```

Scala.js <https://riptutorial.com/zh-CN/scala/topic/9426/scala-js>

8: Scaladoc

- ◦
- /**
- *
- */

	—
@constructor detail	
	—
@return detail	◦
/	—
@param x detail	x◦
@tparam x detail	x◦
@throws detail	◦
	—
@see detail	◦
@note detail	◦
@example detail	◦
@usecase detail	◦
	—
@author detail	◦
@version detail	◦
@deprecated detail	◦

Examples

Scaladoc

```
/**
```

```
* Explain briefly what method does here
* @param x Explain briefly what should be x and how this affects the method.
* @param y Explain briefly what should be y and how this affects the method.
* @return Explain what is returned from execution.
*/
def method(x: Int, y: String): Option[Double] = {
  // Method content
}
```

Scaladoc <https://riptutorial.com/zh-CN/scala/topic/4518/scaladoc>

9: scalaz

ScalazScala

Scala Functor Monad

Examples

ApplyUsage

```
import scalaz._
import Scalaz._

scala> Apply[Option].apply2(some(1), some(2))((a, b) => a + b)
res0: Option[Int] = Some(3)

scala> val intToString: Int => String = _.toString

scala> Apply[Option].ap(1.some)(some(intToString))
res1: Option[String] = Some(1)

scala> Apply[Option].ap(none)(some(intToString))
res2: Option[String] = None

scala> val double: Int => Int = _ * 2

scala> Apply[List].ap(List(1, 2, 3))(List(double))
res3: List[Int] = List(2, 4, 6)

scala> :kind Apply
scalaz.Apply's kind is X[F[A]]
```

FunctorUsage

```
import scalaz._
import Scalaz._

scala> val len: String => Int = _.length
len: String => Int = $$Lambda$1164/969820333@7e758f40

scala> Functor[Option].map(Some("foo"))(len)
res0: Option[Int] = Some(3)

scala> Functor[Option].map(None)(len)
res1: Option[Int] = None

scala> Functor[List].map(List("qwer", "adsfg"))(len)
res2: List[Int] = List(4, 5)

scala> :kind Functor
scalaz.Functor's kind is X[F[A]]
```

ArrowUsage

```
import scalaz._
import Scalaz._
scala> val plus1 = (_: Int) + 1
plus1: Int => Int = $$Lambda$1167/1113119649@6a6bfd97

scala> val plus2 = (_: Int) + 2
plus2: Int => Int = $$Lambda$1168/924329548@6bbe050f

scala> val rev = (_: String).reverse
rev: String => String = $$Lambda$1227/1278001332@72685b74

scala> plus1.first apply (1, "abc")
res0: (Int, String) = (2,abc)

scala> plus1.second apply ("abc", 2)
res1: (String, Int) = (abc,3)

scala> rev.second apply (1, "abc")
res2: (Int, String) = (1,cba)

scala> plus1 *** rev apply(7, "abc")
res3: (Int, String) = (8,cba)

scala> plus1 &&& plus2 apply 7
res4: (Int, Int) = (8,9)

scala> plus1.product apply (1, 2)
res5: (Int, Int) = (2,3)

scala> :kind Arrow
scalaz.Arrow's kind is X[F[A1,A2]]
```

scalaz <https://riptutorial.com/zh-CN/scala/topic/9893/scalaz>

10: Scala

Examples

Scala/

+ - * / %		a + b
== != > < >= <=		a > b
&& & !		a && b
& ^ ~ << >> >>>		a & b ~a a >>> b
= += -= *= /= %= <<= >>= &= ^= =		a += b

ScalaJava

```
:list:::(value)value :: list ◦ 1 :: 2 :: 3 :: Nil1 :: (2 :: (3 :: Nil))
```

Scala

```
class Team {  
  def +(member: Person) = ...  
}
```

```
ITTeam + Jack
```

```
ITTeam.+(Jack)
```

unary_unary_ ◦ unary_!

```
class MyBigInt {  
  def unary_! = ...  
}  
  
var a: MyBigInt = new MyBigInt  
var b = !a
```

	() []	
	! ~	
	* / %	
	+	

	-	
>> >>> <<		
	> >= < <=	
== !=		
	&	
xor	^	
&&		
= += -= *= /= %= >>= <<= &= ^= =		
	,	

Scala◦ >>>>

* / %
+ -
:
= !
< >
&
^

+= *=◦ ==<= >= ==!=◦ ◦ ◦

Scala <https://riptutorial.com/zh-CN/scala/topic/6604/scala>

11: VarValDef

val ""

PlusOneInt: Int = 1

```
trait PlusOne {  
  val i: Int  
  
  val incr = i + 1  
}  
  
class IntWrapper(val i: Int) extends PlusOne
```

i: IntWrapper = 1

val lazy val def lazy val

Scala-Js

Examples

VarValDef

VAR

var Java

```
scala> var x = 1  
x: Int = 1  
  
scala> x = 2  
x: Int = 2  
  
scala> x = "foo bar"  
<console>:12: error: type mismatch;  
found   : String("foo bar")  
required: Int  
    x = "foo bar"  
    ^
```

var

VAL

val

```
scala> val y = 1
y: Int = 1

scala> y = 2
<console>:12: error: reassignment to val
      y = 2
      ^
```

val°

```
scala> val arr = new Array[Int](2)
arr: Array[Int] = Array(0, 0)

scala> arr(0) = 1

scala> arr
res1: Array[Int] = Array(1, 0)
```

def° °

```
scala> def z = 1
z: Int

scala> z = 2
<console>:12: error: value z_= is not a member of object $iw
      z = 2
      ^
```

val ydef z° defdef valvar °

```
scala> val a = {println("Hi"); 1}
Hi
a: Int = 1

scala> def b = {println("Hi"); 1}
b: Int

scala> a + 1
res2: Int = 2

scala> b + 1
Hi
res3: Int = 2
```

val / var / def °

```
scala> val x = (x: Int) => s"value=$x"
x: Int => String = <function1>

scala> var y = (x: Int) => s"value=$x"
y: Int => String = <function1>
```

```
scala> def z = (x: Int) => s"value=$x"
z: Int => String

scala> x(1)
res0: String = value=1

scala> y(2)
res1: String = value=2

scala> z(3)
res2: String = value=3
```

val

lazy valval◦ val◦

vallazy◦ **REPL**

```
scala> lazy val foo = {
  |   println("Initializing")
  |   "my foo value"
  | }
foo: String = <lazy>

scala> val bar = {
  |   println("Initializing bar")
  |   "my bar value"
  | }
Initializing bar
bar: String = my bar value

scala> foo
Initializing
res3: String = my foo value

scala> bar
res4: String = my bar value

scala> foo
res5: String = my foo value
```

◦ lazy val foo◦ val println**execute**bar◦ printlnfoo -◦ barprintln -◦



1. val◦

```
lazy val tiresomeValue = {(1 to 1000000).filter(x => x % 113 == 0).sum}
if (scala.util.Random.nextInt > 1000) {
  println(tiresomeValue)
}
```

tiresomeValue◦ lazy val◦

```

2. object comicBook {
    def main(args:Array[String]): Unit = {
        gotham.hero.talk()
        gotham.villain.talk()
    }
}

class Superhero(val name: String) {
    lazy val toLockUp = gotham.villain
    def talk(): Unit = {
        println(s"I won't let you win ${toLockUp.name}!")
    }
}

class Supervillain(val name: String) {
    lazy val toKill = gotham.hero
    def talk(): Unit = {
        println(s"Let me loosen up Gotham a little bit ${toKill.name}!")
    }
}

object gotham {
    val hero: Superhero = new Superhero("Batman")
    val villain: Supervillain = new Supervillain("Joker")
}

```

lazy ◦ java.lang.NullPointerException ◦ lazy ◦

Def

def

```

def printValue(x: Int) {
    println(s"My value is an integer equal to $x")
}

def printValue(x: String) {
    println(s"My value is a string equal to '$x'")
}

printValue(1) // prints "My value is an integer equal to 1"
printValue("1") // prints "My value is a string equal to '1'"

```

◦

def ◦ ◦ printUs()

```

// print out the three arguments in order.
def printUs(one: String, two: String, three: String) =
    println(s"$one, $two, $three")

```

```

printUs("one", "two", "three")
printUs(one="one", two="two", three="three")
printUs("one", two="two", three="three")
printUs(three="three", one="one", two="two")

```


one, two, three ◦

◦

```
printUs("one", two="two", three="three") // prints 'one, two, three'
printUs(two="two", three="three", "one") // fails to compile: 'positional after named
argument'
```

VarValDef <https://riptutorial.com/zh-CN/scala/topic/3155/var-valdef>

12: XML

Examples

XML

PrettyPrinter XML. xml

```
import scala.xml.{PrettyPrinter, XML}
val xml = XML.loadString("<a>Alana<b><c>Beth</c><d>Catie</d></b></a>")
val formatted = new PrettyPrinter(150, 4).format(xml)
print(formatted)
```

1504

```
<a>
  Alana
  <b>
    <c>Beth</c>
    <d>Catie</d>
  </b>
</a>
```

XML.loadFile("nameoffile.xml")xml.

XML <https://riptutorial.com/zh-CN/scala/topic/1453/xml>

13: Gradle

Examples

1. SCALA_PROJECT/build.gradle

```
group 'scala_gradle'
version '1.0-SNAPSHOT'

apply plugin: 'scala'

repositories {
    jcenter()
    mavenCentral()
    maven {
        url "https://repo.typesafe.com/typesafe/maven-releases"
    }
}

dependencies {
    compile group: 'org.scala-lang', name: 'scala-library', version: '2.10.6'
}

task "create-dirs" << {
    sourceSets*.scala.srcDirs*.each { it.mkdirs() }
    sourceSets*.resources.srcDirs*.each { it.mkdirs() }
}
```

2. gradle tasks

3. gradle create-dirsrc/src, src/resources

4. gradle build

Gradle Scala

Scala Gradle.

GradleScala Scala.

Gradle.

GradleGradle API. ScalaJava. Groovy. Scalagradle [github repo](#) .

-
- scalaVersionscalaVersion
 - major ="2.12"
 - minor ="0"
 - withScalaVersionscalasbt %%
 - createDirs

1. gradle

```
build.gradle

apply plugin: 'scala'
apply plugin: 'maven'

repositories {
    mavenLocal()
    mavenCentral()
}

dependencies {
    compile gradleApi()
    compile "org.scala-lang:scala-library:2.12.0"
}
```

- **ScalaGradle Scala**
- **Gradle Maven**
 - `installMavenLocalRepository`
 - `compile gradleApi() gradle-api-<gradle_version>.jar`

2. Scala

```
package com.btesila.gradle.plugins

import org.gradle.api.{Plugin, Project}

class ScalaCustomPlugin extends Plugin[Project] {
    override def apply(project: Project): Unit = {
        project.getPlugins.apply("scala")
    }
}
```

- `ProjectPluginapply`
- **applyProject**
- **Gradle Scala**

3. scalaVersion

ScalaVersion

```
class ScalaVersion {
    var major: String = "2.12"
    var minor: String = "0"
}
```

Gradle。 `gradle` `ProjectExtensionContainer`。 。
`apply`

- `scalaVersion`
- `ScalaVersion`

```
var scalaVersion = new ScalaVersion
if (!project.getExtensions.getExtraProperties.has("scalaVersion"))
    project.getExtensions.getExtraProperties.set("scalaVersion", scalaVersion)
else
```

```
scalaVersion =
project.getExtensions.getExtraProperties.get("scalaVersion").asInstanceOf[ScalaVersion]
```

```
ext {
    scalaVersion.major = "2.12"
    scalaVersion.minor = "0"
}
```

4. scalaVersionscala-langscalaVersion

```
project.getDependencies.add("compile", s"org.scala-lang:scala-
library:${scalaVersion.major}.${scalaVersion.minor}")
```

```
compile "org.scala-lang:scala-library:2.12.0"
```

5. withScalaVersion

```
val withScalaVersion = (lib: String) => {
    val libComp = lib.split(":")
    libComp.update(1, s"${libComp(1)}_${scalaVersion.major}")
    libComp.mkString(":")
}
project.getExtensions.getExtraProperties.set("withScalaVersion", withScalaVersion)
```

6. createDirs

DefaultTask**Gradle**

```
class CreateDirs extends DefaultTask {
    @TaskAction
    def createDirs(): Unit = {
        val sourceSetContainer =
this.getProject.getConvention.getPlugin(classOf[JavaPluginConvention]).getSourceSets

        sourceSetContainer.forEach { sourceSet =>
            sourceSet.getAllSource.getSrcDirs.forEach(file => if (!file.getName.contains("java"))
file.mkdirs())
        }
    }
}
```

SourceSetContainer◦ **Gradle ScalaJava** ◦

applycreateDir

```
project.getTasks.create("createDirs", classOf[CreateDirs])
```

ScalaCustomPlugin

```
class ScalaCustomPlugin extends Plugin[Project] {
    override def apply(project: Project): Unit = {
```

```

project.getPlugins.apply("scala")

var scalaVersion = new ScalaVersion
if (!project.getExtensions.getExtraProperties.has("scalaVersion"))
    project.getExtensions.getExtraProperties.set("scalaVersion", scalaVersion)
else
    scalaVersion =
project.getExtensions.getExtraProperties.get("scalaVersion").asInstanceOf[ScalaVersion]

project.getDependencies.add("compile", s"org.scala-lang:scala-
library:${scalaVersion.major}.${scalaVersion.minor}")

val withScalaVersion = (lib: String) => {
    val libComp = lib.split(":")
    libComp.update(1, s"${libComp(1)}_${scalaVersion.major}")
    libComp.mkString(":")
}
project.getExtensions.getExtraProperties.set("withScalaVersion", withScalaVersion)

project.getTasks.create("createDirs", classOf[CreateDirs])
}
}

```

Maven

```

gradle install
~/m2/repository

```

Gradle

Gradleid apply◦ **Gradle**id scala◦

```

apply plugin: 'scala'

```

```

apply plugin: "com.btesila.scala.plugin"

```

com.btesila.scala.plugin id◦

ID

SRC /// META-INF / gradle-/ com.btesil.scala.plugin.properties

```

implementation-class=com.btesila.gradle.plugins.ScalaCustomPlugin

```

gradle install ◦

1. Gradle

```

buildscript {
    repositories {
        mavenLocal()
        mavenCentral()
    }
}

```

```

    }

    dependencies {
        //modify this path to match the installed plugin project in your local repository
        classpath 'com.btesila:working-with-gradle:1.0-SNAPSHOT'
    }
}

repositories {
    mavenLocal()
    mavenCentral()
}

apply plugin: "com.btesila.scala.plugin"

```

2. run `gradle createDirs -`

3. scala

```

ext {
    scalaVersion.major = "2.11"
    scalaVersion.minor = "8"
}

println(project.ext.scalaVersion.major)
println(project.ext.scalaVersion.minor)

```

4. Scala

```

dependencies {
    compile withScalaVersion("com.typesafe.scala-logging:scala-logging:3.5.0")
}

```

。

Gradle <https://riptutorial.com/zh-CN/scala/topic/3304/gradle>

14: ScalaCheck

ScalaCheckScalaScalaJava◦ ScalaCheckHaskellQuickCheck◦

ScalaScalaChecksbtScala◦ ScalaTestspecs2◦

Examples

Scalacheckscalatest

scalatestscalacheck◦

- “show pass example” -
- “” - &&
- “” - "argument" |: Props.all&&
- “” - "command" |: Props.all&&

```
import org.scalatest.prop.Checkers
import org.scalatest.{Matchers, WordSpecLike}

import org.scalacheck.Gen._
import org.scalacheck.Prop._
import org.scalacheck.Prop

object Splitter {
  def splitLineByColon(message: String): (String, String) = {
    val (command, argument) = message.indexOf(":") match {
      case -1 =>
        (message, "")
      case x: Int =>
        (message.substring(0, x), message.substring(x + 1))
    }
    (command.trim, argument.trim)
  }

  def splitLineByColonWithBugOnCommand(message: String): (String, String) = {
    val (command, argument) = splitLineByColon(message)
    (command.trim + 2, argument.trim)
  }

  def splitLineByColonWithBugOnArgument(message: String): (String, String) = {
    val (command, argument) = splitLineByColon(message)
    (command.trim, argument.trim + 2)
  }
}

class ScalaCheckSpec extends WordSpecLike with Matchers with Checkers {

  private val COMMAND_LENGTH = 4

  "ScalaCheckSpec " should {
```

```
    "show pass example" in {
```



```

check {
  Prop.forAll(listOfN(COMMAND_LENGTH, alphaChar), alphaStr) {
    (chars, expArgument) =>
      val expCommand = new String(chars.toArray)
      val line = s"$expCommand:$expArgument"
      val (c, p) = Splitter.splitLineByColon(line)
      Prop.all("command" |: c =? expCommand, "argument" |: expArgument =? p)
  }
}

```

```

"show simple example without custom error message " in {
  check {
    Prop.forAll(listOfN(COMMAND_LENGTH, alphaChar), alphaStr) {
      (chars, expArgument) =>
        val expCommand = new String(chars.toArray)
        val line = s"$expCommand:$expArgument"
        val (c, p) = Splitter.splitLineByColonWithBugOnArgument(line)
        c === expCommand && expArgument === p
    }
  }
}

```

```

"show example with error messages on argument" in {
  check {
    Prop.forAll(listOfN(COMMAND_LENGTH, alphaChar), alphaStr) {
      (chars, expArgument) =>
        val expCommand = new String(chars.toArray)
        val line = s"$expCommand:$expArgument"
        val (c, p) = Splitter.splitLineByColonWithBugOnArgument(line)
        Prop.all("command" |: c =? expCommand, "argument" |: expArgument =? p)
    }
  }
}

```

```

"show example with error messages on command" in {
  check {
    Prop.forAll(listOfN(COMMAND_LENGTH, alphaChar), alphaStr) {
      (chars, expArgument) =>
        val expCommand = new String(chars.toArray)
        val line = s"$expCommand:$expArgument"
        val (c, p) = Splitter.splitLineByColonWithBugOnCommand(line)
        Prop.all("command" |: c =? expCommand, "argument" |: expArgument =? p)
    }
  }
}

```

```

[info] - should show example // passed
[info] - should show simple example without custom error message *** FAILED ***
[info]   (ScalaCheckSpec.scala:73)
[info]   Falsified after 0 successful property evaluations.
[info]   Location: (ScalaCheckSpec.scala:73)
[info]   Occurred when passed generated values (
[info]     arg0 = List(), // 3 shrinks

```

```

[info]         arg1 = ""
[info]     )
[info] - should show example with error messages on argument *** FAILED ***
[info]   (ScalaCheckSpec.scala:86)
[info]   Falsified after 0 successful property evaluations.
[info]   Location: (ScalaCheckSpec.scala:86)
[info]   Occurred when passed generated values (
[info]     arg0 = List(), // 3 shrinks
[info]     arg1 = ""
[info]   )
[info]   Labels of failing property:
[info]     Expected "" but got "2"
[info]     argument
[info] - should show example with error messages on command *** FAILED ***
[info]   (ScalaCheckSpec.scala:99)
[info]   Falsified after 0 successful property evaluations.
[info]   Location: (ScalaCheckSpec.scala:99)
[info]   Occurred when passed generated values (
[info]     arg0 = List(), // 3 shrinks
[info]     arg1 = ""
[info]   )
[info]   Labels of failing property:
[info]     Expected "2" but got ""
[info]     command

```

ScalaCheck <https://riptutorial.com/zh-CN/scala/topic/9430/scalacheck>

15: ScalaTest

Examples

Hello World Spec Test

src/test/scalaHelloWorldSpec.scala

```
import org.scalatest.{FlatSpec, Matchers}

class HelloWorldSpec extends FlatSpec with Matchers {

  "Hello World" should "not be an empty String" in {
    val helloWorld = "Hello World"
    helloWorld should not be ("")
  }
}
```

- [FlatSpecMatchers](#) [ScalaTest](#)
- FlatSpec [BDD](#)

Spec Test Cheatsheet

.

```
val helloWorld = "Hello World"
val helloWorldCount = 1
val helloWorldList = List("Hello World", "Bonjour Le Monde")
def sayHello = throw new IllegalStateException("Hello World Exception")
```

val

```
helloWorld shouldBe a [String]
```

String

```
helloWorld shouldEqual "Hello World"
helloWorld should === ("Hello World")
helloWorldCount shouldEqual 1
helloWorldCount shouldBe 1
helloWorldList shouldEqual List("Hello World", "Bonjour Le Monde")
helloWorldList === List("Hello World", "Bonjour Le Monde")
```

```
helloWorld should not equal "Hello"
helloWorld !== "Hello"
helloWorldCount should not be 5
helloWorldList should not equal List("Hello World")
helloWorldList !== List("Hello World")
helloWorldList should not be empty
```

/

```
helloWorld should have length 11  
helloWorldList should have size 2
```

```
val exception = the [java.lang.IllegalStateException] thrownBy {  
    sayHello  
}  
exception.getClass shouldEqual classOf[java.lang.IllegalStateException]  
exception.getMessage should include ("Hello World")
```

ScalaTestSBT

SBT build.sbt

```
libraryDependencies += "org.scalactic" %% "scalactic" % "3.0.0"  
libraryDependencies += "org.scalatest" %% "scalatest" % "3.0.0" % "test"
```

[ScalaTest](#)◦

[ScalaTest](#) <https://riptutorial.com/zh-CN/scala/topic/5506/scalatest>

16:

- `finalimmutable`

[http //docs.scala-lang.org/style/naming-conventions.html](http://docs.scala-lang.org/style/naming-conventions.html)

```
val (a,b) = (1,2)
// a: Int = 1
// b: Int = 2
```

```
val (A,B) = (1,2)
// error: not found: value A
// error: not found: value B
```

Examples

valvar

valvar

```
scala> val a = 123
a: Int = 123

scala> a = 456
<console>:8: error: reassignment to val
      a = 456

scala> var b = 123
b: Int = 123

scala> b = 321
b: Int = 321
```

- `valJavafinal`
- `varJava`

```
val mut = scala.collection.mutable.Map.empty[String, Int]
mut += ("123" -> 123)
mut += ("456" -> 456)
mut += ("789" -> 789)

val imm = scala.collection.immutable.Map.empty[String, Int]
imm + ("123" -> 123)
imm + ("456" -> 456)
imm + ("789" -> 789)

scala> mut
Map(123 -> 123, 456 -> 456, 789 -> 789)

scala> imm
Map()
```

```
scala> imm + ("123" -> 123) + ("456" -> 456) + ("789" -> 789)
Map(123 -> 123, 456 -> 456, 789 -> 789)
```

Scala “”。

Scala

2MapmambMap

```
def merge2Maps(ma: Map[String, Int], mb: Map[String, Int]): Map[String, Int]
```

for ((k, v) <- map)。

```
def merge2Maps(ma: ..., mb: ...): Map[String, Int] = {
  for ((k, v) <- mb) {
    ???
  }
}
```

for 。

```
// this:
for ((k, v) <- map) { ??? }

// is equivalent to:
map.foreach { case (k, v) => ??? }
```

“”

foreach 。

result

mambscala.collection.immutable.Map maresult Map

```
val result = mutable.Map() ++ ma
```

mbmakekeymb。

```
mb.foreach { case (k, v) => result += (k -> v) }
```

“”

```
def merge2Maps(ma: Map[String, Int], mb: Map[String, Int]): Map[String, Int] = {
  val result = scala.collection.mutable.Map() ++ ma
  mb.foreach { case (k, v) => result += (k -> v) }
  result.toMap // to get back an immutable Map
}
```

```
scala> merge2Maps(Map("a" -> 11, "b" -> 12), Map("b" -> 22, "c" -> 23))
Map(a -> 11, b -> 22, c -> 23)
```

foreach .foldLeft

```
def merge2Maps(ma: Map[String, Int], mb: Map[String, Int]): Map[String, Int] = {
  mb.foldLeft(ma) { case (result, (k, v)) => result + (k -> v) }
  // or more concisely mb.foldLeft(ma) { _ + _ }
}
```

""ma.foldLeftzero °

MapMap°

.foldLeft .foldLeft° °

<https://riptutorial.com/zh-CN/scala/topic/6298/>

17:

Examples

◦

```
//create a component that will be injected
trait TimeUtil {
  lazy val timeUtil = new TimeUtilImpl()

  class TimeUtilImpl{
    def now() = new DateTime()
  }
}

//main controller is depended on time util
trait MainController {
  _ : TimeUtil => //inject time util into main controller

  lazy val mainController = new MainControllerImpl()

  class MainControllerImpl {
    def printCurrentTime() = println(timeUtil.now()) //timeUtil is injected from TimeUtil
  }
}

object MainApp extends App {
  object app extends MainController
    with TimeUtil //wire all components

  app.mainController.printCurrentTime()
}
```

TimeUtilMainController◦

_: TimeUtil => TimeUtilMainController ◦ MainControllerTimeUtil ◦

TimeUtilImpl ◦ ◦

◦ GuiceBinding

<https://riptutorial.com/zh-CN/scala/topic/5909/>

18:

23

◦ Tuple1Tuple22 ◦ ◦

0

Tuple0Unit ◦

Examples

◦ ◦ 2“”◦

```
scala> val x = (1, "hello")
x: (Int, String) = (1,hello)
scala> val y = 2 -> "world"
y: (Int, String) = (2,world)
scala> val z = 3 → "foo"      //example of using U+2192 RIGHTWARD ARROW
z: (Int, String) = (3,foo)
```

x2◦ ._1 ._22 ◦ x._1x◦ x._2◦ ◦

2Maps(key -> value)

```
scala> val m = Map[Int, String](2 -> "world")
m: scala.collection.immutable.Map[Int,String] = Map(2 -> world)

scala> m + x
res0: scala.collection.immutable.Map[Int,String] = Map(2 -> world, 1 -> hello)

scala> (m + x).toList
res1: List[(Int, String)] = List((2,world), (1,hello))
```

1a◦

◦

```
scala> val l = List(1 -> 2, 2 -> 3, 3 -> 4)
l: List[(Int, Int)] = List((1,2), (2,3), (3,4))
```

```
scala> l.map((e1: Int, e2: Int) => e1 + e2)
```

```
<console>:9: error: type mismatch;
 found   : (Int, Int) => Int
 required: ((Int, Int)) => ?
       l.map((e1: Int, e2: Int) => e1 + e2)
```

Scala◦ ◦ _1_2

```
scala> l.map(e => e._1 + e._2)
res1: List[Int] = List(3, 5, 7)
```

case

```
scala> l.map{ case (e1: Int, e2: Int) => e1 + e2}
res2: List[Int] = List(3, 5, 7)
```

。

<https://riptutorial.com/zh-CN/scala/topic/4971/>

19:

Scala

Scala

def

- Function1
-
-
-

Examples

◦

◦

```
(x: Int, y: Int) => x + y
```

val

```
val sum = (x: Int, y: Int) => x + y
```

◦ map

```
// Returns Seq("FOO", "BAR", "QUX")
Seq("Foo", "Bar", "Qux").map((x: String) => x.toUpperCase)
```

```
Seq("Foo", "Bar", "Qux").map((x) => x.toUpperCase)
```

```
Seq("Foo", "Bar", "Qux").map(x => x.toUpperCase)
```

◦

```
Seq("Foo", "Bar", "Qux").map(_.toUpperCase)
```

◦ ◦

```
// Returns "FooBarQux" in both cases
Seq("Foo", "Bar", "Qux").reduce((s1, s2) => s1 + s2)
Seq("Foo", "Bar", "Qux").reduce(_ + _)
```

—°

```
val sayHello = () => println("hello")
```

◦ $f(x)g(x)h(x) = f(g(x))$ ◦

Function1 ◦ **Scala** Function1 andThen compose ◦ compose

```
val f: B => C = ...
val g: A => B = ...

val h: A => C = f compose g
```

andThen h(x) = g(f(x)) **'DSL'**

```
val f: A => B = ...
val g: B => C = ...

val h: A => C = f andThen g
```

fg ◦ h ◦

```
def andThen(g: B => C): A => C = new (A => C) {
  def apply(x: A) = g(self(x))
}
```

fghfg ◦

PartialFunctions

```
trait PartialFunction[-A, +B] extends (A => B)
```

PartialFunctionFunction1 ◦ ◦ Function1true isDefinedAt◦

```
{ case i: Int => i + 1 } // or equivalently { case i: Int => i + 1 }
```

PartialFunctions ◦

<https://riptutorial.com/zh-CN/scala/topic/477/>

20:

Scala^o [`scala.Dynamic`] [scaladoc]^o ^o [Dynamic scaladoc]<http://www.scala-lang.org/api/2.12.x/scala/Dynamic.html>

- `class FooDynamic`
- `foo.field`
- `foo.field = value`
- `foo.method`
- `foo.methodnamedArg = xy`

Dynamicscala.language.dynamicsscala.language.dynamics -language:dynamicsdynamics^o Dynamic^o

Examples

```
class Foo extends Dynamic {
  // Expressions are only rewritten to use Dynamic if they are not already valid
  // Therefore foo.realField will not use select/updateDynamic
  var realField: Int = 5
  // Called for expressions of the type foo.field
  def selectDynamic(fieldName: String) = ???
  def updateDynamic(fieldName: String)(value: Int) = ???
}
```

```
val foo: Foo = ???
foo.realField // Does NOT use Dynamic; accesses the actual field
foo.realField = 10 // Actual field access here too
foo.unrealField // Becomes foo.selectDynamic(unrealField)
foo.field = 10 // Becomes foo.updateDynamic("field")(10)
foo.field = "10" // Does not compile; "10" is not an Int.
foo.x() // Does not compile; Foo does not define applyDynamic, which is used for methods.
foo.x.apply() // DOES compile, as Nothing is a subtype of () => Any
// Remember, the compiler is still doing static type checks, it just has one more way to
// "recover" and rewrite otherwise invalid code now.
```

```
class Villain(val minions: Map[String, Minion]) extends Dynamic {
  def applyDynamic(name: String)(jobs: Task*) = jobs.foreach(minions(name).do)
  def applyDynamicNamed(name: String)(jobs: (String, Task)*) = jobs.foreach {
    // If a parameter does not have a name, and is simply given, the name passed as ""
    case ("", task) => minions(name).do(task)
    case (subsys, task) => minions(name).subsystems(subsys).do(task)
  }
}
```

```
val gru: Villain = ???
gru.blu() // Becomes gru.applyDynamic("blu")()
// Becomes gru.applyDynamicNamed("stu")(("fooe", ???), ("boomer", ???), ("", ???),
//      ("computer breaker", ???), ("fooe", ???))
// Note how the `???` without a name is given the name ""
// Note how both occurrences of `fooe` are passed to the method
gru.stu(fooe = ???, boomer = ???, ???, `computer breaker` = ???, fooe = ???)
```

```
gru.ERR("a") // Somehow, scalac thinks "a" is not a Task, though it clearly is (it isn't)
```

```
val dyn: Dynamic = ???  
dyn.x(y) = z
```

```
dyn.selectDynamic("x").update(y, z)
```

```
dyn.x(y)
```

```
dyn.applyDynamic("x")(y)
```

◦

<https://riptutorial.com/zh-CN/scala/topic/8296/>

21:

Scala ◦ connectioncom.sqlorg.http ◦ com.sql.connectionorg.http.connection◦

Examples

```
package com {  
  package utility {  
    package serialization {  
      class Serializer  
      ...  
    }  
  }  
}
```

package ◦ package ◦ packagemath1.scalamath2.scala◦

math1.scala

```
package org {  
  package math {  
    package statistics {  
      class Interval  
    }  
  }  
}
```

math2.scala

```
package org {  
  package math {  
    package probability {  
      class Density  
    }  
  }  
}
```

study.scala

```
import org.math.probability.Density  
import org.math.statistics.Interval  
  
object Study {  
  
  def main(args: Array[String]): Unit = {  
    var a = new Interval()  
    var b = new Density()  
  }  
}
```

ScalaJava◦

o -

```
io.super.math
```

<https://riptutorial.com/zh-CN/scala/topic/8231/>

22: SAM

Java 8。

Examples

Lambda

Scala 2.12+~~-Xexperimental~~ -Xfuture2.11.X

lambdaSAM

2.11.8

```
trait Runnable {  
  def run(): Unit  
}  
  
val t: Runnable = () => println("foo")
```

2.11.8

```
trait Runnable {  
  def run(): Unit  
  def concrete: Int = 42  
}  
  
val t: Runnable = () => println("foo")
```

SAM <https://riptutorial.com/zh-CN/scala/topic/3664/-sam->

23:

Examples

Monad

`monadF[_] 2 flatMap unit ◦`

`List[T] Set[T]Option[T] ◦`

`Monad M M[T]flatMapunit`

```
trait M[T] {  
  def flatMap[U](f: T => M[U]): M[U]  
}  
  
def unit[T](x: T): M[T]
```

1. `(m flatMap f) flatMap g = m flatMap (x => f(x) flatMap g)`
◦ `mf gfg m◦`
2. `unit(x) flatMap f == f(x)`
◦ `fxmonadfx◦`
3. `m flatMap unit == m`
◦ `"monadmonad◦`

```
val m = List(1, 2, 3)  
def unit(x: Int): List[Int] = List(x)  
def f(x: Int): List[Int] = List(x * x)  
def g(x: Int): List[Int] = List(x * x * x)  
val x = 1
```

1.

```
(m flatMap f).flatMap(g) == m.flatMap(x => f(x) flatMap g) //Boolean = true  
//Left side:  
List(1, 4, 9).flatMap(g) // List(1, 64, 729)  
//Right side:  
m.flatMap(x => (x * x) * (x * x) * (x * x)) //List(1, 64, 729)
```

2.

```
unit(x).flatMap(x => f(x)) == f(x)  
List(1).flatMap(x => x * x) == 1 * 1
```

3.

```
//m flatMap unit == m  
m.flatMap(unit) == m
```

```
List(1, 2, 3).flatMap(x => List(x)) == List(1,2,3) //Boolean = true
```

Monads

monad List[T] Option[T] **monad-like** Either[T] Future[T] ◦ forflatMap

```
val a = List(1, 2, 3)
val b = List(3, 4, 5)
for {
  i <- a
  j <- b
} yield(i * j)
```

```
a flatMap {
  i => b map {
    j => i * j
  }
}
```

monad monadicfor-comprehension◦

<https://riptutorial.com/zh-CN/scala/topic/4112/>

24:

Examples

```
import scala.reflect.runtime.universe._  
val mirror = runtimeMirror(getClass.getClassLoader)  
val module = mirror.staticModule("org.data.TempClass")
```

<https://riptutorial.com/zh-CN/scala/topic/5824/>

25:

- `objectToSynchronizeOn.synchronized { /* code to run */ }`
- `synchronized { /* code to run, can be suspended with wait */ }`

Examples

`synchronized` ◦ [JavaJVM](#) ◦

```
anInstance.synchronized {  
  // code to run when the intrinsic lock on `anInstance` is acquired  
  // other thread cannot enter concurrently unless `wait` is called on `anInstance` to suspend  
  // other threads can continue of the execution of this thread if they `notify` or  
  `notifyAll` `anInstance`'s lock  
}
```

`object S` ◦

```
/* within a class, def, trait or object, but not a constructor */  
synchronized {  
  /* code to run when an intrinsic lock on `this` is acquired */  
  /* no other thread can get the this lock unless execution is suspended with  
  * `wait` on `this`  
  */  
}
```

<https://riptutorial.com/zh-CN/scala/topic/3371/>

26:

- `aFunction10_ // '_curry'.`
- `nArityFunction.curried // n-arity curried`
- `anotherFunctionx_Stringz // . .`

Examples

curried

```
def multiply(factor: Int)(numberToBeMultiplied: Int): Int = factor * numberToBeMultiplied

val multiplyBy3 = multiply(3)_ // resulting function signature Int => Int
val multiplyBy10 = multiply(10)_ // resulting function signature Int => Int

val sixFromCurriedCall = multiplyBy3(2) //6
val sixFromFullCall = multiply(3)(2) //6

val fortyFromCurriedCall = multiplyBy10(4) //40
val fortyFromFullCall = multiply(10)(4) //40
```

```
def numberOrCharacterSwitch(toggleNumber: Boolean)(number: Int)(character: Char): String =
  if (toggleNumber) number.toString else character.toString

// need to explicitly specify the type of the parameter to be curried
// resulting function signature Boolean => String
val switchBetween3AndE = numberOrCharacterSwitch(_: Boolean)(3)('E')

switchBetween3AndE(true) // "3"
switchBetween3AndE(false) // "E"
```

```
def minus(left: Int, right: Int) = left - right

val numberMinus5 = minus(_: Int, 5)
val fiveMinusNumber = minus(5, _: Int)

numberMinus5(7) // 2
fiveMinusNumber(7) // -2
```

2

```
def add: (Int, Int) => Int = (x, y) => x + y
val three = add(1, 2)
```

Currying `add Int Int Int`

```
val addCurried: (Int) => (Int => Int) = add2.curried
//           ^~~ take *one* Int
//           ^~~~ return a *function* from Int to Int
```

```
val add1: Int => Int = addCurried(1)
val three: Int = add1(2)
val allInOneGo: Int = addCurried(1)(2)
```

◦

```
def add3: (Int, Int, Int) => Int = (a,b,c) => a + b + c + d
def add3Curr: Int => (Int => (Int => Int)) = add3.curried

val x = add3Curr(1)(2)(42)
```

◦

scalaarity 2

```
val f: (A, B) => C // a function that takes two arguments of type `A` and `B` respectively
                  // and returns a value of type `C`
```

```
val curriedF: A => B => C // a function that take an argument of type `A`
                        // and returns *a function*
                        // that takes an argument of type `B` and returns a `C`
```

arity-2curry

```
def curry[A, B, C](f: (A, B) => C): A => B => C = {
  (a: A) => (b: B) => f(a, b)
}
```

```
val f: (String, Int) => Double = {(_, _) => 1.0}
val curriedF: String => Int => Double = curry(f)
f("a", 1)           // => 1.0
curriedF("a")(1)    // => 1.0
```

Scala

1. curried◦ curriedF

```
def curriedFasAMethod(str: String)(int: Int): Double = 1.0
val curriedF = curriedFasAMethod _
```

2. A => B => C(A, B) => C Function.uncurried

```
val f: (String, Int) => Double = Function.uncurried(curriedF)
f("a", 1) // => 1.0
```

Currying

Currying ◦

1. ◦ 1
- 2.

◦ 2

1

```
val totalYearlyIncome: (Int, Int) => Int = (income, bonus) => income + bonus
```

2-arity curried

```
val totalYearlyIncomeCurried: Int => Int => Int = totalYearlyIncome.curried
```

/

```
Int => (Int => Int)
```

```
val partialTotalYearlyIncome: Int => Int = totalYearlyIncomeCurried(10000)
```

```
partialTotalYearlyIncome(100)
```

2

```
val carManufacturing: (String, String) => String = (wheels, body) => wheels + body
```

```
class CarWheelsFactory {  
  def applyCarWheels(carManufacturing: (String, String) => String): String => String =  
    carManufacturing.curried("applied wheels..  
}  
  
class CarBodyFactory {  
  def applyCarBody(partialCarWithWheels: String => String): String =  
    partialCarWithWheels("applied car body..  
}
```

CarWheelsFactory◦

```
val carWheelsFactory = new CarWheelsFactory()  
val carBodyFactory   = new CarBodyFactory()  
  
val carManufacturing: (String, String) => String = (wheels, body) => wheels + body  
  
val partialCarWheelsApplied: String => String =  
  carWheelsFactory.applyCarWheels(carManufacturing)  
val carCompleted = carBodyFactory.applyCarBody(partialCarWheelsApplied)
```

Currying◦

◦ ◦

```
case class CreditCard(creditInfo: CreditCardInfo, issuer: Person, account: Account)
```



```
object CreditCard {  
  def getPremium(totalCards: Int, creditCard: CreditCard): Double = { ... }  
}
```

◦

```
val creditCards: List[CreditCard] = getCreditCards()  
val allPremiums = creditCards.map(CreditCard.getPremium).sum //type mismatch; found : (Int,  
CreditCard) ⇒ Double required: CreditCard ⇒ ?
```

CreditCard.getPremium◦ ◦ getPremium◦

```
object CreditCard {  
  def getPremium(totalCards: Int)(creditCard: CreditCard): Double = { ... }  
}  
  
val creditCards: List[CreditCard] = getCreditCards()  
  
val getPremiumWithTotal = CreditCard.getPremium(creditCards.length)_  
  
val allPremiums = creditCards.map(getPremiumWithTotal).sum
```

<https://riptutorial.com/zh-CN/scala/topic/1636/>

27:

- class MetervalAnyVal
- type Meter = Double

◦

Examples

```
type Meter = Double
```

Double

```
type Second = Double
var length: Meter = 3
val duration: Second = 1
length = duration
length = 0d
```

/◦

```
case class Meter(meters: Double) extends AnyVal
case class Gram(grams: Double) extends AnyVal
```

```
var length = Meter(3)
var weight = Gram(4)
//length = weight //type mismatch; found : Gram required: Meter
```

AnyVal JVMDouble ◦

Velocity aka MeterPerSecond

- [Squants](#)
-
- [ScalaQuantity](#)

<https://riptutorial.com/zh-CN/scala/topic/5966/-->

28:

Examples

ScalaJava if ◦

```
if(x < 1984) {  
    println("Good times")  
} else if(x == 1984) {  
    println("The Orwellian Future begins")  
} else {  
    println("Poor guy...")  
}
```

ifevaluation

```
val result = if(x > 0) "Greater than 0" else "Less than or equals 0"  
\ result: String = Greater than 0
```

if result◦

if ◦ String ◦ ififelseAny

```
val result = if(x > 0) "Greater than 0"  
// result: Any = Greater than 0
```

printlnUnit

```
val result = if(x > 0) println("Greater than 0")  
// result: Unit = ()
```

if ScalaJava◦ Scala◦

if◦

<https://riptutorial.com/zh-CN/scala/topic/4171/>

29:

Scala 2.10.0。

Examples

Hello String Interpolation

s。

```
val name = "Brian"
println(s"Hello $name")
```

“Hello Brian”。

f

```
val num = 42d
```

f_{num}

```
println(f"$num%2.2f")
42.00
```

e。 num

```
println(f"$num%e")
4.200000e+01
```

num

```
println(f"$num%a")
0x1.5p5
```

<https://docs.oracle.com/javase/6/docs/api/java/util/Formatter.html#detail>

```
def f(x: String) = x + x
val a = "A"

s"${a}"      // "A"
s"${f(a)}"   // "AA"
```

scala \$ f。 fString

```
s"$f(a)" // compile-time error (missing argument list for method f)
```

◦

```
my"foo${bar}baz"
```

```
new scala.StringContext("foo", "baz").my(bar)
```

scala.StringContextmy◦ s

```
implicit class MyInterpolator(sc: StringContext) {
  def my(subs: Any*): String = {
    val pit = sc.parts.iterator
    val sit = subs.iterator
    // Note parts.length == subs.length + 1
    val sb = new java.lang.StringBuilder(pit.next())
    while(sit.hasNext) {
      sb.append(sit.next().toString)
      sb.append(pit.next())
    }
    sb.toString
  }
}
```

```
my"foo${bar}baz"
```

```
new MyInterpolation(new StringContext("foo", "baz")).my(bar)
```

◦

```
case class Let(name: Char, value: Int)

implicit class LetInterpolator(sc: StringContext) {
  def let(value: Int): Let = Let(sc.parts(0).charAt(0), value)
}

let"a=${4}" // Let(a, 4)
let"b=${"foo"}" // error: type mismatch
let"c=" // error: not enough arguments for method let: (value: Int)Let
```

Scala Scala quasiquotes API◦

n"p0\${i0}p1"new StringContext("p0", "p1").n(i0) StringContext◦ nunapplyunapplySeq◦

StringContext◦ unapplySeq[scala.util.matching.Regex](#)

```
implicit class PathExtractor(sc: StringContext) {
  object path {
    def unapplySeq(str: String): Option[Seq[String]] =
      sc.parts.map(Regex.quote).mkString("^", "([^/]+)", "$").r.unapplySeq(str)
  }
}

"/documentation/scala/1629/string-interpolation" match {
  case path"/documentation/${topic}/${id}/${_}" => println(s"$topic, $id")
}
```

```
case _ => ???  
}
```

pathapply°

°

```
println(raw"Hello World In English And French\nEnglish:\tHello World\nFrench:\t\tBonjour Le  
Monde")
```

```
Hello World In English And French\nEnglish:\tHello World\nFrench:\t\tBonjour Le Monde
```

\n\t°

```
println("Hello World In English And French\nEnglish:\tHello World\nFrench:\t\tBonjour Le  
Monde")
```

```
Hello World In English And French  
English:      Hello World  
French:       Bonjour Le Monde
```

<https://riptutorial.com/zh-CN/scala/topic/1629/>

30:

◦ Scala ◦ Scala ◦ [Macro Paradise] [] ◦ [Macro Paradise]<http://docs.scala-lang.org/overviews/macros/paradise.html>

- `def x=x_impl // xx_impl`
- `def macroTransform(annottees: Any*): Any = macro impl //`

`scala.language.macros = language:macros ;`

Examples

◦

```
import scala.annotation.{compileTimeOnly, StaticAnnotation}
import scala.reflect.macros.whitebox.Context

@compileTimeOnly("enable macro paradise to expand macro annotations")
class noop extends StaticAnnotation {
  def macroTransform(annottees: Any*): Any = macro linkMacro.impl
}

object linkMacro {
  def impl(c: Context)(annottees: c.Expr[Any]*): c.Expr[Any] = {
    import c.universe._

    c.Expr[Any] (q"{..$annottees}")
  }
}
```

`@compileTimeOnly`[paradise](#) ◦ [SBT](#) ◦

```
@noop
case class Foo(a: String, b: Int)

@noop
object Bar {
  def f(): String = "hello"
}

@noop
def g(): Int = 10
```

AST ◦ ASTAST ◦

```
import reflect.macros.blackbox.Context

object Macros {
  // This macro simply sees if the argument is the result of an addition expression.
  // E.g. isAddition(1+1) and isAddition("a"+1).
  // but !isAddition(1+1-1), as the addition is underneath a subtraction, and also
```

```

// !isAddition(x.+), and !isAddition(x.+(a,b)) as there must be exactly one argument.
def isAddition(x: Any): Boolean = macro isAddition_impl

// The signature of the macro implementation is the same as the macro definition,
// but with a new Context parameter, and everything else is wrapped in an Expr.
def isAddition_impl(c: Context)(expr: c.Expr[Any]): c.Expr[Boolean] = {
  import c.universe._ // The universe contains all the useful methods and types
  val plusName = TermName("+").encodedName // Take the name + and encode it as $plus
  expr.tree match { // Turn expr into an AST representing the code in isAddition(...)
    case Apply(Select(_, `plusName`), List(_)) => reify(true)
    // Pattern match the AST to see whether we have an addition
    // Above we match this AST
    //           Apply (function application)
    //           /      \
    //       Select  List(_) (exactly one argument)
    // (selection ^ of entity, basically the . in x.y)
    //       /      \
    //   -      \
    //       `plusName` (method named +)
    case _ => reify(false)
    // reify is a macro you use when writing macros
    // It takes the code given as its argument and creates an Expr out of it
  }
}

```

Tree[◦] reifyExpr q **quasiquote** Tree[◦] q expr.tree Tree[◦]

```

// No Exprs, just Trees
def isAddition_impl(c: Context)(tree: c.Tree): c.Tree = {
  import c.universe._
  tree match {
    // q is a macro too, so it must be used with string literals.
    // It can destructure and create Trees.
    // Note how there was no need to encode + this time, as q is smart enough to do it itself.
    case q"${_} + ${_}" => q"true"
    case _ => q"false"
  }
}

```

Context[◦]

◦ ◦

```

import reflect.macros.blackbox.Context

def debtMark(message: String): Unit = macro debtMark_impl
def debtMarkImpl(c: Context)(message: c.Tree): c.Tree = {
  message match {
    case Literal(Constant(msg: String)) => c.info(c.enclosingPosition, msg, false)
    // false above means "do not force this message to be shown unless -verbose"
    case _ => c.abort(c.enclosingPosition, "Message must be a
string literal.")
    // Abort causes the compilation to completely fail. It's not even a compile error, where
    // multiple can stack up; this just kills everything.
  }
  q"()" // At runtime this method does nothing, so we return ()
}

```


??? !!!?!? ◦ ?!?!!! ◦

```
import reflect.macros.blackbox.Context

def ?!? : Nothing = macro impl_?!?
def !!! : Nothing = macro impl_!!!

def impl_?!?(c: Context): c.Tree = {
  import c.universe._
  c.warning(c.enclosingPosition, "Unimplemented!")
  q"${termNames.ROOTPKG}.scala.Predef.???"
  // If someone were to shadow the scala package, scala.Predef.??? would not work, as it
  // would end up referring to the scala that shadows and not the actual scala.
  // ROOTPKG is the very root of the tree, and acts like it is imported anew in every
  // expression. It is actually named _root_, but if someone were to shadow it, every
  // reference to it would be an error. It allows us to safely access ??? and know that
  // it is the one we want.
}

def impl_!!!(c: Context): c.Tree = {
  import c.universe._
  c.error(c.enclosingPosition, "Unimplemented!")
  q"${termNames.ROOTPKG}.scala.Predef.???"
}
```

<https://riptutorial.com/zh-CN/scala/topic/3808/>

31:

- {clauses} body
- {clauses}
- forclausesbody
- forclauses

for/	
for for◦	
"""◦ yieldforUnit ◦	
for◦	

Examples

```
for (x <- 1 to 10)
  println("Iteration number " + x)
```

```
x110◦ forUnit ◦
```

foryield"""

```
for ( x <- 1 to 10 if x % 2 == 0)
  yield x
```

```
scala.collection.immutable.IndexedSeq[Int] = Vector(2, 4, 6, 8, 10)
```

◦

For

```
for {
  x <- 1 to 2
  y <- 'a' to 'd'
} println("(" + x + "," + y + ")")
```

to◦ ◦

```
(1,a)
(1,b)
(1,c)
(1,d)
(2,a)
```

```
(2,b)
(2,c)
(2,d)
```

```
for (
  x <- 1 to 2
  y <- 'a' to 'd'
) println("(" + x + "," + y + ")")
```

yieldval

```
val a = for {
  x <- 1 to 2
  y <- 'a' to 'd'
} yield "(%s,%s)".format(x, y)
// a: scala.collection.immutable.IndexedSeq[String] = Vector((1,a), (1,b), (1,c), (1,d),
(2,a), (2,b), (2,c), (2,d))
```

Monadic

[monadic](#) 'for comprehension'

```
for {
  x <- Option(1)
  y <- Option("b")
  z <- List(3, 4)
} {
  // Now we can use the x, y, z variables
  println(x, y, z)
  x // the last expression is *not* the output of the block in this case!
}

// This prints
// (1, "b", 3)
// (1, "b", 4)
```

Unit ◦

monadic `M Option yieldM Unit ◦`

```
val a = for {
  x <- Option(1)
  y <- Option("b")
} yield {
  // Now we can use the x, y variables
  println(x, y)
  // whatever is at the end of the block is the output
  (7 * x, y)
}

// This prints:
// (1, "b")
// The val `a` is set:
// a: Option[(Int, String)] = Some((7,b))
```

yield monadic OptionList ◦ ◦

For

Map

```
val map = Map(1 -> "a", 2 -> "b")
for (number <- map) println(number) // prints (1,a), (2,b)
for ((key, value) <- map) println(value) // prints a, b
```

```
val list = List(1,2,3)
for(number <- list) println(number) // prints 1, 2, 3
```

for **Scala** ◦ withFilter foreach flatMapmap◦ for◦

forpN gNcN

```
for(p0 <- x0 if g0; p1 <- g1 if c1) { ??? }
```

...withFilterforeach withFilter

```
g0.withFilter({ case p0 => c0 case _ => false }).foreach({
  case p0 => g1.withFilter({ case p1 => c1 case _ => false }).foreach({
    case p1 => ???
  })
})
```

for / yield

```
for(p0 <- g0 if c0; p1 <- g1 if c1) yield ???
```

...withFilterflatMapde-sugar

```
g0.withFilter({ case p0 => c0 case _ => false }).flatMap({
  case p0 => g1.withFilter({ case p1 => c1 case _ => false }).map({
    case p1 => ???
  })
})
```

map flatMap◦

for◦ ◦

<https://riptutorial.com/zh-CN/scala/topic/669/>

32:

- `re.findAllInsCharSequenceMatchIterator`
- `re.findAllMatchInsCharSequence[]`
- `re.findFirstInsCharSequenceOption [String]`
- `re.findFirstMatchInsCharSequence[]`
- `re.findPrefixMatchInsCharSequence[]`
- `re.findPrefixOfsCharSequenceOption [String]`
- `re.replaceAllInsCharSequencereplacerMatch => StringString`
- `re.replaceAllInsCharSequencereplacementStringString`
- `re.replaceFirstInsCharSequencereplacementStringString`
- `re.replaceSomeInsCharSequencereplacerMatch => Option [String]String`
- `re.splitsCharSequenceArray [String]`

Examples

[scala.collection.immutable.StringOps](#)_r [scala.util.matching.Regex](#)_o ScalaJava

```
val r0: Regex = """"(\d{4})-(\d{2})-(\d{2})""".r // :)
val r1: Regex = """"(\d{4})-(\d{2})-(\d{2})""".r // :(
```

[scala.util.matching.Regex](#)ScalaAPI [java.util.regex.Pattern](#)_o Scala_x

```
val dateRegex = """"(?x:
  (\d{4}) # year
  -(\d{2}) # month
  -(\d{2}) # day
)""".r
```

```
r def r(names: String*): Regexdef r(names: String*): Regexo
```

```
""""(\d{4})-(\d{2})-(\d{2})""".r("y", "m", "d").findFirstMatchIn(str) match {
  case Some(matched) =>
    val y = matched.group("y").toInt
    val m = matched.group("m").toInt
    val d = matched.group("d").toInt
    java.time.LocalDate.of(y, m, d)
  case None => ???
}
```

```
val re = """"\((.*?)\)""".r
```

```
val str =
```

```
"(The) (example) (of) (repeating) (pattern) (in) (a) (single) (string) (I) (had) (some) (trouble) (with) (once) "
```

```
re.findAllMatchIn(str).map(_.group(1)).toList
res2: List[String] = List(The, example, of, repeating, pattern, in, a, single, string, I, had,
some, trouble, with, once)
```


33:

◦ ◦ ParArray ParVector mutable.ParHashMap immutable.ParHashMapParRange ◦ ◦

Examples

par◦ seq◦ VectorParVector

```
scala> val vect = (1 to 5).toVector
vect: Vector[Int] = Vector(1, 2, 3, 4, 5)

scala> val parVect = vect.par
parVect: scala.collection.parallel.immutable.ParVector[Int] = ParVector(1, 2, 3, 4, 5)

scala> parVect.seq
res0: scala.collection.immutable.Vector[Int] = Vector(1, 2, 3, 4, 5)
```

par

```
scala> vect.map(_ * 2)
res1: scala.collection.immutable.Vector[Int] = Vector(2, 4, 6, 8, 10)

scala> vect.par.map(_ * 2)
res2: scala.collection.parallel.immutable.ParVector[Int] = ParVector(2, 4, 6, 8, 10)
```

- ◦

◦

◦ ◦ ◦ ◦ ◦

◦

```
scala> val list = (1 to 1000).toList
list: List[Int] = List(1, 2, 3, 4, 5, 6, 7, 8, 9, 10...)

scala> list.reduce(_ - _)
res0: Int = -500498

scala> list.reduce(_ - _)
res1: Int = -500498

scala> list.reduce(_ - _)
res2: Int = -500498

scala> val listPar = list.par
listPar: scala.collection.parallel.immutable.ParSeq[Int] = ParVector(1, 2, 3, 4, 5, 6, 7, 8, 9, 10...)

scala> listPar.reduce(_ - _)
res3: Int = -408314
```

```
scala> listPar.reduce(_ - _)
res4: Int = -422884

scala> listPar.reduce(_ - _)
res5: Int = -301748
```

foreach ◦ reduceMap ◦

```
scala> val wittyOneLiner = Array("Artificial", "Intelligence", "is", "no", "match", "for",
"natural", "stupidity")

scala> wittyOneLiner.foreach(word => print(word + " "))
Artificial Intelligence is no match for natural stupidity

scala> wittyOneLiner.par.foreach(word => print(word + " "))
match natural is for Artificial no stupidity Intelligence

scala> print(wittyOneLiner.par.reduce(_ + " " + _))
Artificial Intelligence is no match for natural stupidity

scala> val list = (1 to 100).toList
list: List[Int] = List(1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15...
```

<https://riptutorial.com/zh-CN/scala/topic/3882/>

34:

- `whileboolean_expression{block_expression}`
- `do {block_expression} whileboolean_expression`

<code>boolean_expression</code>	<code>truefalse◦</code>
<code>block_expression</code>	<code>boolean_expressiontrue ◦</code>

`whiledo-whileblock_expression ◦`

`whiledo-whilefalse◦`

Examples

```
var line = 0
var maximum_lines = 5

while (line < maximum_lines) {
  line = line + 1
  println("Line number: " + line)
}
```

Do-While

```
var line = 0
var maximum_lines = 5

do {
  line = line + 1
  println("Line number: " + line)
} while (line < maximum_lines)
```

`do / whilebreak / continue`

```
if(initial_condition) do if(filter) {
  ...
} while(continuation_condition)
```

<https://riptutorial.com/zh-CN/scala/topic/650/>

35:

- ATrait {...}
- class AClass...ATrait {...}
- class AClassATraitBClass
- class AClassBTraitATrait
- AClassCTraitATraitCTrait
- ATraitBTrait

Examples

◦
◦ ◦ ◦

```
class Ball {  
  def roll(ball : String) = println("Rolling : " + ball)  
}  
  
trait Red extends Ball {  
  override def roll(ball : String) = super.roll("Red-" + ball)  
}  
  
trait Green extends Ball {  
  override def roll(ball : String) = super.roll("Green-" + ball)  
}  
  
trait Shiny extends Ball {  
  override def roll(ball : String) = super.roll("Shiny-" + ball)  
}  
  
object Balls {  
  def main(args: Array[String]) {  
    val ball1 = new Ball with Shiny with Red  
    ball1.roll("Ball-1") // Rolling : Shiny-Red-Ball-1  
  
    val ball2 = new Ball with Green with Shiny  
    ball2.roll("Ball-2") // Rolling : Green-Shiny-Ball-2  
  }  
}
```

superroll()◦ ◦ ◦

Scala◦

```
trait Identifiable {  
  def getIdentifier: String  
  def printIndentification(): Unit = println(getIdentifier)  
}  
  
case class Puppy(id: String, name: String) extends Identifiable {  
  def getIdentifier: String = s"$name has id $id"}
```

```
}
```

Identifiable AnyRef ◦ Identifiable.getIdentifierPuppy ◦ PuppyIdentifiable.printIdentification ◦

REPL

```
val p = new Puppy("K9", "Rex")
p.getIdentifier // res0: String = Rex has id K9
p.printIdentification() // Rex has id K9
```

Scala Traits Traits Java ◦ ◦ [mixin](#) ◦

Scala

```
trait traitA {
  def name = println("This is the 'grandparent' trait.")
}

trait traitB extends traitA {
  override def name = {
    println("B is a child of A.")
    super.name
  }
}

trait traitC extends traitA {
  override def name = {
    println("C is a child of A.")
    super.name
  }
}

object grandChild extends traitB with traitC

grandChild.name
```

grandChild.traitB.traitC.traitB.traitC.traitA ◦

```
C is a child of A.
B is a child of A.
This is the 'grandparent' trait.
```

superclass trait ◦ grandChild

grandChild -> traitC -> traitB -> traitA -> AnyRef -> Any

```
trait Printer {
  def print(msg : String) = println (msg)
}

trait DelimitWithHyphen extends Printer {
  override def print(msg : String) {
```

```

        println("-----")
        super.print(msg)
    }
}

trait DelimitWithStar extends Printer {
    override def print(msg : String) {
        println("*****")
        super.print(msg)
    }
}

class CustomPrinter extends Printer with DelimitWithHyphen with DelimitWithStar

object TestPrinter{
    def main(args: Array[String]) {
        new CustomPrinter().print("Hello World!")
    }
}

```

```

*****
-----
Hello World!

```

CustomPrinter

CustomPrinter - > DelimitWithStar - > DelimitWithHyphen - > - > AnyRef - >

Scala ◦ super()◦

```

class Shape {
    def paint (shape: String): Unit = {
        println(shape)
    }
}

trait Color extends Shape {
    abstract override def paint (shape : String) {
        super.paint(shape + "Color ")
    }
}

trait Blue extends Color {
    abstract override def paint (shape : String) {
        super.paint(shape + "with Blue ")
    }
}

trait Border extends Shape {
    abstract override def paint (shape : String) {
        super.paint(shape + "Border ")
    }
}

trait Dotted extends Border {
    abstract override def paint (shape : String) {
        super.paint(shape + "with Dotted ")
    }
}

```

```

}

class MyShape extends Shape with Dotted with Blue {
  override def paint (shape : String) {
    super.paint(shape)
  }
}

```

◦

1. First Shape

Shape -> AnyRef -> Any

2. Dotted

Dotted -> Border -> Shape -> AnyRef -> Any

3. Blue ◦ Blue

Blue -> Color -> Shape -> AnyRef -> Any

MyShape **2** Shape -> AnyRef -> Any ◦ ◦ Blue

Blue -> Color -> Dotted -> Border -> Shape -> AnyRef -> Any

4. Circle

-> -> -> -> -> -> -> ->

super ◦ ◦ new MyShape().paint("Circle ")

```

Circle with Blue Color with Dotted Border

```

◦

<https://riptutorial.com/zh-CN/scala/topic/1056/>

36:

- `valueExtractedValue1_ / ** /= valueToBeExtracted`
- `valueToBeExtracted match {case extractorextractedValue1_=> ???}`
- `valtuple1tuple2tuple3= tupleWith3Elements`
- `object Foo {def unapplyfooFooOption [String] = Somefoo.x; }`

Examples

xy

```
val (x, y) = (1337, 42)
// x: Int = 1337
// y: Int = 42
```

—

```
val (_, y: Int) = (1337, 42)
// y: Int = 42
```

```
val myTuple = (1337, 42)
myTuple._1 // res0: Int = 1337
myTuple._2 // res1: Int = 42
```

22._1._22°

```
val persons = List("A." -> "Lovelace", "G." -> "Hopper")
val names = List("Lovelace, A.", "Hopper, G.")

assert {
  names ==
    (persons map { name =>
      s"${name._2}, ${name._1}"
    })
}

assert {
  names ==
    (persons map { case (given, surname) =>
      s"$surname, $given"
    })
}
```

° Scalacase °

```
case class Person(name: String, age: Int) // Define the case class
val p = Person("Paola", 42) // Instantiate a value with the case class type

val Person(n, a) = p // Extract values n and a
// n: String = Paola
```

```
// a: Int = 42
```

naval **p**""。

```
val p2 = Person("Angela", 1337)

val List(Person(n1, a1), Person(_, a2)) = List(p, p2)
// n1: String = Paola
// a1: Int = 42
// a2: Int = 1337
```

- ""。
- ◦ _◦ val ◦

```
val ls = List(p1, p2, p3) // List of Person objects
ls.map(person => person match {
  case Person(n, a) => println("%s is %d years old".format(n, a))
})
```

personPerson na ◦

Unapply -

unapplyOption

```
class Foo(val x: String)

object Foo {
  def unapply(foo: Foo): Option[String] = Some(foo.x)
}

new Foo("42") match {
  case Foo(x) => x
}
// "42"
```

getisEmptyunapplyOption ◦ Bar unapplyBar

```
class Bar(val x: String) {
  def get = x
  def isEmpty = false
}

object Bar {
  def unapply(bar: Bar): Bar = bar
}

new Bar("1337") match {
  case Bar(x) => x
}
// "1337"
```

unapplyBoolean getisEmpty◦ DivisibleByTwo

```
object DivisibleByTwo {
  def unapply(num: Int): Boolean = num % 2 == 0
}

4 match {
  case DivisibleByTwo() => "yes"
  case _ => "no"
}
// yes

3 match {
  case DivisibleByTwo() => "yes"
  case _ => "no"
}
// no
```

unapply° °

case°

```
case class Pair(a: String, b: String)
val p: Pair = Pair("hello", "world")
val x Pair y = p
//x: String = hello
//y: String = world
```

2°

```
object Foo {
  def unapply(s: String): Option[(Int, Int)] = Some((s.length, 5))
}
val a Foo b = "hello world!"
//a: Int = 12
//b: Int = 5
```

```
scala> val address = "()(.):(\d+)"
address: scala.util.matching.Regex = (.):(\d+)

scala> val address(host, port) = "some.domain.org:8080"
host: String = some.domain.org
port: String = 8080
```

MatchError

```
scala> val address(host, port) = "something not a host and port"
scala.MatchError: something not a host and port (of class java.lang.String)
```

° °

Windows

```
object UserPrincipalName {
  def unapply(str: String): Option[(String, String)] = str.split('@') match {
```



```

    case Array(u, d) if u.length > 0 && d.length > 0 => Some((u, d))
    case _ => None
  }
}

object DownLevelLogonName {
  def unapply(str: String): Option[(String, String)] = str.split('\\') match {
    case Array(d, u) if u.length > 0 && d.length > 0 => Some((d, u))
    case _ => None
  }
}

def getDomain(str: String): Option[String] = str match {
  case UserPrincipalName(_, domain) => Some(domain)
  case DownLevelLogonName(domain, _) => Some(domain)
  case _ => None
}

```

```

object UserPrincipalName {
  def unapply(obj: Any): Option[(String, String)] = obj match {
    case upn: UserPrincipalName => Some((upn.username, upn.domain))
    case str: String => str.split('@') match {
      case Array(u, d) if u.length > 0 && d.length > 0 => Some((u, d))
      case _ => None
    }
    case _ => None
  }
}

```

OptiontryParse

```

UserPrincipalName.unapply("user@domain") match {
  case Some((u, d)) => ???
  case None => ???
}

```

<https://riptutorial.com/zh-CN/scala/topic/930/>

37:

vals ◦ ◦ ◦

- OderskySpoonVenners *Scala*

Odersky ◦

Examples

◦

-
-
- monad-like api `map flatMap fold`

Scala

- `Cake patternReader Monad` ◦
- `implicit` ◦

◦ ◦

◦

- ◦
- `formap` ◦

```
if (userAuthorized.nonEmpty) {  
  makeRequest().map {  
    case Success(response) =>  
      someProcessing(..)  
      if (resendToUser) {  
        sendToUser(...)  
      }  
    ...  
  }  
}
```

`EitherValidation`

```
for {  
  user      <- authorizeUser  
  response  <- requestToThirdParty(user)  
  _         <- someProcessing(...)  
} {  
  sendToUser  
}
```

- `valvar` ◦ ◦
-

`recursioncomprehensions` ◦

- `val` ◦
- CQRSCRUD ◦
- `var` **actor** ◦
- `mutable` ◦

<https://riptutorial.com/zh-CN/scala/topic/4376/>

Examples

```
import scala.concurrent.Future
import scala.concurrent.ExecutionContext.Implicits.global

object FutureDivider {
  def divide(a: Int, b: Int): Future[Int] = Future {
    // Note that this is integer division.
    a / b
  }
}
```

divideab ◦

- - map◦ `FutureDivider.divide◦ ab`

```
object Calculator {
  def calculateAndReport(a: Int, b: Int) = {
    val eventualQuotient = FutureDivider.divide(a, b)

    eventualQuotient.map {
      quotient => println(quotient)
    }
  }
}
```

FutureFuture◦ `550divideArithmeticException◦ ◦`

recover◦

```
object Calculator {
  def calculateAndReport(a: Int, b: Int) = {
    val eventualQuotient = FutureDivider.divide(a, b)

    eventualQuotient.recover {
      case ex: ArithmeticException => println(s"It failed with: ${ex.getMessage}")
    }
  }
}
```

failedFuture

```
object Calculator {
  def calculateAndReport(a: Int, b: Int) = {
    val eventualQuotient = FutureDivider.divide(a, b)

    // Note the use of the dot operator to get the failed projection and map it.
    eventualQuotient.failed.map {
      ex => println(s"It failed with: ${ex.getMessage}")
    }
  }
}
```

```
}
}
```

Future。。

```
object Calculator {
  def calculateAndReport(a: Int, b: Int) = {
    val eventualQuotient = FutureDivider divide(a, b)

    eventualQuotient map {
      quotient => println(s"Quotient: $quotient")
    } recover {
      case ex: ArithmeticException => println(s"It failed with: ${ex.getMessage}")
    }
  }
}
```

◦ List[Future[Int]] List[Int] ◦ List[Future[Int]]Future[List[Int]] ◦ Futuresequence◦

```
def listOfFuture: List[Future[Int]] = List(1,2,3).map(Future(_))
def futureOfList: Future[List[Int]] = Future.sequence(listOfFuture)
```

sequenceF[G[T]]G[F[T]] FG

traverse◦ x => xsequence◦

```
def listOfFuture: List[Future[Int]] = List(1,2,3).map(Future(_))
def futureOfList: Future[List[Int]] = Future.traverse(listOfFuture)(x => x)
```

listOfFuture◦ Future◦

```
def futureOfList: Future[List[Int]] = Future.traverse(List(1,2,3))(Future(_))
```

List(1,2,3)x => xFuture(_)IntFuture ◦ List[Future[Int]]◦

-

for comprehension◦

f1, f2, f3Future[String]one, two, three

```
val fCombined =
  for {
    s1 <- f1
    s2 <- f2
    s3 <- f3
  } yield (s"$s1 - $s2 - $s3")
```

fCombinedFuture[String]one - two - three◦

ExectionContext◦

flatMap bodyFuture◦

```
val result1 = for {  
  first <- Future {  
    Thread.sleep(2000)  
    System.currentTimeMillis()  
  }  
  second <- Future {  
    Thread.sleep(1000)  
    System.currentTimeMillis()  
  }  
} yield first - second  
  
val fut1 = Future {  
  Thread.sleep(2000)  
  System.currentTimeMillis()  
}  
val fut2 = Future {  
  Thread.sleep(1000)  
  System.currentTimeMillis()  
}  
val result2 = for {  
  first <- fut1  
  second <- fut2  
} yield first - second
```

result1result2◦

yield<http://docs.scala-lang.org/tutorials/FAQ/yield.html>

<https://riptutorial.com/zh-CN/scala/topic/3245/>

39:

sealed trait case objects **Scala**

1. ◦
2. `scala.MatchError`

```
def isWeekendWithBug(day: WeekDays.Value): Boolean = day match {  
  case WeekDays.Sun | WeekDays.Sat => true  
}
```

```
isWeekendWithBug(WeekDays.Fri)  
scala.MatchError: Fri (of class scala Enumeration$Val)
```

```
def isWeekendWithBug(day: WeekDay): Boolean = day match {  
  case WeekDay.Sun | WeekDay.Sat => true  
}
```

Warning: match may not be exhaustive.
It would fail on the following inputs: Fri, Mon, Thu, Tue, Wed
def isWeekendWithBug(day: WeekDay): Boolean = day match {
 ^

[Scala Enumeration](#) ◦

Examples

Scala Enumeration

[Enumeration](#) [Java](#) ◦

```
object WeekDays extends Enumeration {  
  val Mon, Tue, Wed, Thu, Fri, Sat, Sun = Value  
}  
  
def isWeekend(day: WeekDays.Value): Boolean = day match {  
  case WeekDays.Sat | WeekDays.Sun => true  
  case _ => false  
}  
  
isWeekend(WeekDays.Sun)  
res0: Boolean = true
```

```
object WeekDays extends Enumeration {  
  val Mon = Value("Monday")  
  val Tue = Value("Tuesday")  
  val Wed = Value("Wednesday")  
  val Thu = Value("Thursday")  
  val Fri = Value("Friday")  
  val Sat = Value("Saturday")  
  val Sun = Value("Sunday")  
}
```

```

}

println(WeekDays.Mon)
>> Monday

WeekDays.withName("Monday") == WeekDays.Mon
>> res0: Boolean = true

```

```

object Parity extends Enumeration {
  val Even, Odd = Value
}

WeekDays.Mon.isInstanceOf[Parity.Value]
>> res1: Boolean = true

```

Enumerationsealed

```

sealed trait WeekDay

object WeekDay {
  case object Mon extends WeekDay
  case object Tue extends WeekDay
  case object Wed extends WeekDay
  case object Thu extends WeekDay
  case object Fri extends WeekDay
  case object Sun extends WeekDay
  case object Sat extends WeekDay
}

```

sealedWeekDay◦ WeekDay◦

◦

```

val allWeekDays = Seq(Mon, Tue, Wed, Thu, Fri, Sun, Sat)

```

sealed◦

```

sealed trait CelestialBody

object CelestialBody {
  case object Earth extends CelestialBody
  case object Sun extends CelestialBody
  case object Moon extends CelestialBody
  case class Asteroid(name: String) extends CelestialBody
}

```

sealed◦

```

sealed trait WeekDay { val name: String }

object WeekDay {
  case object Mon extends WeekDay { val name = "Monday" }
  case object Tue extends WeekDay { val name = "Tuesday" }
  (...)
}

```



```
}
```

```
sealed case class WeekDay(name: String)

object WeekDay {
  object Mon extends WeekDay("Monday")
  object Tue extends WeekDay("Tuesday")
  (...)
}
```

traitcaseallValues-macro

- allElements◦

-

```
import EnumerationMacros._

sealed trait WeekDay
object WeekDay {
  case object Mon extends WeekDay
  case object Tue extends WeekDay
  case object Wed extends WeekDay
  case object Thu extends WeekDay
  case object Fri extends WeekDay
  case object Sun extends WeekDay
  case object Sat extends WeekDay
  val allWeekDays: Set[WeekDay] = sealedInstancesOf[WeekDay]
}
```

```
import scala.collection.immutable.TreeSet
import scala.language.experimental.macros
import scala.reflect.macros.blackbox

/**
 * A macro to produce a TreeSet of all instances of a sealed trait.
 * Based on Travis Brown's work:
 * http://stackoverflow.com/questions/13671734/iteration-over-a-sealed-trait-in-scala
 * CAREFUL: !!! MUST be used at END OF code block containing the instances !!!
 */
object EnumerationMacros {
  def sealedInstancesOf[A]: TreeSet[A] = macro sealedInstancesOf_impl[A]

  def sealedInstancesOf_impl[A: c.WeakTypeTag](c: blackbox.Context) = {
    import c.universe._

    val symbol = weakTypeOf[A].typeSymbol.asClass

    if (!symbol.isClass || !symbol.isSealed)
      c.abort(c.enclosingPosition, "Can only enumerate values of a sealed trait or class.")
    else {

      val children = symbol.knownDirectSubclasses.toList

      if (!children.forall(_.isModuleClass)) c.abort(c.enclosingPosition, "All children must be objects.")
    }
  }
}
```

```
else c.Expr[TreeSet[A]] {  
  
    def sourceModuleRef(sym: Symbol) =  
Ident(sym.asInstanceOf[scala.reflect.internal.Symbols#Symbol  
    ].sourceModule.asInstanceOf[Symbol]  
    )  
  
    Apply(  
        Select(  
            reify(TreeSet).tree,  
            TermName("apply")  
        ),  
        children.map(sourceModuleRef(_))  
    )  
    }  
    }  
    }  
}
```

<https://riptutorial.com/zh-CN/scala/topic/1499/>

40:

- case Foo // case
- case class Foo a1 ... aN // a1 ... aN case
- case object Bar //

Examples

case equals ◦

```
class Foo(val i: Int)
val a = new Foo(3)
val b = new Foo(3)
println(a == b) // "false" because they are different objects
```

```
case class Foo(i: Int)
val a = Foo(3)
val b = Foo(3)
println(a == b) // "true" because their members have the same value
```

case Scala ◦ ◦

```
case class Person(name: String, age: Int)
```

...

```
class Person(val name: String, val age: Int)
  extends Product with Serializable
{
  def copy(name: String = this.name, age: Int = this.age): Person =
    new Person(name, age)

  def productArity: Int = 2

  def productElement(i: Int): Any = i match {
    case 0 => name
    case 1 => age
    case _ => throw new IndexOutOfBoundsException(i.toString)
  }

  def productIterator: Iterator[Any] =
    scala.runtime.ScalaRunTime.typedProductIterator(this)

  def productPrefix: String = "Person"

  def canEqual(obj: Any): Boolean = obj.isInstanceOf[Person]

  override def hashCode(): Int = scala.runtime.ScalaRunTime._hashCode(this)

  override def equals(obj: Any): Boolean = this.eq(obj) || obj match {
    case that: Person => this.name == that.name && this.age == that.age
    case _ => false
  }
}
```

```

}

override def toString: String =
  scala.runtime.ScalaRunTime._toString(this)
}

```

case

```

object Person extends AbstractFunction2[String, Int, Person] with Serializable {
  def apply(name: String, age: Int): Person = new Person(name, age)

  def unapply(p: Person): Option[(String, Int)] =
    if(p == null) None else Some((p.name, p.age))
}

```

object case^o toStringhashCode^o **case**

```

object Foo extends Product with Serializable {
  def productArity: Int = 0

  def productIterator: Iterator[Any] =
    scala.runtime.ScalaRunTime.typedProductIterator(this)

  def productElement(i: Int): Any =
    throw new IndexOutOfBoundsException(i.toString)

  def productPrefix: String = "Foo"

  def canEqual(obj: Any): Boolean = obj.isInstanceOf[this.type]

  override def hashCode(): Int = 70822 // "Foo".hashCode()

  override def toString: String = "Foo"
}

```

case^o

-

- public

```

case class Dog1(age: Int)
val x = Dog1(18)
println(x.age) // 18 (success!)

class Dog2(age: Int)
val x = new Dog2(18)
println(x.age) // Error: "value age is not a member of Dog2"

```

- toString equals hashCode copy applyunapply

```

case class Dog(age: Int)
val d1 = Dog(10)
val d2 = d1.copy(age = 15)

```

-

```
sealed trait Animal // `sealed` modifier allows inheritance within current build-unit only
case class Dog(age: Int) extends Animal
case class Cat(owner: String) extends Animal
val x: Animal = Dog(18)
x match {
  case Dog(x) => println(s"It's a $x years old dog.")
  case Cat(x) => println(s"This cat belongs to $x.")
}
```

Scala `val` `case` `mutator`.

```
case class Foo(i: Int)

val fooInstance = Foo(1)
val j = fooInstance.i // get
fooInstance.i = 2      // compile-time exception (mutation: reassignment to val)
```

Scala `var` `case`

```
case class Bar(var i: Int)

val barInstance = Bar(1)
val j = barInstance.i // get
barInstance.i = 2      // set
```

Scala `case`

```
import scala.collection._

case class Bar(m: mutable.Map[Int, Int])

val barInstance = Bar(mutable.Map(1 -> 2))
barInstance.m.update(1, 3) // mutate m
barInstance                // Bar(Map(1 -> 3))
```

Scala `mm` `m` `instanceA` `instanceB`

```
import scala.collection.mutable

case class Bar(m: mutable.Map[Int, Int])

val m = mutable.Map(1 -> 2)
val barInstanceA = Bar(m)
val barInstanceB = Bar(m)
barInstanceA.m.update(1, 3)
barInstanceA // Bar = Bar(Map(1 -> 3))
barInstanceB // Bar = Bar(Map(1 -> 3))
m            // scala.collection.mutable.Map[Int,Int] = Map(1 -> 3)
```

Scala `copy`

Scala

```
case class Person(firstName: String, lastName: String, grade: String, subject: String)
val putu = Person("Putu", "Kevin", "A1", "Math")
val mark = putu.copy(firstName = "Ketut", lastName = "Mark")
// mark: People = People(Ketut,Mark,A1,Math)
```

```
grade = A1 subject = Math firstNamelastName ◦
```

```
◦ Personname ◦ nameString ◦ StringPersonnameString
```

```
def logError(message: ErrorMessage): Unit = ???
case class Person(name: String)
val maybeName: Either[String, String] = ??? // Left is error, Right is name
maybeName.foreach(logError) // But that won't stop me from logging the name as an error!
```

```
case class PersonName(value: String)
case class ErrorMessage(value: String)
case class Person(name: PersonName)
```

```
PersonNameErrorMessageString ◦
```

```
val maybeName: Either[ErrorMessage, PersonName] = ???
maybeName.foreach(reportError) // ERROR: tried to pass PersonName; ErrorMessage expected
maybeName.swap.foreach(reportError) // OK
```


```
String / unboxPersonName/◦ PersonNameErrorMessage
```

```
case class PersonName(val value: String) extends AnyVal
case class ErrorMessage(val value: String) extends AnyVal
```

<https://riptutorial.com/zh-CN/scala/topic/1022/>

41:

- partialFunction
- { //



Examples

```
def f(x: Int): String = x match {  
  case 1 => "One"  
  case 2 => "Two"  
  case _ => "Unknown!"  
}  
  
f(2)  // "Two"  
f(3)  // "Unknown!"
```

_°

```
def g(x: Int): String = x match {  
  case 1 => "One"  
  case 2 => "Two"  
}  
  
g(1)  // "One"  
g(3)  // throws a MatchError
```

case _ => <do something> ° ° °

° °

Onetwo

```
val One: Int = 1  
val two: Int = 2
```

```
def g(x: Int): String = x match {  
  case One => "One"  
  case `two` => "Two"  
}
```

Java ° case ° °

```
def f(x: Int): String = x match {  
  case _ => "Default"
```

```

    case 1 => "One"
  }

  f(5) // "Default"
  f(1) // "Default"

```

◦ ◦

◦ ◦ ◦

```

def tabulate(char: Char, tab: List[(Char, Int)]): List[(Char, Int)] = tab match {
  case Nil => List((char, 1))
  case (`char`, count) :: tail => (char, count + 1) :: tail
  case head :: tail => head :: tabulate(char, tail)
}

```

char`"""tabulate('x', ...) case`

```

case('x', count) => ...

```

Scala◦

Seq

```

def f(ints: Seq[Int]): String = ints match {
  case Seq() =>
    "The Seq is empty !"
  case Seq(first) =>
    s"The seq has exactly one element : $first"
  case Seq(first, second) =>
    s"The seq has exactly two elements : $first, $second"
  case s @ Seq(_, _, _) =>
    s"$s is a Seq of length three and looks like ${s}" // Note individual elements are not
    bound to their own names.
  case s: Seq[Int] if s.length == 4 =>
    s"$s is a Seq of Ints of exactly length 4" // Again, individual elements are not bound
    to their own names.
  case _ =>
    "No match was found!"
}

```

S

```

def f(ints: Seq[Int]): String = ints match {
  case Seq(first, second, tail @ _*) =>
    s"The seq has at least two elements : $first, $second. The rest of the Seq is $tail"
  case Seq(first, tail @ _*) =>
    s"The seq has at least one element : $first. The rest of the Seq is $tail"
  // alternative syntax
  // here of course this one will never match since it checks
  // for the same thing as the one above
  case first +: tail =>
    s"The seq has at least one element : $first. The rest of the Seq is $tail"
  case _ =>

```



```

    "The seq didn't match any of the above, so it must be empty"
  }
}

```

◦

`Nil::SequenceList ◦ Seq( ...)+:◦`

`::WrappedArray Vector`

```

scala> def f(ints:Seq[Int]) = ints match {
  | case h :: t => h
  | case _ => "No match"
  | }
f: (ints: Seq[Int])Any

```

```

scala> f(Array(1,2))
res0: Any = No match

```

`+:`

```

scala> def g(ints:Seq[Int]) = ints match {
  | case h+:t => h
  | case _ => "No match"
  | }
g: (ints: Seq[Int])Any

```

```

scala> g(Array(1,2).toSeq)
res4: Any = 1

```

Caseif◦

```

def checkSign(x: Int): String = {
  x match {
    case a if a < 0 => s"$a is a negative number"
    case b if b > 0 => s"$b is a positive number"
    case c => s"$c neither positive nor negative"
  }
}

```

```

def f(x: Option[Int]) = x match {
  case Some(i) if i % 2 == 0 => doSomething(i)
  case None      => doSomethingIfNone
}

```

`MatchError ◦`

```

def f(x: Option[Int]) = x match {
  case Some(i) if i % 2 == 0 => doSomething(i)
  case _ => doSomethingIfNoneOrOdd
}

```

casecase

```
case class Student(name: String, email: String)

def matchStudent1(student: Student): String = student match {
  case Student(name, email) => s"$name has the following email: $email" // extract name and email
}
```

-

```
def matchStudent2(student: Student): String = student match {
  case Student("Paul", _) => "Matched Paul" // Only match students named Paul, ignore email
  case Student(name, _) if name == "Paul" => "Matched Paul" // Use a guard to match students named Paul, ignore email
  case s if s.name == "Paul" => "Matched Paul" // Don't use extractor; use a guard to match students named Paul, ignore email
  case Student("Joe", email) => s"Joe has email $email" // Match students named Joe, capture their email
  case Student(name, email) if name == "Joe" => s"Joe has email $email" // use a guard to match students named Joe, capture their email
  case Student(name, email) => s"$name has email $email." // Match all students, capture name and email
}
```

```
def f(x: Option[Int]) = x match {
  case Some(i) => doSomething(i)
  case None    => doSomethingIfNone
}
```

foldmap / getOrElse

```
def g(x: Option[Int]) = x.fold(doSomethingIfNone)(doSomething)
def h(x: Option[Int]) = x.map(doSomething).getOrElse(doSomethingIfNone)
```

Scala“”

```
sealed trait Shape
case class Square(height: Int, width: Int) extends Shape
case class Circle(radius: Int) extends Shape
case object Point extends Shape

def matchShape(shape: Shape): String = shape match {
  case Square(height, width) => "It's a square"
  case Circle(radius)        => "It's a circle"
  //no case for Point because it would cause a compiler warning.
}
```

case class Shape match Shape ◦ ◦

```
val emailRegex: Regex = "(.+)?@(.+)?\\.?(.+)?".r

"name@example.com" match {
  case emailRegex(userName, domain, topDomain) => println(s"Hi $userName from $domain")
  case _ => println(s"This is not a valid email.")
}
```

◦ userNamedomain ◦ topDomain ◦ **String** str.rnew Regex(str) ◦ r ◦

@

@◦

```
sealed trait Shape
case class Rectangle(height: Int, width: Int) extends Shape
case class Circle(radius: Int) extends Shape
case object Point extends Shape

(Circle(5): Shape) match {
  case Rectangle(h, w) => s"rectangle, $h x $w."
  case Circle(r) if r > 9 => s"large circle"
  case c @ Circle(_) => s"small circle: ${c.radius}" // Whole matched object is bound to c
  case Point => "point"
}
```

> res0: String = small circle: 5

◦

```
case Circle(r) if r > 9 => s"large circle"
```

```
case c @ Circle(_) if c.radius > 9 => s"large circle"
```

```
Seq(Some(1), Some(2), None) match {
  // Only the first element of the matched sequence is bound to the name 'c'
  case Seq(c @ Some(1), _) => head
  case _ => None
}
```

> res0: Option[Int] = Some(1)

[isInstanceOf\[B\]](#)

```
val anyRef: AnyRef = ""

anyRef match {
  case _: Number      => "It is a number"
  case _: String      => "It is a string"
  case _: CharSequence => "It is a char sequence"
}
//> res0: String = It is a string
```

```
anyRef match {
  case _: Number      => "It is a number"
  case _: CharSequence => "It is a char sequence"
  case _: String      => "It is a string"
}
//> res1: String = It is a char sequence
```

“”◦ “”◦

```

case class Foo(s: String)
case class Bar(s: String)
case class Woo(s: String, i: Int)

def matcher(g: Any):String = {
  g match {
    case Bar(s) => s + " is classy!"
    case Foo(_) => "Someone is wicked smart!"
    case Woo(s, _) => s + " is adventurous!"
    case _ => "What are we talking about?"
  }
}

print(matcher(Foo("Diana"))) // prints 'Diana is classy!'
print(matcher(Bar("Hadas"))) // prints 'Someone is wicked smart!'
print(matcher(Woo("Beth", 27))) // prints 'Beth is adventurous!'
print(matcher(Option("Katie"))) // prints 'What are we talking about?'

```

FooWoo _ " " Hadas27 " ".

tableswitchlookupswitch

@switchtableswitchmatch .

@switchfinal val . tableswitch / lookupswitch .

```

import annotation.switch

def suffix(i: Int) = (i: @switch) match {
  case 1 => "st"
  case 2 => "nd"
  case 3 => "rd"
  case _ => "th"
}

```

```

scala> suffix(2)
res1: String = "2nd"

scala> suffix(4)
res2: String = "4th"

```

Scala 2.8+ - @switch

- tableswitchlookupswitch.

Java

- [tableswitch](#) " " "
- [lookupswitch](#) " " "

|case

```

def f(str: String): String = str match {

```

```

    case "foo" | "bar" => "Matched!"
    case _ => "No match."
}

f("foo") // res0: String = Matched!
f("bar") // res1: String = Matched!
f("fubar") // res2: String = No match.

```

```

sealed class FooBar
case class Foo(s: String) extends FooBar
case class Bar(s: String) extends FooBar

val d = Foo("Diana")
val h = Bar("Hadas")

// This matcher WILL NOT work.
def matcher(g: FooBar):String = {
  g match {
    case Foo(s) | Bar(s) => print(s) // Won't work: s cannot be resolved
    case Foo(_) | Bar(_) => _ // Won't work: _ is an unbound placeholder
    case _ => "Could not match"
  }
}

```

```

def matcher(g: FooBar):String = {
  g match {
    case Foo(_) | Bar(_) => "Is either Foo or Bar." // Works fine
    case _ => "Could not match"
  }
}

```

```

def matcher(g: FooBar):String = {
  g match {
    case Foo(s) => s
    case Bar(s) => s
    case _ => "Could not match"
  }
}

```

List

```

val pastries = List(("Chocolate Cupcake", 2.50),
                    ("Vanilla Cupcake", 2.25),
                    ("Plain Muffin", 3.25))

```

```

pastries foreach { pastry =>
  pastry match {
    case ("Plain Muffin", price) => println(s"Buying muffin for $price")
    case p if p._1 contains "Cupcake" => println(s"Buying cupcake for ${p._2}")
    case _ => println("We don't sell that pastry")
  }
}

```

- if ◦

<https://riptutorial.com/zh-CN/scala/topic/661/>

42:

- `@AnAnnotation def someMethod = {...}`
- `@AnAnnotationsomeClass {...}`
- `@AnnotationWithArgsannotation_argsdef someMethod = {...}`

@	◦
SomeAnnotation	
constructor_args	◦ ◦

Scala-lang[Java](#) ◦

Examples

[deprecated](#) ◦

```
@deprecated
def anUnusedLegacyMethod(someArg: Any) = {
  ...
}
```

```
@deprecated def anUnusedLegacyMethod(someArg: Any) = {
  ...
}
```

```
/**
 * @param num Numerator
 * @param denom Denominator
 * @throws ArithmeticException in case `denom` is `0`
 */
class Division @throws[ArithmeticException] (/*no annotation parameters*/) protected (num: Int,
denom: Int) {
  private[this] val wrongValue = num / denom

  /** Integer number
   * @param num Value */
  protected[Division] def this(num: Int) {
    this(num, 1)
  }
}
object Division {
  def apply(num: Int) = new Division(num)
  def apply(num: Int, denom: Int) = new Division(num, denom)
}
```

`protected ◦ @throws:( () ◦`

◦

case

```
case class Division @throws[ArithmeticException]("denom is 0") (num: Int, denom: Int) {  
  private[this] val wrongValue = num / denom  
}
```

scala.annotation.StaticAnnotationscala.annotation.ClassfileAnnotationScala◦

```
package animals  
// Create Annotation `Mammal`  
class Mammal(indigenous:String) extends scala.annotation.StaticAnnotation  
  
// Annotate class Platypus as a `Mammal`  
@Mammal(indigenous = "North America")  
class Platypus{}
```

API◦

```
scala>import scala.reflect.runtime.{universe ⇒ u}  
  
scala>val platypusType = u.typeOf[Platypus]  
platypusType: reflect.runtime.universe.Type = animals.reflection.Platypus  
  
scala>val platypusSymbol = platypusType.typeSymbol.asClass  
platypusSymbol: reflect.runtime.universe.ClassSymbol = class Platypus  
  
scala>platypusSymbol.annotations  
List[reflect.runtime.universe.Annotation] = List(animals.reflection.Mammal("North America"))
```

<https://riptutorial.com/zh-CN/scala/topic/3783/>

43:

“” ° °

Examples

genRandom°

```
def genRandom: Stream[String] = {
  val random = scala.util.Random.nextFloat()
  println(s"Random value is: $random")
  if (random < 0.25) {
    Stream.empty[String]
  } else {
    (("%.3f : A random number" format random) #:: genRandom
  }
}

lazy val randos = genRandom // getRandom is lazily evaluated as randos is iterated through

for {
  x <- randos
} println(x) // The number of times this prints is effectively randomized.
```

#:: construct °

°

```
// factorial
val fact: Stream[BigInt] = 1 #:: fact.zipWithIndex.map{case (p,x)=>p*(x+1)}
fact.take(10) // (1, 1, 2, 6, 24, 120, 720, 5040, 40320, 362880)
fact(24)      // 620448401733239439360000

// the Fibonacci series
val fib: Stream[BigInt] = 0 #:: fib.scan(1:BigInt)(_+_)
fib.take(10) // (0, 1, 1, 2, 3, 5, 8, 13, 21, 34)
fib(124)     // 36726740705505779255899443

// random Ints between 10 and 99 (inclusive)
def rndInt: Stream[Int] = (util.Random.nextInt(90)+10) #:: rndInt
rndInt.take(10) // (20, 95, 14, 44, 42, 78, 85, 24, 99, 85)
```

VarValDef° def° val° °

```
// def with extra output per calculation
def fact: Stream[Int] = 1 #:: fact.zipWithIndex.map{case (p,x)=>print("!");p*(x+1)}
fact(5) // !!!!!!!!!!!!!!! 120
fact(4) // !!!!!!!!!!!!!!! 24
fact(7) // !!!!!!!!!!!!!!! 5040

// now as val
val fact: Stream[Int] = 1 #:: fact.zipWithIndex.map{case (p,x)=>print("!");p*(x+1)}
fact(5) // !!!!! 120
```

```
fact(4) // 24
fact(7) // !! 5040
```

Streamval°

```
val rndInt: Stream[Int] = (util.Random.nextInt(90)+10) #:: rndInt
rndInt.take(5) // (79, 79, 79, 79, 79)
```

```
// Generate stream that references itself in its evaluation
lazy val primes: Stream[Int] =
  2 #:: Stream.from(3, 2)
    .filter { i => primes.takeWhile(p => p * p <= i).forall(i % _ != 0) }
    .takeWhile(_ > 0) // prevent overflowing

// Get list of 10 primes
assert(primes.take(10).toList == List(2, 3, 5, 7, 11, 13, 17, 19, 23, 29))

// Previously calculated values were memoized, as shown by toString
assert(primes.toString == "Stream(2, 3, 5, 7, 11, 13, 17, 19, 23, 29, ?)")
```

<https://riptutorial.com/zh-CN/scala/topic/3702/>

44:

Scala - ◦

LispRubyErlangScala◦ ◦

'_◦ ◦

```
'ATM
'IPv4
'IPv6
'map_to_operations
'data_format_2006

// Using the `Symbol.apply` method

Symbol("hakuna matata")
Symbol("To be or not to be that is a question")
```

```
'8'th_division
'94_pattern
'bad-format
```

Examples

case

argumentList ◦

```
def loadData(dataSource: Symbol): Try[String] = dataSource match {
  case 'database => loadDatabase() // Loading data from database
  case 'file => loadFile() // Loading data from file
  case 'prompt => askUser() // Asking user for data
  case 'argumentList => argumentListExtract() // Accessing argument list for data
  case _ => Failure(new Exception("Unsupported data source"))
}
```

StringSymbol◦ ◦

◦

<https://riptutorial.com/zh-CN/scala/topic/6419/>

45:

- `class MyClass{} // curly braces are optional here as class body is empty`
- `class MyClassWithMethod {def method: MyClass = ???}`
- `new MyClass() //Instantiate`
- `object MyObject // Singleton object`
- `class MyClassWithGenericParameters[V1, V2](v1: V1, i: Int, v2: V2)`
- `class MyClassWithImplicitFieldCreation[V1](val v1: V1, val i: Int)`
- `new MyClassWithGenericParameters(2.3, 4, 5) new MyClassWithGenericParameters[Double, Any](2.3, 4, 5)`
- `class MyClassWithProtectedConstructor protected[my.pack.age](s: String)`

Examples

Scala“”。

```
class MyClass{} // curly braces are optional here as class body is empty
```

new

```
var instance = new MyClass()
```

```
var instance = new MyClass
```

Scala。

```
class MyClass(arg : Int) // Class definition
var instance = new MyClass(2) // Instance instantiation
instance.arg // not allowed
```

MyClassInt。 MyClassarg

```
class MyClass(arg : Int){
  val prop = arg // Class field declaration
}
```

```
var obj = new MyClass(2)
obj.prop // legal statement
```

public

```
class MyClass(val arg : Int) // Class definition with arg declared public
var instance = new MyClass(2) // Instance instantiation
instance.arg //arg is now visible to clients
```

{ } vs

MyClass

```
class MyClass
```

Scala

```
val obj = new MyClass()
```

```
val obj = new MyClass
```

◦ ◦

```
val newThread = new Thread { new Runnable {  
    override def run(): Unit = {  
        // perform task  
        println("Performing task.")  
    }  
}  
  
newThread.start // prints no output
```

Performing task.◦ ◦ new Thread{}◦ Thread

```
val newThread = new Thread {  
    //creating anonymous class extending Thread  
}
```

Runnable◦ public Thread(Runnable target)optional () public Thread()run()◦ ◦

```
val newThread = new Thread ( new Runnable {  
    override def run(): Unit = {  
        // perform task  
        println("Performing task.")  
    }  
}  
)
```

{ }()◦

SingletonCompanion

ScalaJava◦ Scala*Singleton Objects*◦ Singleton_{new}◦

```
object Factorial {  
    private val cache = Map[Int, Int]()  
    def getCache = cache  
}
```

object*singleton'class'trait'*◦ ◦

```
Factorial.getCache() //returns the cache
```

Java

Scala

```
class Factorial(num : Int) {

  def fact(num : Int) : Int = if (num <= 1) 1 else (num * fact(num - 1))

  def calculate() : Int = {
    if (!Factorial.cache.contains(num)) { // num does not exists in cache
      val output = fact(num) // calculate factorial
      Factorial.cache += (num -> output) // add new value in cache
    }

    Factorial.cache(num)
  }
}

object Factorial {
  private val cache = scala.collection.mutable.Map[Int, Int]()
}

val factfive = new Factorial(5)
factfive.calculate // Calculates the factorial of 5 and stores it
factfive.calculate // uses cache this time
val factfiveagain = new Factorial(5)
factfiveagain.calculate // Also uses cache
```

cache

```
object Factorialclass Factorial { private Factorialcache
```

.

```
object Dog {
  def bark: String = "Raf"
}

Dog.bark() // yields "Raf"
```

```
class Dog(val name: String) {

}

object Dog {
  def apply(name: String): Dog = new Dog(name)
}

val dog = Dog("Barky") // Object
val dog = new Dog("Barky") // Class
```

variable.isInstanceOf[Type]

```
variable match {
  case _: Type => true
```

```

    case _ => false
}

```

asInstanceOf

```

val list: List[Any] = List(1, 2, 3)           //> list : List[Any] = List(1, 2, 3)

val upcasting = list.asInstanceOf[Seq[Int]]    //> upcasting : Boolean = true

val shouldBeFalse = list.asInstanceOf[List[String]]
                                           //> shouldBeFalse : Boolean = true

```

```

val chSeqArray: Array[CharSequence] = Array("a") //> chSeqArray : Array[CharSequence] =
Array(a)
val correctlyReified = chSeqArray.asInstanceOf[Array[String]]
                                           //> correctlyReified : Boolean = false

val stringIsACharSequence: CharSequence = ""    //> stringIsACharSequence : CharSequence = ""

val sArray = Array("a")                       //> sArray : Array[String] = Array(a)
val correctlyReified = sArray.asInstanceOf[Array[String]]
                                           //> correctlyReified : Boolean = true

//val arraysAreInvariantInScala: Array[CharSequence] = sArray
//Error: type mismatch; found   : Array[String] required: Array[CharSequence]
//Note: String <: CharSequence, but class Array is invariant in type T.
//You may wish to investigate a wildcard type such as `_ <: CharSequence`. (SLS 3.2.10)
//Workaround:
val arraysAreInvariantInScala: Array[_ <: CharSequence] = sArray
                                           //> arraysAreInvariantInScala : Array[_ <:
CharSequence] = Array(a)

val arraysAreCovariantOnJVM = sArray.asInstanceOf[Array[CharSequence]]
                                           //> arraysAreCovariantOnJVM : Boolean = true

```

variable.asInstanceOf[Type]

```

variable match {
  case _: Type => true
}

```

```

val x = 3                                     //> x : Int = 3
x match {
  case _: Int => true//better: do something
  case _ => false
}                                           //> res0: Boolean = true

x match {
  case _: java.lang.Integer => true//better: do something
  case _ => false
}                                           //> res1: Boolean = true

x.asInstanceOf[Int]                         //> res2: Boolean = true

//x.asInstanceOf[java.lang.Integer]//fruitless type test: a value of type Int cannot also be

```

```

a Integer

trait Valuable { def value: Int}
case class V(val value: Int) extends Valuable

val y: Valuable = V(3)
y.isInstanceOf[V]
y.asInstanceOf[V]

//> y : Valuable = V(3)
//> res3: Boolean = true
//> res4: V = V(3)

```

JVMJS/。

Scala。 。 。

```

class Foo(x: Int, y: String) {
  val xy: String = y * x
  /* now xy is a public member of the class */
}

class Bar {
  ...
}

```

val

```

class Baz(val z: String)
// Baz has no other members or methods, so the body may be omitted

val foo = new Foo(4, "ab")
val baz = new Baz("I am a baz")
foo.x // will not compile: x is not a member of Foo
foo.xy // returns "abababab": xy is a member of Foo
baz.z // returns "I am a baz": z is a member of Baz
val bar0 = new Bar
val bar1 = new Bar() // Constructor parentheses are optional here

```

```

class DatabaseConnection
  (host: String, port: Int, username: String, password: String) {
  /* first connect to the DB, or throw an exception */
  private val driver = new AwesomeDB.Driver()
  driver.connect(host, port, username, password)
  def isConnected: Boolean = driver.isConnected
  ...
}

```

;connectdisconnectIO。

“”。

```
def this(...) = ee
```

```

class Person(val fullName: String) {
  def this(firstName: String, lastName: String) = this(s"$firstName $lastName")
}

// usage:
new Person("Grace Hopper").fullName // returns Grace Hopper
new Person("Grace", "Hopper").fullName // returns Grace Hopper

```



```
class Person private(val fullName: String) {  
    def this(firstName: String, lastName: String) = this(s"$firstName $lastName")  
}  
  
new Person("Ada Lovelace") // won't compile  
new Person("Ada", "Lovelace") // compiles
```

◦

<https://riptutorial.com/zh-CN/scala/topic/2047/>

46:

Examples

Option ◦

```
sealed abstract class Option[+A] {
  def isEmpty: Boolean
  def get: A

  final def fold[B](ifEmpty: => B)(f: A => B): B =
    if (isEmpty) ifEmpty else f(this.get)

  // lots of methods...
}

case class Some[A](value: A) extends Option[A] {
  def isEmpty = false
  def get = value
}

case object None extends Option[Nothing] {
  def isEmpty = true
  def get = throw new NoSuchElementException("None.get")
}
```

fold B◦

◦ x Ax ◦

```
def f[A](x: A): A = x

f(1)           // 1
f("two")       // "two"
f[Float](3)    // 3.0F
```

Scala◦ A*

```
def g[A](x: A): A = 2 * x // Won't compile
```

Ints

```
trait IntList { ... }

class Cons(val head: Int, val tail: IntList) extends IntList { ... }

class Nil extends IntList { ... }
```

BooleanDouble

```
trait List[T] {  
  def isEmpty: Boolean  
  def head: T  
  def tail: List[T]  
}  
  
class Cons[T](val head: T, val tail: List[T]) extends List[T] {  
  def isEmpty: Boolean = false  
}  
  
class Nil[T] extends List[T] {  
  def isEmpty: Boolean = true  
  
  def head: Nothing = throw NoSuchElementException("Nil.head")  
  
  def tail: Nothing = throw NoSuchElementException("Nil.tail")  
}
```

<https://riptutorial.com/zh-CN/scala/topic/782/-->

47:

Examples

Scala ◦ ""

```
val i = 1 + 2           // the type of i is Int
val s = "I am a String" // the type of s is String
def squared(x : Int) = x*x // the return type of squared is Int
```

◦ ◦

```
val i: Int = 1 + 2
val s: String = "I am a String"
def squared(x : Int): Int = x*x
```

Scala

```
case class InferedPair[A, B](a: A, b: B)

val pairFirstInst = InferedPair("Husband", "Wife") //type is InferedPair[String, String]

// Equivalent, with type explicitly defined
val pairSecondInst: InferedPair[String, String]
    = InferedPair[String, String]("Husband", "Wife")
```

Java 7 [Diamond Operator](#) ◦

Scala ◦

```
def add(a, b) = a + b // Does not compile
def add(a: Int, b: Int) = a + b // Compiles
def add(a: Int, b: Int): Int = a + b // Equivalent expression, compiles
```

```
// Does not compile
def factorial(n: Int) = if (n == 0 || n == 1) 1 else n * factorial(n - 1)
// Compiles
def factorial(n: Int): Int = if (n == 0 || n == 1) 1 else n * factorial(n - 1)
```

◦

```
def get[T]: Option[T] = ???
```

Nothing ◦ NotNothing RuntimeClassClassTagsNothing RuntimeClass

```
@implicitNotFound("Nothing was inferred")
sealed trait NotNothing[-T]
```

```

object NotNothing {
  implicit object notNothing extends NotNothing[Any]
  //We do not want Nothing to be inferred, so make an ambiguous implicit
  implicit object `\n The error is because the type parameter was resolved to Nothing` extends
NotNothing[Nothing]
  //For classtags, RuntimeClass can also be inferred, so making that ambiguous too
  implicit object ` \n The error is because the type parameter was resolved to RuntimeClass`
extends NotNothing[RuntimeClass]
}

object ObjectStore {
  //Using context bounds
  def get[T: NotNothing]: Option[T] = {
    ???
  }

  def newArray[T](length: Int = 10)(implicit ct: ClassTag[T], evNotNothing: NotNothing[T]):
Option[Array[T]] = ???
}

```

```

object X {
  //Fails to compile
  //val nothingInferred = ObjectStore.get

  val anOption = ObjectStore.get[String]
  val optionalArray = ObjectStore.newArray[AnyRef]()

  //Fails to compile
  //val runtimeClassInferred = ObjectStore.newArray()
}

```

<https://riptutorial.com/zh-CN/scala/topic/4918/>

48:

Examples

◦ ◦

type Apply[A]Projection type Apply[A] def apply[A](a: A): Apply[A] ◦

```
trait Projection {  
  type Apply[A] // <: Any  
  def apply[A](a: A): Apply[A]  
}
```

type Apply[A]◦

map◦ **map**HList

```
sealed trait HList {  
  type Map[P <: Projection] <: HList  
  def map[P <: Projection](p: P): Map[P]  
}
```

HNil◦ trait HNilHNilHNil.type

```
sealed trait HNil extends HList  
case object HNil extends HNil {  
  type Map[P <: Projection] = HNil  
  def map[P <: Projection](p: P): Map[P] = HNil  
}
```

HCons◦ P#Apply[H] ◦ T#Map[P] HList

```
case class HCons[H, T <: HList](head: H, tail: T) extends HList {  
  type Map[P <: Projection] = HCons[P#Apply[H], T#Map[P]]  
  def map[P <: Projection](p: P): Map[P] = HCons(p.apply(head), tail.map(p))  
}
```

- HCons[Option[String], HCons[Option[Int], HNil]]HCons[Option[String], HCons[Option[Int], HNil]]

```
HCons("1", HCons(2, HNil)).map(new Projection {  
  type Apply[A] = Option[A]  
  def apply[A](a: A): Apply[A] = Some(a)  
})
```

<https://riptutorial.com/zh-CN/scala/topic/3738/>

49:

“” ◦ ◦ ◦ Scala continuation`shift / reset`◦

continuation <https://github.com/scala/scala-continuations>

- `reset {...} // Continuations`
- `shift {...} //`
- `A @cpsParam [BC] //A => BC`
- `@cps [A] // @cpsParam[AA]`
- `@suspendable // @cpsParam[UnitUnit]`

`shiftresetInt.+ Long`◦ ◦ “”API◦

◦ [continuation monad](#) `monadcontinuationflatMap`◦

Examples

Continuations

```
// Takes a callback and executes it with the read value
def readFile(path: String)(callback: Try[String] => Unit): Unit = ???

readFile(path) { _.flatMap { file1 =>
  readFile(path2) { _.foreach { file2 =>
    processFiles(file1, file2)
  }}
}}
```

`readFilereadFile`◦

`continuation`◦

```
reset { // Reset is a delimiter for continuations.
  for { // Since the callback hell is relegated to continuation library machinery.
    // a for-comprehension can be used
    file1 <- shift(readFile(path1)) // shift has type ((A => B) => C) => A)
    // We use it as (((Try[String] => Unit) => Unit) => Try[String])
    // It takes all the code that occurs after it is called, up to the end of reset, and
    // makes it into a closure of type (A => B).
    // The reason this works is that shift is actually faking its return type.
    // It only pretends to return A.
    // It actually passes that closure into its function parameter (readFile(path1) here),
    // And that function calls what it thinks is a normal callback with an A.
    // And through compiler magic shift "injects" that A into its own callsite.
    // So if readFile calls its callback with parameter Success("OK"),
    // the shift is replaced with that value and the code is executed until the end of reset,
    // and the return value of that is what the callback in readFile returns.
    // If readFile called its callback twice, then the shift would run this code twice too.
    // Since readFile returns Unit though, the type of the entire reset expression is Unit
  }
```

```

    // Think of shift as shifting all the code after it into a closure,
    // and reset as resetting all those shifts and ending the closures.
    file2 <- shift(readFile(path2))
  } processFiles(file1, file2)
}

// After compilation, shift and reset are transformed back into closures
// The for comprehension first desugars to:
reset {
  shift(readFile(path1)).flatMap { file1 => shift(readFile(path2)).foreach { file2 =>
processFiles(file1, file2) } }
}
// And then the callbacks are restored via CPS transformation
readFile(path1) { _.flatMap { file1 => // We see how shift moves the code after it into a
closure
  readFile(path2) { _.foreach { file2 =>
    processFiles(file1, file2)
  }}
}} // And we see how reset closes all those closures
// And it looks just like the old version!

```

resetshift reset $\circ$ shift(((A => B) => C) => A) (((A => B) => C) => (A @cpsParam[B, C])) $\circ$ CPS $\circ$
 shiftreset "" $\circ$

reset A @cpsParam[B, C]A $\circ$ A => B B C "" CPS C

Scaladoc

```

val sessions = new HashMap[UUID, Int=>Unit]
def ask(prompt: String): Int @suspendable = // alias for @cpsParam[Unit, Unit]. @cps[Unit] is
also an alias. (@cps[A] = @cpsParam[A,A])
  shift {
    k: (Int => Unit) => {
      println(prompt)
      val id = uuidGen
      sessions += id -> k
    }
  }

def go(): Unit = reset {
  println("Welcome!")
  val first = ask("Please give me a number") // Uses CPS just like shift
  val second = ask("Please enter another number")
  printf("The sum of your numbers is: %d\n", first + second)
}

```

ask "" $\circ$ go $\circ$

<https://riptutorial.com/zh-CN/scala/topic/8312/>

50:

- `trait {selfId => / selfId this /}`
- `trait Type {selfIdOtherType => /*selfId OtherType */`
- `trait Type {selfIdOtherType1 with OtherType2 => /* selfIdOtherType1OtherType2 */`

◦

Examples

◦ `this`◦

◦

```
trait Container[+T] {  
  def add(o: T): Unit  
}  
  
trait PermanentStorage[T] {  
  /* Constraint on self type: it should be Container  
   * we can refer to that type as `identifier`, usually `this` or `self`  
   * or the type's name is used. */  
  identifier: Container[T] =>  
  
  def save(o: T): Unit = {  
    identifier.add(o)  
    //Do something to persist too.  
  }  
}
```

Container PermanentStorage ◦

<https://riptutorial.com/zh-CN/scala/topic/4639/>

51:

Scala `def val var class` ◦

-
-
- []
- [fromWhere]
-
- protected [fromWhere]

Examples

public ◦

```
package com.example {
  class FooClass {
    val x = "foo"
  }
}

package an.other.package {
  class BarClass {
    val foo = new com.example.FooClass
    foo.x // <- Accessing a public value from another package
  }
}
```

◦

```
package com.example {
  class FooClass {
    private val x = "foo"
    def aFoo(otherFoo: FooClass) {
      otherFoo.x // <- Accessing from another instance of the same class
    }
  }
  class BarClass {
    val f = new FooClass
    f.x // <- This will not compile
  }
}
```

◦

```
package com.example {
  class FooClass {
    private val x = "foo"
    private[example] val y = "bar"
  }
  class BarClass {
    val f = new FooClass
  }
}
```

```

    f.x // <- Will not compile
    f.y // <- Will compile
  }
}

```

“ - ”。

```

class FooClass {
  private[this] val x = "foo"
  def aFoo(otherFoo: FooClass) = {
    otherFoo.x // <- This will not compile, accessing x outside the object instance
  }
}

```

。

```

class FooClass {
  protected val x = "foo"
}
class BarClass extends FooClass {
  val y = x // It is a subclass instance, will compile
}
class ClassB {
  val f = new FooClass
  f.x // <- This will not compile
}

```

。

```

package com.example {
  class FooClass {
    protected[example] val x = "foo"
  }
  class ClassB extends FooClass {
    val y = x // It's in the protected scope, will compile
  }
}
package com {
  class BarClass extends com.example.FooClass {
    val y = x // <- Outside the protected scope, will not compile
  }
}

```

<https://riptutorial.com/zh-CN/scala/topic/9705/>

ParseResult

ParseResult

- ◦
- ◦ ◦
- ◦ ◦

Examples

```
import scala.util.parsing.combinator._

class SimpleParser extends RegexParsers {
  // Define a grammar rule, turn it into a regex, and apply it the input.
  def word: Parser[String] = "[A-Z][a-z]+" ^> { _.toString }
}

object SimpleParser extends SimpleParser {
  val parseAlice = parse(word, "Alice went to Alamo Square.")
  val parseBarb = parse(word, "barb went Upside Down.")
}

//Successfully finds a match
println(SimpleParser.parseAlice)
//Fails to find a match
println(SimpleParser.parseBarb)
```

```
[1.6] parsed: Alice
res0: Unit = ()

[1.1] failure: string matching regex `[A-Z][a-z]+' expected but `b' found

barb went Upside Down.
^
```

Alice[1.6]1 6◦

<https://riptutorial.com/zh-CN/scala/topic/3730/>

53: Scala

Examples

Linuxdpkg

DebianUbuntu.deb◦ [Scala](#)◦ scala-xxxdeb◦

scala deb

```
sudo dpkg -i scala-x.x.x.deb
```

```
which scala
```

PATH◦ scala

```
scala
```

Scala REPL◦

Ubuntu

[curl](#)[Lightbend](#)

```
curl -O http://downloads.lightbend.com/scala/2.xx.x/scala-2.xx.x.tgz
```

```
tar/usr/local/share/opt/bin
```

```
unzip scala-2.xx.x.tgz
mv scala-2.xx.x /usr/local/share/scala
```

```
PATH~/.profile~/.bash_profile~/.bashrc
```

```
$SCALA_HOME=/usr/local/share/scala
export PATH=$SCALA_HOME/bin:$PATH
```

```
which scala
```

PATH◦ scala

```
scala
```

Scala REPL◦

Mac OSXMacports

MacPorts Mac OS X

```
port list | grep scala
```

Scala◦ Scala2.11

```
sudo port install scala2.11
```

2.11◦

\$PATH◦

```
which scala
```

Scala◦

```
scala
```

Scala REPL◦

Scala <https://riptutorial.com/zh-CN/scala/topic/2921/scala>

54:

Examples

Scala `+ - * ++ ◦ 1 + 2 1.+(2) ◦ """ ◦`

```
class Matrix(rows: Int, cols: Int, val data: Seq[Seq[Int]]){
  def +(that: Matrix) = {
    val newData = for (r <- 0 until rows) yield
      for (c <- 0 until cols) yield this.data(r)(c) + that.data(r)(c)

    new Matrix(rows, cols, newData)
  }
}
```

```
val a = new Matrix(2, 2, Seq(Seq(1,2), Seq(3,4)))
val b = new Matrix(2, 2, Seq(Seq(1,2), Seq(3,4)))

// could also be written a.+(b)
val sum = a + b
```

◦ Scala ◦

`parcimony ◦ ◦ add+ ◦`

`unary_◦ unary_+ unary_- unary_!unary_~`

```
class Matrix(rows: Int, cols: Int, val data: Seq[Seq[Int]]){
  def +(that: Matrix) = {
    val newData = for (r <- 0 until rows) yield
      for (c <- 0 until cols) yield this.data(r)(c) + that.data(r)(c)

    new Matrix(rows, cols, newData)
  }

  def unary_- = {
    val newData = for (r <- 0 until rows) yield
      for (c <- 0 until cols) yield this.data(r)(c) * -1

    new Matrix(rows, cols, newData)
  }
}
```

```
val a = new Matrix(2, 2, Seq(Seq(1,2), Seq(3,4)))
val negA = -a
```

`parcimony ◦ ◦`

<https://riptutorial.com/zh-CN/scala/topic/2271/>

55:

- class Some [+ T]valueTOption [T]
- []
- [T]T

Some (value) Some (value) None ◦

Examples

Option **S** - NoneSome (x) x ◦

```
val option: Option[String] = ???

option.map(_.trim) // None if option is None, Some(s.trim) if Some(s)
option.foreach(println) // prints the string if it exists, does nothing otherwise
option.forall(_.length > 4) // true if None or if Some(s) and s.length > 4
option.exists(_.length > 4) // true if Some(s) and s.length > 4
option.toList // returns an actual list
```

OptionNull

Java_{null}◦ ScalaOptionnull◦ Optionnull◦

NoneOption◦ SomeOption◦

```
val nothing = Option(null) // None
val something = Option("Aren't options cool?") // Some("Aren't options cool?")
```

nullJava

```
val resource = Option(JavaLib.getResource())
// if null, then resource = None
// else resource = Some(resource)
```

getResource()nullresourceNone◦ Some(resource)◦ OptionOption◦ None value == null isDefined

```
val resource: Option[Resource] = Option(JavaLib.getResource())
if (resource.isDefined) { // resource is `Some(_)` type
  val r: Resource = resource.get
  r.connect()
}
```

null

```
val resource: Option[Resource] = Option(JavaLib.getResource())
if (resource.isEmpty) { // resource is `None` type.
```



```
System.out.println("Resource is empty! Cannot connect.")
}
```

Option "" Option.foreach

```
val resource: Option[Resource] = Option(JavaLib.getResource())
resource foreach (r => r.connect())
// if r is defined, then r.connect() is run
// if r is empty, then it does nothing
```

ResourceOption[Resource]Option◦ getOrElse

```
lazy val defaultResource = new Resource()
val resource: Resource = Option(JavaLib.getResource()).getOrElse(defaultResource)
```

JavaScalaOption JavaOptionnull

```
val resource: Option[Resource] = ???
JavaLib.sendResource(resource.orNull)
JavaLib.sendResource(resource.getOrElse(defaultResource)) //
```

Option◦ Option◦

Option SomeNone ◦

Some None◦

Optionnull◦ NullPointerException Map FlatMap◦

```
val countries = Map(
  "USA" -> "Washington",
  "UK" -> "London",
  "Germany" -> "Berlin",
  "Netherlands" -> "Amsterdam",
  "Japan" -> "Tokyo"
)

println(countries.get("USA")) // Some(Washington)
println(countries.get("France")) // None
println(countries.get("USA").get) // Washington
println(countries.get("France").get) // Error: NoSuchElementException
println(countries.get("USA").getOrElse("Nope")) // Washington
println(countries.get("France").getOrElse("Nope")) // Nope
```

Option[A] ◦ ◦

OptionflatMap◦ ◦ Option •◦

```
val firstOption: Option[Int] = Option(1)
val secondOption: Option[Int] = Option(2)
```

```
val myResult = for {
  firstValue <- firstOption
  secondValue <- secondOption
} yield firstValue + secondValue
// myResult: Option[Int] = Some(3)
```

NoneNone ◦

```
val firstOption: Option[Int] = Option(1)
val secondOption: Option[Int] = None

val myResult = for {
  firstValue <- firstOption
  secondValue <- secondOption
} yield firstValue + secondValue
// myResult: Option[Int] = None
```

Monad **S**◦ Monad

◦ OptionIterable .toIterableOptionIterable ◦

```
val option: Option[Int] = Option(1)
val iterable: Iterable[Int] = Iterable(2, 3, 4, 5)

// does NOT compile since we cannot mix Monads in a for comprehension
// val myResult = for {
//   optionValue <- option
//   iterableValue <- iterable
// } yield optionValue + iterableValue

// It does compile when adding a .toIterable on the option
val myResult = for {
  optionValue <- option.toIterable
  iterableValue <- iterable
} yield optionValue + iterableValue
// myResult: Iterable[Int] = List(2, 3, 4, 5)
```

for comprehension◦ .toIterable ◦

<https://riptutorial.com/zh-CN/scala/topic/2293/>

56:

Examples

◦ ◦ ◦

Scala◦ @tailrec◦ ◦

◦

```
def fact(i : Int) : Int = {  
    if(i <= 1) i  
    else i * fact(i-1)  
}  
  
println(fact(5))
```

```
(fact 5)  
(* 5 (fact 4))  
(* 5 (* 4 (fact 3)))  
(* 5 (* 4 (* 3 (fact 2))))  
(* 5 (* 4 (* 3 (* 2 (fact 1)))))  
(* 5 (* 4 (* 3 (* 2 (* 1 (fact 0))))))  
(* 5 (* 4 (* 3 (* 2 (* 1 * 1))))))  
(* 5 (* 4 (* 3 (* 2))))  
(* 5 (* 4 (* 6)))  
(* 5 (* 24))  
120
```

@tailrec could not optimize @tailrec annotated method fact: it contains a recursive call not in tail position

◦

```
def fact_with_tailrec(i : Int) : Long = {  
    @tailrec  
    def fact_inside(i : Int, sum: Long) : Long = {  
        if(i <= 1) sum  
        else fact_inside(i-1, sum*i)  
    }  
    fact_inside(i, 1)  
}  
  
println(fact_with_tailrec(5))
```

```
(fact_with_tailrec 5)  
(fact_inside 5 1)  
(fact_inside 4 5)  
(fact_inside 3 20)  
(fact_inside 2 60)  
(fact_inside 1 120)
```

fact_inside◦ fact_with_tail 1000000 fact_with_tail 3◦ ◦

trampolinescala.util.control.TailCalls

StackOverflowError◦ ScalaTailCallcontinuation◦

TailCallscaladoc

```
import scala.util.control.TailCalls._

def isEven(xs: List[Int]): TailRec[Boolean] =
  if (xs.isEmpty) done(true) else tailcall(isOdd(xs.tail))

def isOdd(xs: List[Int]): TailRec[Boolean] =
  if (xs.isEmpty) done(false) else tailcall(isEven(xs.tail))

// Does this List contain an even number of elements?
isEven((1 to 100000).toList).result

def fib(n: Int): TailRec[Int] =
  if (n < 2) done(n) else for {
    x <- tailcall(fib(n - 1))
    y <- tailcall(fib(n - 2))
  } yield (x + y)

// What is the 40th entry of the Fibonacci series?
fib(40).result
```

<https://riptutorial.com/zh-CN/scala/topic/3889/>

Examples

```
sealed trait SuperType
case object A extends SuperType
case object B extends SuperType
case object C extends SuperType

val pfA: PartialFunction[SuperType, Int] = {
  case A => 5
}

val pfB: PartialFunction[SuperType, Int] = {
  case B => 10
}

val input: Seq[SuperType] = Seq(A, B, C)

input.map(pfA orElse pfB orElse {
  case _ => 15
}) // Seq(5, 10, 15)
```

`orElse` ◦ ◦ ◦

◦ [Akka Actor](#) ◦

`collect`

case _ ◦ `ScalaScala``collect` ◦ /◦

1

```
val sqRoot: PartialFunction[Double, Double] = { case n if n > 0 => math.sqrt(n) }
```

`collect` **combinator**

```
List(-1.1, 2.2, 3.3, 0).collect(sqRoot)
```

```
List(-1.1, 2.2, 3.3, 0).filter(sqRoot.isDefinedAt).map(sqRoot)
```

2

```
sealed trait SuperType // `sealed` modifier allows inheritance within current build-unit only
case class A(value: Int) extends SuperType
case class B(text: String) extends SuperType
case object C extends SuperType

val input: Seq[SuperType] = Seq(A(5), B("hello"), C, A(25), B(""))
```

```
input.collect {
  case A(value) if value < 10    => value.toString
  case B(text) if text.nonEmpty => text
} // Seq("5", "hello")
```

- ◦ case◦
- ◦
- if◦

Scala **partial** - PartialFunctionFunction1◦ case

```
val pf: PartialFunction[Boolean, Int] = {
  case true => 7
}

pf.isDefinedAt(true) // returns true
pf(true) // returns 7

pf.isDefinedAt(false) // returns false
pf(false) // throws scala.MatchError: false (of class java.lang.Boolean)
```

- Function1 **total** ◦

Scala◦ case

```
sealed trait SuperType // `sealed` modifier allows inheritance within current build-unit only
case object A extends SuperType
case object B extends SuperType
case object C extends SuperType

val input: Seq[SuperType] = Seq(A, B, C)

input.map {
  case A => 5
  case _ => 10
} // Seq(5, 10, 10)
```

match◦

```
input.map { item =>
  item match {
    case A => 5
    case _ => 10
  }
} // Seq(5, 10, 10)
```

case

```
val input = Seq("A" -> 1, "B" -> 2, "C" -> 3)

input.map { case (a, i) =>
  a + i.toString
} // Seq("A1", "B2", "C3")
```

map

◦

```
val numberNames = Map(1 -> "One", 2 -> "Two", 3 -> "Three")

// 1. No extraction
numberNames.map(it => s"${it._1} is written ${it._2}" )

// 2. Extraction within a normal function
numberNames.map(it => {
    val (number, name) = it
    s"$number is written $name"
})

// 3. Extraction via a partial function (note the brackets in the parentheses)
numberNames.map({ case (number, name) => s"$number is written $name" })
```

partial ◦

<https://riptutorial.com/zh-CN/scala/topic/1638/>

Examples

Try with `map` `getOrElse` `flatMap`

```
import scala.util.Try

val i = Try("123".toInt)    // Success(123)
i.map(_ + 1).getOrElse(321) // 124

val j = Try("abc".toInt)    // Failure(java.lang.NumberFormatException)
j.map(_ + 1).getOrElse(321) // 321

Try("123".toInt) flatMap { i =>
  Try("234".toInt)
    .map(_ + i)
} // Success(357)
```

Try with pattern matching

```
Try(parsePerson("John Doe")) match {
  case Success(person) => println(person.surname)
  case Failure(ex)    => // Handle error ...
}
```

/

```
def getPersonFromWebService(url: String): Either[String, Person] = {

  val response = webServiceClient.get(url)

  response.webService.status match {
    case 200 => {
      val person = parsePerson(response)
      if(!isValid(person)) Left("Validation failed")
      else Right(person)
    }

    case _ => Left(s"Request failed with error code $response.status")
  }
}
```

```
getPersonFromWebService("http://some-webservice.com/person") match {
  case Left(errorMessage) => println(errorMessage)
  case Right(person)      => println(person.surname)
}
```

```
val maybePerson: Option[Person] = getPersonFromWebService("http://some-
webservice.com/person").right.toOption
```


null **Java** null ◦ Some None **Option** ◦

try-catch **Option** ◦

`Option[T] Some(value) T None`

```
def findPerson(name: String): Option[Person]
```

`None ◦ Person Some ◦ Option ◦`

```
findPerson(personName) match {  
  case Some(person) => println(person.surname)  
  case None => println(s"No person found with name $personName")  
}
```

mapgetOrElse

```
val name = findPerson(personName).map(_.firstName).getOrElse("Unknown")  
println(name) // Prints either the name of the found person or "Unknown"
```

```
val name = findPerson(personName).fold("Unknown")(_.firstName)  
// equivalent to the map getOrElse example above.
```

Java

Option **Java**

```
val s: Option[String] = Option("hello")  
s.orNull              // "hello": String  
s.getOrElse(null)    // "hello": String  
  
val n: Option[Int] = Option(42)  
n.orNull             // compilation failure (Cannot prove that Null <: Int.)  
n.getOrElse(null)    // 42
```

exception **Future** **recover** ◦

```
def runFuture: Future = Future { throw new FairlyStupidException }  
  
val itWillBeAwesome: Future = runFuture
```

`.....FutureException ◦ FairlyStupidExceptionException`

```
val itWillBeAwesomeOrIllRecover = runFuture recover {  
  case stupid: FairlyStupidException =>  
    BadRequest("Another stupid exception!")  
}
```

recoverThrowablePartialFunction Future◦

Future

```
def runNotFuture: Unit = throw new FairlyStupidException

try {
  runNotFuture
} catch {
  case e: FairlyStupidException => BadRequest("Another stupid exception!")
}
```

Future◦ ◦

try-catch

Try OptionEither ScalaJavatry-catchfinally◦ catch

```
try {
  // ... might throw exception
} catch {
  case ioe: IOException => ... // more specific cases first
  case e: Exception => ...
  // uncaught types will be thrown
} finally {
  // ...
}
```

EitherOption

EitherOptionscala.util.control.Exceptionscala.util.control.Exception

```
import scala.util.control.Exception._

val plain = "71a"
val optionInt: Option[Int] = catching(classOf[java.lang.NumberFormatException]) opt {
  plain.toInt }
val eitherInt = Either[Throwable, Int] = catching(classOf[java.lang.NumberFormatException])
  either { plain.toInt }
```

<https://riptutorial.com/zh-CN/scala/topic/910/>

Examples

+ - “ProducerAA”

```
trait Producer[+A] {
  def produce: A
}
```

“”◦ AProducer[X] <: Producer[Y] X <: Y ◦ Producer[Cat] Producer[Animal] ◦

◦ Co[Cat] <: Co[Animal] Co[Cat] def handle(a: Cat): Unit Co[Animal] Animal def handle(a: Cat): Unit

```
trait Co[+A] {
  def produce: A
  def handle(a: A): Unit
}
```

◦ BA◦ Option[X] <: Option[Y] X <: Y Option[X] <: Option[Y] Option[X] def getOrElse[B >: X] (b: => B): B X◦ Option[Y] Y

```
trait Option[+A] {
  def getOrElse[B >: A] (b: => B): B
}
```

- trait A[B] “AB”◦ A[Cat] A[Animal] / - A[Cat] <: A[Animal] A[Cat] >: A[Animal] Cat Animal◦

◦

- - “HandlerAA”

```
trait Handler[-A] {
  def handle(a: A): Unit
}
```

“”◦ AHandler[X] <: Handler[Y] X >: Y ◦ Handler[Animal] Handler[Cat] Handler[Animal]◦

◦ Contra[Animal] <: Contra[Cat] Contra[Animal] def produce: Animal Contra[Cat]

```
trait Contra[-A] {
  def handle(a: A): Unit
  def produce: A
}
```

- Handler[Animal] Handler[Cat] “”◦

◦ ofCat ofAnimal

```
implicit def ofAnimal: Handler[Animal] = ???
implicit def ofCat: Handler[Cat] = ???

implicitly[Handler[Cat]].handle(new Cat)
```

dotty scala.math.OrderingTo

```
trait Person
object Person {
  implicit def ordering[A <: Person]: Ordering[A] = ???
}
```

★

```
trait Animal { def name: String }
case class Dog(name: String) extends Animal

object Animal {
  def printAnimalNames(animals: Seq[Animal]) = {
    animals.foreach(animal => println(animal.name))
  }
}

val myDogs: Seq[Dog] = Seq(Dog("Curly"), Dog("Larry"), Dog("Moe"))

Animal.printAnimalNames(myDogs)
// Curly
// Larry
// Moe
```

Seq[Dog]Seq[Animal] Seq ◦

★

◦ T ◦

```
trait LocalVariance[T]{
  /// ??? throws a NotImplementedError
  def produce: T = ???
  // the implicit evidence provided by the compiler confirms that S is a
  // subtype of T.
  def handle[S](s: S)(implicit evidence: S <:< T) = {
    // and we can use the evidence to convert s into t.
    val t: T = evidence(s)
    ???
  }
}

trait A {}
trait B extends A {}

object Test {
  val lv = new LocalVariance[A] {}

  // now we can pass a B instead of an A.
  lv.handle(new B {})
}
```

```
}
```

<https://riptutorial.com/zh-CN/scala/topic/1651/>

Examples

A trait

```
trait Show[A] {
  def show(a: A): String
}
```

◦

```
object Show {
  implicit val intShow: Show[Int] = new Show {
    def show(x: Int): String = x.toString
  }

  implicit val dateShow: Show[java.util.Date] = new Show {
    def show(x: java.util.Date): String = x.getTime.toString
  }

  // ..etc
}
```

```
def log[A](a: A)(implicit showInstance: Show[A]): Unit = {
  println(showInstance.show(a))
}
```

```
def log[A: Show](a: A): Unit = {
  println(implicitly[Show[A]].show(a))
}
```

log◦ logAShow[A]

```
log(10) // prints: "10"
log(new java.util.Date(1469491668401L)) // prints: "1469491668401"
log(List(1,2,3)) // fails to compile with
                  // could not find implicit value for evidence parameter of type
                  Show[List[Int]]
```

Show◦ String◦ toString◦ toString◦ ShowlogString◦

◦

```
trait Show[A] {
  def show: String
}
```

Scala◦ PersonShow

```
class Person(val fullName: String) {  
  def this(firstName: String, lastName: String) = this(s"$firstName $lastName")  
}
```

PersonShow

```
object Person {  
  implicit val personShow: Show[Person] = new Show {  
    def show(p: Person): String = s"Person(${p.fullname}) "  
  }  
}
```

object Person class Personobject Person ◦

ScalaSimple Type Class◦

import◦ Simple Type Classlog

```
object MyShow {  
  implicit val personShow: Show[Person] = new Show {  
    def show(p: Person): String = s"Person(${p.fullname}) "  
  }  
}  
  
def logPeople(persons: Person*): Unit = {  
  import MyShow.personShow  
  persons foreach { p => log(p) }  
}
```

Scala◦ ""◦ /◦

```
// The mathematical definition of "Addable" is "Semigroup"  
trait Addable[A] {  
  def add(x: A, y: A): A  
}
```

trait

```
object Instances {  
  
  // Instance for Int  
  // Also called evidence object, meaning that this object saw that Int learned how to be  
  added  
  implicit object addableInt extends Addable[Int] {  
    def add(x: Int, y: Int): Int = x + y  
  }  
  
  // Instance for String  
  implicit object addableString extends Addable[String] {  
    def add(x: String, y: String): String = x + y  
  }  
}
```

```
}
```

Addable

```
import Instances._  
val three = addableInt.add(1,2)
```

1.add(2) ◦ **“Ops”**Addable◦

```
object Ops {  
  implicit class AddableOps[A](self: A)(implicit A: Addable[A]) {  
    def add(other: A): A = A.add(self, other)  
  }  
}
```

add IntString

```
object Main {  
  
  import Instances._ // import evidence objects into this scope  
  import Ops._       // import the wrappers  
  
  def main(args: Array[String]): Unit = {  
  
    println(1.add(5))  
    println("mag".add("net"))  
    // println(1.add(3.141)) // Fails because we didn't create an instance for Double  
  
  }  
}
```

simulacrum“Ops”

```
import simulacrum._  
  
@typeclass trait Addable[A] {  
  @op("|+|") def add(x: A, y: A): A  
}
```

<https://riptutorial.com/zh-CN/scala/topic/3835/>

61:

Examples

◦

```
val names = List("Kathryn", "Allie", "Beth", "Serin", "Alana")
```

sorted() [math.Ordering](#) [lexographic](#)

```
names.sorted
// results in: List(Alana, Allie, Beth, Kathryn, Serin)
```

sortWith

```
names.sortWith(_.length < _.length)
// results in: List(Beth, Allie, Serin, Alana, Kathryn)
```

sortBy

```
//A set of vowels to use
val vowels = Set('a', 'e', 'i', 'o', 'u')

//A function that counts the vowels in a name
def countVowels(name: String) = name.count(l => vowels.contains(l.toLowerCase))

//Sorts by the number of vowels
names.sortBy(countVowels)
//result is: List(Kathryn, Beth, Serin, Allie, Alana)
```

[reverse](#)

```
names.sorted.reverse
//results in: List(Serin, Kathryn, Beth, Allie, Alana)
```

Java [java.util.Arrays.sort](#) **Scala** [scala.util.Sorting.quickSort](#)

```
java.util.Arrays.sort(data)
scala.util.Sorting.quickSort(data)
```

/◦ [Scala Collection sortedsortWithsortBy Performance](#) ◦

nx

[fill](#)◦ List fill

```
// List.fill(n) (x)
scala > List.fill(3) ("Hello World")
```

```
res0: List[String] = List(Hello World, Hello World, Hello World)
```

Cheatsheet

VectorList ◦ ListVector ◦

```
List[Int]()           // Declares an empty list of type Int
List.empty[Int]       // Uses `empty` method to declare empty list of type Int
Nil                  // A list of type Nothing that explicitly has nothing in it

List(1, 2, 3)         // Declare a list with some elements
1 :: 2 :: 3 :: Nil    // Chaining element prepending to an empty list, in a LISP-style
```

```
List(1, 2, 3).headOption // Some(1)
List(1, 2, 3).head       // 1

List(1, 2, 3).lastOption // Some(3)
List(1, 2, 3).last       // 3, complexity is O(n)

List(1, 2, 3)(1)         // 2, complexity is O(n)
List(1, 2, 3)(3)         // java.lang.IndexOutOfBoundsException: 4
```

```
0 :: List(1, 2, 3)       // List(0, 1, 2, 3)
```

```
List(1, 2, 3) :+ 4       // List(1, 2, 3, 4), complexity is O(n)
```

```
List(1, 2) ::: List(3, 4) // List(1, 2, 3, 4)
List.concat(List(1,2), List(3, 4)) // List(1, 2, 3, 4)
List(1, 2) ++ List(3, 4) // List(1, 2, 3, 4)
```

```
List(1, 2, 3).find(_ == 3)           // Some(3)
List(1, 2, 3).map(_ * 2)              // List(2, 4, 6)
List(1, 2, 3).filter(_ % 2 == 1)     // List(1, 3)
List(1, 2, 3).fold(0)((acc, i) => acc + i * i) // 1 * 1 + 2 * 2 + 3 * 3 = 14
List(1, 2, 3).foldLeft("Foo")(_ + _.toString) // "Foo123"
List(1, 2, 3).foldRight("Foo")(_ + _.toString) // "123Foo"
```

Cheatsheet

Mapmap ◦

```
Map[String, Int]()
val m1: Map[String, Int] = Map()
val m2: String Map Int = Map()
```

tuples ◦

```
val l = List(("a", 1), ("b", 2), ("c", 3))
val m = l.toMap // Map(a -> 1, b -> 2, c -> 3)
```

```
val m = Map("a" -> 1, "b" -> 2, "c" -> 3)

m.get("a")    // Some(1)
m.get("d")    // None
m("a")        // 1
m("d")        // java.util.NoSuchElementException: key not found: d

m.keys        // Set(a, b, c)
m.values      // MapLike(1, 2, 3)
```

```
Map("a" -> 1, "b" -> 2) + ("c" -> 3)           // Map(a -> 1, b -> 2, c -> 3)
Map("a" -> 1, "b" -> 2) + ("a" -> 3)           // Map(a -> 3, b -> 2)
Map("a" -> 1, "b" -> 2) ++ Map("b" -> 3, "c" -> 4) // Map(a -> 1, b -> 3, c -> 4)
```

map find forEachTuples ◦ `_1 _2` **case**

```
m.find(_._1 == "a") // Some((a,1))
m.map {
  case (key, value) => (value, key)
} // Map(1 -> a, 2 -> b, 3 -> c)
m.filter(_._2 == 2) // Map(b -> 2)
m.foldLeft(0){
  case (acc, (key, value: Int)) => acc + value
} // 6
```

“”map◦

```
val someFunction: (A) => (B) = ???
collection.map(someFunction)
```

```
collection.map((x: T) => /*Do something with x*/)
```

2

```
// Initialize
val list = List(1,2,3)
// list: List[Int] = List(1, 2, 3)

// Apply map
list.map((item: Int) => item*2)
// res0: List[Int] = List(2, 4, 6)

// Or in a more concise way
list.map(_*2)
// res1: List[Int] = List(2, 4, 6)
```

filter“”◦ map Boolean

```
val someFunction: (a) => Boolean = ???
```

```
collection.filter(someFunction)
```

```
collection.filter((x: T) => /*Do something that returns a Boolean*/)
```

```
val list = 1 to 10 toList
// list: List[Int] = List(1, 2, 3, 4, 5, 6, 7, 8, 9, 10)

// Filter out all elements that aren't evenly divisible by 2
list.filter((item: Int) => item % 2==0)
// res0: List[Int] = List(2, 4, 6, 8, 10)
```

```
case class Person(firstName: String,
                  lastName: String,
                  title: String)

// Make a sequence of people
val people = Seq(
  Person("Millie", "Fletcher", "Mrs"),
  Person("Jim", "White", "Mr"),
  Person("Jenny", "Ball", "Miss") )

// Make labels using map
val labels = people.map( person =>
  s"${person.title}. ${person.lastName}"
)

// Filter the elements beginning with J
val beginningWithJ = people.filter(_.firstName.startsWith("J"))

// Extract first names and concatenate to a string
val firstNames = people.map(_.firstName).reduce( (a, b) => a + "," + b )
```

Scala

Scala Collections◦

Scala ◦ [Scala](#) ◦

◦ ◦ List() ◦

◦

```
val numList = List[Int](1, 2, 3, 4, 5)
numList.reduce((n1, n2) => n1 + n2) // 15

val numSet = Set[Int](1, 2, 3, 4, 5)
numSet.reduce((n1, n2) => n1 + n2) // 15

val numArray = Array[Int](1, 2, 3, 4, 5)
numArray.reduce((n1, n2) => n1 + n2) // 15
```

Traversable◦

VectorList ◦ ListVector ◦

Traversable **trait**foreach◦

- **Map** - map flatMapcollect◦

```
List(1, 2, 3).map(num => num * 2) // double every number = List(2, 4, 6)

// split list of letters into individual strings and put them into the same list
List("a b c", "d e").flatMap(letters => letters.split(" ")) // = List("a", "b", "c", "d", "e")
```

- -toList toArray◦ **'to'**toList'List ◦

```
val array: Array[Int] = List[Int](1, 2, 3).toArray // convert list of ints to array of ints
```

- - isEmpty nonEmpty sizehasDefiniteSize◦ ◦

```
List().isEmpty // true
List(1).nonEmpty // true
```

- - head last findOption◦

```
val list = List(1, 2, 3)
list.head // = 1
list.last // = 3
```

- - filter tail slice drop◦

```
List(-2, -1, 0, 1, 2).filter(num => num > 0) // = List(1, 2)
```

- - partition splitAt spangroupBy◦

```
// split numbers into < 0 and >= 0
List(-2, -1, 0, 1, 2).partition(num => num < 0) // = (List(-2, -1), List(0, 1, 2))
```

- - exists forallcount◦

```
List(1, 2, 3, 4).forall(num => num > 0) // = true, all numbers are positive
List(-3, -2, -1, 1).forall(num => num < 0) // = false, not all numbers are negative
```

- - foldLeft /: foldLeft foldRight :\ reduceLeftreduceRight◦ ◦

fold

```
val nums = List(1,2,3,4,5)
var initialValue:Int = 0;
var sum = nums.fold(initialValue){
```

```
(accumulator,currentElementBeingIterated) => accumulator + currentElementBeingIterated
}
println(sum) //prints 15 because 0+1+2+3+4+5 = 15
```

fold()◦ ◦

```
def sum(x: Int, y: Int) = x+ y
val nums = List(1, 2, 3, 4, 5)
var initialValue: Int = 0
val sum = nums.fold(initialValue)(sum)
println(sum) // prints 15 because 0 + 1 + 2 + 3 + 4 + 5 = 15
```

```
initialValue = 2;
sum = nums.fold(initialValue){
  (accumulator,currentElementBeingIterated) => accumulator + currentElementBeingIterated
}
println(sum) //prints 17 because 2+1+2+3+4+5 = 17
```

fold - foldLeftfoldRight ◦

foldLeft()◦ foldRight()◦ fold()foldLeft()◦ fold()foldLeft()◦

```
def fold[A1 >: A](z: A1)(op: (A1, A1) => A1): A1 = foldLeft(z)(op)
```

fold() foldLeft()foldRight()◦ foldLeft()foldRight() fold()◦

fold()foldLeft()foldRight()◦ ◦

foldLeft()foldRight()◦ foldRight()◦

foreach

foreach◦ ◦

```
scala> val x = List(1,2,3)
x: List[Int] = List(1, 2, 3)

scala> x.foreach { println }
1
2
3
```

foreach◦ foreach◦ map filter **a** for comprehension◦

```
def myFunc(a: Int) : Int = a * 2
List(1,2,3).foreach(myFunc) // Returns nothing
```

reduce() reduceLeft()reduceRight **folds**◦ reduce◦ ◦ ◦ ◦ ◦

```
val nums = List(1,2,3,4,5)
```

```
sum = nums.reduce({ (a, b) => a + b })
println(sum) //prints 15

val names = List("John", "Koby", "Josh", "Matilda", "Zac", "Mary Poppins")

def findLongest(nameA:String, nameB:String):String = {
  if (nameA.length > nameB.length) nameA else nameB
}

def findLastAlphabetically(nameA:String, nameB:String):String = {
  if (nameA > nameB) nameA else nameB
}

val longestName:String = names.reduce(findLongest(_,_))
println(longestName) //prints Mary Poppins

//You can also omit the arguments if you want
val lastAlphabetically:String = names.reduce(findLastAlphabetically)
println(lastAlphabetically) //prints Zac
```

reduce。

1. reduce。
2. Reduce。
3. Reduce。

<https://riptutorial.com/zh-CN/scala/topic/686/>

62:

Scala

◦

Function1arity apply

◦ Scala

◦ Scala Seqmap

Examples

Scala

```
object MyObject {
  def mapMethod(input: Int): String = {
    int.toString
  }
}

Seq(1, 2, 3).map(MyObject.mapMethod) // Seq("1", "2", "3")
```

MyObject.mapMethodmap map mapList[A]A

```
def map[B](f: (A) => B): List[B]
```

f: (A) => BAB AB mapMethodInt A String B mapMethodmap

```
Seq(1, 2, 3).map(x: Int => int.toString)
```

◦

• ◦

• ◦

• ◦

```
object HOF {
  def main(args: Array[String]) {
    val list =
List(("Srini", "E"), ("Subash", "R"), ("Ranjith", "RK"), ("Vicky", "s"), ("Sudhar", "s"))
    //HOF
    val fullNameList= list.map(n => getFullName(n._1, n._2))

  }
}
```



```
def getFullName(firstName: String, lastName: String): String = firstName + "." +
lastName
}
```

mapgetFullName(n._1,n._2)◦ **HOF**◦

Scala def func(arg: => String) ◦ StringString◦ ◦

```
def calculateData: String = {
  print("Calculating expensive data! ")
  "some expensive data"
}

def dumbMediator(preconditions: Boolean, data: String): Option[String] = {
  print("Applying mediator")
  preconditions match {
    case true => Some(data)
    case false => None
  }
}

def smartMediator(preconditions: Boolean, data: => String): Option[String] = {
  print("Applying mediator")
  preconditions match {
    case true => Some(data)
    case false => None
  }
}

smartMediator(preconditions = false, calculateData)

dumbMediator(preconditions = false, calculateData)
```

smartMediator**None**"Applying mediator" smartMediator "Applying mediator" ◦

dumbMediator**None**"Calculating expensive data! Applying mediator" ◦

◦

<https://riptutorial.com/zh-CN/scala/topic/1642/>

S. No		Contributors
1	Scala	4444 , Andy Hayden , Ani Menon , Community , David G. , David Portabella , dk14 , Donald.McLean , Gabriele Petronella , Grzegorz Oledzki , implicitdef , isaias-b , J Atkin , Jean , Jonathan , mammothbane , marcospereira , Marek Skiba , mdarwin , Nathaniel Ford , NeoWelkin , Nicofisi , Priya , rolve , Shoe , sschaef , Thomas Andrews , Tyler James Harden , Ven , Vogon Jeltz
2	Hive	Camilo Sampedro
3	Implicits	Andy Hayden , dimitrisli , Gábor Bakos , HTNW , implicitdef , ipoteka , Jose Antonio Jimenez Saez , Michael Zajac , Nathaniel Ford , nattyddubbs , Simon , spiffman , Suma , Timo , vsminkov
4	Java	Andrzej Jozwik , Dan Hulme , Gábor Bakos , mvn , the21st , thekingofkings
5	JSON	ipoteka , John , Muki , Nathaniel Ford , pedrorijo91 , suj1th , void , Wogan , zoitol
6	Quasiquotes	gregghz
7	Scala.js	Camilo Sampedro
8	Scaladoc	Camilo Sampedro , Gábor Bakos , Nathaniel Ford
9	scalaz	chengpohi
10	Scala	Gábor Bakos , Shaido , Suminda Sirinath S. Dharmasena
11	VarValDef	Aamir , John Starich , jwvh , linkhyrule5 , Nathaniel Ford , Shastick , Shuklaswag , stefanobaghino , ZbyszekKr
12	XML	Nathaniel Ford , Rockie Yang , vsnytc
13	Gradle	Bianca Tesila , Nathaniel Ford , Rjk
14	ScalaCheck	Andrzej Jozwik
15	ScalaTest	Nadim Bahadoor , Nathaniel Ford
16		Filippo Vitale
17		Hoang Ong
18		corvus_192 , evan.oman , Lawtsy , Nathaniel Ford

19		Aravindh S, Archeg, Camilo Sampedro, ches, corvus_192, Dawny33, Gábor Bakos, Gabriele Petronella, implicitdef, ipoteka, Jean, jwvh, michael_s, Nathaniel Ford, raam86, rjsvaljean, ScientiaEtVeritas, Shastick, stefanobaghino, Sven Koschnicke, vise890, wheaties
20		HTNW
21		Alex Javarotti, Nathaniel Ford, NetanelRabinowitz
22	SAM	Gábor Bakos, Gabriele Petronella, Nathaniel Ford
23		ipoteka, Nathaniel Ford
24		Sachin Janani
25		Gábor Bakos
26		Adamos Loizou, alphaloop, Amr Gawish, dimitrisli, Luka Jacobowitz, Nathaniel Ford, rjsvaljean, Suma, vise890
27		Gábor Bakos
28		corvus_192, Nathaniel Ford, ScientiaEtVeritas
29		Andy Hayden, Ayberk, Brian, implicitdef, J Cracknell, Nadim Bahadoor
30		gregghz, HTNW, Nathaniel Ford
31		Andy Hayden, J Cracknell, jwvh, LivingRobot, Nathaniel Ford, ScientiaEtVeritas
32		dmitry, J Cracknell, Nathaniel Ford
33		Nathaniel Ford, Shuklaswag
34		J Cracknell, Nathaniel Ford
35		André Laszlo, Andy Hayden, Donald.McLean, Louis F., Nathaniel Ford, Rumoku, Sudhir Singh, Vagon Jeltz
36		Andy Hayden, Dan Hulme, Dan Simon, Gábor Bakos, gilad hoch, Idloj, J Cracknell, jwvh, knutwalker, Łukasz, Martin Seeler, Michael Ahlers, Nathaniel Ford, Suma, W.P. McNeill
37		corvus_192, ipoteka, Nathaniel Ford, RamenChef, Sarvesh Kumar Singh, Shuklaswag
38		isaias-b, kevin628, Nathaniel Ford, nukie, Shastick

39		Andy Hayden , Cortwave , Daniel Schröter , Gábor Bakos , implicitdef , ipoteka , Nathaniel Ford , phantomastray , Red Mercury
40		Andy Hayden , Dan Simon , dk14 , Gábor Bakos , HTNW , J Cracknell , keegan , made raka teja , Marc Grue , Nathaniel Ford , pedrorijo91 , Rumoku , ScientiaEtVeritas , suj1th , Suma
41		Ali Dehghani , Andrzej Jozwik , Andy Hayden , CPS , Dan Simon , Daniel Werner , Filippo Vitale , Gábor Bakos , implicitdef , insan-e , jilen , jozic , JRomero , Justin Bailey , Louis F. , mammothbane , Matt , Nadim Bahadoor , Nathaniel Ford , Peter Neyens , Sergio , Shastick , Shoe , Simon , Suma , T.Grottker , user6062072 , vdebergue , vsminkov , Yagüe
42		Gábor Bakos , Nathaniel Ford , Thomas Matecki
43		jwvh , Nathaniel Ford , Oleg Pyzhcov
44		ZbyszekKr
45		Aamir , Gábor Bakos , mdarwin , mirosval , MSmedberg , Nathaniel Ford , ScientiaEtVeritas , steve , Sudhir Singh , Tzach Zohar , vivek
46		akauppi , Andy Hayden , Eero Helenius , Nathaniel Ford , vivek
47		Gábor Bakos , Nathaniel Ford , suj1th
48		J Cracknell
49		dmitry , HTNW
50		Gábor Bakos , irundaia
51		Camilo Sampedro
52		Nathaniel Ford
53	Scala	Hristo Iliev , Matas Vaitkevicius , Nathaniel Ford , Rjk
54		corvus_192 , implicitdef , inzi , mnoronha , Nathaniel Ford , Simon
55		Bruce Lowe , CPS , earldouglas , evan.oman , Governa , John Starich , Matthew Scharley , Nathaniel Ford , R Pieters , ScientiaEtVeritas , suj1th , Tzach Zohar , Vasilij Levykin
56		Dmitry Bystritsky , Gábor Bakos , jilen , jwvh , michael_s , ScientiaEtVeritas , teldosas
57		acjay , Akash Sethi , David Leppik , dimitrisli , jwvh , Suma , Tzach Zohar

58		Andy Hayden , Graham , John Starich , made raka teja , mnoronha , Nathaniel Ford , Simon , Suma , tacos_tacos_tacos , Tzach Zohar
59		acjay , J Cracknell , Reactormonk
60		Arseniy Zhizhelev , Daniel C. Sobral , Gábor Bakos , gregghz , Nathaniel Ford , TomTom , Yawar
61		Anton , Camilo Sampedro , deepkimo , Donald.McLean , doub1ejack , EdgeCaseBerg , Filippo Vitale , George , implicitdef , ipoteka , Jason , John Starich , Mr D , Nathaniel Ford , raam86 , Shastick , Suma , Tundebabzy , Vasiliy Levykin
62		acjay , ches , Nathaniel Ford , nukie , Rajat Jain , Srini